

Address Register	Register Number	Register Type	Units	I/O	40 by 25 Alpha-numeric	80 by 25 Alpha-numeric	Graphic Modes
0	R0	Horizontal Total	Character	Write Only	38	71	38
1	R1	Horizontal Displayed	Character	Write Only	28	50	28
2	R2	Horizontal Sync Position	Character	Write Only	2D	5A	2D
3	R3	Horizontal Sync Width	Character	Write Only	0A	0A	0A
4	R4	Vertical Total	Character Row	Write Only	1F	1F	7F
5	R5	Vertical Total Adjust	Scan Line	Write Only	06	06	06
6	R6	Vertical Displayed	Character Row	Write Only	19	19	64
7	R7	Vertical Sync Position	Character Row	Write Only	1C	1C	70
8	R8	Interlace Mode	-	Write Only	02	02	02
9	R9	Maximum Scan Line Address	Scan Line	Write Only	07	07	01
A	R10	Cursor Start	Scan Line	Write Only	06	06	06
B	R11	Cursor End	Scan Line	Write Only	07	07	07
C	R12	Start Address (H)	-	Write Only	00	00	00
D	R13	Start Address (L)	-	Write Only	00	00	00
E	R14	Cursor Address (H)	-	Read/Write	XX	XX	XX
F	R15	Cursor Address (L)	-	Read/Write	XX	XX	XX
10	R16	Light Pen (H)	-	Read Only	XX	XX	XX
11	R17	Light Pen (L)	-	Read Only	XX	XX	XX
Note: All register values are given in hexadecimal							

6845 Register Description

1-104 Color/Graphics Adapter