Routed Experts Are Not Redundant: The Shared-Expert Gradient Race in Small Mixture-of-Experts Models

TBD

Abstract

Small Mixture-of-Experts (MoE) language models with a DeepSeek-style shared expert are a popular testbed for interpretability, because they are cheap to train and every token can be labelled. A recurring observation in this regime is that the routed experts appear *redundant*: ablating the entire routed branch barely changes perplexity, while the single always-on shared expert dominates the feed-forward computation. We show that this "routed redundancy" is largely an **artifact of undertraining**, and we identify its cause. Using a 134M-parameter MoE trained from scratch on a three-domain, token-labelled corpus, we find that (i) the shared expert carries ∼80% of the feed-forward ablation impact at 98M tokens but the routed and shared branches become **balanced by ∼300M tokens** and stay balanced through 1B (4 seeds, tight error bars); (ii) this early dominance is a **gradient-exposure race**—the shared expert receives gradient from 100% of tokens versus $\sim k/E$ per routed expert, so it wins the early optimization race; and (iii) the race is **causally controllable**: slowing the shared expert's learning rate shifts the routed-activation crossover dose-dependently (the shared branch's share of ablation impact at 98M tokens drops from 0.80 to 0.14) **at no perplexity cost**. A single hyperparameter thus reallocates computation to the routed experts without changing model quality. The control **reproduces at 2× depth**, and a *temporary* handicap suffices: once the shared expert's learning rate is ramped back to parity, the reallocation persists to 1B tokens. Finally we identify what sets *where* the split lands—not the number of experts, but the **routed:shared width ratio**. Holding the routed branch byte-for-byte identical and varying only the shared expert's width moves the shared branch's share from 0.28 to 0.81, and the ratio orders every configuration we measured across 8× in ratio, 8× in expert count and 4× in parameter count. We further report the axes of specialization (surface form > domain > frequency, position irrelevant). Three of our own conclusions were overturned by seed replication or better controls and are reported as such.

1 Introduction

Mixture-of-Experts layers replace a dense feed-forward block with a router that dispatches each token to a small number of experts. The DeepSeekMoE design (2) adds an always-on *shared expert* alongside the *routed* experts, on the intuition that the shared expert absorbs common computation and frees the routed experts to specialize. Because small MoEs are cheap and controllable, they are widely used to study expert specialization.

In this small-scale regime, a striking and repeatedly observed phenomenon is that the routed experts look nearly useless: removing all of them costs little perplexity, while removing the lone shared expert costs a lot. It is tempting to conclude that small MoEs are over-parametrized on the routed side, or that the shared expert suppresses the routed experts.

We show that this conclusion is **premature**. The apparent redundancy is a transient property of early training that disappears with enough tokens, and its cause is a simple, controllable optimization dynamic. Our contributions:

1. **Observation.** Branch importance is a function of tokens seen: routed "redundancy" and shared dominance vanish by ∼300M tokens (Section 4).

2. **Mechanism.** The dominance is a *gradient-exposure race*—the shared expert is updated on every token, each routed expert on a k/E fraction—proven causally by slowing the shared expert and watching the crossover shift, at no quality cost (Section 5).

3. **Control.** One hyperparameter (shared-expert learning rate) sets when—and whether—the routed experts engage, and a *temporary* handicap is enough: the reallocation persists after the handicap is lifted (Section 5).

4. **What sets the split.** Where the two branches settle is governed by the routed:shared *width ratio*, not by the number of experts; this supersedes an earlier non-monotonic #experts result of ours, confounded by total routed capacity (Section 6).

Along the way we characterize *what* the experts specialize by, and we explicitly retract three earlier findings that did not survive replication or better controls (Section 7). We view the honest, seed-replicated, causal methodology as part of the contribution.

2 Related work

Sparse MoE layers. Conditional computation via a sparsely-gated MoE layer was introduced by Shazeer et al. (14) and scaled by GShard (9) and Switch Transformer (5), which also established the auxiliary load-balancing loss. ST-MoE (17) added the router z-loss for stability. Our model uses both, in a top-2 configuration (8).

Shared experts. DeepSeekMoE (2) introduced the always-on shared expert alongside fine-grained routed experts, arguing it absorbs common knowledge and thereby *frees* the routed experts to specialize; the design carries through DeepSeek-V2/V3 (3, 4), which also motivate auxiliary-loss-free routing by the balance–specialization tension. We reproduce the "shared enables specialization" effect (Section 7) but show it is only visible once balancing is off, and—more importantly—that at small scale the shared expert *dominates* the computation for a mechanistic reason unrelated to specialization.

Expert specialization studies. Analyses of Mixtral (8) report that experts specialize more by token/syntactic identity than by topic; OLMoE (10) studies specialization and routing across training in open MoEs. We add a controlled, domain-labelled probe with causal branch ablation and, crucially, identify a training-dynamics cause for the small-scale "routed redundancy" that these observational studies do not address.

Architecture components. Our backbone uses MLA (3), RoPE (15), RMSNorm (16), and optional YaRN context extension (13); the distillation experiment follows Hinton et al. (6) with a Mistral-7B teacher (7). Pre-training data are FineWeb-Edu (12), Cosmopedia-v2 (1), and OpenWebMath (11).

To our knowledge, the central claim—that small-MoE routed redundancy is an *undertraining artifact* caused by a *gradient-exposure race* between the shared and routed experts, and is *causally controllable* by the shared-expert learning rate at no quality cost—is new.

Table 1: Branch importance vs. tokens (baseline, 4 seeds, batch 64).

tokens	PPL	remove shared	remove all routed	routed NMI	shared share
98M	4.18	$+3.44 \pm 0.17$	$+0.82 \pm 0.03$	0.0121	0.81
197M	3.63	$+2.37 \pm 0.17$	$+1.58 \pm 0.06$	0.0148	0.60
295M	3.41	$+1.99 \pm 0.14$	$+1.98 \pm 0.06$	0.0161	0.50
491M	3.20	$+1.99 \pm 0.16$	$+2.25 \pm 0.01$	0.0168	0.47
983M	3.00	$+2.45 \pm 0.18$	$+2.48 \pm 0.11$	0.0174	0.50

3 Setup

Model. A decoder-only MoE re-implemented from scratch in PyTorch: Multi-head Latent Attention (MLA), RoPE, RMSNorm, and per layer a MoE block with 8 routed experts + 1 shared expert and top-2 routing (134M parameters, 8 layers, hidden 512, context 512). Every expert, routed or shared, has intermediate width 1024 unless stated otherwise; Section 6 varies the two widths independently and writes them I (per routed expert) and I_{shared}. During analysis we run the MoE in inference mode (no capacity dropping), which we verified is numerically identical to the training MoE when no tokens are dropped.

Data. Pre-training streams three token-labelled corpora: FineWeb-Edu (`web`, 60%), Cosmopedia-v2 (`edu`, 25%), OpenWebMath (`math`, 15%), tokenized with the Mistral vocabulary (32k). Sequences are packed to 512 tokens. The domain labels are the key lever: they let us attribute routing to a known variable. Held-out per-domain evaluation packs each domain separately (one label per sequence).

Metrics. *Branch importance*: ΔPPL from ablating a whole branch (all routed experts, or the shared expert). This whole-branch ablation is the correct causal probe—single-expert ablation is misleading because top-2 routing reroutes to the survivors. The *shared share* is $\Delta_{\text{shared}}/(\Delta_{\text{shared}} + \Delta_{\text{routed}})$. *Specialization*: gate-weighted normalized mutual information $\text{NMI}(\text{Expert}; \text{axis}) = I/H$, averaged over layers, against a label-permutation null (≈ 0 everywhere). *Balance*: std of top-1 expert load. Between-condition tests are exact permutation tests on seed-level values (minimum two-sided $p = 2/\binom{2n}{n}$ for n seeds per group).

Compute. All runs are on one NVIDIA RTX A6000 using a plain single-GPU trainer; the largest models see ∼1B tokens (∼3.4h each).

4 Routed "redundancy" is an undertraining artifact

We train the base model for 30k steps (∼983M tokens, batch 64), 4 seeds, and measure branch importance at each checkpoint (mean ± std, Table 1, Figure 1).

At 98M tokens—the regime of many pilot studies and of our own early experiments—the shared expert carries 81% of the ablation impact and the routed experts look nearly redundant. The crossover to balance happens by ∼295M tokens, after which the branches contribute equally through 1B. All four seeds follow the same trajectory with tight error bars; routed specialization grows in parallel (NMI 0.0008 → 0.017). **Conclusions drawn about routed redundancy or shared dominance below a few hundred million tokens do not generalize.**




Figure 1: Ablation impact (ΔPPL) of removing the shared expert vs. all 8 routed experts, over a 4-seed constant-batch trajectory (bands = ±1 std). The shared expert dominates early; the branches cross to balance by ∼295M tokens.

5 The mechanism: a gradient-exposure race

Why does the shared expert dominate early? It is updated on **every** token; each routed expert is updated on only a $k/E = 2/8 = 25\%$ fraction. The shared expert therefore wins the early optimization race and the residual stream comes to rely on it; the routed experts become load-bearing only once the shared expert saturates.

Formalization. Consider one MoE block whose output on token t is

$$y_t = s(x_t) + \sum_{e \in \text{topk}(t)} g_{t,e}\, f_e(x_t), \tag{1}$$

where s is the shared expert and f_e the routed experts. Over a batch of N tokens, the shared parameters receive gradient aggregated over all N tokens, whereas a routed expert e receives gradient only from the $\approx Nk/E$ tokens routed to it. Under a shared learning rate, the shared expert accumulates roughly $E/k\times$ more effective updates per parameter early in training, when the loss gradient is large and the allocation of "who computes what" is still plastic. The residual pathway greedily routes common computation to whichever sub-module reduces loss fastest—the shared expert—further starving the routed experts (a rich-get-richer dynamic). This yields two testable predictions: (i) reducing the shared expert's learning rate should let the routed experts capture computation earlier (confirmed below); and (ii) the crossover token count should grow with E/k (Section 6, **refuted**—expert count barely moves the split; the relative *width* of the two branches is what governs it).

We test prediction (i) by placing the shared-expert parameters in their own optimizer group at lr × mult, everything else at the base learning rate (2 seeds; values at 98M tokens, Table 2, Figure 2).

Slowing the shared expert makes the routed branch load-bearing **dramatically earlier**—a 5× increase in routed importance at a *fixed* token budget—shifting the crossover from ∼295M tokens

Table 2: Shared-expert LR sweep (2 seeds), at 98M tokens.

shared LR	remove routed	remove shared	shared share	PPL
×1.0 (baseline)	+0.85	+3.46	0.80	4.16
×0.3	+1.94	+2.48	0.56	4.10
×0.1	+4.46	+0.72	0.14	4.10




Figure 2: Shared branch's share of ablation impact vs. tokens, for three shared-expert learning-rate multipliers (2 seeds). Slowing the shared expert shifts the routed-activation crossover earlier, dose-dependently—at unchanged perplexity.

(baseline) to <100M (×0.3) to before training even settles (×0.1, where routed dominate from the start). The effect is monotonic, dose-dependent, tight error bars. This **refutes autonomous routed maturation**: the routed experts were being out-competed, not merely immature. Crucially, **held-out perplexity is unchanged** across conditions. The shared expert is therefore not *necessary* for this computation; the model defaults to placing it there because that expert trains fastest. A single knob reallocates computation to the routed experts at no quality cost.

Does the mechanism hold at scale? We repeat the shared-LR sweep on a 2×-deeper model (16 layers, 251M parameters, 1 seed; Figure 3). The control reproduces almost exactly: at 98M tokens the shared share drops 0.82 → 0.64 → 0.21 for ×1.0/ × 0.3/ × 0.1 (vs. 0.80/0.56/0.14 at 134M), dose-dependent and at unchanged perplexity—the gradient-race mechanism and its knob are robust to depth. The crossover *timing*, however, is scale-dependent: the deeper baseline only reaches a minimum share of 0.54 (∼491M tokens) and does **not** cross to balance within 1B tokens, the shared expert re-asserting dominance (0.59 at 983M). This dip-then-rise shape is universal in our runs: every configuration in Section 6 shows it, at a level set by the width ratio, which is why we report the minimum over the trajectory there rather than the endpoint. Deeper models stay shared-dominated for many more tokens; "enough tokens" for routed balance grows with model size (mechanistically consistent). This strengthens the practical warning but means that *left alone* we observe the crossover complete only at our smallest configuration within our 1B-token budget. The




Figure 3: (left) shared branch's share vs. tokens at two depths—the 8-layer model crosses to balance, the 16-layer model approaches but does not within 1B tokens; (right) the shared-LR control reproduces at 2× depth, dropping the share dose-dependently at both scales.

next experiment shows the deeper model can nonetheless be driven past balance and kept there.

A temporary handicap is enough. If the split is decided by an early race, handicapping the shared expert only *during* that race should suffice. We ramp the shared-expert LR multiplier from ×0.1 up to ×1.0 by step 9000 (∼295M tokens) on the 16-layer model (251M parameters, 1 seed), after which every parameter trains at the base rate (Table 3, Figure 4). The reallocation **does not undo**: by the end of the ramp the ramped run has converged onto the static-×0.1 trajectory, and once the handicap is gone it stays there—0.21 at 983M tokens versus the baseline's 0.59, at equal perplexity (2.88 vs. 2.90). The shared branch re-asserts only slowly (0.14 → 0.21 between 295M and 983M), far more slowly than the baseline's rise. This is what a race-then-commit dynamic predicts, and it makes the knob a *training-schedule* intervention rather than a permanent tax on the shared expert.

How long must the handicap last? Sweeping the ramp endpoint over 98M / 197M / 295M / 491M tokens and changing nothing else gives a **monotone, graded** response: the shared share at 983M tokens is 0.33/0.26/0.21/0.19 against the baseline's 0.59, at final perplexities of 2.88/2.88/2.88/2.89 against 2.90. Together with the dose-response over handicap *strength* above, the race therefore has two independent, monotone control axes. Two features of the curve matter more than its existence. First, **a brief handicap already does most of the work**: lifting it at 98M tokens—one tenth of the budget—still lands at 0.33, roughly two thirds of the total achievable reallocation. Second, **the curve saturates**: the 295M → 491M difference is 0.02, equal to the seed noise on this quantity, so those two points are not distinguishable and extending the handicap past ∼295M tokens buys nothing measurable. The 295M point is 2 seeds; the other three are single-seed, and the whole sweep is at one depth and one handicap strength.

6 What sets the split: the routed:shared width ratio

Section 5 explains *why* the shared expert wins early and shows the race can be rigged; it does not say where the split finally lands. The gradient-race picture naively predicts that quantity should

Table 3: Shared branch share vs. tokens at 16 layers (251M), for a constant, a static and a ramped shared-expert learning rate. The static ×0.1 run stopped at 491M tokens.

tokens	baseline ×1.0	static ×0.1	ramp 0.1 → 1.0
98M	0.84	0.21	0.42
295M (ramp ends)	0.58	0.14	0.15
491M	0.54	0.16	0.16
983M	0.59	—	**0.21**
final PPL	2.90	—	2.89




Figure 4: (left) shared branch's share vs. tokens at 16 layers, for four handicap durations; the tick marks where each handicap was lifted. (right) the resulting dose-response: final share against how long the handicap was held, at flat perplexity.

be governed by E/k. We tested that across eleven 8-layer configurations (top-2, 983M tokens, 1–2 seeds each; seven run specifically for this section), and the prediction fails: expert count barely matters, while the **ratio of the two branches' widths** orders every run we measured.

Two contrasts disentangle the candidates (Table 4). Both hold E=8 and k=2 fixed, so expert count, routing and per-expert gradient share are constant throughout. The second is the decisive one: with I pinned at 1024 the routed branch is byte-for-byte identical across the three runs—same expert count, same per-expert width, same active capacity $k \cdot I = 2048$ —and the split still moves by 0.53. **Absolute routed capacity therefore does not govern the split.**

What the two contrasts have in common is the ratio I/I_{shared}. Grouping every configuration by it—including the four points of our earlier #experts sweep, all of which sat at ratio 1.0—gives non-overlapping bands (Figure 5):

ratio I/I_{shared}	0.25	0.5	1.0	2.0
min shared share	0.72 / 0.79 / 0.81	0.63	0.47 / 0.53 / 0.55 / 0.56	0.25 / 0.28 / 0.37

The ordering holds across 8× in ratio, 8× in expert count ($E \in \{4, \ldots, 32\}$) and 4× in parameter count (58M–234M). Within a band the residual spread is ∼0.1 and is **not** consistently explained by E: at ratio 2.0 more experts *raise* the share (E=4 → 0.25 vs. E=8 → 0.37) while at ratio 0.25

Table 4: The two disentangling contrasts, both at E=8, k=2. Values are the minimum shared share reached over the trajectory.

Varying routed width ($I_{\text{shared}} = 1024$)			
I	256	1024	2048
min shared share	0.79	0.47	0.37
params	58.2M	133.7M	234.4M
Varying shared width ($I = 1024$; routed branch identical)			
I_{shared}	512	1024	4096
min shared share	**0.28**	0.47	**0.81**
params	127.4M	133.7M	171.5M




Figure 5: (left) minimum shared share vs. the branch width ratio, one point per configuration, coloured by expert count; the bands per ratio level do not overlap. (right) the decisive contrast—the routed branch is identical in all three runs and only the shared expert's width changes.

more experts *lower* it (E=32 $\rightarrow$ 0.72 vs. E=8 $\rightarrow$ 0.79). Seed noise on this quantity is $\sim$0.02, an order of magnitude below the effect. Holding total routed capacity fixed instead ($E \cdot I = 8192$ at equal parameters) leaves perplexity flat as well—2.99 / 3.00 / 3.00 / 3.02 for $E = 4/8/16/32$—so expert count is close to a free parameter for both quantities here.

Interpretation. The two results compose rather than compete. The gradient race decides *who gets there first* (Section 5); the relative width of the branches decides *how much each one can absorb*, and therefore where the allocation settles once the race is over. Both are reparametrizations rather than quality levers: across the seven 127M–234M configurations here the minimum shared share spans 0.25 to 0.81 while final perplexity spans only 2.95 to 3.02. Where a small MoE puts its feed-forward computation is, to a good approximation, a free design choice—and the width ratio is the knob that sets it.




Figure 6: Domain specialization (left) and expert load imbalance (right) vs. the auxiliary load-balancing coefficient (4 seeds, ±1 std). Both fall monotonically as balancing strengthens.

7 Supporting characterization and retracted findings

What experts specialize by. On models trained without the load-balancing loss (where specialization is strongest), NMI(Expert; axis) is largest for *surface form* (0.050), then domain (0.034), then token frequency (0.028), and essentially zero for sequence position (0.0003). A conditional-MI check shows the axes are separable—domain routing information is fully retained after conditioning on surface class—so domain specialization is genuine, not a surface-form artifact. This reproduces, in a controlled labelled setting, prior reports that experts organize more by token/surface than by topic.

Load balancing controls specialization. Sweeping the auxiliary loss coefficient $\{0, 10^{-2}, 10^{-1}\}$ moves domain NMI monotonically (0.034/0.0085/0.0010; all pairwise permutation tests significant) and load imbalance in lockstep, at no perplexity cost (Figure 6).

Shared expert enables specialization. With balancing off, routed domain-NMI is higher *with* the shared expert (0.034) than without (0.015, $p = 0.029$): the shared expert acts as a common-capability backstop, consistent with the DeepSeekMoE intuition.

Three retracted findings. (a) At 3 seeds, removing the shared expert appeared to sharpen routed specialization; at 4 seeds this collapsed ($p = 0.54$) and, once balancing is off, the sign reverses. (b) We hypothesized the shared monopoly was a *pathology*; a per-token shared-branch dropout breaks the monopoly entirely (shared share $\to 0.01$) but yields no perplexity gain and no specialization gain—consistent with Section 5's conclusion that the shared/routed split is a near-neutral reparametrization. (c) We previously reported a **non-monotonic dependence on the number of experts**, with a "Goldilocks" optimum at E=8 and monotonically improving perplexity in E. Both halves were confounded: that sweep held per-expert width fixed, so total routed capacity *and* total parameters grew with E while the width ratio stayed at 1.0 throughout—which is exactly why all four points fall inside the single narrow band (0.47–0.56) that Section 6 attributes to ratio 1.0, the apparent optimum lying within that band's residual spread. The perplexity gain (3.28 $\to$ 2.90) was a parameter-count effect: at matched parameters perplexity is flat (2.99–3.02).

We retract the non-monotonic law and the "pick E for engagement" recommendation that followed from it. We report all three as negatives.

Distillation (preliminary). On-the-fly distillation from a Mistral-7B teacher, compared to a batch/step-matched from-scratch control at 98M tokens, appears to engage the routed branch more (remove-routed $+1.03 \rightarrow +1.74$) but at a small next-token PPL cost and from a single seed; not established.

8 Practical recommendations

1. **Do not diagnose expert redundancy on an undertrained model.** Below a few hundred million tokens the shared expert dominates for optimization reasons, not architectural ones; measure branch importance as a trajectory, not at a single early checkpoint.

2. **To engage the routed experts sooner, slow the shared expert** (e.g. a $\times 0.3$ LR multiplier). This reallocates computation to the routed branch at no measured perplexity cost—valuable when routed experts are the object of study or when balanced load is desired. The handicap need only cover the early race: ramping the multiplier back to $\times 1.0$ by $\sim$300M tokens left the reallocation in place through 1B.

3. **Set the routed:shared width ratio, not the expert count, to control engagement.** How much of the feed-forward computation the routed branch ends up carrying is governed by I/I_{shared}: widening the shared expert starves the routed branch even when the routed branch is untouched, and narrowing it does the reverse. If you want routed experts that are actually used, do not make the shared expert wide. Expert count is close to a free parameter for this purpose—it moved neither the split (at matched ratio) nor perplexity (at matched parameters) in our sweeps.

4. **Report seeds, use matched batch sizes, and match capacity when sweeping architecture.** The sign of a specialization effect and the magnitude of branch-importance metrics were sensitive to seed and batch size at fixed tokens; and our own #experts sweep (retraction (c)) was confounded because it let total capacity ride along with the variable under study.

9 Limitations

Pilot scale (58M–251M parameters, $\leq$1B tokens, 512 context, a single hardware configuration and data mix). Held-out evaluation uses a skip-offset of the training streams rather than a fully disjoint split. Held-out NMI and branch-importance magnitudes are sensitive to batch size at fixed token count, so cross-experiment magnitude comparisons should use matched batches; the within-experiment, matched-batch comparisons and the token trajectories are the reliable ones. The width-ratio result of Section 6 spans $8\times$ in ratio but at a single depth and a single token budget, and we characterize the ordering, not a functional form: whether the split depends on the ratio alone or on ratio and depth jointly is untested. The hysteresis result is single-seed, at one ramp endpoint and one depth. Distillation results are single-seed. Whether the $\sim$300M-token crossover and the gradient-race control persist at larger scale is untested.

10 Conclusion

In small shared-expert MoEs, the routed experts are not redundant—they are out-competed by the shared expert in a gradient-exposure race that resolves with training and that a single learning-rate knob controls at no quality cost, even when applied only temporarily. Where the two branches finally settle is set by their width ratio rather than by the number of experts, and across a 0.25-to-0.81 range of splits perplexity moves by less than 0.1—the placement of feed-forward computation in a small MoE is close to a free design choice. The practical takeaways are concrete: do not diagnose expert redundancy on an undertrained MoE; to engage the routed experts sooner, slow the shared expert; and to engage them *more*, do not make the shared expert wide. The methodology—a cheap, controllable, domain-labelled testbed with causal branch ablation, seed replication, and the willingness to retract—is offered alongside the findings. All code, configs, and the analysis toolkit run on a single GPU and are released with the paper.

References

[1] Loubna Ben Allal, Anton Lozhkov, Guilherme Penedo, et al. Cosmopedia: How to create large-scale synthetic data for pre-training. *Hugging Face Blog*, 2024.

[2] Damai Dai, Chengqi Deng, Chenggang Zhao, et al. DeepSeekMoE: Towards ultimate expert specialization in mixture-of-experts language models. *arXiv preprint arXiv:2401.06066*, 2024.

[3] DeepSeek-AI. DeepSeek-V2: A strong, economical, and efficient mixture-of-experts language model. *arXiv preprint arXiv:2405.04434*, 2024.

[4] DeepSeek-AI. DeepSeek-V3 technical report. *arXiv preprint arXiv:2412.19437*, 2024.

[5] William Fedus, Barret Zoph, and Noam Shazeer. Switch transformers: Scaling to trillion parameter models with simple and efficient sparsity. *Journal of Machine Learning Research (JMLR)*, 2022.

[6] Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. Distilling the knowledge in a neural network. *arXiv preprint arXiv:1503.02531*, 2015.

[7] Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023.

[8] Albert Q Jiang, Alexandre Sablayrolles, Antoine Roux, et al. Mixtral of experts. *arXiv preprint arXiv:2401.04088*, 2024.

[9] Dmitry Lepikhin, HyoukJoong Lee, Yuanzhong Xu, Dehao Chen, Orhan Firat, Yanping Huang, Maxim Krikun, Noam Shazeer, and Zhifeng Chen. GShard: Scaling giant models with conditional computation and automatic sharding. In *International Conference on Learning Representations (ICLR)*, 2021.

[10] Niklas Muennighoff, Luca Soldaini, Dirk Groeneveld, et al. OLMoE: Open mixture-of-experts language models. *arXiv preprint arXiv:2409.02060*, 2024.

[11] Keiran Paster, Marco Dos Santos, Zhangir Azerbayev, and Jimmy Ba. OpenWebMath: An open dataset of high-quality mathematical web text. *arXiv preprint arXiv:2310.06786*, 2023.

[12] Guilherme Penedo, Hynek Kydlíček, Anton Lozhkov, et al. The FineWeb datasets: Decanting the web for the finest text data at scale. *arXiv preprint arXiv:2406.17557*, 2024.

[13] Bowen Peng, Jeffrey Quesnelle, Honglu Fan, and Enrico Shippole. YaRN: Efficient context window extension of large language models. *arXiv preprint arXiv:2309.00071*, 2023.

[14] Noam Shazeer, Azalia Mirhoseini, Krzysztof Maziarz, Andy Davis, Quoc Le, Geoffrey Hinton, and Jeff Dean. Outrageously large neural networks: The sparsely-gated mixture-of-experts layer. In *International Conference on Learning Representations (ICLR)*, 2017.

[15] Jianlin Su, Yu Lu, Shengfeng Pan, Ahmed Murtadha, Bo Wen, and Yunfeng Liu. RoFormer: Enhanced transformer with rotary position embedding. *arXiv preprint arXiv:2104.09864*, 2021.

[16] Biao Zhang and Rico Sennrich. Root mean square layer normalization. *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[17] Barret Zoph, Irwan Bello, Sameer Kumar, Nan Du, Yanping Huang, Jeff Dean, Noam Shazeer, and William Fedus. ST-MoE: Designing stable and transferable sparse expert models. *arXiv preprint arXiv:2202.08906*, 2022.