BULKING APP • AI MIGRATION PACKAGE

Personal Profile & Personalisation Specification

Document 02 of 07 • Version 1.0

Purpose
Define the personal context, preferences, constraints and adaptation rules the application should use to personalise meal planning, tracking, exercise and daily guidance.

Critical rule: historical details are starting context, not guaranteed current facts. The application must let the user confirm, update or correct personal data and must not silently treat stale values as current.

Profile area	Established context	Application behaviour
Diet	Vegetarian; eggs allowed	No meat or fish; editable dietary rules.
Food style	Indian foods and familiar ingredients preferred	Prioritise accessible, practical meals.
Goal	Gain body mass	Support gradual, monitored progress.
Cooking	Easy-to-follow meals preferred	Account for preparation time and complexity.
Exercise	Calisthenics; pull-up bar and dip bar	Plan around available equipment and recovery.
Budget	Value-conscious choices	Rank for practicality and cost without compromising safety.

1. Purpose and rules for using this profile

This document is the canonical description of how the Bulking App should personalise its behaviour to the project owner. It complements Document 01, which describes the project and AI development rules. The actual editable profile stored by the app should eventually be the source of truth for changing values.

1.1 Required distinction between data types

- **Stable preferences:** dietary pattern, cuisine preferences, preferred cooking effort and available equipment. These still need to be editable.
- **Changing profile values:** weight, height if it changes, age, daily schedule, budget and current goal.
- **Daily observations:** appetite, sleep, energy, soreness, digestion, bloating, meals eaten and exercise completed.
- **Derived values:** calculated trends, estimated intake or adherence metrics. Label these as calculations or estimates.
- **AI suggestions:** generated meal plans, substitutions and interpretations. They are not facts until confirmed or explicitly recorded.

1.2 Freshness and confirmation

- Store dates for changing profile facts when useful; do not use an old value indefinitely without indicating its age.
- Allow the user to correct profile values without editing source code.
- If a key input is missing or stale, ask for it only when it materially affects the decision. Otherwise provide a cautious, labelled suggestion.
- Never silently overwrite a confirmed preference based on one meal, one symptom or one day of behaviour.
- Do not assume that details mentioned in old conversations remain true today.

2. Known personal context

The following information has been established in prior project discussions. Treat it as a useful starting profile and confirm time-sensitive or health-relevant details before relying on them for current recommendations.

Field	Known historical value or preference	Handling rule
Dietary pattern	Vegetarian	Default to vegetarian meals; do not suggest meat or fish.
Eggs	Allowed	Eggs can be included where suitable; not every meal needs eggs.
Cuisine	Indian food preferred	Prioritise familiar Indian meals and readily available ingredients.
Height	172 cm previously stated	Confirm if used for calculations; editable profile value.
Weight	40 kg previously stated	Treat as historical until reconfirmed; use dated weigh-ins for trends.
Age	21 years previously stated	Confirm current age when relevant; do not rely on stale age.
Goal	Gain weight/mass	Use an explicit, configurable goal; do not maximise calories without limits.
Activity	Sedentary workdays; more active on weekends; walking commute mentioned	Use as a starting hypothesis; support updates.
Workout style	Calisthenics	Prioritise bodyweight movements and available equipment.
Equipment	Pull-up bar and dip bar	Do not require a gym or equipment not owned.
Supplements	Mass gainer and digestion pills mentioned	Track only products/doses confirmed by user; do not prescribe.

Health-related caution: if the previously stated weight and height remain accurate, the user may be significantly underweight. The app should avoid aggressive or medically prescriptive targets and recommend discussion with a qualified clinician or dietitian. It must not diagnose a cause or imply a supplement is necessary.

3. Food preferences and meal design

3.1 Food selection priorities

1. Respect dietary restrictions first: vegetarian, with eggs allowed.
2. Prefer familiar Indian meals and ingredients the user can reasonably obtain.
3. Use food already available at home when it fits the plan, especially perishables that should be used soon.
4. Prefer easy, repeatable meals and low preparation effort on busy days.
5. Consider cost and ingredient availability when ranking substitutions.
6. Consider nutritional adequacy and the user's tolerances before convenience or cost.
7. Offer variety where useful, but do not introduce unfamiliar or complicated meals just to make a plan look diverse.

3.2 Cooking effort and meal practicality

- Each recipe should identify complexity (easy, medium or hard) and, where possible, preparation time and active cooking time.
- A busy-day plan should favour quick meals, leftovers or simple assembly rather than several complex recipes.
- Make portions and ingredient quantities understandable in household units where appropriate, while storing normalised units for calculations.
- A suggested meal must not require unavailable ingredients unless clearly marked as items to buy.
- Allow substitutions without silently changing the dietary pattern.

3.3 Milk-based shakes and calorie-dense foods

Milk-based shakes have been part of the user's historical routine. The user has preferred shakes without oats and has previously used ingredients such as milk, bananas, peanuts/peanut butter, sugar and mass gainer. These are examples of prior preferences, not mandatory ingredients or a prescription.

- Do not include oats in shakes unless the user changes this preference.
- Keep shake recipes configurable by ingredient and quantity.
- Do not assume milk, peanut butter or mass gainer is always well tolerated; digestive symptoms have been reported with some combinations.
- Offer food-based alternatives and smaller or split servings when appropriate, without asserting a medical cause.
- Show estimated nutrition and clearly identify uncertain product-label values.

3.4 Food inventory must influence recommendations

- Use current stock and quantities when proposing meals.
- Distinguish in-stock items from shopping-list items.
- Track perishable quantities and, where supported, expiry or freshness information.
- Avoid duplicate inventory fields when one canonical record can represent the same fact.
- Do not treat a planned purchase as available until the user confirms it has been acquired.
- If inventory is incomplete, say so and provide an editable suggestion rather than inventing stock.

4. Meal timing and routine

An earlier routine mentioned a morning shake around 9:30 AM, lunch around 3 PM, dinner around 8 PM and a night shake around 11 PM. This is historical context, not a rigid schedule. The app should use the current routine confirmed by the user and actual logs.

Routine principle	Expected app behaviour
Flexible timing	Allow meals and reminders to move as work, sleep or social plans change.

Routine principle	Expected app behaviour
Realistic reminders	Use a manageable number; avoid repeatedly nagging after dismissal.
Missed meals	Offer a practical next step; do not recommend extreme compensation by default.
Eating out	Allow approximate logging and a flexible remaining-day plan without judgement.
Routine changes	Use recent confirmed schedules rather than historical times as permanent rules.

4.1 Day planning should be actionable

- Present a clear schedule with meal names, portions and preparation notes.
- Indicate which ingredients are available and which need purchasing.
- Allow meal swaps and regeneration of only the affected meal where practical.
- Preserve accepted choices unless the user requests a change.
- Avoid a long daily questionnaire when the app already has enough reliable context.

5. Nutrition personalisation rules

The application should help the user plan for weight gain, but nutrition targets must be configurable, transparent and cautious enough to avoid unsupported medical claims.

5.1 Targets and calculations

- Store targets separately from observed intake. A target is not proof of what was consumed.
- Use current confirmed profile inputs for estimates and label estimates clearly.
- Do not hardcode a universal calorie or protein target for all future situations.
- Explain assumptions used when estimating energy needs or evaluating progress.
- Allow targets to be adjusted based on sustained trends and, where appropriate, professional guidance.
- Do not encourage extreme intake, rapid weight gain or escalating supplement doses as a default response to missed targets.

5.2 Meal nutrition data

- Represent nutrients at recipe and serving level where practical.
- Record serving size, ingredient quantity and units so totals can be recalculated.
- Identify whether nutrition values come from a product label, food dataset, user entry or estimate.
- Use the user's supplied product label for packaged foods or mass gainers where possible.
- Do not display false precision when ingredient sizes, brands or preparation methods are unknown.

5.3 Progress interpretation

- Use trends across multiple weigh-ins rather than reacting to a single measurement.
- Recognise that short-term weight changes can reflect hydration, food volume and normal variation.
- Compare progress over suitable periods and show missing data or low confidence.
- Use logged intake and adherence as context, not grounds for blame.
- If progress is unexpectedly poor or symptoms are concerning, recommend professional advice rather than repeatedly increasing targets automatically.

6. Digestion and appetite tracking

The user has reported bloating in connection with some shake ingredients, including milk, peanut butter and mass gainer. The app should capture these observations in a structured, non-diagnostic way.

6.1 What to record

- Meal or shake consumed and approximate time.
- Ingredient and amount, when known.
- User-reported symptom, such as bloating or discomfort.
- Optional severity or impact using a simple consistent scale.
- Timing of the symptom relative to food, when the user can report it.
- Other relevant context the user chooses to record.

6.2 How to use observations

- Describe patterns as possible associations, not proof of causation.
- Do not diagnose lactose intolerance, food allergy, malabsorption or another condition.
- Do not automatically remove entire food groups or recommend supplements/medications based on a few entries.
- Allow the user to mark a record as uncertain or identify another possible cause.
- If symptoms are persistent, severe or worrying, encourage consultation with a qualified healthcare professional.

6.3 Keep tracking lightweight

Logging should be quick enough to sustain. Prefer optional structured choices and short notes over long daily questionnaires. Do not force every field to be completed before saving a meal or check-in.

7. Exercise and habit personalisation

The user's established preference is calisthenics, with a pull-up bar and dip bar available. Plans should be feasible with this equipment and bodyweight movements rather than assuming gym access.

- Support progressive, manageable workouts and record completed sessions separately from planned sessions.
- Consider recovery, soreness, sleep and schedule when suggesting training.
- Allow alternatives if equipment, ability or space is unavailable.
- Avoid assuming advanced ability or prescribing excessive volume without assessment.
- Support private habit tracking; a public leaderboard is not wanted.
- Make reminders adjustable and dismissible.
- Track supplements as user-entered products; do not prescribe them or assume safety.

8. Daily check-in and tracking behaviour

The application is intended to track weight and selected daily variables without overloading the user with subjective questions. Exact database columns must be confirmed in Document 03; the product behaviour should follow these rules.

Variable	Use in personalisation	Rule
Weight	Long-term trend and plan review	Date-stamped value with validated range and precision.
Sleep	Recovery and routine context	Use a simple, clearly defined input.
Soreness	Workout adjustment	Optional and consistently defined.
Digestion	User-reported tolerance patterns	Record observation; do not diagnose.
Appetite	Meal practicality feedback	Lightweight and optional if included.
Energy	Daily routine and training context	Use a consistent scale if collected.
Food intake	Actual consumption and nutrition totals	Derive from meal logs where possible; never from plan alone.

8.1 Avoid redundant and low-value data

- Do not create multiple fields that represent the same concept without a clear purpose.
- Do not require a generic 'feeling' field when specific variables already capture the information needed.
- Keep subjective fields clearly defined so a score means the same thing across days.
- Do not infer unrecorded values simply to fill a chart.
- Allow a check-in to be saved partially when some fields are unavailable.

9. Personalisation engine: decision order

When generating or adjusting a plan, use the following order of priority. A lower priority must not override a higher-priority constraint.

1. **Safety and hard constraints:** dietary restrictions, explicit exclusions, serious safety considerations and validated inputs.
2. **Current user intent:** the goal or change requested now.
3. **Current facts:** confirmed profile, available inventory, existing plan, meal logs and current schedule.
4. **Practicality:** preparation time, cost, familiar foods, equipment and realistic adherence.
5. **Nutrition goals:** configurable targets and reasonable meal balance, with uncertainty made visible.
6. **Historical patterns:** trends in weight, intake, digestion, sleep and adherence.
7. **Variety and optional optimisation:** refinements only when they do not conflict with higher priorities.

9.1 Do not let AI silently mutate records

- The AI may propose a plan; the app validates and presents it before saving when confirmation is required.
- An explicit request to log a known meal should use deterministic logging logic.
- Do not deduct inventory twice because the same command was retried.
- Do not rewrite historical logs to make them match a new plan.
- Make edits and corrections visible to the user.

10. Preferences that should be configurable

These settings should live in the app's profile or preferences layer rather than being hardcoded in prompts. The exact storage schema is a technical decision for Document 03.

Preference	Configuration	Default from known context
Dietary pattern	Selectable and editable	Vegetarian
Eggs	Allowed / not allowed	Allowed
Cuisine	Preferred cuisine and meals	Indian foods
Foods to avoid	User-maintained exclusions	No extra exclusions assumed
Shake preferences	Ingredient inclusion/exclusion and serving size	No oats in shakes unless changed
Cooking effort	Easy / medium / complex	Prefer easy
Budget	Editable cost sensitivity	Value-conscious
Meal timing	Editable schedule and reminders	Current confirmed routine
Equipment	Available equipment list	Pull-up bar and dip bar
Training	Training style and schedule	Calisthenics focus
Tracking burden	Optional fields and reminder settings	Keep routine simple

11. Examples of expected personalised behaviour

These examples describe intended behaviour, not a claim that every corresponding feature already exists.

Example A — Suggesting breakfast

When asked for breakfast, check the current plan, dietary preferences, known inventory and time available. Suggest a practical vegetarian option, mark missing ingredients and allow portion adjustment. Do not assume a food is in stock because it appeared in a past meal.

Example B — Logging food by voice

If the user says, “I ate three eggs,” treat it as an actual consumption event. Resolve important ambiguity, then use the meal-log workflow. Inventory changes must follow documented rules and must not be applied twice on retry. The event must not be stored only as a note on the meal plan.

Example C — Digestive discomfort after a shake

Record the reported symptom and known ingredients. Later, the app may show repeated associations, but it must not conclude that an ingredient caused the symptom or diagnose a condition.

Example D — Missed meals

Offer a practical next meal or revised remaining-day plan. Do not prescribe an excessive compensatory meal or frame the missed meal as failure.

Example E — Flat weight trend

Assess the amount and quality of data, adherence and time period first. Present review options; do not automatically make a large calorie increase based on a few weigh-ins.

12. Data quality and privacy

- Collect only personal information that supports an explicit feature or decision.
- Keep the profile private; do not expose it in public dashboards or unnecessary logs.
- Never put credentials or API secrets in profile data, prompts committed to Git or documentation.
- Label estimates, inferred patterns and AI suggestions so they are not confused with user-entered facts.
- Provide a correction path for inaccurate profile values and historical entries.
- Send no more personal context to an AI provider than the current task needs.
- Where practical, send a compact profile summary rather than the entire history.

13. Profile maintenance and updates

The profile must evolve as the user's circumstances change. The app should not require a code deployment to change a preference, schedule, equipment list or target that belongs in user settings.

1. When the user explicitly changes a preference, update the canonical profile value.
2. If a value affects an active plan, explain whether the plan needs regeneration.
3. Preserve historical records so trends remain interpretable; do not retroactively rewrite history unless correcting an error.
4. If an old value is no longer reliable, mark it stale or ask for confirmation at the next relevant point.
5. Update this document only when a durable preference or product rule changes; use the live profile for frequently changing values.

14. Acceptance criteria for personalisation

- Dietary preferences are applied consistently across meal suggestions and substitutions.
- The user can update relevant profile settings without editing source code.
- Stale measurements are not silently treated as current.
- Meal suggestions reflect current inventory when inventory data is available.
- The app distinguishes planned food from consumed food.
- Digestive observations are described cautiously and never used to diagnose.
- Historical weight changes are analysed as trends with missing data and uncertainty made visible.
- The system does not invent personal facts, stock, nutrient values or completed actions.
- Routine AI-provider failure does not prevent manual logging or reading saved data.
- Recommendations remain practical for the user's equipment, food preferences, preparation effort and budget.

15. Copy-ready instruction for the incoming AI

Use this document as the personalisation specification. Confirm time-sensitive measurements and profile details rather than assuming old values remain current. Keep preferences editable, separate facts from estimates and AI suggestions, respect the vegetarian-with-eggs preference and Indian-food focus, and plan practical meals from current inventory and schedule. Track digestion as user-reported observations, not diagnoses. Preserve the separation between meal plans and actual meal logs. Before changing code or schema, inspect the live implementation and record discrepancies. Do not hardcode values that belong in the user profile.

End of Document 02 • Next: Technical Architecture & Database