

# 1 Glint: VM image distribution in an OpenStack 2 multi-cloud environment

3 **A. Charbonneau, M. Conklin, R. Demarais, C. Driemel, I. Gable,**  
4 **C. Leavett-Brown, M. Paterson, R.J Sobie, R. Taylor**

5 University of Victoria, Victoria, Canada

6 E-mail: rsobie@uvic.ca

7 **Abstract.** The use of cloud computing is becoming widespread in the HEP community. In  
8 many instances, individual clouds are being federated to appear as a single infrastructure that  
9 can be connected, for example, to the WLCG. For a small number of clouds, it is relatively  
10 easy to manage the virtual machine images on all the sites. However, as the number of clouds  
11 increases, then keeping track of the images requires a more robust management system. Glint  
12 is designed to manage virtual machine images on OpenStack clouds. Glint makes it easy to  
13 distribute images on multiple clouds in a reliable and error free manner.

## 14 1. Introduction

15 The use of clouds in HEP is becoming a significant source of computing resources for MC  
16 production and data analysis. There are a number of compelling reasons for the migration to  
17 clouds: clouds give researchers quick and dynamic access to unused or opportunistic resources;  
18 sites find it easier to manage multiple project that have their own specific software requirements;  
19 and cloud technology is supported by a large international community of developers.

20 If a cloud site is colocated with other traditional HEP computing resources or the resource  
21 has been transformed to a cloud, then it can be viewed as another grid site on the WLCG.  
22 Utilizing opportunistic resources (private non-HEP or commercial) can be done by directly  
23 linking the cloud to the project workload management system (for example, VMDIRAC [1]).  
24 Alternatively, one can unify the clouds into a single infrastructure (“grid of clouds”). The  
25 HTCondor/CloudScheduler [2] or VAC/VCycle [3] were presented at this conference and are  
26 two methods for unifying clouds.


27 We have established a distributed cloud system using HTCondor/CloudScheduler for particle  
28 physics and astronomy applications [4, 5]. The distributed cloud is currently used by the ATLAS  
29 [6] and Belle-II [7] experiments. The system is designed to boot user or project-specific virtual  
30 machines (VM’s), making it easy to run HTC batch workloads from multiple projects.

31 The majority of the clouds today are using OpenStack software. OpenStack clouds require  
32 that a user boot an image from the local Glance repository. If a user wants to use multiple  
33 clouds, either manually or with our HTCondor/CloudScheduler system, then the image must  
34 be manually uploaded to the Glance repository of each cloud. Transferring VM images manually  
35 becomes tedious and error prone as one gets access to more IaaS clouds. We realized that we  
36 required a better way of managing the VM images and we developed Glint help us manage VM  
37 images over multiple OpenStack clouds.

The Glint service is designed for OpenStack clouds and the Glance repository with a pluggable architecture to allow support for different cloud types. Through a web browser or command-line interface, the user can identify clouds and control the distribution of images. Glint is currently used with the distributed cloud systems for ATLAS and Belle-II. In this paper, we describe the design and implementation of Glint. The source code is available from the Git repository [8].

## 2. Design

Glint is designed to operate as an OpenStack service. The glint service is comprised of 4 components. The service component, which actually pushes and pulls data from different Glance repositories; The GUI component, which provides a user friendly interface integrated with the OpenStack's Horizon dashboard; The Command Line Interface component, which allows users to try out glint without having to change or add another dashboard; And the Application Programming Interface, which allow developers to create their own tools. Figure ?? depicts a software component model of glint and it's integration with OpenStack.




**Figure 1.** Glint Software Components

There are 3 main services Glint provides; Glint allows users to create remote sites representing a remote glance repository; Glint users can add their remote repository credentials for Glint management; Finally, Glint uses a multithreaded manager to manage image distribution. Image management is the most complicated operation provided by Glint. Figure 2 depicts the process of moving an image between two sites.


Glint is designed around OpenStack's Keystone for user authentication. This design requires a user to have an openstack account on the site that Glint is using as its primary host. Therefore the user must login and register with Glint which will then use Keystone to check if the user is valid (c.f., Figure 3). If the user is valid, Keystone will generate an authentication token that the glint service maintains. User requests are then performed on behalf of glint using the token for authentication.

The concepts of remote OpenStack sites and remote site credentials is essential in the design of glint. Users can add remote sites as a source and destination of images. Site credentials can then be added so Glint can use the site without having to request input from the user everytime the site is accessed. Figure 4 depicts the user added a remote site to the glint service.


OpenStack's Glance service provides the image copying and deleting functionality. Glint relies on this service to move images around remote sites. Figure 5 depicts the image distribution process. It requires the user to select which images they want on each site, once the user is happy they can save the new configuration. Glint proceeds to create a new thread for each transfer or delete operation.



**Figure 2.** Image Distribution Design




**Figure 3.** Glint User Login



**Figure 4.** Glint - Create remote site and add remote credential

### 71 3. Implementation

72 Glint design and implementation is done within the OpenStack framework. There are 4 main  
 73 components that were developed and deployed to work with OpenStack. The image transfer



**Figure 5.** Glint - Reconfigure Image Distribution

component, the API, the CLI and the horizon webpage elements.

The image transfer component is an HTTP service that uses Openstack's Keystone and Glance services. The objective of the service is to integrate remote OpenStack clouds for the purposes of moving images seamlessly among them. The implementation is written in the python programming language and uses OpenStack's python APIs provided to use the Glance and Keystone services.

The API (Application Programming Interface) is written in python and provides users of the Glint service to construct their own applications ontop of Glint. There are plans to provide java and c/c++ APIs in the future.

The CLI (Command Line Interface) is written in python and uses the API. The CLI is the first application to use the Glint API. The CLI provides all the functionality that is provided by the modified Horizon dashboard.

The modified Horizon dashboard is a set of added webpages to provide a friendly user interface with the familiar Horizon dashboard. The pages are added to the images management tab that Horizon already provides.

The code for the 4 main components is managed within 2 Eclipse projects using the PyDev and Git plugins. The PyDev plugin understands the semantics of python and allows the GUI to provide proper functionality that is relavent for python development. The Git plugin allows the use of Git and GitHub as our versioning system to track changes and maintain the projects.

The first Eclipse project is a modified version of OpenStack's Horizon dashboard. This dashboard includes pages relevant to image distribution. Webpages in Horizon are described with python classes and use Django's powerful templating engine to provide a uniform presentation to the user.

The second Eclipse project includes the API, CLI and the image transfer service. These are all developed in python and can use either Django or Paste to serve HTTP requests. Django-PyDev plugin is used for the project and provides django related functions to manage the HTTP service componet of the software. An API is provided for python to extend the functionality of the Glint service. The CLI is the first extension of the service that uses the API. The CLI is written in python and takes advantage of the ArgParse python module. The CLI and the modified Horizon interface are the two methods currently offered to interact with the image distribution service. The CLI and the Horizon interface are independant of each other, for example you can use the service with the CLI without the modified Horizon dashboard.

## 4. Deployment

### 4.1. Service Deployment

It is recommended to deploy the glint service to the same secure machine that the Keystone and Glance services are running. This is because glint maintains a database of username, passwords and authentication tokens in its database. So it is important to keep glint on a secure machine. Once glint is installed, you can use it immediately via the CLI (aka glint client application).

Another deployment strategy is to also install the modified Horizon dashboard. This dashboard allows users to use the local OpenStack site to use the service to add remote sites specific for themselves (i.e., other OpenStack sites the user has credentials on).

### 4.2. Image Deployment

Figure 6 depicts a basic deployment of an image using Glint with 3 OpenStack sites. Each OpenStack site is independent and has their own user and tenant management. The credentials of each site is stored on Glint securely and used by the service when the image deployment needs to be changed.




Figure 6. An overview

Glint is available on PyDev as required for deployment via StackForge for OpenStack integration. The latest version is currently deployed for image distribution at the University of Victoria.

## References

- [1] VM dirac
- [2] Gable chep talk
- [3] VAC vcycle
- [4] HPCS cloud paper

- 128 [5] Sobie NYC talk
- 129 [6] Ryan CHEP talk
- 130 [7] Sobie Belle-II talk
- 131 [8] *Glint*, a system for managing VM images on multiple clouds. <https://github.com/hep-gc/glint>