

# F# Training

## Computation Expressions (CE)

2025 July



# Table of contents

---

- Intro
- Builder
- CE monoidal
- CE monadic
- CE applicative
- Creating CEs



# 1. Intro



# Presentation

1. Computation expressions in F# provide a convenient **syntax** for writing computations that can be sequenced and combined using control flow constructs and bindings.
2. Depending on the kind of computation expression, they can be thought of as a way to express monads, monoids, monad transformers, and applicatives  
→ **Functional patterns** seen previously, *except monad transformers* !

 [Learn F# - Computation Expressions](#), by Microsoft

Built-in CEs: `async` and `task`, `seq`, `query`

→ Easy to use, once we know the syntax and its keywords

We can write our own CE too

→ More challenging!

# Syntax

CE = block like `myCE { body }` where `body` looks like **imperative** F# code with:

- regular keywords: `let`, `do`, `if/then/else`, `match`, `for`...
- dedicated keywords: `yield`, `return`
- "banged" keywords: `let!`, `do!`, `match!`, `yield!`, `return!`

These keywords hide a “**machinery**” to perform background **specific** effects:

- Asynchronous computations like with `async` and `task`
- State management: e.g. a sequence with `seq`
- Absence of value with `option` CE
- ...

# 2. Builder



# Builder

A *computation expression* relies on an object called *Builder*.

⚠ This is not exactly the *Builder* OO design pattern.

For each supported **keyword** (`let!`, `return`...), the *Builder* implements one or more related **methods**.

👉 Compiler accepts **flexibility** in the builder **method signature**, as long as the methods can be **chained together** properly when the compiler evaluates the CE on the **caller side**.

- ✅ Versatile, ⚠ Difficult to design and to test
- Given method signatures illustrate only typical situations.

# Builder example: `logger {}`

Need: log the intermediate values of a calculation

```
// First version
let log value = printfn $"{value}"

let loggedCalc =
    let x = 42
    log x // ①
    let y = 43
    log y // ①
    let z = x + y
    log z // ①
    z
```

## Issues ⚠

- ① *Verbose*: the `log x` interfere with reading
- ② *Error prone*: easy to forget to log a value, or to log the wrong variable after a bad copy-paste-update...



# Builder example: `logger {}` (2)

💡 V2: make logs implicit in a CE by implementing a custom `let!` / `Bind()` :

```
type LoggingBuilder() =
    let log value = printfn $"{value}"; value
    member _.Bind(x, f) = x ▷ log ▷ f
    member _.Return(x) = x

let logger = LoggingBuilder()

// ---

let loggedCalc = logger {
    let! x = 42      // ➡ Implicitly perform `log x`
    let! y = 43      // ➡ `log y`
    let! z = x + y   // ➡ `log z`
    return z
}
```

# Builder example: `logger {}` (3)

The 3 consecutive `let!` are desugared into 3 **nested** calls to `Bind` with:

- 1st argument: the right side of the `let!` (e.g. `42` with `let! x = 42`)
- 2nd argument: a lambda taking the variable defined at the left side of the `let!` (e.g. `x`) and returning the whole expression below the `let!` until the `}`


```
// let! x = 42
logger.Bind(42, (fun x →
  // let! y = 43
  logger.Bind(43, (fun y →
    // let! z = x + y
    logger.Bind(x + y, (fun z →
      logger.Return z)
    ))
  ))
)
```

# Builder - Bind vs let!

`logger { let! var = expr in cexpr }` is desugared as:  
`logger.Bind(expr, fun var → cexpr)`

## 👉 Key points:


- `var` and `expr` appear in reverse order
- `var` is used in the rest of the computation `cexpr`  
→ highlighted using the `in` keyword of the verbose syntax
- the lambda `fun var → cexpr` is a **continuation** function



# CE desugaring: tips 💡

I found a simple way to desugar a computation expression:

→ Write a failing unit test and use [Unquote](#) - [Example](#)



```
3 open Swensen.Unquote
4 open Xunit
5 open Xunit.Abstractions
6
7 > type LoggerBuilder(logMessage: string → unit) = ...
14
15 type LoggerTests(output: ITestOutputHelper) =
16     [<Theory>]
17     [<InlineData("✓", 85)>]
18     [<InlineData("✗", 850)>]
19     member _.`3 Binds`(_, expected) =
20         test
21             <@ logger {
22                 let! x = 42
23                 let! y = 43
24                 let! z = x + y
25                 return z
26             } = expected @>
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
```

LoggerTests (2 tests) Failed: One or more child tests fail

3 Binds (2 tests) Failed: One or more child tests failed

3 Binds<String>(\_arg1: "✓", expected: 85) Success

3 Binds<String>(\_arg1: "✗", expected: 850) Failed

```
(fun builder@ -> builder@.Bind(42, (fun _arg2 -> let x = _arg2 in builder@.Bind(43, (fun _arg3 -> let y = _arg3 in builder@.Bind(x + y, (fun _arg4 -> let z = _arg4 in builder@.Return(z)))))) _).logger = expected
(fun builder@ -> builder@.Bind(42, (fun _arg2 -> let x = _arg2 in builder@.Bind(43, (fun _arg3 -> let y = _arg3 in builder@.Bind(x + y, (fun _arg4 -> let z = _arg4 in builder@.Return(z)))))) FSharpTraining.LoggerTests.logger = 850)
```

# Builder constructor parameter

The builder can be constructed with additional parameters.

→ The CE syntax allows us to pass these arguments when using the CE:

```
type LoggingBuilder(prefix: string) =  
    let log value = printfn $"{prefix}{value}"; value  
    member _.Bind(x, f) = x ▷ log ▷ f  
    member _.Return(x) = x  
  
let logger prefix = LoggingBuilder(prefix)  
  
// ---  
  
let loggedCalc = logger "[Debug] " {  
    let! x = 42      // ➡ Output "[Debug] 42"  
    let! y = 43      // ➡ Output "[Debug] 43"  
    let! z = x + y    // ➡ Output "[Debug] 85"  
    return z  
}
```

# Builder example: `option {}`

Need: successively try to find in maps by identifiers

→ Steps:

1. `roomRateId` in `policyCodesByRoomRate` map → `policyCode`
2. `policyCode` in `policyTypesByCode` map → `policyType`
3. `policyCode` and `policyType` → `result`

```
// 1: with match expressions → nesting!  
match policyCodesByRoomRate.TryFind(roomRateId) with  
| None → None  
| Some policyCode →  
    match policyTypesByCode.TryFind(policyCode) with  
    | None → None  
    | Some policyType → Some(buildResult policyCode policyType)
```

# Builder example: `option {}` (2)

```
// 2: with Option module helpers → terser but harder to read
policyCodesByRoomRate.TryFind(roomRateId)
▷ Option.bind (fun policyCode → policyCode, policyTypesByCode.TryFind(policyCode))
▷ Option.map (fun (policyCode, policyType) → buildResult policyCode policyType)
```



# Builder example: `option {}` (3)

```
// 3: with an option CE → both terse and readable 🎉

type OptionBuilder() =
    member _.Bind(x, f) = x ▷ Option.bind f
    member _.Return(x) = Some x


let option = OptionBuilder()

// ---

option {
    let! policyCode = policyCodesByRoomRate.TryFind(roomRateId)
    let! policyType = policyTypesByCode.TryFind(policyCode)
    return buildResult policyCode policyType
}
```




# 3. CE monoidal



# CE monoidal

A monoidal CE can be identified by the usage of `yield` and `yield!` keywords.  
→ The relationship with the monoid is not visible here but in the builder methods:

- `+` operation → `Combine` method
- `e` neutral element → `Zero` method



# CE monoidal builder methods

```
// Method      | Signature                                     | CE syntax supported
Yield          : T → M<T>                     ; yield x
YieldFrom      : M<T> → M<T>                 ; yield! xs
Zero           : unit → M<T>                  ; if // without `else` // Monoid neutral element
Combine        : M<T> * M<T> → M<T>           // Monoid + operation
Delay          : (unit → M<T>) → Delayed<T>   ; // always required with Combine
For            : seq<T> * (T → M<U>) → M<U>    ; for i in seq do yield ... ; for i = 0 to n do yield ...
               (* or *) seq<M<U>>

// Other additional methods
Run            : Delayed<T> → M<T>
While          : (unit → bool) * Delayed<T> → M<T> ; while cond do yield ...
TryWith        : M<T> → (exn → M<T>) → M<T>       ; try/with
TryFinally     : Delayed<T> * (unit → unit) → M<T> ; try/finally
```

1. We use the generic type notation `M<T>`, like we did for functional patterns.
2. Same for `Delayed<T>`, presented later 📌


# CE monoidal vs comprehension

- Similar syntax from caller perspective
- Distinct overlapping concepts

**Comprehension** is the concise, declarative syntax to build collections with ranges `start..end` and control flow keywords `if`, `for`, `while`...

Minimal set of methods expected for each:

- Monoidal CE: `Yield`, `Combine`, `Zero`
- Comprehension: `For`, `Yield`



# CE monoidal example: multiplication {} (1)

Let's build a CE that multiplies the integers yielded in the computation body:

→ CE type: `M<T> = int` · Monoid operation = `*` · Neutral element = `1`

```
type MultiplicationBuilder() =  
    member _.Zero() = 1  
    member _.Yield(x) = x  
    member _.Combine(x, y) = x * y  
    member _.Delay(f) = f () // eager evaluation  
  
    member m.For(xs, f) =  
        (m.Zero(), xs)  
        |> Seq.fold (fun res x → m.Combine(res, f x))  
  
let multiplication = MultiplicationBuilder()  
  
let shouldBe10 = multiplication { 5; 2 } // ➡ Implicit `yield`s // = 5 * 2  
let factorialOf5 = multiplication { for i in 2..5 → i } // 2 * 3 * 4 * 5
```

# CE monoidal example: multiplication {} (2)

Desugared `multiplication { 5; 2 }:`

```
// Original
let shouldBe10 =
  multiplication.Delay(fun () →
    multiplication.Combine(
      multiplication.Yield(5),
      multiplication.Delay(fun () →
        multiplication.Yield(2)
      )
    )
  )

// Simplified (without Delay)
let shouldBe10 =
  multiplication.Combine(
    multiplication.Yield(5),
    multiplication.Yield(2)
  )
```

# CE monoidal example: multiplication {} (3)

Desugared `multiplication { for i in 1..5 → i }:`

```
// Original
let factorialOf5 =
    multiplication.Delay (fun () →
        multiplication.For({1..5}, (fun _arg2 →
            let i = _arg2 in multiplication.Yield(i))
        )
    )

// Simplified
let factorialOf5 =
    multiplication.For({1..5}, (fun i → multiplication.Yield(i)))
```

# CE monoidal `Delayed<'t>` type (1/3)

`Delayed<'t>` represents a delayed computation and is used in these methods:

- `Delay` defines the CE `Delayed<'t>` as its return type
- `Combine`, `Run`, `While` and `Tryfinally` used it as input parameter

```
Delay      : thunk: (unit → M<T>) → Delayed<T>
Combine    : M<T> * Delayed<T> → M<T>
Run        : Delayed<T> → M<T>
While      : predicate: (unit → bool) * Delayed<T> → M<T>
TryFinally : Delayed<T> * finalizer: (unit → unit) → M<T>
```

- `Delay` is called with the current expression (of type `M<T>`) before each method taking a `Delayed<T>` argument
- `Delayed<T>` is internal to the CE → given `Delayed<T> ≠ M<T>`, `Run` is called at the end of the chain to get back the `M<T>`



# CE monoidal `Delayed<'t>` type (2/3)

👉 Enables to implement **laziness and short-circuiting** at the CE level.

Example: lazy `multiplication {}` with `Combine` optimized when `x = 0`

# CE monoidal `Delayed<'t>` type (3/3)

Difference	Eager	Lazy
<code>Delay</code> return type	<code>int</code>	<code>unit → int</code>
<code>Run</code>	Omitted	Required to get back an <code>int</code>
<code>Combine</code> 2nd parameter	<code>int</code>	<code>unit → int</code>
<code>For</code> calling <code>Delay</code>	Omitted	Explicit but not required

```
module Eager =
    type MultiplicationBuilder() =
        member _.Zero() = 1
        member _.Yield(x) = x
        member _.Delay(thunk: unit → int) = thunk () // eager evaluation
        member _.Combine(x, y) = x * y

        member m.For(xs, f) =
            (m.Zero(), xs) |> Seq.fold (fun res x → m.Combine(res, f x))
```

```
module Lazy =
    type MultiplicationBuilder() =
        member _.Zero() = 1
        member _.Yield(x) = x
        member _.Delay(thunk: unit → int) = thunk // lazy evaluation
        member _.Run(delayedX: unit → int) = delayedX()

        member _.Combine(x: int, delayedY: unit → int) : int =
            match x with
            | 0 → 0 // short-circuit for multiplication by zero
            | _ → x * delayedY()

        member m.For(xs, f) =
            (m.Zero(), xs) |> Seq.fold (fun res x → m.Combine(res, m.Delay(fun () → f x)))
```

# CE monoidal to generate a collection (1/4)

`multiplication {}` returns an `int` from possibility multiple yielded ints.


≠ `seq {}` returns a `'t seq` from any number of yielded value of type `t`

→ It's a more common use case for a monoidal CE.

💡 Let's build a `list {}` monoidal CE!

# CE monoidal to generate a collection (2/4)

Let's test the CE to generate the list `[begin; 16; 9; 4; 1; 2; 4; 6; 8; end]`  
(Desugared code simplified)




```
list {  
  yield "begin"  
  for i in -4..4 do  
    if i < 0 then yield $"{i * i}"  
    elif i > 0 then yield $"{2 * i}"  
  yield "end"  
}
```

```
list.Delay (fun () →  
  list.Combine(  
    list.Yield "begin",  
    list.Delay (fun () →  
      list.Combine(  
        list.For({-4..4}, (fun i →  
          if i < 0 then list.Yield $"{i * i}"  
          elif i > 0 then list.Yield $"{2 * i}"  
          else list.Zero()  
        )),  
        list.Delay (fun () →  
          list.Yield "end"  
        )  
      )  
    )  
  )  
)
```

# CE monoidal to generate a collection (3/4)

Comparison with the same expression in a regular list:



```
[
  yield "begin"
  for i in -4..4 do
    if i < 0 then yield "${i * i}"
    elif i > 0 then yield "${2 * i}"
  yield "end"
]
```

```
Seq.delay (fun () →
  Seq.append
    (Seq.singleton "begin")
    (Seq.delay (fun () →
      Seq.append
        (
          {-4..4} : int seq
          ▷ Seq.collect (fun i →
            if i < 0 then Seq.singleton "${i * i}"
            elif i > 0 then Seq.singleton "${2 * i}"
            else Seq.empty
          ) : string seq
        )
        (Seq.delay (fun () →
          Seq.singleton "end"
        ))
      )
    )
  )
) : string seq
▷ Seq.toList : string list
```

# CE monoidal to generate a collection (4/4)

`list { expr }` vs `[ expr ]`:

- `[ expr ]` uses a hidden `seq` all through the computation and ends with a `toList`
- All methods are inlined:

Method	<code>list { expr }</code>	<code>[ expr ]</code>
Combine	<code>xs @ ys ⇒ List.append</code>	<code>Seq.append</code>
Yield	<code>[x] ⇒ List.singleton</code>	<code>Seq.singleton</code>
Zero	<code>[] ⇒ List.empty</code>	<code>Seq.empty</code>
For	<code>Seq.collect</code> & <code>Seq.toList</code>	<code>Seq.collect</code>


# 4. CE monadic



# CE monadic

A monadic CE can be identified by the usage of `let!` and `return` keywords, revealing the monadic `bind` and `return` operations.

Behind the scene, builders of these CE should/can implement these methods:






# CE monadic vs CE monoidal (1/2)

## **Return** (monad) vs **Yield** (monoid)

- Same signature:  $T \rightarrow M<T>$
- A series of **return** is not expected  
→ Monadic **Combine** takes only a monadic command **M<unit>** as 1st param
- CE enforces appropriate syntax by implementing 1! of these methods:
  - **seq {}** allows **yield** but not **return**
  - **async {}**: vice versa



# CE monadic vs CE monoidal (2/2)

## For and While

Method	CE	Signature
For	Monoidal	$\text{seq}\langle T \rangle * (T \rightarrow M\langle U \rangle) \rightarrow M\langle U \rangle \text{ or } \text{seq}\langle M\langle U \rangle \rangle$
	Monadic	$\text{seq}\langle T \rangle * (T \rightarrow M\langle \text{unit} \rangle) \rightarrow M\langle \text{unit} \rangle$
While	Monoidal	$(\text{unit} \rightarrow \text{bool}) * \text{Delayed}\langle T \rangle \rightarrow M\langle T \rangle$
	Monadic	$(\text{unit} \rightarrow \text{bool}) * (\text{unit} \rightarrow M\langle \text{unit} \rangle) \rightarrow M\langle \text{unit} \rangle$

👉 ≠ use cases:

- Monoidal: Comprehension syntax
- Monadic: Series of effectful commands

# CE monadic and delayed

Like monoidal CE, monadic CE can use a `Delayed<'t>` type.  
→ Impacts on the methods signature:



# CE monadic examples (1/2)

👉 The initial CE studied—`logger {}` and `option {}`—was monadic.

**Other example:** `result {}` CE handling:

- `if` w/o `else` → `Zero`
- `do! command` → `Combine`
- lazy evaluation → `Delay`, `Run`

# CE monadic examples (2/2)



# CE monadic: FSharpPlus monad CE

FSharpPlus provides a monad CE

- Works for all monadic types: Option, Result, ... and even Lazy 🎉
- Supports monad stacks with monad transformers !

## ! Limits:

- Confusing: the monad CE has 4 flavours to cover all cases: delayed or strict, embedded side-effects or not
- Based on SRTP: can be very long to compile!
- Documentation not exhaustive, relying on Haskell knowledges
- Very Haskell-oriented: not idiomatic F#

# Monad stack, monad transformers

A monad stack is a composition of different monads.

→ Example: `Async` + `Option`.

How to handle it?

→ Academic style vs idiomatic F#

## 1. Academic style (with FSharpPlus)

Monad transformer (here `MaybeT`)

→ Extends `Async` to handle both effects

→ Resulting type: `MaybeT<Async<'t>>`

- ✓ reusable with other inner monad
- ✗ less easy to evaluate the resulting value
- ✗ not idiomatic





# Monad stack, monad transformers (2)

## 2. Idiomatic style

Custom CE `asyncOption`, based on the `async` CE, handling `Async<Option<'t>>` type



⚠ Limits: not reusable, just copiable for `asyncResult` for instance



# 5. <sup>CE</sup> Applicative



# CE Applicative

An applicative CE is revealed through the usage of the `and!` keyword (*F# 5*).

An applicative CE builder is special compared to monoidal and monadic CE builders:

- Not following the definition of the applicative: no method matching `apply`
- Based on `MergeSources: M<'T1> * M<'T2> → M<'T1 * 'T2>`
- Fine tuning with `BindNReturn` method matching the `mapN` functions,  $N \geq 2$


# CE Applicative example

[FsToolkit.ErrorHandling](#) offers:

- Type `Validation<'Ok, 'Err> ≡ Result<'Ok, 'Err list>`
- CE `validation {}` supporting `let! ... and! ...` syntax.

Allows errors to be accumulated in use cases like:

- Parsing external inputs
- *Smart constructor (example on the next slide...)*



# CE Applicative example (2)



# 6. Creating CEs



# Types

The CE builder methods definition can involve not 2 but 3 types:

- The wrapper type `M<T>`
- The `Delayed<T>` type
- An `Internal<T>` type



# `M<T>` wrapper type


👉 We use the generic type notation `M<T>` to indicate any of these aspects: generic or container.

Examples of candidate types:

- Any generic type
- Any monoidal, monadic, or applicative type
- `string` as it contains `char`s
- Any type itself as `type Identity<'t> = 't` – see previous `logger {}` CE

# Delayed<T> type

- Return type of `Delay`
- Parameter to `Run`, `Combine`, `While`, `TryWith`, `TryFinally`
- Default type when `Delay` is not defined: `M<T>`
- Common type for a real delay: `unit → M<T>` - see `member _.Delay f = f`





# `Delayed<T>` type example: `eventually {}`

Union type used for both wrapper and delayed types:



# Delayed<T> type example: eventually {} (2)

The output values are maintained to be evaluated interactively, step by step:



# Internal<T> type

`Return`, `ReturnFrom`, `Yield`, `YieldFrom`, `Zero` can return a type internal to the CE.  
`Combine`, `Delay`, and `Run` handle this type.

💡 Highlights the usefulness of `ReturnFrom`, `YieldFrom`, implemented as an *identity* function until now.

# Builder methods without type (1)

— *Another trick regarding types* —

Any type can be turned into a CE by adding builder methods as extensions.

Example: `activity {}` CE to configure an `Activity` without passing the instance

- Type with builder extension methods: `System.Diagnostics.Activity`
- Return type: `unit` (no value returned)
- Internal type involved: `type ActivityAction = delegate of Activity → unit`
- CE behaviour:
  - monoidal internally: composition of `ActivityAction`
  - like a `State` monad externally, with only the setter(s) part

# Builder methods without type (2)



# Builder methods without type (3)

- The `activity` instance supports the CE syntax thanks to its extensions.
- The extension methods are marked as not `EditorBrowsable` for proper DevExp.
- Externally, the `activity` is implicit in the CE body, like a `State` monad.
- Internally, the state is handled as a composition of `ActivityAction`.
- The final `Run` enables us to evaluate the built `ActivityAction`, resulting in the change (mutation) of the `activity` (the side effect).

# CE creation guidelines

- Choose the main **behaviour**: monoidal? monadic? applicative?
  - Prefer a single behaviour unless it's a generic/multi-purpose CE
- Create a **builder** class
- Implement the main **methods** to get the selected behaviour
- Use/Test your CE to verify it compiles (*see typical compilation errors below*), produces the expected result, performs well.



# CE creation tips 💡

- Overload methods to support more use cases like different input types
  - `Async<Return<_,_>>` + `Async<_>` + `Result<_,_>`
  - `Option<_>` and `Nullable<_>`
- Get inspired by the existing codebases that provide CEs
  - e.g. Tips found in [FsToolkit/OptionCE.fs](#):
    - Undocumented `Source` methods
    - Force the method overload order with extension methods
      - to get a better code completion assistance.

[🔗 Computation Expressions Workshop: 6 - Extensions | GitHub](#)



# Custom operations

What: builder methods annotated with `[<CustomOperation("myOperation")>]`

Use cases: add new keywords, build a custom DSL

→ Example: the `query` core CE supports `where` and `select` keywords like LINQ


**⚠ Warning:** you may need additional things that are not well documented:

- Additional properties for the `CustomOperation` attribute:
  - `AllowIntoPattern`, `MaintainsVariableSpace`
  - `IsLikeJoin`, `IsLikeGroupJoin`, `JoinConditionWord`
  - `IsLikeZip`...
- Additional attributes on the method parameters, like `[<ProjectionParameter>]`

[!\[\]\(e3f8612927870f2e0f9f5989e6dd3064\_img.jpg\) Computation Expressions Workshop: 7 - Query Expressions | GitHub](#)

# CE benefits

- **Increased Readability:** imperative-like code
- **Reduced Boilerplate:** hides a "machinery"
- **Extensibility:** we can write our own "builder" for specific logic



# CE limits ⚠️

- **Compiler error messages** within a CE body can be cryptic
- **Nesting different CEs** can make the code more cumbersome
  - E.g. `async` + `result`
  - Alternative: custom combining CE - see `asyncResult` in [FsToolkit](#)
- Writing our own CE can be **challenging**
  - Implementing the right methods, each the right way
  - Understanding the underlying concepts

# Other CEs

We've seen 2 libraries that extend F# and offer their CEs:

- FSharpPlus → `monad`
- FsToolkit.ErrorHandling → `option`, `result`, `validation`

Many libraries have their own DSL (*Domain Specific Language*).  
Some are based on computation expression(s):

- [Expecto](#): Testing library (`test "..." { ... }`)
- [Farmer](#): Infra as code for Azure (`storageAccount { ... }`)
- [Saturn](#): Web framework on top of ASP.NET Core (`application { ... }`)

# 7. Wrap up





# Computation expression (CE)

- Syntactic sugar: inner syntax: standard or "banged" (`let!`)  
→ Imperative-like • Easy to use
- CE is based on a *builder*
  - instance of a class with standard methods like `Bind` and `Return`
- *Separation of Concerns*
  - Business logic in the CE body
  - Machinery behind the scene in the CE builder
- Little issues for nesting or combining CEs
- Underlying functional patterns: monoid, monad, applicative
- Libraries: FSharpPlus, FsToolkit, Expecto, Farmer, Saturn...



# Additional resources

- [Code examples in FSharpTraining.sln](#) —Romain Deneau
- [\*The "Computation Expressions" series\*](#) —F# for Fun and Profit
- [All CE methods | Learn F#](#) —Microsoft
- [Computation Expressions Workshop](#)
- [The F# Computation Expression Zoo](#) —Tomas Petricek and Don Syme
  - [Documentation | Try Joinads](#) —Tomas Petricek
- Extending F# through Computation Expressions:  [Video](#) •  [Article](#)

Thanks 🙏

