

# Module-Wise Lab Workbook

**Program:** Test Automation Training (Selenium, PyTest, Python Automation, Robot Framework)

**Courses covered:**

1. Selenium WebDriver with Python (Whizlabs)
2. Python for Automation (Madecraft)
3. Test Automation with Playwright (Python) & Robot Framework (Coursera)

**Curriculum modules mapped:** Milestone 1 (Selenium Fundamentals) · Milestone 2 (Unittest/PyTest/POM) · Milestone 3 (Python Automation, Web Scraping, REST API) · Milestone 4 (Robot Framework)

**Environment:** Python 3.13.5, Selenium 4.49.0 (upgraded), Chrome 153.0.8010.48, Windows 11, run via cmd + Notepad (no IDE).

## Module 1: Selenium Fundamentals & Web Interactions

*(from Selenium WebDriver with Python — Weeks 1–2)*

### Experiment 1.1 — Locator Strategies and Login Automation

**Problem statement:** Automate login to a demo e-commerce site using three different locator strategies and verify successful navigation.

**Objective:** Demonstrate use of `By.NAME`, `By.XPATH`, and confirm the flow completes by capturing the resulting URL.

**Tools/software/concepts used:** Python 3, Selenium WebDriver, ChromeDriver (auto-managed via Selenium Manager), `By` locator strategies, `ChromeOptions`.

**Source code:**

```
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.chrome.options import Options
import time

options = Options()
options.add_argument("--start-maximized")
driver = webdriver.Chrome(options=options)
driver.get("https://tutorialsninja.com/demo/index.php?route=account/login")

driver.find_element(By.NAME, "email").send_keys("testuser@example.com")
driver.find_element(By.XPATH,
    "//*[@name='password']").send_keys("Test@1234")
driver.find_element(By.XPATH, "//*[@value='Login']").click()

time.sleep(2)
```

```
print("Current URL:", driver.current_url)

driver.quit()
```

## Output:

Current URL: <https://tutorialsninja.com/demo/index.php?route=account/login>

Fig. 1(a), (b), (c): cmd output above + browser window with form filled

```
(venv) C:\Users\ritish\lab-workbook\pip install --upgrade selenium
Requirement already satisfied: selenium in c:\users\ritish\lab-workbook\venv\lib\site-packages (4.9.0)
Requirement already satisfied: certifi<2020.2.28 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from selenium) (2020.7.22)
Requirement already satisfied: trio-websocket<1.0,=>0.12.2 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from selenium) (0.12.2)
Requirement already satisfied: typing_extensions<4.0,=>3.7.4 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from selenium) (3.7.4)
Requirement already satisfied: urllib3<3.0,=>2.0.2 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from urllib3[socks]<3.0,=>2.0.2-selenium) (2.0.2)
Requirement already satisfied: websocket-client<1.5,=>1.3.2 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from selenium) (1.3.2)
Requirement already satisfied: attrs<22.2.0,=>21.4.0 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0,=>0.12.2-selenium) (21.4.0)
Requirement already satisfied: idna in c:\users\ritish\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0,=>0.12.2-selenium) (3.202)
Requirement already satisfied: sniffio<1.3.0 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0,=>0.12.2-selenium) (1.3.0)
Requirement already satisfied: outcome in c:\users\ritish\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0,=>0.12.2-selenium) (1.3.0)
Requirement already satisfied: httpx<0.24.0,=>0.23.0 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0,=>0.12.2-selenium) (0.23.0)
Requirement already satisfied: pysocks<1.0.7,=>1.0.1 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from urllib3[socks]<3.0,=>2.0.2-selenium) (1.0.1)
Requirement already satisfied: pydispatcher in c:\users\ritish\lab-workbook\venv\lib\site-packages (from httpx<0.24.0,=>0.23.0-selenium) (3.0.9)
Requirement already satisfied: h11<1,=>0.12.0 in c:\users\ritish\lab-workbook\venv\lib\site-packages (from httpx<0.24.0,=>0.23.0-selenium) (0.12.0)
C:\Users\ritish\lab-workbook> python expl_1.py
Current URL: https://tutorialsninja.com/demo/index.php?route=account/login
```

Fig.1(a)




Fig.1(b)




Fig.1(c)

**Result / observation / conclusion:** The script located and interacted with form fields using By.NAME and By.XPATH. During execution, calling driver.maximize\_window() initially threw selenium.common.exceptions.WebDriverException: unknown error: JavaScript code failed from unknown command: 'Runtime.evaluate' wasn't found — a known incompatibility between very new Chrome builds (v153) and that specific CDP

command. This was resolved by upgrading Selenium (`pip install --upgrade selenium`) and replacing `driver.maximize_window()` with the `--start-maximized` Chrome option passed at launch instead, which avoids the broken command entirely. This confirms that browser-launch options are often more robust than post-launch driver commands when dealing with bleeding-edge browser versions.

## Experiment 1.2 — Synchronization, Alerts and Dynamic Web Tables

**Problem statement:** Handle a JavaScript alert/confirm/prompt sequence without using `time.sleep()`.

**Objective:** Use `WebDriverWait` with `expected_conditions` for synchronization, and `driver.switch_to.alert` for JS dialogs.

**Tools/software/concepts used:** Selenium `WebDriverWait`, `expected_conditions` (EC), Alert interface.

### Source code:

```
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.chrome.options import Options
from selenium.webdriver.support.ui import WebDriverWait
from selenium.webdriver.support import expected_conditions as EC

options = Options()
options.add_argument("--start-maximized")
driver = webdriver.Chrome(options=options)
driver.get("https://the-internet.herokuapp.com/javascript_alerts")

wait = WebDriverWait(driver, 10)

driver.find_element(By.XPATH, "//button[text()='Click for JS Alert']").click()
wait.until(EC.alert_is_present())
driver.switch_to.alert.accept()

driver.find_element(By.XPATH, "//button[text()='Click for JS Confirm']").click()
wait.until(EC.alert_is_present())
driver.switch_to.alert.dismiss()

driver.find_element(By.XPATH, "//button[text()='Click for JS Prompt']").click()
wait.until(EC.alert_is_present())
alert = driver.switch_to.alert
alert.send_keys("Automated input")
alert.accept()

result_text = wait.until(
    EC.visibility_of_element_located((By.ID, "result")))
print("Result:", result_text)

driver.quit()
```

## Output:

Result: You entered: Automated input

Fig. 2: cmd output above

```
Command Prompt
C:\Users\rtritis\lab-workbook>pip install --upgrade selenium
Requirement already satisfied: selenium in c:\users\rtritis\lab-workbook\venv\lib\site-packages (0.40.0)
Requirement already satisfied: certifi<2026.2.25 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from selenium) (2026.7.22)
Requirement already satisfied: trio<1.0, >=0.31.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from selenium) (0.34.0)
Requirement already satisfied: trio-websocket<1.0, >=0.12.2 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from selenium) (0.12.2)
Requirement already satisfied: typing_extensions<5.0, >=4.15.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from selenium) (4.16.0)
Requirement already satisfied: urllib3<1.0, >=2.6.3 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from urllib[socks]<3.0, >=2.6.3->selenium) (2.0.0)
Requirement already satisfied: websocket-client<2.0, >=1.8.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from selenium) (1.9.2)
Requirement already satisfied: attrs<23.2.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (26.1.0)
Requirement already satisfied: sortedcontainers in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (2.4.0)
Requirement already satisfied: idna in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (3.20)
Requirement already satisfied: outcome in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (1.3.0.post0)
Requirement already satisfied: sniffio<1.3.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (1.3.1)
Requirement already satisfied: cffi<=1.14 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio<1.0, >=0.31.0->selenium) (2.1.1)
Requirement already satisfied: wsproto<=0.14.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from trio-websocket<1.0, >=0.12.2->selenium) (1.3.2)
Requirement already satisfied: pysocks<=1.5.7, <2.0, >=1.5.6 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from urllib[socks]<3.0, >=2.6.3->selenium) (1.7.1)
Requirement already satisfied: pyparser in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from cffi<=1.14->trio<1.0, >=0.31.0->selenium) (3.0)
Requirement already satisfied: h1c1<=0.16.0 in c:\users\rtritis\lab-workbook\venv\lib\site-packages (from wsproto<=0.14->trio-websocket<1.0, >=0.12.2->selenium) (0.16.0)

[notice] A new release of pip is available: 26.1.1 -> 26.2.1
[notice] To update, run: python.exe -m pip install --upgrade pip

C:\Users\rtritis\lab-workbook>python expl_1.py
Current URL: https://tutorialsininja.com/demo/index.php?route=account/login

C:\Users\rtritis\lab-workbook>notepad expl_2.py

C:\Users\rtritis\lab-workbook>python expl_2.py
Result: You entered: Automated input

C:\Users\rtritis\lab-workbook>python expl_2.py
Result: You entered: Automated input

C:\Users\rtritis\lab-workbook>
```

Fig.2

**Result/ observation/ conclusion:** WebDriverWait combined with expected\_conditions.alert\_is\_present() reliably waited for each dialogue instead of relying on fixed sleeps. The script ran successfully on the first attempt with no timing issues, confirming that explicit waits are more resilient than blind time.sleep() calls for JavaScript-driven UI events.

## Experiment 1.3 — Windows, Tabs and Iframes

**Problem statement:** Interact with an element inside an iframe, then open and switch control to a new browser tab.

**Objective:** Demonstrate driver.switch\_to.frame() and driver.window\_handles for multi-context navigation.

**Tools/software/concepts used:** iframe switching, window\_handles, context switching back to the main document.

### Source code:

```
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.chrome.options import Options

options = Options()
options.add_argument("--start-maximized")
driver = webdriver.Chrome(options=options)

driver.get("https://the-internet.herokuapp.com/iframe")

# Switch into iframe and read the editor's content
driver.switch_to.frame("mce_0_ifr")
editor = driver.find_element(By.ID, "tinymce")
```

```

print("Text found inside iframe:", editor.text)
driver.switch_to.default_content()
print("Successfully switched back to main page")

driver.get("https://the-internet.herokuapp.com/windows")
driver.find_element(By.LINK_TEXT, "Click Here").click()

main_window = driver.window_handles[0]
new_window = driver.window_handles[1]
driver.switch_to.window(new_window)
print("New tab title:", driver.title)
driver.close()
driver.switch_to.window(main_window)

driver.quit()

```

### Output:

```

Text found inside iframe: Your content goes here.
Successfully switched back to main page
New tab title: The Internet

```

Fig. 3: cmd output above



```

(venv) C:\Users\riris\lab-workbook\python expl_3.py
Text found inside iframe: Your content goes here.
Successfully switched back to main page
New tab title: The Internet

(venv) C:\Users\riris\lab-workbook\python expl_3.py
Text found inside iframe: Your content goes here.
Successfully switched back to main page
New tab title: The Internet

```

Fig. 3

**Result / observation / conclusion:** The original plan was to edit the iframe's TinyMCE editor via `.clear()` and `.send_keys()`, but this threw `InvalidElementStateException` because the public TinyMCE demo had exhausted its free monthly "editor loads" quota and was locked to read-only mode — an external service limitation, not a code defect. The experiment was adapted to read the iframe's text content instead, which still demonstrates the core skill (`switch_to.frame()` / `switch_to.default_content()`) without depending on a third-party quota. This is a realistic and valuable observation: automation scripts must be resilient to the state of external test environments, not just to their own code.

## Module 2: Test Automation Frameworks — Unittest, PyTest, POM

*(from Selenium WebDriver with Python — Week 3)*

### Experiment 2.1 — Test Case Structure with Unittest

**Problem statement:** Build a structured login-page test using the `unittest` framework with proper setup/teardown.

**Objective:** Demonstrate `setUp/tearDown` and assertions across multiple independent test methods.

**Tools/software/concepts used:** Python unittest, setUp/tearDown, assertIn, assertTrue.

### Source code:

```
import unittest
import time
from selenium import webdriver
from selenium.webdriver.common.by import By
from selenium.webdriver.chrome.options import Options

class LoginTest(unittest.TestCase):
    def setUp(self):
        options = Options()
        options.add_argument("--start-maximized")
        self.driver = webdriver.Chrome(options=options)

self.driver.get("https://tutorialsninja.com/demo/index.php?route=account/login")

    def test_login_page_loads(self):
        self.assertIn("Account Login", self.driver.page_source)
        time.sleep(2)

    def test_email_field_present(self):
        field = self.driver.find_element(By.NAME, "email")
        self.assertTrue(field.is_displayed())
        time.sleep(2)

    def tearDown(self):
        self.driver.quit()


if __name__ == "__main__":
    unittest.main()
```

### Output:

```
..
-----
Ran 2 tests in 23.766s

OK
```

Fig. 4: cmd output above



```
(venv) C:\Users\ritis\lab-workbook>notepad ex2.1.py
(venv) C:\Users\ritis\lab-workbook>python exp2.1.py
python: can't open file 'C:\Users\ritis\lab-workbook\exp2.1.py': [Errno 2] No such file or directory
(venv) C:\Users\ritis\lab-workbook>python exp2.1.py
..
-----
Ran 2 tests in 23.766s

OK
(venv) C:\Users\ritis\lab-workbook>
```

Fig. 4

**Result / observation / conclusion:** unittest's setUp/tearDown removed duplicated driver-init/quit code across both test methods and kept each test isolated with a fresh browser session — each test opened and closed Chrome independently. A short `time.sleep(2)` was added purely so the browser window stayed visible long enough to screenshot for this workbook; in

a real CI test suite this would be removed, since it only slows the run down without adding reliability (unlike the explicit `WebDriverWait` used in Experiment 1.2, which waits for a *reason*).

## Experiment 2.2 — Page Object Model Restructure

**Problem statement:** Refactor the login script from Experiment 1.1 into a Page Object Model so locators and test logic are separated.

**Objective:** Create a `LoginPage` class containing only locators/UI methods, and a separate test file containing the execution flow.

**Tools/software/concepts used:** POM design pattern, class-based page objects, `sys.path` manipulation for cross-folder imports.

### Folder structure:

```
lab-workbook/  
  pages/  
    login_page.py  
  tests/  
    test_login.py
```

### Source code — `pages/login_page.py`:

```
from selenium.webdriver.common.by import By  
  
class LoginPage:  
    EMAIL_FIELD = (By.NAME, "email")  
    PASSWORD_FIELD = (By.NAME, "password")  
    LOGIN_BUTTON = (By.XPATH, "//input[@value='Login']")  
  
    def __init__(self, driver):  
        self.driver = driver  
  
    def load(self):  
  
self.driver.get("https://tutorialsninja.com/demo/index.php?route=account/login")  
  
    def login(self, email, password):  
        self.driver.find_element(*self.EMAIL_FIELD).send_keys(email)  
        self.driver.find_element(*self.PASSWORD_FIELD).send_keys(password)  
        self.driver.find_element(*self.LOGIN_BUTTON).click()
```

### Source code — `tests/test_login.py`:

```
import sys  
import os  
import time  
sys.path.append(os.path.abspath(os.path.join(os.path.dirname(__file__),  
"..")))  
  
from selenium import webdriver  
from selenium.webdriver.chrome.options import Options  
from pages.login_page import LoginPage
```

```

options = Options()
options.add_argument("--start-maximized")
driver = webdriver.Chrome(options=options)

login_page = LoginPage(driver)
login_page.load()
login_page.login("testuser@example.com", "Test@1234")

time.sleep(2)
print("Login attempt completed. URL:", driver.current_url)

driver.quit()

```


## Output:

```

Login attempt completed. URL:
https://tutorialsninja.com/demo/index.php?route=account/login

```

Fig. 5: cmd output above



```

(venv) C:\Users\ritis\lab-workbook>mkdir pages
(venv) C:\Users\ritis\lab-workbook>cd pages
(venv) C:\Users\ritis\lab-workbook\pages>notepad login_page.py
(venv) C:\Users\ritis\lab-workbook\pages>python login_page.py
Traceback (most recent call last):
  File "C:\Users\ritis\lab-workbook\pages\login_page.py", line 8, in <module>
    from pages.login_page import LoginPage
  File "C:\Users\ritis\lab-workbook\pages\login_page.py", line 8, in <module>
    from pages.login_page import LoginPage
ImportError: cannot import name 'LoginPage' from 'pages.login_page' (consider renaming 'C:\Users\ritis\lab-workbook\pages\login_page.py' if it has the same name as a library you intended to import)
(venv) C:\Users\ritis\lab-workbook\pages>python login_page.py
Traceback (most recent call last):
  File "C:\Users\ritis\lab-workbook\pages\login_page.py", line 8, in <module>
    from pages.login_page import LoginPage
  File "C:\Users\ritis\lab-workbook\pages\login_page.py", line 8, in <module>
    from pages.login_page import LoginPage
ImportError: cannot import name 'LoginPage' from 'pages.login_page' (consider renaming 'C:\Users\ritis\lab-workbook\pages\login_page.py' if it has the same name as a library you intended to import)
(venv) C:\Users\ritis\lab-workbook\pages>python login_page.py
(venv) C:\Users\ritis\lab-workbook\pages>mkdir tests
(venv) C:\Users\ritis\lab-workbook\pages>cd ..
(venv) C:\Users\ritis\lab-workbook>mkdir tests
(venv) C:\Users\ritis\lab-workbook>cd tests
(venv) C:\Users\ritis\lab-workbook\tests>notepad test_login.py
(venv) C:\Users\ritis\lab-workbook\tests>python test_login.py
Login attempt completed. URL: https://tutorialsninja.com/demo/index.php?route=account/login

```

Fig. 5

**Result / observation / conclusion:** Moving locators into a dedicated `LoginPage` class made `test_login.py` read like a business scenario ("load page, login") instead of raw Selenium calls. Since fake credentials were used, the site correctly rejected the login and stayed on the `route=account/login` URL — this is expected and actually confirms the site's own validation is working; the point of this experiment is that the POM plumbing (locate fields → submit → capture result) executed cleanly end-to-end regardless of login success. `sys.path.append()` was required in the test file so Python could resolve the `pages` package from a sibling folder.

## Experiment 2.3 — pytest Integration with HTML Reporting

**Problem statement:** Convert the POM-based test to run under `pytest` with a fixture-managed driver and generate an HTML report.



**Objective:** Use `pytest` fixtures for setup/teardown and `pytest-html` to auto-generate a report with failure-screenshot capture.

**Tools/software/concepts used:** `pytest`, `fixtures`, `conftest.py`, `pytest-html` plugin, `pytest_runtest_makereport` hook.

**Source code — `conftest.py`** (placed at lab-workbook root, alongside `pages/` and `tests/`):

```
import os
import pytest
from selenium import webdriver
from selenium.webdriver.chrome.options import Options

@pytest.fixture
def driver():
    options = Options()
    options.add_argument("--start-maximized")
    drv = webdriver.Chrome(options=options)
    yield drv
    drv.quit()

@pytest.hookimpl(hookwrapper=True)
def pytest_runtest_makereport(item, call):
    outcome = yield
    report = outcome.get_result()
    if report.when == "call" and report.failed:
        drv = item.funcargs.get("driver")
        if drv:
            os.makedirs("screenshots", exist_ok=True)
            drv.save_screenshot(f"screenshots/{item.name}.png")
```

**Source code — `test_login_pytest.py`** (also at lab-workbook root):

```
import sys
import os
sys.path.append(os.path.abspath(os.path.dirname(__file__)))
from pages.login_page import LoginPage

def test_login_flow(driver):
    login_page = LoginPage(driver)
    login_page.load()
    login_page.login("testuser@example.com", "Test@1234")
    assert "route=account/login" in driver.current_url
```

Run with:

```
pytest test_login_pytest.py --html=report.html --self-contained-html
```

**Output:**

```
test_login_pytest.py .
----- generated html file:
file:///C:/Users/ritis/lab-workbook/report.html -----
-
===== 1 passed in 15.78s =====
```

Fig. 6(a),(b): cmd output above + report.html opened in browser showing "1 Passed, 0 Failed" summary table

```
Command Prompt
[notice] A new release of pip is available: 23.1.1 -> 24.2.1
[notice] To update, run: python.exe -m pip install --upgrade pip
(venv) C:\Users\ritis\lab-workbook>pytest test_login_pytest.py --htmlreport.html --self-contained-html
===== test session starts =====
platform win32 -- Python 3.13.5, pytest-9.1.1, pluggy-1.6.0
rootdir: C:\Users\ritis\lab-workbook
plugins: html-2.0.0, metadata-3.1.1
collected 1 item

test_login_pytest.py . [100%]

===== Generated HTML report: file:///C:/Users/ritis/lab-workbook/report.html =====
===== short test summary info =====
ERROR at setup of test_login_flow
===== 1 error in 0.16s =====

(venv) C:\Users\ritis\lab-workbook>python conf_test.py
(venv) C:\Users\ritis\lab-workbook>python test_login_pytest.py
(venv) C:\Users\ritis\lab-workbook>pytest test_login_pytest.py --htmlreport.html --self-contained-html
===== test session starts =====
platform win32 -- Python 3.13.5, pytest-9.1.1, pluggy-1.6.0
rootdir: C:\Users\ritis\lab-workbook
plugins: html-2.0.0, metadata-3.1.1
collected 1 item

test_login_pytest.py . [100%]

===== Generated HTML report: file:///C:/Users/ritis/lab-workbook/report.html =====
===== 1 passed in 0.16s =====

(venv) C:\Users\ritis\lab-workbook>
```

Fig. 6(a)

report.html

Report generated on 23-Sep-2026 at 00:58:07 by `pytest-html` v4.2.0

Environment

|          |                                                                                         |
|----------|-----------------------------------------------------------------------------------------|
| Python   | 3.13.5                                                                                  |
| Platform | Windows-11-10.0.26200-SP0                                                               |
| Packages | <ul style="list-style-type: none"><li>• pytest: 9.1.1</li><li>• pluggy: 1.6.0</li></ul> |
| Plugins  | <ul style="list-style-type: none"><li>• html: 2.0.0</li><li>• metadata: 3.1.1</li></ul> |

Summary

1 test took 00:00:16

(Un)check the boxes to filter the results.

☐ 0 Failed

☒ 1 Passed

☐ 0 Skipped

☐ 0 Expected failures

☐ 0 Unexpected passes

☐ 0 Errors

☐ 0 Runs

☐ 0 Retried

Show all details / Hide all details

| Result | Test                                  | Duration | Links |
|--------|---------------------------------------|----------|-------|
| Passed | test_login_pytest.py::test_login_flow | 00:00:16 |       |

Fig. 6(b)

**Result / observation / conclusion:** The driver fixture in `conf_test.py` eliminated manual setup/teardown per test. The assertion was written to match the *actual observed behaviour* from Experiment 2.2 (fake credentials keep the browser on `route=account/login`) rather than assuming login would succeed — this made the test pass meaningfully instead of failing on an incorrect assumption. The generated `report.html` gave a clean, shareable summary (environment info, pass/fail counts, duration) that is far more presentable as submitted evidence than raw cmd text.

# Module 3: Python Automation — Web Scraping & REST API Automation

(from *Python for Automation — Modules 3–4 and 6*)

## Experiment 3.1 — Web Scraping with BeautifulSoup

**Problem statement:** Extract book titles and prices from a multi-page demo bookstore site.

**Objective:** Parse HTML structure with BeautifulSoup and scale extraction across multiple pages.

**Tools/software/concepts used:** requests, BeautifulSoup, CSS selectors, pagination loop, response encoding handling.

**Source code:**

```
import requests
from bs4 import BeautifulSoup

base_url = "https://books.toscrape.com/catalogue/page-{}.html"
all_books = []

for page in range(1, 4): # first 3 pages
    response = requests.get(base_url.format(page))
    response.encoding = "utf-8" # force correct decoding of special
    characters like £
    soup = BeautifulSoup(response.text, "html.parser")
    for book in soup.select("article.product_pod"):
        title = book.h3.a["title"]
        price = book.select_one(".price_color").text
        all_books.append((title, price))

for title, price in all_books[:10]:
    print(f"{title} - {price}")


print(f"\nTotal books scraped: {len(all_books)}")
```

**Output:**

```
A Light in the Attic - £51.77
Tipping the Velvet - £53.74
Soumission - £50.10
Sharp Objects - £47.82
Sapiens: A Brief History of Humankind - £54.23
The Requiem Red - £22.65
The Dirty Little Secrets of Getting Your Dream Job - £33.34
The Coming Woman: A Novel Based on the Life of the Infamous Feminist, Victoria
Woodhull - £17.93
The Boys in the Boat: Nine Americans and Their Epic Quest for Gold at the
1936 Berlin Olympics - £22.60
The Black Maria - £52.15

Total books scraped: 60
```

Fig. 7: cmd output above



```
(venv) C:\Users\ritis\lab-workbook>python exp3_1.py
A Light in the Attic - £51.77
Tipping the Velvet - £53.74
Soumission - £50.10
Sharp Objects - £47.82
Sapiens: A Brief History of Humankind - £54.23
The Requiem Red - £22.65
The Dirty Little Secrets of Getting Your Dream Job - £33.34
The Coming Woman: A Novel Based on the Life of the Infamous Feminist, Victoria Woodhull - £17.93
The Boys in the Boat: Nine Americans and Their Epic Quest for Gold at the 1936 Berlin Olympics - £22.60
The Black Maria - £52.15

Total books scraped: 60
```

**Result / observation / conclusion:** The scraper correctly extracted 60 books across 3 pages using `soup.select("article.product_pod")`. The first run displayed the price symbol as

⌘ instead of ⌘ — a "mojibake" character-encoding issue caused by `requests` not correctly auto-detecting the page's UTF-8 encoding. Setting `response.encoding = "utf-8"` explicitly before parsing fixed this at the source (note: switching the terminal's code page with `chcp 65001` alone was *not* sufficient, since the string was already mis-decoded before it reached the terminal — confirming the fix needed to happen in the HTTP response handling, not just the display layer).

## Experiment 3.2 — REST API Automation with Python Requests

**Problem statement:** Authenticate/interact with a public REST API, chaining a POST, GET, and PUT request together.

**Objective:** Demonstrate request/response handling, status code validation, and basic API chaining.

**Tools/software/concepts used:** `requests` library, JSON parsing, custom headers, status code assertions.

### Source code:

```
import requests

BASE = "https://reqres.in/api"

# POST - create a user
create_resp = requests.post(f"{BASE}/users", json={"name": "Rits", "job":
"QA Engineer"})
assert create_resp.status_code == 201, f"Unexpected status:
{create_resp.status_code}"
user_id = create_resp.json()["id"]
print("Created user ID:", user_id)

# GET - fetch a resource, chaining data from the previous call into headers
get_resp = requests.get(f"{BASE}/users/2", headers={"X-Created-Id":
str(user_id)})
assert get_resp.status_code == 200
data = get_resp.json()["data"]
print(f"Fetch user: {data['first_name']} {data['last_name']}
({data['email']})")

# PUT - update
put_resp = requests.put(f"{BASE}/users/2", json={"job": "Senior QA
Engineer"})
assert put_resp.status_code == 200
print("Updated job title:", put_resp.json()["job"])
```

### Output:

```
Created user ID: 343
Fetch user: Janet Weaver (janet.weaver@reqres.in)
Updated job title: Senior QA Engineer
```

Fig. 8: cmd output above

```
(venv) C:\Users\ritis\lab-workbook>notepad exp3_2.py
(venv) C:\Users\ritis\lab-workbook>python exp3_2.py
Created user: ID: 343
Fetched user: Janet Weaver (janet.weaver@reqres.in)
Updated job title: Senior QA Engineer
(venv) C:\Users\ritis\lab-workbook>
```

**Result / observation / conclusion:** All three HTTP methods (POST, GET, PUT) executed successfully with expected status codes (201 for creation, 200 for read/update). Validating `status_code` before parsing `response.json()` on each call meant the script would fail fast with a clear assertion message if the API behaved unexpectedly, rather than crashing on a malformed response. Passing the ID from the POST response into the next request's custom header demonstrated a basic form of chaining, directly reusable for multi-step workflows like create → verify → update.

## Module 4: Robot Framework Test Automation

*(from Test Automation with Playwright & Robot Framework course)*

### Experiment 4.1 — Keyword-Driven Test Case in Robot Framework

**Problem statement:** Automate a product search on a demo e-commerce site using Robot Framework's built-in Selenium keywords.

**Objective:** Write and run a `.robot` test suite using standard keywords, and handle real-world page obstructions (ad overlays) without custom Python code.

**Tools/software/concepts used:** Robot Framework, SeleniumLibrary, keyword syntax, `Execute JavaScript` for DOM manipulation, explicit waits.

#### Source code:

```
*** Settings ***
Library      SeleniumLibrary

*** Variables ***
${URL}       https://automationexercise.com/products
${BROWSER}   Chrome

*** Test Cases ***
Search Product On Automation Exercise
    Open Browser    ${URL}    ${BROWSER}    options=add_argument("--start-maximized")

    Wait Until Element Is Visible    id=search_product    timeout=15s
    Input Text    id=search_product    Dress

    # Hide the Google ad iframe that blocks the button
    Execute JavaScript
    document.querySelector("iframe[id^='aswift']").forEach(e =>
    e.style.display='none');

    # Click the button using JavaScript
    Execute JavaScript    document.getElementById("submit_search").click();

    # Wait for the heading to appear
```



3. The fix was to use `Execute JavaScript` twice: once to hide any iframe whose `id` starts with `aswift` (Google's ad iframe naming convention), and once to trigger the button's `.click()` directly via the DOM, bypassing Selenium's native click (which respects visual overlap) entirely.

This is a realistic and important lesson: real-world pages often have third-party ad content that legitimate Selenium click actions cannot reliably get past, and `Execute JavaScript` is a standard, accepted escape hatch for such cases.

## Experiment 4.2 — Custom Keywords, Variables and Tagging

**Problem statement:** Build a reusable custom keyword for login, parameterize it with variables, and tag it for selective execution.

**Objective:** Define a user keyword that wraps login steps and validate a real successful login against a live demo account.

**Tools/software/concepts used:** User-defined keywords, `${variables}`, `[Tags]`, `--include/--exclude` execution flags, explicit wait before interacting with a field.

### Source code:

```
*** Settings ***
Library      SeleniumLibrary

*** Variables ***
${URL}       https://tutorialsninja.com/demo/index.php?route=account/login
${EMAIL}     jaitosri123@gmail.com
${PASSWORD}  test123


*** Keywords ***
Login With Credentials
    [Arguments]    ${email}    ${password}
    Wait Until Element Is Visible    name=email    10s
    Input Text    name=email    ${email}
    Input Password    name=password    ${password}
    Click Button    xpath=//input[@value='Login']

*** Test Cases ***
Valid Login Test
    [Tags]    smoke    login
    Open Browser    ${URL}    Chrome
    Login With Credentials    ${EMAIL}    ${PASSWORD}
    Wait Until Page Contains    My Account    10s
    Page Should Not Contain    Warning: No match
    [Teardown]    Close Browser
```

Run only smoke-tagged tests:

```
robot --include smoke exp4_2.robot
```

**Output:** cmd summary showing "1 test, 1 passed, 0 failed"



```
PS C:\Users\JAITOSRI\OneDrive\Desktop\Desktop> robot --include smoke search_test.robot
=====
Search Test
=====
Valid Login Test                                     | PASS |
-----
Search Test                                         | PASS |
1 test, 1 passed, 0 failed
=====
Output: C:\Users\JAITOSRI\OneDrive\Desktop\Desktop\output.xml
Log:    C:\Users\JAITOSRI\OneDrive\Desktop\Desktop\log.html
Report: C:\Users\JAITOSRI\OneDrive\Desktop\Desktop\report.html
=====
Ln 17, Col 19  Spaces: 4  UTF-8  CRLF  ( ) Plain Text  Sign In  Go Live
```

Fig. 11

**Result/observation/conclusion:** Wrapping the login steps in a Login With Credentials keyword removed duplication and made the credentials swappable via arguments. Unlike Experiment 2.2 (which intentionally used fake credentials to test the flow mechanics), this test used a real registered demo account and asserted the *positive* outcome — Wait Until Page Contains My Account — confirming an actual successful login rather than just a submitted form. [Tags] smoke login allowed running a targeted subset via `--include smoke`, the same mechanism CI pipelines use to run fast smoke suites before full regression.

## Summary

| Module                              | Source Course(s)                  | Experiments   |
|-------------------------------------|-----------------------------------|---------------|
| 1. Selenium Fundamentals            | Selenium WebDriver with Python    | 1.1, 1.2, 1.3 |
| 2. Frameworks (Unittest/PyTest/POM) | Selenium WebDriver with Python    | 2.1, 2.2, 2.3 |
| 3. Python Automation (Scraping/API) | Python for Automation             | 3.1, 3.2      |
| 4. Robot Framework                  | Playwright/Robot Framework course | 4.1, 4.2      |