

Copyright © 2002-2008 The Khronos Group Inc. All Rights Reserved.

This specification is protected by copyright laws and contains material proprietary to the Khronos Group, Inc. It or any components may not be reproduced, republished, distributed, transmitted, displayed, broadcast or otherwise exploited in any manner without the express prior written permission of Khronos Group. You may use this specification for implementing the functionality therein, without altering or removing any trademark, copyright or other notice from the specification, but the receipt or possession of this specification does not convey any rights to reproduce, disclose, or distribute its contents, or to manufacture, use, or sell anything that it may describe, in whole or in part.

Contents

1	Overview	1
1.1	Conventions	1
2	OpenGL Operation	2
2.1	OpenGL Fundamentals	2
2.1.1	Fixed-Point Computation	3
2.2	GL State	3
2.3	GL Command Syntax	3
2.4	Basic GL Operation	3
2.5	GL Errors	3
2.6	Begin/End Paradigm	4
2.7	Vertex Specification	5
2.8	Vertex Arrays	5
2.9	Buffer Objects	7
2.10	Rectangles	8
2.11	Coordinate Transformations	8
2.12	Clipping	10
2.13	Current Raster Position	10
2.14	Colors and Coloring	10
2.15	Vertex Shaders	11
2.15.1	Loading and Compiling Shader Sources	11
2.15.2	Shader Binaries	12
2.15.3	Program Objects	13
3	Rasterization	15
3.1	Invariance	15
3.2	Antialiasing	15
3.3	Points	15
3.3.1	Point Sprite Rasterization	15
4.3.1	Basic Be Rasterization	10
2.8	te	10

3.8.1	Copy Texture	20
3.8.2	Compressed Textures	22
3.8.3	Texture Wrap Modes	22
3.8.4	Texture Minification	22
3.8.5	Texture Magnification	22
3.8.6	Texture Framebuffer Attachment	22
3.8.7	Texture Completeness	22
3.8.8	Manual Mipmap Generation	23
3.8.9	Texture State	23
3.8.10	Texture Environments and Texture Functions	24
3.9	Color Sum	28
3.10	Fog	28
3.11	Fragment Shaders	28
4	Per-Fragment Operations and the Framebuffer	29
4.1	Per-Fragment Operations	30

Chapter 1

Overview

This document outlines the OpenGL ES 2.0 specification. OpenGL ES 2.0 implements the

the window-system-provided framebuffer. Similarly, display of framebuffer contents on a CRT monitor or LCD panel (including the transformation of individual framebuffer values by such techniques as gamma correction) is not addressed by OpenGL ES. Framebuffer configuration occurs outside of OpenGL ES in conjunction with the window-system.

The initialization of an OpenGL ES context itself occurs when the window-system allocates a window for OpenGL ES rendering and is influenced by the state of the window-system-provided framebuffer.

2.1.1 Fixed-Point Computation

The OpenGL ES 2.0 specification supports fixed-point vertex attributes using a 32-bit two's-complement signed representation with 16 bits to the right of the binary point (fraction bits). The OpenGL ES 2.0 pipeline requires the same range and precision requirements as specified in Section 2.1.1 of the OpenGL 2.0 specification.

2.2 GL State

OpenGL 2.0	Common
NO_ERROR	
I NVALI D_ENUM	
I NVALI D_VALUE	
I NVALI D_OPERATI ON	
STACK_OVERFLOW	–
STACK_UNDERFLOW	–
OUT_OF_MEMORY	
TABLE_TOO_LARGE	–

Table 2.1: Error Disposition

2.7 Vertex Specification

The OpenGL ES 2.0 specification does not include the concept of Begin and End. Vertices are specified

OpenGL 2.0	Common
------------	--------

OpenGL



|



FLOAT, HIGH_FLOAT, LOW_INT, MEDIUM_INT or HIGH_INT. *range* points to an array of two integers in which encodings of the format's numeric range are returned. If *min* and *max* are the smallest and largest values representable in the format, then the values returned are defined to be

$$range[0] = \text{blog}_2(jmin)c$$

$$range[1] = \text{blog}_2(jmax)c$$

precision points

OpenGL 2.0	Common
void GetShaderSource (ui nt shader, si zei buf si ze, si zei *l ength, char *source)	

Chapter 3

Rasterization

3.1 Invariance

The invariance rules are retained in full.

3.2 Antialiasing

Multisampling is supported though an implementation is not required to provide a multisample buffer. Multisampling can be enabled and/or disabled in OpenGL using the Enable/Disable command. Multisampling is only enabled in OpenGL ES 2.0, if the EGLconfig associated with the target render surface uses a multisample buffer.

3.3.1 Point Sprite Rasterization

Point sprite rasterization produces a fragment for each framebuffer pixel whose center lies inside a square



OpenGL 2.0	Common
void GetHistogram (enum target, boolean reset, enum format, enum type, void *values)	–
void GetHistogramParameterfv (enum target, enum pname, T *params)	–
void Enable/Disable (MI NMAX)	–
void Minmax (enum target, enum internal format, boolean sink)	–
void ResetMinmax (enum target)	–
void GetMinmax (enum target, boolean reset, enum format, enum types, void *	

3.8 Texturing

1D textures, and depth textures are not supported. 2D textures, and cube maps are supported with the following exceptions: only a limited number of image format and type combinations are supported, listed in Table 3.1. 3D textures are not required but can be optionally supported through the `OES_texture_3D` extension.

OpenGL 2.0 implements power of two and non-power of two 1D, 2D, 3D textures and cube-maps. The power and non-power of two textures support all texture wrap modes and ab w mip-apspe nin]TJ 0 -13.55 Td [(fpenG

non-power of two

3.8.2 Compressed Textures

Compressed textures are supported including sub-image specification; however, no method for reading back a compressed texture image is included, so implementation vendors must provide separate tools for creating compressed images. The generic compressed internal formats are not supported, so compression of textures using `TexImage2D`, `TexImage3D` is not supported.

3.8.3 Texture Wrap Modes

Wrap modes `REPEAT`, `CLAMP_TO_EDGE` and `MIRRORED_REPEAT` are the only wrap modes supported for texture coordinates. The texture parameters to specify the magnification and minification filters are supported. Texture priorities, LOD clamps, and explicit base and maximum level specification, auto mipmap generation, depth texture and texture comparison modes are not supported. Texture objects are supported,

3.8.10 Texture Environments and Texture Functions

OpenGL 2.0

Chapter 4

Per-Fragment Operations and the Framebuffer

OpenGL 2.0

currently bound framebuffer object. **CopyPixels**

There is no multisample buffer so the value of the implementation-dependent state variables `SAMPLES` and `SAMPLE_BUFFERS` are both 0

Framebuffer objects are deleted by calling

```
void DeleteFramebuffers(sizei n, uint *framebuffers);
```

framebuffers contains *n* names of framebuffer objects to be deleted. After a framebuffer object is

If *texture* is zero, then *textarget*, and *level* are ignored. If *texture* is not zero, then *texture* must either name an existing texture object with an target of *textarget*, or *texture* must name an existing cube map texture and *textarget* must be one of: TEXTURE_

the current programmable vertex and/or fragment processing state makes it possible to sample from the texture object **T** bound to texture unit **U**

while either of the following conditions are true:

the value of `TEXTURE_MIN_FILTER` for texture object **T** is `NEAREST` or `LINEAR`, and the value of `FRAMEBUFFER_ATTACHMENT_TEXTURE_LEVEL` for attachment point **A** is the base level for the texture object **T**, or

the value of `TEXTURE`

labeled FRAMEBUFFER_UNSUPPORTED.

n Selection is not used by many applications. There are other methods that applications cat1(not)Tmet-300(tho]

5.6 Hints

Hints are retained except for the hints relating to the unsupported polygon smoothing and compression of textures (including retrieving compressed textures) features.

OpenGL 2.0	Common
void Hint (enum target, enum mode)	
target = PERSPECTIVE_CORRECTION_HINT	—
target = POINT_SMOOTH_HINT	—
target = LINE_SMOOTH_HINT	—
target = FOG_HINT	—
target = TEXTURE_COMPRESSION_HINT	—
target = POLYGON_SMOOTH_HINT	—
target = GENERATE_MIPMAP_HINT	

OpenGL 2.0	Common
void GetBufferPointerv (enum target, enum pname, void **params)	–
boolean IsShader (ui nt shader)	
boolean IsProgram (ui nt program)	
void GetProgramiv (ui nt program, enum pname, i nt *params)	
void GetAttachedShaders (ui nt program, si ze i maxcount, si ze i *count, ui nt *shaders)	
void GetProgramInfoLog (ui nt program, si ze i bufsi ze, si ze i *length, char *i nfol og)	
void GetShaderiv (ui nt shader, enum pname, i nt *params)	
void GetShaderInfoLog (ui nt shader, si ze i bufsi ze, si ze i *length, char *i nfol og)	y
void GetShaderSource (ui nt shader, si ze i bufsi ze, si ze i *length, char *source)	y
void GetUniformfifgv (ui nt program, i nt l ocati on, T *params)	

6.2 State Tables

The following tables summarize state that is present in the OpenGL ES 2.0 specification. The tables also indicate which state variables are obtained with what commands. State variables that can be obtained using any of `GetBooleanv`, `GetIntegerv`, or `GetFloatv` are listed with just one of these commands - the one that is most appropriate given the type of data to be returned. These state variables cannot be obtained using `IsEnabled`. However, state variables for which `IsEnabled` is listed as the query command can also be obtained using `GetBooleanv`, `GetIntegerv`, and `GetFloatv`. State variables for which any other command is listed as the query command can be obtained only by using that command.

State appearing in *italic* indicates unnamed state. All state has initial values identical to those specified in OpenGL 2.0.

State	Queryable	Minimum Value	Get
<i>Begin/end object</i>	–	–	–
<i>Previous line vertex</i>	–	–	–
<i>First line-vertex flag</i>	–	–	–



State

State	Queryable	Minimum	
-------	-----------	---------	--

State	Queryable	Minimum Value	Get
-------	-----------	---------------	-----

State	Queryable	Minimum Value	Get
SCI_SSOR_TEST		<i>False</i>	IsEnabled
SCI_SSOR_BOX		0,0,w,h	GetIntegerv
ALPHA_TEST	–	–	–
ALPHA_TEST_FUNC	–	–	–
ALPHA_TEST_REF			

State	Queryable	Minimum Value	Get
-------	-----------	------------------	-----

State	Queryable	Minimum Value	Get

State	Queryable	Minimum Value	Get
MI NMAX	-	-	-
MI NMAX_FORMAT	-	-	-
MI NMAX			

State	Queryable	Minimum Value	Get
CURRENT_PROGRAM		0	GetIntegerv

State and State Requests

State	Queryable	Minimum Value	Get
MAX_TEXTURE_UNITS	–	–	–

State		Queryable	Minimum Value	Get
FRAMEBUFFER BINDING			0	GetIntegerv

Appendix A

Appendix B

Acknowledgements

Jitaek Lim, Samsung

John Howson, Imagination Technologies

John Kessenich, 3DLabs

Jacob Ström, Ericsson

Jani Vaarala, Nokia

Jarkko Kemppainen, Nokia

John B(emppa0d.dltb)-250(oftwk)10area

John Javismppa0d.dltb oftwk

Jhn ndependenta

oonacn Nokia

orhnrlnxa

ustihnrlnxa

Nokia

ishioa,rnacoenia

e, Samsung

isukk

oralnxa

a,

o15(v)65(a,)-250DMPg

T35(reK)25vo15(etth,)-250(3DLabs)]TJ0 g 0 G0 g 0 G 0 -18.189 Td [NicJlacn Imagination Technologies
roa,

ya,

y ntertpaimenta

y ntertpaimenta

y

nkmppa0d.Symbiang

eg ISg

Tronskia, Nokia

Tron

T35(imon)-250Suoarntla,

homacn

Tom McReynolds, Nvidia

Tom Olson, Texas Instruments

Ville Miettinen, Hybrid Graphics

Woo Sedo Kim, LG Electronics

Yong Moo Kim, LG Electronics

Yoshihiko Kuwahara, DMP

Yoshiyuki Kato, Mitsubishi

Young Seok Kim, ETRI

Yukitaka Takemuta, DMP

Appendix D

OES Extensions

OpenGL ES extensions that have been approved by the Khronos OpenGL ES working group are described in this chapter. These extensions are not required to be supported by a conformant OpenGL ES implementation, but are expected to be widely available; they define functionality that is likely to move into the required