

The OpenGL[®]

Copyright c

2.9 Buffer Objects

| | | |
|-------|--|-----|
| 3.9 | Texturing | 210 |
| 3.9.1 | Texture Image Specification | 212 |
| 3.9.2 | Alternate Texture Image Specification Commands | 227 |

| | | |
|-------|------------------------------|-----|
| 6.1.5 | Stipple Query | 374 |
| 6.1.6 | Color Matrix Query | 375 |
| 6.1.7 | Color Table Query | 375 |

CONTENTS

| | | |
|--------|--------------------------------|-----|
| I.3.9 | Texture Border Clamp | 499 |
| I.3.10 | Point Parameters | 499 |
| I.3.11 | Vertex Blend | 499 |

| | | |
|--------|---|-----|
| I.3.49 | Vertex Array Objects | 506 |
| I.3.50 | Versioned Context Creation | 506 |
| I.3.51 | Uniform Buffer Objects | 506 |
| I.3.52 | Restoration of features removed from OpenGL 3.0 | 506 |

List of Tables

| | | |
|------|---|-----|
| 2.1 | GL command suffixes | 14 |
| 2.2 | GL data types | 16 |
| 2.3 | Summary of GL errors | 19 |
| 2.4 | Triangles generated by triangle strips with adjacency. | 28 |
| 2.5 | Vertex array sizes (values per vertex) and data types | 36 |
| 2.6 | Variables that direct the execution of InterleavedArrays | 45 |
| 2.7 | Buffer object binding targets. | 48 |
| 2.8 | Buffer object parameters and their values. | 49 |
| 2.9 | Buffer object initial state. | 51 |
| 2.10 | Buffer object state set by MapBufferRange | 54 |
| 2.11 | Summary of lighting parameters. | 73 |
| 2.12 | Correspondence of lighting parameter symbols to names. | 78 |
| 2.13 | OpenGL Shading Language type tokens | 98 |
| 2.14 | Transform feedback modes | 131 |
| 2.15 | Provoking vertex selection. | 135 |
| 3.1 | PixelStore parameters. | 170 |
| 3.2 | TexEnv parameters. | 190 |

Chapter 1

or **texturing** is enabled) relies on the existence of a framebuffer. Further, some of OpenGL is specifically concerned with framebuffer manipulation.

1.3 Programmer's View of OpenGL

To the programmer, OpenGL is a set of commands that allow the specification of geometric objects in two or three dimensions, together with commands that control

1.5 Our View

We view OpenGL as a pipeline having some programmable stages and some state-driven stages that control a set of specific drawing operations. This model should engender a specification that satisfies the needs of both programmers and implementors. It does not, however, necessarily provide a model for implementation. An implementation must produce results conforming to those produced by the speci-

previously invoked GL commands, except where explicitly specified otherwise. In general, the effects of a GL command on either GL modes or the framebuffer must be complete before any subsequent command can have any such effects.

section 1.7.2.

Allocation and initialization of GL contexts is also done using these companion APIs. GL contexts can typically be associated with different default framebuffers, and some context state is determined at the time this association is performed.

It is possible to use a GL context *without* a default framebuffer, in which case a framebuffer object must be used to perform all rendering. This is useful for applications needing to perform *offscreen rendering*.

The GL is designed to be run on a range of graphics platforms with varying graphics capabilities and performance. To accommodate this variety, we specify ideal behavior instead of actual behavior for certain GL operations. In cases where

2.1.3 Unsigned 11-Bit Floating-Point Numbers

```

      0
      0.0;
      2 14
V =
      .

```

$$E = 0; M = 0$$

general, this representation is used for signed normalized fixed-point texture or framebuffer values.

Everywhere that signed normalized fixed-point values are converted, the equation used is specified.

Conversion from Floating-Point to Normalized Fixed-Point

The conversion from a floating-point value f to the corresponding unsigned normalized fixed-point value c is defined as follows:

Ev

We distinguish two types of state. The first type of state, called GL *server state*

| Type Descriptor | Corresponding GL Type |
|-----------------|-----------------------|
| b | byte |

2.6.1 Begin and End


Vertices making up one of the supported geometric object types are specified by enclosing commands defining those vertices between the two commands

```
void Begin( enum mode );
void End( void );
```

There is no limit on the number of vertices that may be specified between a **Begin** and an **End**. The *mode* parameter of **Begin** determines the type of geometric object that will be drawn. The *mode* parameter of **Begin** must be one of the following:



vertex *A*, the second stored as vertex *B*, the third stored as vertex *A*, and so on. Any vertex after the second one sent forms a triangle from vertex *A*, vertex *B*, and the current vertex (in that order).



tion 2.15

2.7. VERTEX SPECIFICATION

specify the current homogeneous texture coordinates, named s , t , r , and q . The **TexCoord1** family of commands set the s coordinate to the provided single argument while setting t and r to 0 and q to 1. Similarly, **TexCoord2** sets s and t to the specified values, r to 0 and q to 1; **TexCoord3** sets s , t , and r , with q set to 1, and **TexCoord4** sets all four texture coordinates.

Implementations must support at least two sets of texture coordinates. The commands

```
void MultiTexCoord1f(GLuint texture, GLuint coord, GLfloat s);
void MultiTexCoord1fv(GLuint texture, GLuint coord, const GLfloat* s);
void MultiTexCoord1i(GLuint texture, GLuint coord, GLint s);
void MultiTexCoord1iv(GLuint texture, GLuint coord, const GLint* s);
void MultiTexCoord2f(GLuint texture, GLuint coord, GLfloat s, GLfloat t);
void MultiTexCoord2fv(GLuint texture, GLuint coord, const GLfloat* st);
void MultiTexCoord2i(GLuint texture, GLuint coord, GLint s, GLint t);
void MultiTexCoord2iv(GLuint texture, GLuint coord, const GLint* st);
void MultiTexCoord3f(GLuint texture, GLuint coord, GLfloat s, GLfloat t, GLfloat r);
void MultiTexCoord3fv(GLuint texture, GLuint coord, const GLfloat* st);
void MultiTexCoord3i(GLuint texture, GLuint coord, GLint s, GLint t, GLint r);
void MultiTexCoord3iv(GLuint texture, GLuint coord, const GLint* st);
void MultiTexCoord4f(GLuint texture, GLuint coord, GLfloat s, GLfloat t, GLfloat r, GLfloat q);
void MultiTexCoord4fv(GLuint texture, GLuint coord, const GLfloat* st);
void MultiTexCoord4i(GLuint texture, GLuint coord, GLint s, GLint t, GLint r, GLint q);
void MultiTexCoord4iv(GLuint texture, GLuint coord, const GLint* st);
```



```
void Color f34gfbsifd ubusuig( T components );  
void Color f34gfbsifd ubusuigv( T components );  
void SecondaryColor3 fbsifd ubusuig( T components );  
void SecondaryColor3 fbsifd ubusuigv( T components );
```

The **Color** command has two major variants: **Color3** and **Color4**. The four value

The resulting value(s) are loaded into the generic attribute at slot *index*, whose components are named

The state required to support vertex specification consists of four floating-point numbers per texture coordinate set to store the current texture coordinates s , t , r , and q , three floating-point numbers to store the three coordinates of the current normal, one floating-point number to store the current fog coordinate, four floating-point values to store the current RGBA color, four floating-point values to store the current RGBA secondary color, one floating-point value to store the current color index, and the value of `MAX_VERTEX_ATTRIBS - 1` four-component vectors to store generic vertex attributes.

There is no notion of a current vertex, so no state is devoted to vertex coordinates or generic attribute zero. The initial texture coordinates are $(s; t; r; q) = (0; 0; 0; 1)$ for each texture coordinate set. The initial current normal has coordinates $(0; 0; 1)$. The initial fog coordinate is zero. The initial RGBA color is $(R; G; B; A) = (1; 1; 1; 1)$ and the initial RGBA secondary color is $(0; 0; 0; 1)$. The initial color index is 1. The initial values for all generic vertex attributes are $(0; 0; 0; 0; 1; 0)$.

2.8 Vertex Arrays

The vertex specification commands described in section 2.7 accept data in almost any format, but their use requires many command executions to specify even simple geometry. Vertex data may also be placed into arrays that are stored in the client's address space (described here) or in the server's address space (described in section 2.9). Blocks of data in these arrays may then be used to specify multiple vertices.

```
void FogCoordPointer( enum type, size_t stride,  
                    void *pointer );  
void TexCoordPointer( int
```


called, followed by a call to **Begin** where *mode* is the same as the mode used by the previous **Begin**.

When one of the ***BaseVertex** drawing commands specified in section 2.8.1 is


```
if ( mode or count is invalid )  
    generate appropriate error  
el se
```

| | |
|---------------|----------|
| <i>format</i> | <i>e</i> |
|---------------|----------|

representing the restart index.

In the initial state, the client active texture unit selector is TEXTURE0, the

2.9.2 Creating Buffer Object Data Stores


The data store of a buffer object is created and initialized by calling

```
void BufferData( enum target, size_t size, const  
void *data, enum usage );
```

with *target* set to one of the targets listed in table 2.7, *size*

| Name | Value |
|------|-------|
|------|-------|

MAP_INVALID_DATE_RANGE_BIT indicates that the previous contents of the



and *mbaccess* is the value of the *access* enum parameter passed to **MapBuffer**.

`INVALID_ENUM` is generated if *access* is not one of the values described above.

Other errors are generated as described above for **MapBufferRange**.

504 (If) -1 void F53 10.9091 Tf 217f 19068r (\$MapperWithM) 192 Range CH_EXPLICIT_BIT flag, modifications. 9091 T6o03ag,

2.9.7 Array Indices in Buffer Objects

Blocks of array indices **may be stored in buffer objects with the same format op-**

2.10 Vertex Array Objects

The buffer objects that are to be used by the vertex stage of the GL are collected

2.11 Rectangles

There is a set of GL commands to support efficient specification of rectangles as two corner vertices.

current matrix mode is set with

```
void MatrixMode(enum mode);
```


$\begin{matrix} \text{O} & & & 1 \\ & & & 0 \\ \text{B} & R & & 0 \\ \text{B} & & & 0 \\ \text{B} & & & 0 \\ @ & & & A \\ & 0 & 0 & 0 & 1 \end{matrix}$

the coordinates $(l \ b \ n)^T$ and (

commands include those accessing the current matrix stack (if `MATRIX_MODE` is `TEXTURE`), **TexEnv** commands controlling point sprite coordinate replacement (see section 3.4), **TexGen** (section 2.12.3), **Enable/Disable** (if any texture coordinate generation enum is selected), as well as queries of the current texture coordinates and current raster texture coordinates. If the texture coordinate set

x_o , y_o , z_o , and w_o are the object coordinates of the vertex. $p_1; \dots; p_4$ are specified by calling **TexGen** with

A texture coordinate generation function is enabled or disabled using

2.13. *FIXED-FUNCTION VERTEX LIGHTING AND COLORING*

2.13.1 Lighting

GL lighting computes colors for each vertex sent to the GL. This is accomplished by applying an equation defined by a client-specified lighting model to a collection of parameters that can include the vertex coordinates, the coordinates of one or more light sources, the current normal, and parameters defining the characteristics of the light sources and a current material. The following discussion assumes that

| Parameter | Type | Default Value | Description |
|---------------------|-------|-------------------|-------------|
| Material Parameters | | | |
| \mathbf{a}_{cm} | color | (0.2;0.2;0.2;1.0) | |

2.13. *FIXED-FUNCTION VERTEX LIGHTING AND COLORING*

where

$$f_i = \begin{cases} 1; & \mathbf{n} \cdot \mathbf{VP}_{pli} \geq 0; \\ 0; & \text{otherwise,} \end{cases} \quad (2.8)$$

$$\mathbf{h}_i = \begin{cases} \mathbf{VP}_{pli} + \mathbf{VP}_e; & v_{bs} = \text{TRUE}; \\ \mathbf{VP}_{pli} + \begin{bmatrix} 0 & 0 & 1 \end{bmatrix}^T; & v_{bs} = \text{FALSE}; \end{cases} \quad (2.9)$$

att

selected. Two-sided color mode is enabled and disabled by calling **Enable** or




Figure 2.12. **ColorMaterial** operation. Material properties are continuously updated from the current color while **ColorMaterial** is enabled and has the appropriate mode. Only the front material properties are included in this figure. The back material properties are treated identically, except that *face* must be BACK

2.13. VER LIGHTING AND COLORING

Next, let

$$s = \bigotimes_{i=0}^n (att_i)(spot_i)(s)$$

2.14 Vertex Shaders

The sequence of operations described in sections 2.12 through 2.13 is a fixed-function method for processing vertex data. Applications can also use vertex shaders to describe the operations that occur on vertex values and their associated data.

A vertex shader is an array of strings containing source code for the operations that are meant to occur on each vertex that is processed. The language used for vertex shaders is described in the OpenGL Shading Language Specification.

and `INVALID_OPERATION` if the provided name identifies an object that is not the expected type.

To create a shader object, use the command

```
ui nt CreateShader( enum type );
```

The shader object is empty when it is created. The *type* argument specifies the type of shader object to be created. For vertex shaders, *type* must be `VERTEX_SHADER`. A non-zero name that can be used to reference the shader object is returned. If an error occurs, zero will be returned.

The command

```
voi d ShaderSource( ui nt shader, si ze_t count
```

Each shader object has an information log, which is a text string that is overwritten as a result of compilation. This information log can be queried with **GetShaderInfoLog**

had no programmable stages and the fixed-function paths will be used instead.
If *program* has not been successfully linked, the error

attribute variable is declared as a `mat2x3`,

For the selected attribute, the type of the attribute is returned into *type*.

When a program is linked, any active attributes without a binding specified

is executed. In cases where the compiler and linker cannot make a conclusive determination, the uniform will be considered active.

Sets of uniforms can be grouped into *uniform blocks*. The values of each uniform in such a set are extracted from the data store of a buffer object corresponding to the uniform block. OpenGL Shading Language syntax serves to delimit named blocks of uniforms that can be backed by a buffer object. These are referred to as *named uniform blocks*, and are assigned a *uniform block index*. Uniforms that are declared outside of a named uniform block are said to be part of the *default uniform block*. Default uniform blocks have no name or uniform block index. Like uniforms, uniform blocks can be active or inactive. Active uniform blocks are those that contain active uniforms after a program has been compiled and linked.

The amount of storage available for uniform variables in the default uniform block accessed by a vertex shader is specified by the value of the implementation-

sociated with the default uniform block, use the command

```
i nt
```

```
void GetActiveUniformBlockName(ui nt program,
    ui nt uniformBlockIndex, si ze i bufSize, si ze i *length,
    char *uniformBlockName);
```

program is the name of a program object for which the command **LinkProgram** has been issued in the past. It is not necessary for *program* to have been linked successfully. The link could have failed because the number of active uniforms exceeded the limit.

uniformBlockIndex must be an active uniform block index of *program*, in the range zero to the value of `ACTIVE_UNIFORM_BLOCKS - 1`. The value of `ACTIVE_UNIFORM_BLOCKS` can be queried with **GetProgramiv** (see section 6.1.16). If *uniformBlockIndex* is greater than or equal to the value of `ACTIVE_UNIFORM_BLOCKS`, the error `INVALID_VALUE` is generated.

The string name of the uniform block identified by *uniformBlockIndex* is returned into *uniformBlockName*. The name is null-terminated. The actual number of characters written into *uniformBlockName*, excluding the null terminator, is returned in *length*. If *length* is `NULL`, the function returns the number of characters written into *uniformBlockName*.

2.14. VERTEX SHADERS

| |
|---|
| OpenGL Shading Language Type Tokens (continued) |
|---|

If *pname* is `UNIFORM_OFFSETFROM_OFFSETFROM_OFFSETFROM_94SEFROM_`. `Td(UNIFORM,) - 318(then) - 317`

The given values are loaded into the default uniform block uniform variable location identified by *location*

Uniform*

combined limit. The combined uniform block use limit can be obtained by calling **GetIntegerv** with a *pname* of `MAX_COMBINED_UNIFORM_BLOCKS`.

2.14. VERTEX SHADERS

2. If the member is a two- or four-component vector with components consuming N basic machine units, the base alignment is $2N$ or $4N$, respectively.
3. If the member is a three-component vector with components consuming N basic machine units, the base alignment is $4N$.
- 4.

Uniform Buffer Object Bindings

The value an active uniform inside a named uniform block is extracted from the data store of a buffer object bound to one of an array of uniform buffer binding points. The number of binding points can be queried using **GetIntegerv** with the constant `MAX_UNIFORM_BUFFER_BINDINGS`.

Rebinding

as the mechanism to communicate values to a geometry shader, if one is active, or to communicate values to the fragment shader and to the fixed-function processing that occurs after vertex shading.

If a geometry shader is not active, the values of all varying and special variables are expected to be interpolated across the primitive being rendered, unless flatshaded. Otherwise, the values of varying and special variables are expected to be constant across the primitive being rendered.

terminated strings specifying the names of the varying variables to use for transform feedback. The varying variables specified in *varyings* can be either built-in varying variables (beginning with "gl_") or user-defined ones. Varying variables are written out in the order they appear in the array *varyings*. *bufferMode* is either INTERLEAVED_ATTRIBS or SEPARATE_ATTRIBS, and identifies the mode used to capture the varying variables when transform feedback is active. The error INVALID_VALUE is generated if *bufferMode* is SEPARATE_ATTRIBS and *count* is greater than the value of the implementation-dependent limit MAX_TRANSFORM_FEEDBACK_SEPARATE_ATTRIBS.

The state set by

last such varying variable. The value of `TRANSFORM_FEEDBACK_VARYINGS` can be queried with **GetProgramiv** (see section 6.1.16). If *index* is greater than or equal to `TRANSFORM_FEEDBACK_VARYINGS`, the error `INVALID_VALUE` is generated. The parameter *program*

Normals are not transformed to eye coordinates, and are not rescaled or normalized (section 2.12.2).

Normalization of `AUTO_NORMAL` evaluated normals is not performed. (section 5.1).

Texture coordinates are not `ye`).

`TPer((svttureertxture)((slighting((sis(not)-2(ye)ot)-rmed.)-42((section)]TJ1 0 0 rg 1 0 0 RG [-250(2.12.2)]`

Texel Fetches

The OpenGL Shading Language texel fetch functions provide the ability to extract a single texel from a specified texture image. The integer coordinates passed to

2.14. VERTEX SHADERS

the vertex comes from a vertex array command that specifies a complete primitive (a vertex array drawing command other than **ArrayElement**).

2.15. GEOMETRY SHADERS

types. There are six vertices available for each program invocation. The first, third and fifth vertices refer to attributes of the first, second and third vertex of the triangle, respectively. The second, fourth and sixth vertices refer to attributes of the vertices adjacent to the edges from the first to the second vertex, from the second to the third vertex, and from the third to the first vertex, respectively.

2.15.2 Geometry Shader Output Primitives

A geometry shader can generate primitives of one of three types. The supported output primitive types are points (POINTS

put varying variables generates the values of these input varying variables, including values for built-in as well as user-defined varying variables. Values for any varying variables that are not written by a vertex shader are undefined. Additionally, a geometry shader has access to a built-in variable that holds the ID of the current primitive. This ID is generated by the primitive assembly stage that sits in between the vertex and geometry shader.

Additionally, geometry shaders can write to one or more varying variables for each vertex they output. These values are optionally flatshaded (using the OpenGL

Shading Language varying qualifier `flat`).

2.15. GEOMETRY SHADERS

Structure member `gl_Position` holds the per-vertex position, as written by the vertex shader to its built-in output variable `gl_Position`. Note that

2.15. GEOMETRY SHADERS

Similarly to the limit on vertex shader output components (see section 2.14.6), there is a limit on the number of components of built-in and user-defined output varying variables that can be written by the geometry shader, given by the value of the implementation-dependent constant `MAX_GEOMETRY_OUTPUT_COMPONENTS`.

ones). The parameters n and f are clamped to the range $[0;1]$, as are all arguments of type `clampd` or `clampf`.

Viewport transformation parameters are specified using

```
void Viewport(int
```


2.17. ASYNCHRONOUS QUERIES

the query to be available and then uses the results to determine if subsequent rendering commands are discarded. If *mode* is `QUERY_NO_WAIT`, the GL may choose to

| |
|--------------------|
| Transform Feedback |
|--------------------|

While transform feedback is active, the set of attached buffer objects and the set of varying variables captured may not be changed. If transform feedback is active, the error `INVALID_OPERATION` is generated by **UseProgram**, by **LinkProgram** if *program* is the currently active program object, and by **BindBufferRange** or **BindBufferBase** if *target* is `TRANSFORM_FEEDBACK_BUFFER`.

Buffers should not be bound or in use for both transform feedback and other purposes. Specifically, if buffers simultaneously bound to

buffer is full.

2.21 Flatshading

vertex behavior of quad primitives. The initial value of **the shade mode is SMOOTH** and the initial value of the provoking vertex mode is `LAST_VERTEX_CONVENTION`.

2.22 Primitive Clipping

Primitives are clipped to the *clip volume*. In clip coordinates, the *view volume* is defined by

$$\begin{matrix} W_C & X_C & W_C \\ W_C & Y_C & W_C \\ W_C & Z_C & W_C \end{matrix}$$

This view volume may be further restricted by as many as n client-defined **clip planes to generate the clip volume**. Each client-defined plane specifies a half-space. $(n$

When a vertex shader is active, the vector $x_e \ y_e \ z_e \ w_e$ is computed instead of $x_v \ y_v \ z_v \ w_v$.

and P_2 , then t is given by

$$P = tP_1 + (1 - t)P_2:$$

The value of t is used to clip color, secondary color, texture coordinate, fog coordinate, and vertex shader varying variables as described in section 2.22.1.

If the primitive is a polygon, then it is passed if every one of its edges lies

Let the colors assigned to the two vertices P_1 and P_2 of an unclipped edge be c_1 and c_2 . The value of t (section 2.22) for a clipped point P is used to obtain the color associated with P as

$$c = tc_1 + (1 - t)c_2:$$

(For a color index color, multiplying a color by a scalar means multiplying the index by the scalar. For an RGBA color, it means multiplying each of R, G, B, and A by the scalar. Both primary and secondary colors are treated in the same fashion.)

RGBA component must convert to a value that matches the component as specified in the **Color** command: if m is less than the number of bits b with which the

If depth clamping (si8ENT

IN8EN85N74 (to8EN74 (to8EN75a2g8N) F181550109081dTf94p97424920 [(1)50(P5)10.9001Tf3.0312 0 Td [mi

If the value of the fog source is `FOG_COORD_SRC`, then the current raster distance is set to the value of the current fog coordinate. Otherwise, the raster distance is set to

Chapter 3

Rasterization

Rasterization is the process by which a primitive is converted to a two-dimensional image. Each point of this image contains such information as color and depth. Thus, rasterizing a primitive consists of two parts. The first is to determine which squares of an integer grid in window coordinates are occupied by the primitive. The second is assigning a depth value and one or more color values to each such square. The results of this process are passed on to the next stage of the GL (per-fragment operations), which uses the information to update the appropriate locations in the framebuffer. Figure 3.1 diagrams the rasterization process. The color values assigned to a fragment are initially determined by the rasterization operations (sections 3.4 through 3.8) and modified by either the execution of the texturing, color sum, and fog operations defined in sections 3.9, 3.10, and 3.11, or by a fragment shader as defined in section




Figure 3.1.

Several factors affect rasterization. Primitives may be discarded before rasterization. *Lines and polygons may be stippled.* Points may be given differing

The details of how antialiased fragment coverage values are computed are dif-

have fixed sample locations, the returned values may only reflect the locations of samples within some pixels.

Second, each fragment includes `SAMPLES` depth values and sets of associated data, instead of the single depth value and set of associated data that is maintained

3.4. *POINTS*





Figure 3.2.

$$t = \begin{matrix} 8 \\ < \\ \frac{1}{2} + (y_{f+1} \end{matrix}$$



window-coordinate column (for a y -major line, no two fragments may appear in the same row).

4.

3.5.2 Other Line Segment Features

We have just described the rasterization of non-antialiased line segments of width



3.6. *POLYGONS*

If

modes affect only the final rasterization of polygons: in particular, a polygon's ver-

the fragment center. An implementation may choose to assign the same associated data values to more than one sample by barycentric evaluation using any location within the pixel including the fragment center or one of the sample locations. The color value and the set of texture coordinates need not be evaluated at the same location.

When using a vertex shader, the `noperspective` and `flat` qualifiers affect

| Parameter Name | Type | Initial Value | Valid Range |
|----------------|------|---------------|-------------|
|----------------|------|---------------|-------------|

In addition to storing pixel data in client memory, pixel data may also be stored in buffer objects (described in section [2.9](#)). The current pixel unpack and pack buffer objects are designated by the

3.7. *PIXEL RECTANGLES*

a width, an integer describing the internal format of the table, six integer values describing the resolutions of each of the red, green, blue, alpha, luminance, and intensity components of the table, and two groups of four floating-point numbers to store the table scale and bias. Each initial array is null (zero width, internal format RGBA, with zero-sized components). The initial value of the scale parameters is (1,1,1,1) and the initial value of the bias parameters is (0,0,0,0).

In addition to the color lookup tables, partially instantiated proxy color lookup tables are maintained. Each proxy table includes width and internal format state values, as well as state for the red, green, blue, alpha, luminance, and intensity component resolutions. Proxy tables do not include image data, nor do they include scale and bias parameters. When **ColorTable** is executed with *target* specified as one of the proxy color table names listed in table 3.4, the proxy state values of the

3.7. *PIXEL RECTANGLES*

The image is formed with coordinates i such that i increases from left to right, starting at zero. Image location i is specified by the i th pixel, counting from zero.

The error `INVALID_VALUE` is generated if $w_i L_{ero} \dots t/F427.099091 \ T f 80.557 \ 0 \ T86 \ ter557 \ 0 \ [(n557 \ 0 \ [13.$

exactly as if these arguments were passed to **CopyPixels** with argument *type* set to **COLOR**, stopping after the final expansion to **RGBA**.

Subsequent processing is identical to that described for **ConvolutionFilter2D**, beginning with scaling by **CONVOLUTION_FILTER_SCALE**. Parameters *target*, *internalformat*, *width*, and *height* are specified using the same values, with the same meanings, as the equivalent arguments of **ConvolutionFilter2D**. *format* is taken to be **RGBA**.

The command `glConvolutionFilter2D` . *format*





Figure 3.7. Transfer of pixel rectangles to the GL. Output is RGBA pixels if the GL

| Element Size | Default Bit Ordering | Modified Bit Ordering |
|--------------|----------------------|-------------------------------|
| 8 bit | [7::0] | [7::0] |
| 16 bit | [15::0] | [7::0][15::8] |
| 32 bit | [31::0] | [7::0][15::8][23::16][31::24] |

Table 3.7: Bit ordering modification of elements when `UNPACK_SWAP_BYTES` is enabled. These reorderings are defined only when GL data type `ubyte` has 8 bits, and then only for GL data types with 8, 16, or 32 bits. Bit 0 is the least significant.

of basic machine units needed to store in memory the corresponding GL data type

SKIP_PIXELS



SKIP_ROWS



| type | Parameter |
|--------|--|
| type 2 | 091 Tf 20.902 0 Td [(P)15(arameter)]TJ59 9.9626[J]0 191 Tf 1495.3E4.25.25UNSIGNED_ |

the pixel.

Components are normally packed with the first component in the most signif-

UNSIGNED_INTEGER:

31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1 0

| Format | First | Second | Third | Fourth |
|--------|-------|--------|-------|--------|
|--------|-------|--------|-------|--------|

Conversion to floating-point

This step applies only to groups of floating-point components. It is not performed on indices or integer components. For groups containing both components and indices, such as

3.7.5 Rasterization of Pixel Rectangles

Pixels are drawn using

```
void DrawPixels(size_t width, size_t height, enum format,  
enum type, void *data);
```

Final Conversion

For a color index, final conversion consists of masking the bits of the index to the left of the binary point by $2^n - 1$, where n is the number of bits in an index buffer.

For integer RGBA components, no conversion is performed. For floating-point RGBA components, if fragment color clamping is enabled, each element is clamped to $[0; 1]$, and may be converted to fixed-point according to equation 2.4. If fragment color clamping is disabled, RGBA components are unmodified. Fragment color clamping is controlled by calling

```
void ClampColor( enum target, enum clamp );
```

with *target* set to CLAMP_FRAGMENT_COLOR. If *clamp* is

(either z_x or z_y

must have 2

3.7. *PIXEL RECTANGLES*

Border Mode REDUCE

The width and height of source images convolved with border mode REDUCE are

where $C[i^0:j^0]$

ALPHA_BIAS. The resulting components replace each component of the original group.

That is, if M_C is the color matrix, a subscript of s represents the scale term for a component, and a subscript of b represents the bias term, then the components

$$\begin{matrix} \circ & R^1 \\ B & G \\ B & C \\ @ & B \\ & A \end{matrix}$$

are transformed to

$$\begin{matrix} \circ & R \\ B & \\ B & \\ @ & \end{matrix}$$

3.7. *PIXEL RECTANGLES*



rays of one- or two-dimensional images, consisting of one or more layers. Two-dimensional multisample and two-dimensional multisample array textures are special two-dimensional and two-dimensional array textures, respectively, containing multiple samples in each texel. Cube maps are special two-dimensional array textures with six layers that represent the faces of a cube. When accessing a cube map, the texture coordinates are projected onto one of the six faces of the cube. Rect-

with a different number of supported texture coordinate sets and texture image units, some texture units may consist of only one of the two sub-units.

The active texture unit selector selects the texture image unit accessed by commands involving texture image processing (section 3.9). Such commands include all variants of **TexEnv** (except f

by the renderer can be obtained by querying the value of `NUM_COMPRESSED_TEXTURE_FORMATS`

Texture and renderbuffer color formats (see section

3.9. TEXTURING

| | | | | | |
|-------|------|-----|-----|-----|--|
| Sized | Base | R | G | B | |
|-------|------|-----|-----|-----|--|

| Sized internal color formats continued from previous page | | | | | | |
|---|------|----------|----------|----------|----------|--|
| Sized | Base | <i>R</i> | <i>G</i> | <i>B</i> | <i>A</i> | |

| | | | |
|-------|------|---|--|
| Sized | Base | A | |
|-------|------|---|--|


image format may not be affected by the *data* parameter. Allocations must be invariant; the same allocation and compressed image format must be chosen each

where w_s , h_s , and d_s are the specified image *width*, *height*, and *depth*, and w_t , h_t , and d_t are the dimensions of the texture image internal to the border. If w_t , h_t , or d_t are less than zero, then the error `INVALID_VALUE` is generated.

An image with zero width, height, or depth indicates the null texture. If the null texture is specified for the level-of-detail specified by texture parameter `TEXTURE_BASE_LEVEL` (see section 3.9.6), it is as if texturing were disabled.

The maximum border width b_t is 1. If *border* is less than zero, or greater than b_t , then the error `INVALID_VALUE` is generated.

The maximum allowable width, height, or depth of a texel array for a three-dimensional texture is an implementation-dependent function of the level-of-detail and internal format of the resulting image array. It must be at least $2^{k \cdot lod} + 2b_t$ for image arrays of level-of-detail 0 through k , where k is the log base 2 of `MAX_3D_TEXTURE_SIZE`, lod is the level-of-detail of the image array, and b_t is the



3.9. TEXTURING

The command

```
void CopyTexImage1D(enum target, int level,  
                    enum internalformat, int x, int y, size_t width,  
                    int border);
```

defines a one-dimensional texel array in exactly the manner of **TexImage1D**, except that the image data are taken from the framebuffer, rather than from client memory. Currently, *target* must be `TEXTURE_1D`. For the purposes of decoding the texture image, **CopyTexImage1D** is equivalent to calling **CopyTexImage2D** with corresponding arguments and *height* of 1, except that the *height* of the image is always 1, regardless of the value of *border*. *level*, *internalformat*, and *border* are specified using the same values, with the same meanings, as the equivalent arguments of **TexImage1D**.

and **CopyTexSubImage2D** must be one of TEXTURE_2D, TEXTURE_1D_ARRAY, TEXTURE_RECTANGLE, TEXTURE_CUBE_MAP_POSITIVE_X, TEXTURE_CUBE_MAP_NEGATIVE_X, TEXTURE_CUBE_MAP_POSITIVE_Y, TEXTURE_CUBE_MAP_NEGATIVE_Y,

3.9. TEXTURING

The *xoffset* argument of **TexSubImage1D** and **CopyTexSubImage1D** speci-

If a pixel unpack buffer is bound (as indicated by a non-zero value of `PIXEL_UNPACK_BUFFER_BINDING`), *data*

If the *target* parameter to any of the **CompressedTexSubImage n D** commands is `TEXTURE_RECTANGLE` or `PROXY_TEXTURE_RECTANGLE`, the error `INVALID_ENUM` is generated.

The image pointed to by *data* and the *imageSize* parameter are interpreted as though they were provided to **CompressedTexImage1D**, **CompressedTexImage2D**, and **CompressedTexImage3D**. These commands do not provide for image format conversion, so an `INVALID_OPERATION` error results if *format* does

Calling `CompressedTexSubImage3D`, `CompressedTexSubImage2D`, or

```
void TexImage3DMultisample(enum target, size_t samples,
                           int internalformat, size_t width, size_t height,
                           size_t depth, boolean fixedsamplelocations);
```

establish the data storage, format, dimensions, and number of samples of a multisample texture's image. Fo8 0 Td [38 0 T9091 Tf 63.64908 Td [(T)92(exImage3D2ultisample)]TJ/F41

Texture parameters for a cube map texture apply to the cube map as a whole; the six distinct two-dimensional texture images use the texture parameters of the cube map itself.

If the value of texture parameter `GENERATE_MIPMAP` is `TRUE`, specifying or changing texel arrays may have side effects, which are discussed in the

Major Axis Direction

$$\begin{aligned}
 u^l(x; y) &= \begin{cases} \text{clamp}(u(x; y); 0; w_t); & \text{TEXTURE_WRAP_S is CLAMP} \\ u(x; y); & \text{otherwise} \end{cases} \\
 v^l(x; y) &= \begin{cases} \text{clamp}(v(x; y); 0; h_t); & \text{TEXTURE_WRAP_T is CLAMP} \\ v(x; y); & \text{otherwise} \end{cases} \\
 w^l(x; y) &= \begin{cases} \text{clamp}(w(x; y); 0; h_t); & x; y \end{cases}
 \end{aligned}$$

$$\begin{aligned}i_0 &= \text{wrap}(bu^\ell \quad 0.5c) \\j_0 &= \text{wrap}(bv^\ell \quad 0.5c)\end{aligned}$$

$$I = \text{clamp}(bt + 0.5c; 0; h_t - 1):$$

For mipmap filters

affects the texture image attached to *target*. For cube map textures, an `INVALID_OPERATION` error is generated if the texture bound to *target* is not cube complete, as defined in section 3.9.12.

Mipmap generation replaces texel array levels $level_{base} + 1$ through q with arrays derived from the $level_{base}$ array, regardless of their previous contents. All

TEXTURE_MIN_FILTER as described in section 3.9.9

The $level_{base}$ arrays of each of the six texture images making up the cube

3.9.14 Texture Objects

In addition to the default textures `TEXTURE_1D`, `TEXTURE_2D`, `TEXTURE_3D`, `TEXTURE_1D_ARRAY`, `TEXTURE_2D_ARRAY`, `TEXTURE_RECTANGLE`, `TEXTURE_BUFFER`, `TEXTURE_CUBE_MAP`, `TEXTURE_2D_MULTISAMPLE`, and `TEXTURE_2D_MULTISAMPLE_ARRAY`, named one-, two-, and three-dimensional, one- and two-dimensional array, rectangular, buffer, cube map, two-dimensional multisample, and two-dimensional multisample array texture objects can be created and operated upon. The name space for texture objects is the unsigned integers, with zero reserved by the GL.

A texture object is created by *binding* an unused name to one of these texture targets. The binding is effected by calling

```
void BindTexture(enum target, ui nt texture);
```

with

TEXTURE_2D_ARRAY, TEXTURE_RECTANGLE, TEXTURE_BUFFER, TEXTURE_CUBE_MAP, TEXTURE_2D_MULTISAMPLE, or TEXTURE_2D_MULTISAMPLE_ARRAY respectively while 0 is bound to the corresponding targets.

Texture objects are deleted by calling

```
void DeleteTextures(size_t n, GLuint *textures);
```

textures contains *n* names of texture objects to be deleted. After a texture object is deleted, it has no contents or dimensionality, and its name is again unused. If a texture that is currently bound to any of the *target* bindings of **BindTexture** is deleted, it is as though **BindTexture** had been executed with the same *target* and *texture* zero. Additionally, special care must be taken when deleting a texture if any of the images of the texture are attached to a framebuffer object. See section 4.4.2 for details.

Unused names in *textures* are silently ignored, as is the value zero.

The command

```
void GenTextures(size_t n, GLuint *textures);
```

returns *n* previously unused texture object names in *textures*. These names are

AreTexturesResident



| SRC <i>n</i> _RGB | OPERAND <i>n</i> _RGB | Argument |
|-------------------|----------------------------------|------------------|
| TEXTURE | SRC_COLOR ONE_MINUS_SRC_COLOR | C_s 1 C_s |

3.9.16 Texture Comparison Modes

Texture values can also be computed according to a specified comparison function. Texture parameter `TEXTURE_COMPARE_MODE` specifies the comparison operands, and parameter `TEXTURE_COMPARE_FUNC` specifies the comparison function. The format of the resulting texture sample is determined by the value of `DEPTH_TEXTURE_MODE`.

Depth Texture Comparison Mode

If the currently bound texture's base internal format is `DEPTH_COMPONENT` or `DEPTH_STENCIL`, then `DEPTH_TEXTURE_MODE`, `TEXTURE_COMPARE_MODE` and `TEXTURE_COMPARE_FUNC` control the output of the texture unit as described below. Otherwise, the texture unit operates in the normal manner and texture comparison is bypassed.

Let D_t be the depth texture value and D_{ref} be the reference value, defined as follows:

For fixed-function, non-cubemap texture lookups, D_{ref} is the interpolated r texture coordinate.

For fixed-function, cubemap texture lookups, D_{ref} is the interpolated q texture coordinate.

For texture lookups generated by an OpenGL Shading Language lookup function, D_{ref} is the reference value for depth comparisons provided by the lookup function.

If the texture's internal format indicates a fixed-point depth texture, then D_t and D_{ref} are clamped to the range $[0;1]$; otherwise no clamping is performed. Then the effective texture value is computed as follows:

If the value of `TEXTURE_COMPARE_MODE` is `NONE`, then

$$r = D_t$$

function1a.381 [(D)]TEXTURE_COMPARE_MODE is TEXTU -205.499 -928549 Td [(tur

c_l is as follows.

$$c_l = \begin{pmatrix} 7.9701 & 4.721 & 89.081 & 9.4 \end{pmatrix} \times 10^{-4}$$

then *param* must be, or *params* must point to an integer that is one of the symbolic constants `FRAGMENT_DEPTH`

3.12 Fragment Shaders

The sequence of operations that are applied to fragments that result from rasterizing a point, line segment, **polygon, pixel rectangle or bitmap as described in sections 3.9 through 3.11** is a fixed-functionality method for processing such fragments. Applications can more generally describe the operations that occur on such fragments by using a *fragment shader*.

A fragment

When a texture lookup is performed in a fragment shader, the GL computes the

If a geometry shader is active, the built-in variable

out variables in a program that has already been linked. The error `INVALID_OPERATION` is generated if *name* starts with the reserved `gl_` prefix.

Chapter 4

Per-Fragment Operations and the Framebuffer

The framebuffer, whether it is the default framebuffer or a framebuffer object (see section

No specific algorithm is required for converting the sample alpha values to a temporary coverage value. It is intended that the number of 1's in the temporary coverage be proportional to the set of alpha values for the fragment, with all 1's corresponding to the maximum of all alpha values, and all 0's corresponding to all alpha values being 0. The alpha values used to generate a coverage value are


```

void StencilFuncSeparate(enum face, enum func, i n t ref,
    u i n t mask);
void StencilOp(enum sfail, enum dpfail, enum dppass);
void StencilOpSeparate(enum face, enum sfail, enum dpfail,
    enum dppass);

```

There are two sets of stencil-related state, the front stencil state set and the back stencil state set. Stencil tests and writes use the front set of stencil state when processing fragments rasterized from non-polygon primitives (points, lines, bitmaps, and image rectangles) and front-facing polygon primitives while the back set of stencil state is used when processing fragments rasterized from back-facing polygon primitives. For the purposes of stencil testing, a primitive is still considered a polygon if it contains the

If the depth buffer test fails, the incoming fragment is discarded. The stencil

BlendEquationSeparate argument *modeRGB* determines the RGB blend function while *modeAlpha* determines the alpha blend equation. **BlendEquation** argument *mode* determines both the RGB and alpha blend equations. *modeRGB* and *modeAlpha* must each be one of `FUNC_ADD`, `FUNC_SUBTRACT`, `FUNC_REVERSE_SUBTRACT`, `MIN`, or `MAX`.

Signed or unsigned normalized fixed-point destination (framebuffer) components

| Function | RGB Blend Factors | Alpha Blend Factor |
|----------|-------------------|--------------------|
|----------|-------------------|--------------------|

```
void BlendColor(cl_ampi red, cl_ampi green, cl_ampi blue
```

4.1. PER-FRAGMENT OPERATIONS

| Argument value | Operation |
|----------------|----------------|
| CLEAR | 0 |
| AND | $s \wedge d$ |
| AND_REVERSE | $s \wedge : d$ |
| COPY | s |
| AND_INVERTED | $: s \wedge d$ |

the logical operation, and **two bits** indicating whether the logical operation is enabled or disabled. The initial state is for the logic operation to be given by COPY, and to be disabled.

| | |
|-------|-------|
| Front | Front |
|-------|-------|

4.2. WHOLEFRAMEBUFFER-3OPERATIONS

to by *bufs*. Specifying a buffer more than once will result in the error

then zero is `NONE`.

The value of the draw buffer selected for fragment color *i* can be queried by calling **GetIntegerv**

4.2. WHOLE FRAMEBUFFER OPERATIONS

4.2.4 The Accumulation Buffer

Each portion of a pixel in the accumulation buffer consists of four values: one for each of R, G, B, and A. The accumulation buffer is controlled exclusively through the use of

```
void Accum(enum op, float value);
```

(except for clearing it). *op* is a symbolic constant indicating an accumulation buffer operation, and *value* is a floating-point value to be used in that operation. The possible operations are ACCUM, LOAD, RETURN, MULT, and ADD.

When the scissor test is enabled (section 4.1.2), then only those pixels within the current scissor box are updated by any

| | |
|----------------|--|
| Parameter Name | |
|----------------|--|

buffer, then the error

attached to the framebuffer at `COLOR_ATTACHMENTi`

or floating-point color buffer, the elements are unmodified.

Conversion of Depth values

This step applies only if *format* is `DEPTH_COMPONENT` or `DEPTH_STENCIL` and the depth buffer uses a fixed-point representation. An element is taken to be a fixed-point value in $[0; 1]$ with m

| <i>type</i> Parameter | GL Data Type | Component Conversion Formula |
|-----------------------|--------------|-----------------------------------|
| UNSIGNED_BYTE | ubyte | $c = (2^8 - 1)f$ |
| BYTE | byte | $c = \frac{(2^8 - 1)f + 1}{2}$ |
| UNSIGNED_SHORT | ushort | $c = (2^{16} - 1)f$ |
| SHORT | short | $c = \frac{(2^{16} - 1)f + 1}{2}$ |
| UNSIGNED_INT | uint | $c = (2^{32} - 1)f$ |
| INT | int | $c = \frac{(2^{32} - 1)f + 1}{2}$ |
| HALF_FLOAT | half | $c = f$ |
| FLOAT | | |

by the locations $(dstX0; dstY0)$ and $(dstX1; dstY1)$. The lower bounds of the rectangle are inclusive, while the upper bounds are exclusive.

4.4. FRAMEBUFFER OBJECTS

further in section [4.4.2](#)

By allowing the images of a renderbuffer to be attached to a framebuffer, the GL provides a mechanism to support *off-screen* rendering. Further, by allowing the images of a texture to be attached to a framebuffer, the GL provides a mechanism to support *render to texture*.

4.4.1 Binding and Managing Framebuffer Objects

The default framebuffer for rendering and readback operations is provided by the window system. In addition, named framebuffer objects can be created and oper-

having a lower left of $(0;0)$ and an upper right of $(width; height)$ for each attachment).

If the number of layers of each attachment are not all identical, rendering will be limited to the smallest 42(numbe)-346f liyers lny-350(Intachment)

information to identify the single image attached to the attachment point, or to indicate that no image is attached. The per-logical buffer attachment point state is listed in table 6.31

There are several types of framebuffer-attachable images:

- The image of a renderbuffer object, which is always two-dimensional.

- A single level of a one-dimensional texture, which is treated as a two-dimensional image with a height of one.

- A single level of a two-dimensional or rectangle texture.

- A single face of a cube map texture level, which is treated as a two-dimensional image.

- A single layer of a one-or two-dimensional array texture or three-dimensional texture, which is treated as a two-dimensional image.

While a framebuffer object is bound, GL operations on the target to which it is bound affect the bound framebuffer object, and queries of the target to which a framebuffer object is bound return state from the bound object.

| Sized Internal Format | Base Internal Format | S bits |
|--------------------------|-------------------------|-----------|
| STENCIL_INDEX1 | | |


```
void RenderbufferStorage(enum target, enum internalformat,  
    GLsizei width, GLsizei height);
```

is equivalent to calling **RenderbufferStorageMultisample** with *samples* equal to zero.
height

texture and *textarget* must be one of TEXTURE_CUBE_MAP_POSITIVE_X, TEXTURE_CUBE_MAP_POSITIVE_Y, TEXTURE_CUBE_MAP_POSITIVE_Z, TEXTURE_CUBE_MAP_NEGATIVE_X, TEXTURE_CUBE_MAP_NEGATIVE_Y, or TEXTURE_CUBE_MAP_NEGATIVE_Z. Otherwise, an INVALID_OPERATION error is generated.

level

The error `INVALID_VALUE` is generated if *texture* is non-zero and *layer* is negative. The error `INVALID_OPERATION` is generated if *texture* is non-zero and is

The internal formats of the attached images can affect the completeness of the framebuffer, so it is useful to first define the relationship between the internal format of an image and the attachment points to which it can be attached.

The following base internal formats from table 3.16 are *color-renderable*: ALPHA, RED, RG, RGB, and RGBA. The sized internal formats from table 3.17 that have a color-renderable base internal format are also color-renderable. No other formats, including compressed internal formats, are color-renderable.

f FRAMEBUFFER_INCOMPLETE_READ_BUFFER

Detaching an image from the framebuffer with

framebuffer object, or to an image attached to the currently bound framebuffer object.

When

$$k = (\text{layer} - b)$$

where b is the texture image's border width and layer is the value of `FRAMEBUFFER_ATTACHMENT_TEXTURE_LAYER` for the selected logical buffer.

For a two-dimensional texture, k and layer are irrelevant; for a one-dimensional texture, k is the texture's layer index.

For a three-dimensional texture, k is the texture's layer index and layer is the texture's slice index.

| Layer Number | Cube Map Face |
|--------------|-----------------------------|
| 0 | TEXTURE_CUBE_MAP_POSITIVE_X |
| 1 | TEXTURE_CUBE_MAP_NEGATIVE_X |
| 2 | TEXTURE_CUBE_MAP_POSITIVE_Y |
| 3 | TEXTURE_CUBE_MAP_NEGATIVE_Y |

Chapter 5

Special Functions

This chapter describes additional GL functionality that does not fit easily into any of the preceding chapters. This functionality consists of **evaluators** (used to model curves and surfaces), **selection** (used to locate rendered primitives on the screen),

| <i>target</i> | <i>k</i> | Values |
|---------------|----------|------------------------------|
| MAP1_VERTEX_3 | 3 | x, y, z vertex coordinates |
| MAP1_VERTEX_4 | 4 | |




Figure 5.1. Map Evaluation.

EvalCoord1 causes evaluation of the enabled one-dimensional maps. The argument is the value (or a pointer to the value) that is the domain coordinate, u

This is done using

```
void MapGrid1ffdg(int  $n$ , T  $u_1^l$ , T  $u_2^l$ );
```

for a one-dimensional map or

```
void MapGrid2ffdg(int  $n_u$ , T  $u_1^l$ , T  $u_2^l$ , int  $n_v$ , T  $v_1^l$ ,  
T  $v_2^l$ );
```

for a two-dimensional map. In the case of **MapGrid1** $u^l = g$

for $i = q_1$

1]eround(

5.3. *FEEDBACK*

352

written. The minimum and maximum (each of which lies in the range $[0;1]$) are each multiplied by 2^{30} .F227 y

buffer is a pointer to an array of floating-point values into which feedback information will be placed, and *n* is a number indicating the maximum number of values that can be written to that array. *type* is a symbolic constant describing the

feedback-list:

- feedback-item feedback-list
- feedback-item

feedback-item:

- point
- line-segment
- polygon
- bitmap
- pixel-rectangle
- passthrough

point:


```
void CallLists( size_t n, enum type 10.9091 10514541 10.9091 Tf 41.825 687.66(0)TJ/F11 Tf 5.4
```


BindRenderbuffer, **DeleteRenderbuffers**, **RenderbufferStorage**, **RenderbufferStorageMultisample**, **FramebufferTexture**, **FramebufferTexture1D**, **FramebufferTexture2D**, **FramebufferTexture3D**, **FramebufferTextureLayer**, **FramebufferRenderbuffer**, and **BlitFramebuffer**.

Program and shader objects: **CreateProgram**, **CreateShader**, **DeleteProgram**, **DeleteShader**, **AttachShader**, **DetachShader**, **BindAttribLocation**, **BindFragDataLocation**, **CompileShader**, **ShaderSource**, **LinkProgram**, and **ValidateProgram**.

5.5 Flush and Finish

The command

5.6. SYNC OBJECTS AND FENCES

5.6.2 Signalling

A fence sync object enters the signaled state only once the corresponding fence command has completed and signaled the sync object.

If the sync object being blocked upon will not be signaled in finite time (for

| Target | Hint description |
|-----------------------------|------------------|
| PERSPECTIVE_CORRECTION_HINT | |

Chapter 6


```
void GetClipPlane( enum plane, double eqn[4] );
```

returns four double-precision values in *eqn*; these are the coefficients of the plane equation of *plane* in eye coordinates (these coordinates are those that were com-

6.1. QUERYING GL STATE

queried as `TEXTURE_INTERNAL_FORMAT`, or as `TEXTURE_COMPONENTS` for com-


| Base Internal Format | R | G | B | A |
|----------------------|---|---|---|---|
| ALPHA | 0 | 0 | | |

6.1.8 Convolution Query

The current contents of a convolution filter image are queried with the command

```
void
```


to pixel pack buffer or client memory starting at *values*



name is the name of the indexed state and *index* is the index of the particular element being queried. *name* may only be `EXTENSIONS`, indicating that the extension name corresponding to the *index*th supported extension should be returned. *index* may range from zero to the value of `NUM_EXTENSIONS` minus one. All extension names, and only the extension names returned in `GetString(EXTENSIONS)` will be returned as individual names, but there is no defined relationship between the order in which names appear in the non-indexed string and the order in which they appear in the indexed query. There is no defined relationship between any particular extension name and the

compute the allowable minimum value (where n is the minimum number of bits) is

$$n = \min\{32, \lceil \log_2(\max ViewportWidth + \max ViewportHeight + 2) \rceil\} eg:$$

The state of a query object can be queried with the commands

```
void GetQueryObjectiv(ui nt id, enum pname,
    i nt *params);
void GetQueryObjectuiv(ui nt id, enum pname,
    ui nt *params);
```

If *id* is not the name of a query object, or if the query object named by *id* is currently active, then an `INVALID_OPERATION`

6.1. QUERYING GL STATE

return information about a bound buffer object. *target* must be one of the targets listed in table 2.7, and *pname*

be in the range zero to the value of `MAX_TRANSFORM_FEEDBACK_SEPARATE_ATTRIBUTES`

returns properties of the shader object named *shader* in *params*. The parameter value to return is specified by *pname*.

If *pname* is `SHADER_TYPE`, `VERTEX_SHADER`, `GEOMETRY_SHADER`, or `FRAGMENT_SHADER` is returned if *shader* is a vertex, geometry, or fragment shader

6.1. ~~QUERYING~~ GL STATE

obtain the vertex attribute state named by *pname* for the generic vertex attribute numbered *index* and places the information in the array *params*. *pname* must be one of VERTEX_ATTRIB_ARRAY_BUFFER_BINDING, VERTEX_ATTRIB_ARRAY_ENABLED, VERTEX_ATTRIB_ARRAY_SIZE, VERTEX_ATTRIB_ARRAY_STRIDE, VERTEX_ATTRIB_ARRAY_TYPE, VERTEX_ATTRIB_ARRAY_NORMALIZED, VERTEX_ATTRIB_ARRAY_INTEGER, or CURRENT_VERTEX_ATTRIB. Note that all the queries except CURRENT_VERTEX_ATTRIB return values stored in the currently bound vertex array object (the value of VERTEX_ARRAY_BUFFER_BINDING). If the zero object is bound, these values are client state. The error INVALID_VALUE is generated if *index* is greater than or equal to MAX_VERTEX_ATTRIBS.

A3 0 9 0 Td [(,)]TJ/13.549 Td [(A3 0 9 0 Td [(,)]TJ.-010han)-251iE.4a(.)]TJ/F44 10.9091 3 127.669 0 Td [

```
void GetUniformiv(ui nt program, i nt location
```

Upon successful return from **GetFramebufferAttachmentParameteriv**, if *pname* is FRAMEBUFFER_ATTACHMENT_OBJECT_TYPE

6.1. *QUERYING GL STATE*


```
void GetRenderbufferParameteriv(enum target, enum pname
```

are ignored. The special *mask* values `ALL_ATTRIB_BITS` and `CLIENT_ALL_ATTRIB_BITS` may be used to push all stackable server and client state, respectively.

The commands

```
void PopAttrib(void);  
void PopClientAttrib(void);
```

reset the values of those state variables that were saved with the last corresponding **PushAttrib** or **PopClientAttrib**

where only the value pertaining to the selected light is returned; with evaluator maps, where only the selected map is returned; and with textures, where only the selected texture or texture parameter is returned. Finally, a “–” in the attribute column indicates that the indicated value is not included in any attribute group (and thus can not be pushed or popped with **PushAttrib**, **PushClientAttrib**, **PopAttrib**, or **PopClientAttrib**).

The M and m

| Type code |
|-----------|
|-----------|

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|-----------|------|-------------|------------------|-------------|------|-----------|
| - | n | BMU | GetBufferSubData | | | |

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|-----------|------|-------------|---------------|-------------|------|-----------|
|-----------|------|-------------|---------------|-------------|------|-----------|

FOG

6.2. STATEA

| | | | | | | |
|-----------|------|-------------|---------------|-------------|------|--------------------------|
| Get value | Type | Get Command | Initial Value | Description | Sec. | Attributr.. STATE TABLES |
|-----------|------|-------------|---------------|-------------|------|--------------------------|

Get Command

Type

Get value

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|----------------------|------|-------------|---------------|-------------|------|-----------|
| TEXTURE_BORDER.COLOR | | | | | | |

Get value
Type
Get Command
Initial

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|--------------|----------------------|-------------------|---------------|-------------|------|-----------|
| DRAW.BUFFERI | 1 Z ₁₁ | GetInteger | see 4.2.1 | | | |

6.2. STATE

| Get value | Type |
|-----------|------|
|-----------|------|

6.2. STATE TABLES

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|------------------------|------|-------------|---------------|-------------|------|-----------|
| UNIFORM_BUFFER_BINDING | Z | | | | | |

6.2. STATE TABLES

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute | Initial Value |
|-----------|------|-------------|---------------|-------------|------|-----------|---------------|
| | | | | | | | 439 |

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|-----------------------------------|------|-------------|---------------|-------------|------|-----------|
| TRANSFORM_FEEDBACK_BUFFER_BINDING | | | | | | |

| Get value | Type | Get Command | Initial Value | Description | Sec. | Attribute |
|-----------------------------|-------|--------------|---------------|-------------|------|-----------|
| PERSPECTIVE.CORRECTION.HINT | Z_3 | GetIntegerv3 | | | | |

6.2. STATE TABLES

6.2. STATEA

6.2. STATE TABLES

Appendix A

Invariance

The OpenGL specification is not pixel exact. It therefore does not guarantee an exact match between images produced by different GL implementations. However, the specification does specify exact matches, in some cases, for images produced

A.2 Multi-pass Algorithms

Invariance is necessary for a whole set of useful multi-pass algorithms. Such al-

A.4. WHAT₁₁(T)GL₁₁(TTHIS₁₁(TMEANS)J/J/F4191T#25.79342.292T/.4.)-457

Appendix B

Corollaries

The following observations are derived from the body and the other appendixes of the specification. Absence of an observation from this list in no way impugns its veracity.

1. The `CURRENT_RASTER_TEXTURE_COORDS` must be maintained correctly at

stencil comparison function; it limits the effect of the update of the stencil buffer.

8. Polygon shading is completed before the polygon mode is interpreted. If the shade model is `FLAT`, all of the points or lines generated by a single polygon

16.

Appendix C

Compressed Texture Image Formats

C.1 RGTC Compressed Texture Image Formats

Compressed texture images stored using the RGTC compressed image encodings are represented as a collection of

C.1.1 Format COMPRESSED_RED_RGTC1

Each 4 × 4 block of texels consists of 64 bits of unsigned red image data.

Each red image data block is encoded as a sequence of 8 bytes, called (in order

C.1. RGTC COMPRESSED TEXTURE IMAGE FORMATS

Appendix D

Shared Objects and Multiple Contexts

This appendix describes special considerations for objects shared between multiple OpenGL context, including deletion behavior and how changes to shared objects are propagated between contexts.

Objects that can be shared between contexts include pixel and vertex buffer objects, **display lists**, program and shader objects, renderbuffer objects, sync objects, and texture objects (except for the texture objects named zero).

Framebuffer, query, and vertex array objects are not shared.

Implementations may allow sharing between contexts implementing different OpenGL versions or different profiles of the same OpenGL version (see appendix E). However, implementation-dependent behavior may result when aspects and/or behaviors of such shared objects do not apply to, and/or are not described by more than one version or profile.

D.1 Object Deletion Behavior

D.1.1 Automatic Unbinding of Deleted Objects

When a buffer, texture, or renderbuffer object is deleted, it is unbound from any bind points it is bound to in the current context, as described for **DeleteBuffers**, **DeleteTextures**, and **DeleteRenderbuffers**. Bind points in other contexts are not affected.

D.1.2 Deleted Object and Object Name Lifetimes

When a buffer, texture, renderbuffer, or sync object is deleted, its name immediately becomes invalid (e.g. is marked unused), but the underlying object will not be deleted until it is no longer *in use*. A buffer, texture, or renderbuffer object is in

D.3 Propagating State Changes

Data is information the GL implementation does not have to inspect, and does not have an operational effect. Currently, data consists of:

- Pixels in the framebuffer.

- The contents of textures and renderbuffers.

- The contents of buffer objects.

State determines the configuration of the rendering pipeline and the driver does

D.3.2 Definitions

In the remainder of this section, the following terminology is used:

An object T is *directly attached* to the current context if it has been bound to

made in another context but not determined to have completed as described in section [D.3.1](#), or after C is bound in the current context, are not guaranteed to be seen.

Appendix E

Profiles and the Deprecation Model

OpenGL 3.0 introduces a deprecation model in which certain features may be

E.1 Core and Compatibility Profiles

OpenGL 3.2 is the first version of OpenGL to define multiple profiles. The *core profile* builds on OpenGL 3.1 by adding features described in section H.1. The *compatibility profile* builds on the combination of OpenGL 3.1 with the special `GL_ARB_compatibility` extension defined together with OpenGL 3.1, adding the same new features and in some cases extending their definition to interact with existing features of OpenGL 3.1 only found in `GL_ARB_compatibility`.

It is not possible to implement both core and compatibility profiles in a single GL context, since the core profile mandates functional restrictions not present in the compatibility profile. Refer to the `WGL_ARB_create_context_profile` and `GLX_ARB_create_context_profile` extensions (see appendix I.3.68) for information on creating a context implementing a specific profile.

E.2 Deprecated and Removed Features

OpenGL 3.0 defined a set of *deprecated features* Opn7 7(es)]TJ41(es)]T r mos-203(set)--204(o)-274(for)8Tf -123

Wide lines - **LineWidth** values greater than 1.0 will generate an `INVALID_VALUE` error.

Global component limit query - the implementation-dependent values `MAX_VARYING_COMPONENTS` and `MAX_VARYING_FLOATS`.

E.2.2 Removed Features

Application-generated object names - the names of all object types, such as buffer, query, and texture objects, must be generated using the corresponding **Gen***

able/Disable targets `RESCALE_NORMAL` and `NORMALIZE` (section 2.12.2);
TexGen* and **Enable/Disable** targets `TEXTURE_GEN_*` (section 2.12.3,
Material*, **Light***, **LightModel***, and **ColorMaterial**, **ShadeModel**,
and **Enable/Disable** targets `LIGHTING`, `VERTEX_PROGRAM_TWO_SIDE`,
`LIGHT`, and `COLOR_MATERIAL` (sections

Separate polygon draw mode - **PolygonMode** *face* values of FRONT and BACK

tion 3.9 referring to nonzero border widths during texture image specification

Display lists - **NewList**, **EndList**, **CallList**, **CallLists**, **ListBase**, **GenLists**, **IsList**, and **DeleteLists** (section 5.4); all references to display lists and behavior when compiling commands into display lists elsewhere in the specification; and all associated state.

Hints - the **PERSPECTIVE_CORRECTION_HINT**, **POINT_SMOOTH_HINT**, **FOG_HINT**, and **GENERATE_MIPMAP_HINT** targets to

F.2. DEPRECATIION MODEL

F.3. CHANGED TOKENS

Changed **ClearBuffer*** in section 4.2.3 to indirect through the draw buffer state by specifying the buffer type and draw buffer number, rather than the attachment name; also changed to accept DEPTH_BUFFER / DEPTH_ATTACHMENT and STENCIL_BUFFER / STENCIL_ATTACHMENT interchangeably, to reduce inconsistency between clearing the default framebuffer and framebuffer objects. Likewise changed **GetFramebufferAttachmentParameteriv** in section 6.1.17 to accept DEPTH_BUFFER / DEPTH_ATTACHMENT and STENCIL_BUFFER / STENCIL_ATTACHMENT interchangeably (bug 3744).

Add proper type suffix to query commands in tables 6.9 and 6.46 (Mark Kilgard).

Update deprecation list in section E.2 to itemize deprecated state for two-sided color selection and include per-texture-unit LOD bias (bug 3735).

Changes in the draft of August 28, 2008:

Andreas Wolf, AMD

Avi Shapira, Graphic Remedy

Barthold Lichtenbelt, NVIDIA (Chair, Khronos OpenGL ARB Working Group)

Benjamin Lipchak, AMD

Mark Callow, HI Corp

Mark Kilgard, NVIDIA (Many extensions on which OpenGL 3.0 features were based)

Appendix G

Version 3.1

OpenGL version 3.1, released on March 24, 2009, is the ninth revision since the original version 1.0.

Unlike earlier versions of OpenGL, OpenGL 3.1 is not upward compatible with earlier versions. The commands and interfaces identified as *deprecated* in OpenGL 3.0 (see appendix [F](#)) have been **removed**

state has become server state, unlike the NV extension where it is client state. As a result, the numeric values assigned to `PRIMITIVE_RESTART` and `PRIMITIVE_RESTART_INDEX` differ from the NV versions of those tokens.

At least 16 texture image units must be accessible to vertex shaders, in addition to the 16 already guaranteed to be accessible to fragment shaders.

Texture buffer objects (`GL_ARB_texture_buffer_object`).

Rectangular textures (`GL_ARB_texture_rectangle`).

Uniform buffer objects (`GL_ARB_uniform_buffer_object`).

Signed normalized texture component formats.

G.2 Deprecation Model

G.4. CREDITS AND ACKNOWLEDGEMENTS

The ARB gratefully acknowledges administrative support by the members of Gold Standard Group, including Andrew Riegel, Elizabeth Riegel, Glenn Fredericks, and Michelle Clark, and technical support from 3EMENTSE and of Khronos.org and OpenGL.org.

Appendix H

Version 3.2

OpenGL version 3.2, released on August 3, 2009, is the tenth revision since the original version 1.0.

Separate versions of the OpenGL 3.2 Specification exist for the *core* and *compatibility* profiles described in appendix E, respectively subtitled the “Core Profile” and the “Compatibility Profile”. This document describes the **Compatibility Profile**. An OpenGL 3.2 implementation *must* be able to create a context supporting the core profile, and may also be able to create a context supporting the compatibility profile.

BGRA vertex component ordering (`GL_ARB_vertex_array_bgra`).

Change flat-shading source value description from “generic attribute” to “varying” in sections [3.5.1017](#)

Remove a reference to unreachable `INVALID_OPERATION` errors from the core profile only in section 6.1.2 (Bug 5365).

Specify that compressed texture component type queries in section 6.1.3 return how components are interpreted after decompression (Bug 5453).

Increase value of `MAX_UNIFORM_BUFFER_BINDINGS` and `MAX_COMBINED_UNIFORM_BLOCK_BINDINGS`

of Khronos.org and OpenGL.org.

Appendix I

Extension Registry, Header Files, and ARB Extensions

I.1 Extension Registry

Many extensions to the OpenGL API have been defined by vendors, groups of vendors, and the OpenGL ARB. In order not to compromise the readability of the GL Specification, such extensions are not integrated into the core language; instead, they are made available online in the *OpenGL Extension Registry*, together

obtained directly from the OpenGL Extension Registry (see section

will be present in the EXTENSIONS string returned by **GetString**, and will be among the EXTENSIONS strings returned by **GetStringi**, as described in section 6.1.4.

I.3.5 Multisample

The name string for multisample is `GL_ARB_multisample`. It was promoted to a core feature in OpenGL 1.3.

I.3.6 Texture Add Environment Mode

The name string for texture add mode is `GL_ARB_texture_env_add`. It was promoted to a core feature in OpenGL 1.3.

I.3.7 Cube Map Textures

The name string for cube mapping is `GL_ARB_texture_cube_map`. It was promoted to a core feature in OpenGL 1.3.

I.3.8 Compressed Textures

I.3.12 Matrix Palette

parameter to be returned when the texture comparison fails. This may be used for ambient lighting of shadowed fragments and other advanced lighting effects.

The name string for shadow ambient is `GL_ARB_shadow_ambient`. **1.3. Winai-250(amRast)-250(ad**

I.3.26 High-Level Vertex Programming

The name string for high-level vertex programming is `GL_ARB_vertex_shader`. It was promoted to a core feature in OpenGL 2.0.

I.3.27 High-Level Fragment Programming

The name string for high-level fragment programming is `GL_ARB_fragment_shader`. It was promoted to a core feature in OpenGL 2.0.

I.3.28 OpenGL Shading Language

The name string for the OpenGL Shading Language is `GL_ARB_shading_language_100`. The presence of this extension string indicates that programs written in version 1 of the Shading Language are accepted by OpenGL. It was promoted to a core feature in OpenGL 2.0.

I.3.29 Non-Power-Of-Two Textures

The name string for non-power-of-two textures is `GL_ARB_texture_non_power_of_two`.for high-level fragment programming is `GL_ARB_fragment_shader`

core functionality introduced in OpenGL 3.0, based on the earlier `GL_EXT_framebuffer_sRGB` extension, and is provided to enable this functionality in older drivers.

To create sRGB format surface for use on display devices, an additional pixel format (config) attribute is required in the window system integration layer. The name strings for the GLX and WGL sRGB pixel format interfaces are

I.3.57 Fragment Coordinate Convention Control

The name string for fragment coordinate convention control is `GL_ARB_fragment_coord_conventions`

The name string for per-buffer blend control is GL_ARB_draw_buffers_
bl end.

ALPHA12, 218

ALPHA16, 218

ALPHA4, 218

ALPHA8, 216, 218

ALPHA, 218

INDEX

CLIP_DISTANCE *i*, 137, 405, 479

CLIP_DISTANCE0, 137

CLIP_PLANE *i*, 136, 405, 479

ClipPlane, 136, 473

COEFF, 370, 432

COLOR, 62, 66, 176, 180, 181, 227,
305, 306, 316

Color, 29, 32, 70, 80, 86, 129, 140

Color*, 472

Color3, 32

Color4, 32

Color[size][type]*v*, 38

COLOR_ARRAY, 37, 46, 399

COLOR_ARRAY_BUFFER_B4132 0 rg 1 0 0 RG [-250(479)]TJ0 g 0 G -666 0 7.051 0 0 RG [-250ING0 g 0 G

COMPILE, [356](#), [459](#)

COMPILE_AND_EXECUTE, [356](#), [357](#)

COMPILE_STATUS, [83](#), [385](#), [433](#)

CompileShader, [83](#), [359](#)

COPY_READ_

DEPTH_BUFFER_BIT, 304, 306, 318–
320, 394
DEPTH_CLAMP, 137, 405
DEPTH_CLEAR_VALUE, 420
DEPTH_COMPONENT, 113, 174, 175,
177, 186,

DYNAMIC_DRAW, 49, 50 DYNAMIC

FILL, 166–169, 348, 410, 459
Finish, 359, 360, 458, 467
FIRST_VERTEX_CONVENTION, 134
FIXED_ONLY, 197, 313, 320, 321, 406
FLAT, 134, 459
flat, 121, 134
FLOAT, 35, 38, 39, 45–47,

MENT_

GetProgramInfoLog, 85, 386, 434

GetProgramiv, 85, 87, 92, 94, 109, 115,

GL_ARB.geometry_shader4, [490](#)
GL_ARB_half_float_pixel, [478](#), [503](#)
GL_ARB_half_float_vertex, [505](#)
GL_ARB

GL_EXT_transform_feedback, 478
gl_FogFragCoord, 114, 122, 124, 140
gl_FragColor, 277, 278, 301
gl_FragCoord, 275
gl_FragCoord.z, 457
gl_FragData, 278, 301
gl_FragData[n], 277, 278
gl_FragDepth, 277, 278, 457
gl_FrontColor, 75, 114, 122, 124, 134
gl_

LOAD, 307
LoadIdentity, 63, 472
LoadMatrix, 62, 63, 472
LoadMatrix[fd], 63
LoadName, 350, 351, 475
LoadTransposeMatrix, 62, 472
LoadTransposeMatrix[fd], 63
LOGICLoadTransposeMatrix[fd],

mat4, 87, 96
mat4x2, 86, 96
mat4x3, 87, 96
Material, 30, 76–78, 81, 459
Material*, 473
MATRIX-

MAX_LIST_NESTING, 444

MAX_MODELVIEW_STACK_-
DEPTH, 443

MAX_NAME_STACK_DEPTH,

MultiDrawElementsBaseVertex, 44, 58
MULTISAMPLE, 149, 155, 162, 168,
207, 210, 284, 297, 411
MULTISAMPLE_BIT, 394
MultiTexCoord, 29, 31, 38
MultiTexCoord[size][type]v, 38
MultMatrix, 62, 63, 472
MultMatrix[fd], 63
MultTransposeMatrix, 62, 472
MultTransposeMatrix[fd], 63

N3F_V3F, 44, 45
NAME_STACK_DEPTH, 453
NAND, 296
NEAREST, 111, 112, 241–243, 247,
248, 250, 252, 253, 255, 266,
319, 334
NEAREST_MIPMAP_-
LINEAR, 241, 250, 252, 254,
256, 334
NEAREST_MIPMAP_NEAREST, 241,
250, 252, 254, 255, , 334
NEAVER, , 2186]TJ0 g 0 G [(-)]TJ1 0 0 rg 1 0 0 RG [(248)]TJ0 g 0 G 0 -13.549 Td [(MNe)5(1wList)]TJ1 0 0
257,

ORDER, 370, 432

Ortho, 63, 65, 459, 472

OUT_OF_MEMORY, 18, 19, 51, 54,
237, 327, 356

PACK_ALIGNMENT, 310, 426

PACK_IMAGE_HEIGHT, 310, 373,
426

PACK_LSB_FIRST, 310, 426

PACK_ROW_LENGTH, 310, 426

PACK_SKIP_IMAGES, 310, 373, 426

PACK_SKIP_

PolygonOffset, 167

PolygonStipple, 165, 170, 474

PopAttrib, 392, 393, 395, 460, 476

PopClientAttrib, 30, 358, 392, 393, 395,
476

INDEX

RGB8UI, 216, 219

RGB9_E5, 175, 216, 219, 268, 314

RGB_INTEGER, 186

RGB_SCALE, 261, 417

RGBA, 176, 177, 180, 182, 186, 189,
194, 201, 202,

samplerBuffer, 97
samplerCube, 97
samplerCubeShadow, 97
SAMPLES, 148, 149, 289, 320, 340,
452
SAMPLES_PASSED, 129, 130, 289,
380
Scale, 63, 64,

412

TEXTURE_BINDING_2D_ARRAY,

412

TEXTURE_BINDING_2D_MULTI-
SAMPLE, 413

TEXTURE_BINDING_2D_MULTI-
SAMPLE_ARRAY, 413

TEXTURE_BINDING_BUFFER, 413

TEXTURE_BINDING_CUBE_MAP,
413

TEXTURE_BINDING_RECTANGLE,
413

TEXTURE_BIT, 393, 394

TEXTURE_BLUE_SIZE, 371

TEXTURE_BLUE_TYPE, 371

TEXTURE_BORDER, 234, 235, 371,
415

TEXTURE_BORDER_COLOR,
239, 241, 248, 256, 370, 414,
481

TEXTURE_BUFFER, 48, 238, 239,
258, 259,

INDEX

541

TRANSFORM

UNIFORM_BLOCK_REFERENCED_-
BY_GEOMETRY_SHADER,
93, 437
UNIFORM_BLOCK_REFERENCED_-
BY_VERTEX_

MULTISAMPLE_ARRAY, 98
UNSIGNED_INT_SAMPLER_2D_-
RECT, 98
UNSIGNED_INT_SAMPLER_3D, 97
UNSIGNED_INT_SAMPLER_-
BUFFER, 98
UNSIGNED_INT_SAMPLER_CUBE,
97
UNSIGNED_INT_VEC2, 88, 96
UNSIGNED_INT_VEC3, 88, 96
UNSIGNED_INT_VEC4, 88, 96
UNSIGNED_NORMALIZED, 371, 390
UNSIGNED_SHORT, 35, 41, 185,

INDEX

544

VERTEX