



DESCRIPTION

ALZ 3742 is based on a high-precision capacitive ceramic oil-free sensor with ranges starting at 40 mbar for measuring liquid levels as low as 40 cm. High overload capacity of the sensor, flush ceramic diaphragm and plastic housing make ALZ 3742 a great choice for the aggressive* and viscous media. Similar model ALZ 3740 in stainless steel housing is available for abrasive media applications.

SPECIFICATIONS

Level: 0.4 mH₂O up to 100 mH₂O

Basic accuracy: $\pm 0.25\%$ of span

Sensor: high-precision ceramic capacitive

Probe: Ø45 mm, plastic

Output signal: 4...20 mA; RS-485 / Modbus RTU; HART®

Media temperature (depends on housing):

PVC: -20...+50 °C,

PVDF: -20...+70 °C

HART® is a registered trademark of the HART Communication Foundation.

APPLICATIONS

Viscous media

Harsh conditions*

Sewage, wastewater

Precise level control in tanks

* please consult the manufacturer for particular media compatibility

TECHNICAL SPECIFICATIONS

MEASURING RANGES

Pressure range, bar	Level, mH ₂ O	Overpressure, bar	Pressure range, bar	Level, mH ₂ O	Overpressure, bar
0...0.04	0...0.4	0.3	0...1	0...10	3
0...0.06	0...0.6	0.3	0...1.6	0...16	6
0...0.1	0...1	1	0...2.5	0...25	6
0...0.16	0...1.6	1	0...4	0...40	15
0...0.25	0...2.5	1	0...6	0...60	15
0...0.4	0...4	1	0...10	0...100	30
0...0.6	0...6	3	-	-	-

PERFORMANCE	P > 0,1 6ap	P ≤ 0,1 6ap
Accuracy, % of span*	≤ ±0.25	≤ ±0.5
Temperature effect (% of span / 10 °C)	≤ ±0.2	≤ ±0.3
Compensated range	-20...+50 °C	0...+50 °C
Power supply effect	≤ ±0.05% of span / 10 V	
Load resistance effect	≤ ±0.05% of span / kOhm (transmitters with current output)	
Long-term stability	≤ ±0.1% of span / year	
Response time (10...90%)	≤ 150 ms	
* Accuracy includes non-linearity, hysteresis and non-repeatability.		

OPERATING CONDITIONS

Medium temperature	PVC	-20...+50 °C
	PVDF	-20...+70 °C
Cable service temperature (static applications)	PVC:	-20...+70 °C
	PUR:	-50...+70 °C
Storage temperature		-20...+50 °C
Vibration resistance		10 g RMS, 25–2000 Hz
Shock resistance		100 g / 11 ms
Service life		> 100 x 10 ⁶ cycles

MECHANICAL SPECIFICATIONS

Housing	PVC; PVDF
Seal	FKM; EPDM; NBR
Diaphragm	ceramics Al ₂ O ₃ 96 %
Cable external jacket	PVC, PUR, FEP
Ingress protection	IP69K

ELECTRICAL SPECIFICATIONS


Output signal	Power supply, U _s	Load resistance, R	Power consumption
4...20 mA / 2-wire	12...36 V	$\leq [(U_s - 12 \text{ V}) / 0.02 \text{ A}] \text{ Ohm}^*$	$\leq 26 \text{ mA}$
4...20 mA / HART®			
0.5...4.5 V / 3-wire	5 V	$\geq 5 \text{ kOhm}$	$\leq 2 \text{ mA}$
0.5...4.5 V / 3-wire	6...15 V		$\leq 7 \text{ mA}$
RS-485 / Modbus RTU	12...36 V	-	

* For output signal 4...20 mA / HART® minimum load resistance for digital communication: 250 Ohm.

ELECTRICAL CONNECTIONS / PIN ASSIGNMENT

Circuits		Cable gland wires
2-wire	power +	white (red)
	power -	brown (blue)
	ground	yellow-green
3-wire	power +	white (red)
	power -	brown (blue)
	signal +	green (black)
	ground	yellow-green
RS-485	power +	white (red)
	power -	brown (blue)
	A	yellow
	B	green (black)
	ground	yellow-green
HART®	power +	white
	power -	brown
	ground	yellow-green

DIMENSIONS (mm)



ORDERING CODE

ALZ 3742		-X	-XXXX	-X	-X	-X	-X	-XX	// X	-XXXX
UNIT OF MEASUREMENT										
	bar	B								
	kg/cm ²	S								
	mH ₂ O	W								
	kPa	K								
	Other (specify when ordering)	X								
UPPER RANGE LIMIT (URL)										
bar, kg/cm ²		mH ₂ O		kPa						
0.04	0040	0.4	0400	4	4000					
0.06	0060	0.6	0600	6	6000					
0.1	0100	1	1000	10	1001					
0.16	0160	1.6	1600	16	1601					
0.25	0250	2.5	2500	25	2501					
0.4	0400	4	4000	40	4001					
0.6	0600	6	6000	60	6001					
1	1000	10	1001	100	1002					
1.6	1600	16	1601	160	1602					
2.5	2500	25	2501	250	2502					
4	4000	40	4001	400	4002					
6	6000	60	6001	600	6002					
10	1001	100	1002	1000	1003					
Other	XXXX	Other	XXXX	Other	XXXX					
ACCURACY										
						0.25% (P > 0.1 bar) (standard)	C			
						0.5% (P ≤ 0.1 bar) (standard)	D			
						Other (specify when ordering)	X			
OUTPUT SIGNAL										
						4...20 mA / 2-wire (standard)	A			
						0.5...4.5 V / 3-wire, U _s = 5 V	R			
						0.5...4.5 V / 3-wire, U _s = 6...15 V	K			
						RS-485 / Modbus RTU	M			
						4...20 mA / HART®	H			
						Other (specify when ordering)	X			
SEALS										
						FKM	F			
						NBR	N			
						EPDM	E			
						Other (specify when ordering)	X			
HOUSING MATERIAL										
						PVC	P			
						PVDF	F			
						Other (specify when ordering)	X			

ORDERING CODE (CONTINUED)

ALZ 3742	-X	-XXXX	-X	-X	-X	-X	-XX	// X	-XXXX
VERSION									
							Standard	00	
							Other (specify when ordering)	XX	
CABLE EXTERNAL JACKET									
							PVC	P	
							PUR	U	
							FEP	T	
							Other (specify when ordering)	X	
CABLE LENGTH									
Any length in meters (e.g., 010M means 10 meters)									XXXM

Example: ALZ 3742-W-6000-D-A-F-P-00 // P-010M

ACCESSORIES

				
Anchoring clamp for submersible transmitter	PZ 1024 Power supply unit	BZ 05 / BZ 10 Dry air junction box for submersible transmitters		