


☒ SELECT DESIRED FINISH:

- ☐ ZINC PRIMED AND
POWDER COATED
- ☐ MILD STEEL GALVANIZED AND
POWDER COATED SLEEVE
- ☐ STAINLESS STEEL SLEEVE
- ☐ BRUSHED
- ☐ BEAD BLASTED
- ☐ FERROCAST
(VARIOUS OPTIONS AVAILABLE)

☒ SELECT DESIRED TOP OPTIONS:

- ☐ FLAT/MITRED
- ☐ WITHOUT GROOVES
- ☐ WITHOUT CLASS 2
REFLECTIVE TAPES




MANUFACTURERS NOTES:

1. FOUNDATION DETAIL FOR INDICATIVE PURPOSES ONLY. PRODUCT TO BE INSTALLED IN ACCORDANCE WITH MARSHALLS SPECIFICATION.
2. FOR HVM COMPLIANCE BOLLARD TO BOLLARD CLEAR GAP MUST NOT EXCEED 47.25".
3. STOP AND START RUN EVERY 49 FEET TO ALLOW FOR EXPANSION.
4. MINIMUM 1 BOLLARD REQUIRED CENTRALLY IN A 2-BOLLARD FOUNDATION.
5. 45° AND CURVED OPTIONS AVAILABLE.
6. PRODUCT MANUFACTURED FROM S355 MILD STEEL.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5416-011



LANDSCAPE PROTECTION - STATIC BOLLARDS

RHINO GUARD® 75-50 CORE 244 PC