



SOLARPATH SUN SOLUTIONS
 123 TOWN SQUARE PL. #333
 JERSEY CITY, NJ 07310
 TOLL FREE: 1-888-333-7652
 PHONE: (201) 490-4499
 FAX: (646) 807-4400
 www.solarpathusa.com

☒ SELECT DESIRED OPTIONS:

☐ GPRS INTEGRATED MANAGEMENT SYSTEM
 (REMOTE CONTROL MONITORING)

☐ WIRELESS REMOTE CONTROLLER

☒ SELECT DESIRED SOLAR PANEL QUANTITY:


☐ 1 PANEL (A)

☐ 2 PANELS (B)


☒ SELECT DESIRED ARM OPTIONS:

☐ 1-SINGLE


☐ 2-DOUBLE



PERSPECTIVE



PLAN VIEW




SIDE VIEW

TECHNICAL SPECIFICATIONS (NPSL)		
SOLAR MODULE PARAMETERS	TYPE	HIGH-EFFICIENCY MONOCRYSTALLINE SILICON
	POWER	UP TO 300W
LED LIGHT PARAMETERS	LIGHT SOURCE POWER	UP TO 120W
	LAMP RATED TOTAL LUMINOUS FLUX	UP TO 15,800LM
	CCT (CORRELATED COLOR TEMPERATURE)	3,000°K - 6,000°K
	COLOR RENDERING INDEX (CRI)	≥ 81
	LIGHT CONTROL VOLTAGE	36VDC
	LIGHTING MATERIAL	DIE-CASTING ALUMINUM

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5336-025.



SOLAR LIGHTS

NPSL