

Firebolt 9 Intents Specification

Document status	APPROVED
Author	Timothy Dibben

- [Constituent parts of an intent](#)
- [Intent Action Types](#)
 - [Home action type](#)
 - [Launch action type](#)
 - [Pre-load action type](#)
 - [Entity action type](#)
 - [Playback action type](#)
 - [Search action type](#)
 - [Section action type](#)
 - [Tune action type](#)
 - [Play-entity action type](#)
 - [Play-query action type](#)
 - [Previous action type](#)
 - [Next action type](#)
 - [Repeat action type](#)
 - [Shuffle action type](#)
 - [Skip-ad action type](#)
 - [Skip-recap action type](#)
 - [Skip-intro action type](#)

An Intent is a message object sent to an application requesting a specific action. This may occur as part of the launch of the application or when it is already loaded. The application shall treat the receipt of an intent as an explicit request to carry out the intent and immediately action it, irrespective of what the application is currently doing. The only exception to this is if the application is carrying out some process that can not be interrupted eg processing a payment.

An application may support multiple intent action types or none, however if an application receives an intent that it does not support, or one that does not contain enough data for an application to fulfil it, it shall ignore it and not present any error to the user.

Constituent parts of an intent

Part	Type	Mandatory	Description	Allowed values															
action	string	Yes	A string specifying the implicit action being requested to be performed	• 'home' • 'launch' • 'pre-load' • 'entity' • 'playback' • 'search' • 'section' • 'tune' • 'play-entity' • 'play-query' • 'previous' • 'next' • 'repeat' • 'shuffle' • 'skip-ad' • 'skip-recap' • 'skip-intro'															
data	object	No	An optional object that contains data to be used by the application in order to fulfil the action	See below															
context	object	Yes	An object defining the source of the intent and optionally properties of that source	<table><tr><th>Name</th><th>Type</th><th>Mandatory</th><th>Allowed values</th><th>Description</th></tr><tr><td>source</td><td>string</td><td>Yes</td><td>Any</td><td>An undefined string indicating the source of the intent eg "voice"</td></tr><tr><td>agePolicy</td><td>string</td><td>No</td><td> • 'app: child' • 'app: teen' • 'app: adult' </td><td>An optional string indicating an age group that the intent is targeting</td></tr></table>	Name	Type	Mandatory	Allowed values	Description	source	string	Yes	Any	An undefined string indicating the source of the intent eg "voice"	agePolicy	string	No	• 'app: child' • 'app: teen' • 'app: adult'	An optional string indicating an age group that the intent is targeting
Name	Type	Mandatory	Allowed values	Description															
source	string	Yes	Any	An undefined string indicating the source of the intent eg "voice"															
agePolicy	string	No	• 'app: child' • 'app: teen' • 'app: adult'	An optional string indicating an age group that the intent is targeting															

Example

```
{
  "action": "playback",
  "data": {
    "entityId": "ABC123"
  },
  "context": {
    "source": "top_10_this_week",
    "agePolicy": "app:child"
  }
}
```

Intent Action Types

Home action type

A request to action a transition to the home page of the application

Definition of data object

The Home action intent does not require a data object

Example

```
{
  "action": "home",
  "context": {
    "source": "apps_rail"
  }
}
```

Launch action type

A request to show the page the app was previously on (or Home page if it's a cold launch) of the application

Definition of data object

Name	Type	Mandatory	Allowed values	Description
dialPayload	URL encoded string	No	Any	The optional DIAL payload
additionalData Url	URL encoded string	No	Any	The optional DIAL URL which allows the first screen application to POST data back to the second screen application

Examples

```
{
  "action": "launch",
  "context": {
    "source": "apps_rail"
  }
}
```

```
{
  "action": "launch",
  "data": {
    "dialPayload": "param1%3Dvalue1%26param2%3Dvalue2",
    "additionalDataUrl": "http%3A%2F%2F127.0.0.1%3A8009%2Fapps%2FmyDialApp%2Fdial_data"
  },
  "context": {
    "source": "DIAL"
  }
}
```

Pre-load action type

A request to pre load the application, but indicates that it will not immediately be activated and is likely to be transitioned into the suspended/hibernated states

Definition of data object

The Pre-load action intent does not require a data object

Example

```
{
  "action": "pre-load",
  "context": {
    "source": "system"
  }
}
```

Entity action type

A request to action a transition to the entity/show page of the specified entity

Definition of data object

Name	Type	Mandatory	Allowed values	Description
entityId	string	Yes	Any	The identifier of the entity, in the target App's scope.
assetId	string	No	Any	The identifier of the asset, in the target App's scope.
seasonId	string	No	Any	The identifier of the season, in the target App's scope.
seriesId	string	No	Any	The identifier of the series, in the target App's scope.
appContentData	string	No	Any	Any extra information required to load the entity page, in the target App's scope.
programType	string	No	Any	An optional indicator of the type of the programme eg 'movie'
entityType	string	No	program	An indicator of the entity type

Examples

```
{
  "action": "entity",
  "data": {
    "entityId": "ABC123"
  },
  "context": {
    "source": "continue_watching"
  }
}
```

```

{
  "action": "entity",
  "data": {
    "entityId": "ABC123",
    "assetId": "asdfs73546",
    "seasonId": "dasfasfhj786876",
    "seriesId": "dsfsf2345",
    "appContentData": "externalId_23456",
    "programType": "series"
  },
  "context": {
    "source": "continue_watching"
  }
}

```

Playback action type

A request to action a transition into the playback of the specified entity

Definition of data object

Name	Type	Mandatory	Allowed values	Description
entityId	string	Yes	Any	The identifier of the entity, in the target App's scope.
assetId	string	No	Any	The identifier of the asset, in the target App's scope.
seasonId	string	No	Any	The identifier of the season, in the target App's scope.
seriesId	string	No	Any	The identifier of the series, in the target App's scope.
appContentData	string	No	Any	Any extra information required by the app to play the asset, in the target App's scope.
programType	string	No	Any	An optional indicator of the type of the programme eg 'movie'
entityType	string	No	program	An indicator of the entity type

Examples

```

{
  "action": "playback",
  "data": {
    "entityId": "ABC123"
  },
  "context": {
    "source": "continue_watching"
  }
}

```

```

{
  "action": "playback",
  "data": {
    "entityId": "ABC123",
    "assetId": "asdfs73546",
    "seasonId": "dasfasfhj786876",
    "seriesId": "dsfsf2345",
    "appContentData": "externalId_23456",
    "programType": "series",
    "entityType": "program"
  },
  "context": {
    "source": "continue_watching"
  }
}

```

Search action type

A request to action a transition to search page of the application, prefill the search box with the supplied query string and initiate the search

Definition of data object

Name	Type	Mandatory	Allowed values	Description
query	string	Yes	Any	The query string to be seeded in the search box

Example

```
{
  "action": "search",
  "data": {
    "query": "die hard"
  },
  "context": {
    "source": "voice"
  }
}
```

Section action type

A request to action a transition to the specified section of the app using the additional data if supplied

Definition of data object

Name	Type	Mandatory	Allowed values	Description
sectionName	string	Yes	Any	The section name, in the target App's scope.
appContentData	string	No	Any	Additional information for the app to present the correct content

Example

```
{
  "action": "section",
  "data": {
    "sectionName": "app:subscribe",
    "appContentData": "Monthly"
  },
  "context": {
    "source": "app:GreatVideoApp"
  }
}
```

Tune action type

A request to action a tune to the specified linear channel, with optional offset options from the live point

Definition of data object

Name	Type	Mandatory	Allowed values	Description
------	------	-----------	----------------	-------------

entity	object	Yes	Name	Type	Mandatory	Allowed values	Description
			entityType	string	Yes	'channel'	
			channelType	string	Yes	'streaming' 'overTheAir'	
			entityId	string	Yes	Any	ID of the channel, in the target App's scope.
			appContentData	string	No	Any	
options	object	No	Name	Type	Mandatory	Allowed values	Description
			assetId	string	No	Any	The ID of a specific 'listing', as scoped by the target App's ID-space, which the App should begin playback from.
			restartCurrentProgram	boolean	No	- true - false	Denotes that the App should start playback at the most recent program boundary, rather than 'live.'
			time	string	No	ISO 8601 Date/Time	ISO 8601 Date/Time where the App should begin playback from.

Example

```
{
  "action": "tune",
  "data": {
    "entity": {
      "entityType": "channel",
      "channelType": "streaming",
      "entityId": "SkyMovies1"
    },
    "options": {
      "restartCurrentProgram": true
    }
  },
  "context": {
    "source": "linear_channel"
  }
}
```

Play-entity action type

A request to start playback of the specified playlist, optionally starting from a specific track

Definition of data object

Name	Type	Mandatory	Allowed values				Description
entity	object	Yes	Name	Type	Mandatory	Allowed values	Description
			entityType	string	Yes	'playlist'	
			entityId	string	Yes	Any	ID of the playlist, in the target App's scope.
options	object	No	Name	Type	Mandatory	Allowed values	Description
			playFirstId	string	No	Any	The Id of the asset in the playlist to play first, in the target App's scope.
			playFirstTrack	number	No	Any	The track number in the playlist to play first

Example

```

{
  "action": "play-entity",
  "data": {
    "entity": {
      "entityType": "playlist",
      "entityId": "BestOf80s"
    },
    "options": {
      "playFirstTrack": 3
    }
  },
  "context": {
    "source": "playlist_selector"
  }
}

```

Play-query action type

A request to start playback of a playlist created by a search

Definition of data object

Name	Type	Mandatory	Allowed values					Description
query	string	Yes	Any					The query to be used to select the content to be played
options	object	No	Name	Type	Mandatory	Allowed values	Description	
			programTypes	string array	No			
			musicTypes	string array	No			

Example

```

{
  "action": "play-query",
  "data": {
    "query": "Queen"
  },
  "context": {
    "source": "music_bands"
  }
}

```

Previous action type

A request to action a transition to the previous media asset in a playlist or series

Definition of data object

The Previous action intent does not require a data object

Example

```

{
  "action": "previous",
  "context": {
    "source": "voice"
  }
}

```

Next action type

A request to action a transition to the next media asset in a playlist or series

Definition of data object

The Next action intent does not require a data object

Example

```
{
  "action": "next",
  "context": {
    "source": "voice"
  }
}
```

Repeat action type

A request to replay the current media asset

Definition of data object

The Repeat action intent does not require a data object

Example

```
{
  "action": "repeat",
  "context": {
    "source": "voice"
  }
}
```

Shuffle action type

A request to start playing randomly another media asset in a playlist or series

Definition of data object

The Repeat action intent does not require a data object

Example

```
{
  "action": "shuffle",
  "context": {
    "source": "voice"
  }
}
```

Skip-ad action type

A request to skip the current advertisement block

Definition of data object

The Skip-ad action intent does not require a data object

Example

```
{
  "action": "skip-ad",
  "context": {
    "source": "voice"
  }
}
```

Skip-recap action type

A request to skip the current recap block

Definition of data object

The Skip-recap action intent does not require a data object

Example

```
{
  "action": "skip-recap",
  "context": {
    "source": "voice"
  }
}
```

Skip-intro action type

A request to skip the current intro block

Definition of data object

The Skip-intro action intent does not require a data object

Example

```
{
  "action": "skip-intro",
  "context": {
    "source": "voice"
  }
}
```