

Scikit-Mol – RDKit integration in Scikit-Learn:


Updates and New Features





Brief Summary

Project started at 2022 RDKit UGM Hackathon



https://github.com/EBjerrum/scikit-mol

Quick RDKit Integration into Scikit-Learn Pipelines

```
In [6]: from sklearn.linear model import Ridge
        from sklearn.pipeline import make pipeline
        from scikit mol.conversions import SmilesToMolTransformer
        from scikit mol.fingerprints import MorganFingerprintTransformer
        model = make_pipeline(SmilesToMolTransformer(),
                              MorganFingerprintTransformer(),
                               Ridge(alpha=10))
        print(model)
        model.fit(smiles list train, y train)
        print(f"Train score is :{model.score(smiles list train, y train):0.2F}")
        print(f"Test score is :{model.score(smiles list test, y test):0.2F}")
       Pipeline(steps=[('smilestomoltransformer', SmilesToMolTransformer()),
                       ('morganfingerprinttransformer',
                        MorganFingerprintTransformer()),
                       ('ridge', Ridge(alpha=10))])
```


► Pipeline

► SmilesToMolTransformer

► MorganFingerprintTransformer

► Ridge

- Featureization from RDKit molecules or SMILES strings
- Integrate into Scikit-Learn models and pipelines
- Fit Scikit-Learn models directly on molecules or SMILES
- Easily get hyperparameter tuning of fingerprinting as compatible with e.g. SKOpt
- Self-documenting and self-contained models
- Use standard scikit-learn classes to build more complex models



Train score is :0.74

Test score is :0.63

Maintenance and Project Improvements

- Online documentation
 https://scikit-mol.readthedocs.io/en/latest/
- Switch to RDKit generators
- Conda package: https://anaconda.org/conda-forge/scikit-mol
- uv build framework


- Improved parallelism using joblib
- Improved handling of parallelism for ad-hoc custom feature transformers



9/10/2025

Pandas Input and Output

- .set_output(transform="pandas")
- Very handy when doing feature importance analysis!
- Column names are checked for consistency when predicting
- model.predict(features[model.feature_names_in_])



	MaxAbsEStateIndex	MaxEStateIndex	MinAbsEStateIndex	MinEStateIndex	qed	SPS	MolWt
0	13.448610	13.448610	0.056985	-0.432587	0.353101	14.289474	522.591980
1	12.863074	12.863074	0.026212	-0.050849	0.682187	16.033333	425.558014
2	13.424788	13.424788	0.266700	-0.413763	0.443905	15.852942	465.588013
3	12.725823	12.725823	0.052996	-0.052996	0.577709	17.812500	478.467987
4	6.356910	6.356910	0.898244	0.898244	0.658108	13.052631	246.313004

154	6.217065	6.217065	0.175664	0.175664	0.916154	35.700001	312.239990
155	0.450245	0.450345	0.400010	0.400010	0 270112	01 71 4005	465 644000

9/10/2025


Safe Inference Mode

- Problematic molecules or SMILES canwill be sent for models by usersGenAl
- safe_inference mode ensures that the whole batch doesn't fail
- Scikit-Mol transformers handle "False" objects (like False, 0, InvalidMol) gracefully
- Scikit-learn estimators should be wrapped in SafeInferenceWrapper

```
from scikit_mol.safeinference import set_safe_inference_mode
from sklearn.pipeline import Pipeline
pipe = Pipeline(
        ("smi2mol", SmilesToMolTransformer()),
        ("mfp",
            MorganFingerprintTransformer(radius=2, fpSize=25)),
        ("safe_regressor",
        SafeInferenceWrapper(LogisticRegression())),
set_safe_inference_mode(pipe, True)
```

Feature Based Applicability Domain Estimators

- Applicability domain estimators now available
- Can be fit to molecular set with a percentile cutoff (i.e. validation set)
- Slight deviation from sklearn api
 - .transform() → returns score
 - .predict() \rightarrow returns 0 or 1
 - .score_transform() → returns 0 to1 (soft boundary)
- bounding box, convex hull, hotelling, isolation forest, kernel density, kNN, leverage, local outlier, mahalanobis, topkat



Conclusion and Acknowledgements

- Scikit-Mol is the original RDKit hackathon initiated project
- New features still being added as contributions from individuals, academia and industry
- Plenty of notebooks and examples at https://scikit-mol.readthedocs.io/en/latest/
- pip/conda install scikit-mol
- Thanks for your attention!

Acknowledgements

Carmen Esposito @cespos, Son Ha @son-ha-264, Ohhyeon Choung @Ohyeon5, Andreas Poehlmann @ap--, Ya Chen @anya-chen, Anton Siomchen @asiomchen, Rafał Bachorz @rafalbachorz, Adrien Chaton @adrienchaton, @VincentAlexanderScholz, Benjamin Ries @RiesBen, @enricogandini, @mikemhenry, Christian Feldmann @c-feldmann, Mieczyslaw Torchala @mieczyslaw, Kyle Barbary @kbarbary, Katja Bjerrum @productivista ...

 Cheminformania Consulting, Aptuit, BASF, Bayer AG, Boehringer Ingelheim, Chodera Lab (MSKCC), EPAM Systems, ETH Zürich, Evotec, Johannes Gutenberg University, Martin Luther University, Odyssey Therapeutics, Open Molecular Software Foundation, Openfree.energy, Polish Academy of Sciences, Productivista, Simulations-Plus Inc., University of Vienna

9/10/2025