

Table 1: M1: Element summary

Element	Qty	Length [m]	Buoyancy [kg]	Weight [kg]
3 Railway Wheels	1		-1350.0	1350.0
3/8 wire rope	1	50.0	-16.5	16.5
41in ORE	1		433.0	
FLNTUSB	1		-0.2	
SBE39 T	1		-0.2	
Zn Anode	1		-0.1	

Table 2: M1: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
Zn Anode		4.5	3/8 wire rope	bulldog	A	4.0
FLNTUSB	2927	20.0	3/8 wire rope	plastic clamp	A	19.4
SBE39 T	3921	30.0	3/8 wire rope	plastic clamp	A	29.4

Table 3: M1: Clamped with summary

Clamp-on	Clamped with	Qty
FLNTUSB	plastic clamp	1
SBE39 T	plastic clamp	1
Zn Anode	bulldog	1

Table 4: M1: Assembly summary

Element	Serial	Length[m]	Section	Clamped with	Height[in ASB]	Weight[kg]
3 Railway Wheels					0.0	1350.0
3/8 wire rope		50.0	A		0.6	16.5
–Zn Anode			A	bulldog	4.5 [4.0 m AE]	
–FLNTUSB	2927		A	plastic clamp	20.0 [19.4 m AE]	
–SBE39 T	3921		A	plastic clamp	30.0 [29.4 m AE]	
41in ORE					50.5	

Table 5: M2: Element summary

Element	Qty	Length [m]	Buoyancy [kg]	Weight [kg]
13mmBS	2		-0.7	
14in Panther Plast	1		17.6	7.1
16mmBS	4		-0.7	
16mmDS	1		-0.7	
3 Railway Wheels	1		-1350.0	1350.0
3/8 wire rope	2	120.0	-39.6	39.6
41in ORE	1		433.0	
6mm AmSteel	1	1.0	0.0	
75kHz+40in+Ti300kHz	1		85.8	297.0
8mm Load Ring	2		-0.5	
FLNTUSB	3		-0.2	
Longranger	1		0.0	
SBE39 T	1		-0.2	
SBE39 ext. T	1		-0.2	
SBE39 sync. T	1		-0.2	
SBE56 T	2		-0.1	
Sentinel	1		0.0	
Zn Anode	2		-0.1	

Table 6: M2: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
Zn Anode		4.6	3/8 wire rope	bulldog	A	4.0
FLNTUSB	2997	10.0	3/8 wire rope	plastic clamp	A	9.4
SBE39 T	3975	15.0	3/8 wire rope		A	14.4
FLNTUSB	3194	20.0	3/8 wire rope	plastic clamp	A	19.4
SBE56 T	7343	30.0	3/8 wire rope	cage	A	29.4
SBE39 ext. T	3799	45.0	3/8 wire rope		A	44.4
Sentinel	20089	51.2	75kHz+40in+Ti300kHz			0.4
Longranger	16870	52.8	75kHz+40in+Ti300kHz			1.9
Zn Anode		57.2	3/8 wire rope	bulldog	B	4.0
FLNTUSB	1835	70.0	3/8 wire rope	plastic clamp	B	16.8
SBE56 T	7344	90.0	3/8 wire rope	plastic clamp	B	36.8
SBE39 sync. T	4456	100.0	3/8 wire rope		B	46.8

Table 7: M2: Clamped with summary

Clamp-on	Clamped with	Qty
FLNTUSB	plastic clamp	3
SBE56 T	cage	1
	plastic clamp	1
Zn Anode	bulldog	2

Table 8: M2: Assembly summary

Element	Serial	Length[m]	Section	Clamped with	Height[in ASB]	Weight[kg]
3 Railway Wheels					0.0	1350.0
16mmBS					0.6	
3/8 wire rope		50.0	A		0.6	16.5
–Zn Anode			A	bulldog	4.6 [4.0 m AE]	
–FLNTUSB	2997		A	plastic clamp	10.0 [9.4 m AE]	
–SBE39 T	3975		A		15.0 [14.4 m AE]	
–FLNTUSB	3194		A	plastic clamp	20.0 [19.4 m AE]	
–SBE56 T	7343		A	cage	30.0 [29.4 m AE]	
–SBE39 ext. T	3799		A		45.0 [44.4 m AE]	
13mmBS					50.6	
8mm Load Ring					50.7	
16mmBS					50.8	
75kHz+40in+Ti300kHz					50.8	297.0
–Sentinel	20089				51.2 [0.4 m AE]	
–Longranger	16870				52.8 [1.9 m AE]	
16mmBS					53.1	
3/8 wire rope		70.0	B		53.2	23.1
–Zn Anode			B	bulldog	57.2 [4.0 m AE]	
–FLNTUSB	1835		B	plastic clamp	70.0 [16.8 m AE]	
–SBE56 T	7344		B	plastic clamp	90.0 [36.8 m AE]	
–SBE39 sync. T	4456		B		100.0 [46.8 m AE]	
13mmBS					123.2	
8mm Load Ring					123.3	
16mmBS					123.4	
41in ORE					123.4	
6mm AmSteel		1.0			124.5	
16mmDS					125.5	
14in Panther Plast					125.5	7.1

Table 9: All: summary of instruments

Element	Serial number	Clamped with	Mooring
75kHz+40in+Ti300kHz [n=1]			M2
FLNTUSB [n=4]	2927	plastic clamp	M1
	1835	plastic clamp	M2
	2997	plastic clamp	M2
	3194	plastic clamp	M2
Longranger [n=1]	16870		M2
SBE39 T [n=2]	3921	plastic clamp	M1
	3975		M2
SBE39 ext. T [n=1]	3799		M2
SBE39 sync. T [n=1]	4456		M2
SBE56 T [n=2]	7343	cage	M2
	7344	plastic clamp	M2
Sentinel [n=1]	20089		M2
Zn Anode [n=3]		bulldog	M1
		bulldog	M2
		bulldog	M2

Table 10: All : Total count of each element

Name	M1	M2	Total
13mmBS	0	2	2
14in Panther Plast	0	1	1
16mmBS	0	4	4
16mmDS	0	1	1
3 Railway Wheels	1	1	2
3/8 wire rope	1	2	3
41in ORE	1	1	2
6mm AmSteel	0	1	1
75kHz+40in+Ti300kHz	0	1	1
8mm Load Ring	0	2	2
FLNTUSB	1	3	4
Longranger	0	1	1
SBE39 T	1	1	2
SBE39 ext. T	0	1	1
SBE39 sync. T	0	1	1
SBE56 T	0	2	2
Sentinel	0	1	1
Zn Anode	1	2	3

Table 11: All : Total count clamp types

Clamp-on	Clamped with	M1	M2	Total
FLNTUSB	plastic clamp	1	3	4
SBE39 T	plastic clamp	1	0	1
SBE56 T	cage	0	1	1
	plastic clamp	0	1	1
Zn Anode	bulldog	1	2	3

Table 12: All: simple section summary

Mooring	Section	Material	Length
M1	A	3/8 wire rope	50.0
M2	A	3/8 wire rope	50.0
M2	B	3/8 wire rope	70.0
M2		6mm AmSteel	1.0

Table 13: Summary of M1, A, length: 50.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		4.5	4.0
FLNTUSB	2927	20.0	19.4
SBE39 T	3921	30.0	29.4

Table 14: Summary of M2, A, length: 50.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		4.6	4.0
FLNTUSB	2997	10.0	9.4
SBE39 T	3975	15.0	14.4
FLNTUSB	3194	20.0	19.4
SBE56 T	7343	30.0	29.4
SBE39 ext. T	3799	45.0	44.4

Table 15: Summary of M2, B, length: 70.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		57.2	4.0
FLNTUSB	1835	70.0	16.8
SBE56 T	7344	90.0	36.8
SBE39 sync. T	4456	100.0	46.8