

Table 1: W310 ■: Element summary

Element	Qty	Length [m]	Buoyancy [kg]
100 cm Signature Frame	1		-7.5
10mm Load Ring	3		0.5
13mmBS	9		-0.7
14in Panther Plast	1		17.6
16mmBS	10		-0.7
16mmDS	1		-0.7
3/8 chain SL	1	2.0	-4.7
3/8 wire rope	4	285.5	-94.2
30in	2		149.0
6mm AmSteel	1	1.0	0.0
75kHz+40in+Ti300kHz	1		85.8
8mm Load Ring	6		0.5
Anchor W310	1		-900.0
FLNTUSB	3		-0.2
Longranger	1		0.0
RBRquartz TP	1		-0.2
Ribuck Dual Kit for Sonardyne ORT	1		-35.0
SBE37 SMP plastic CTP	3		0.0
SBE37 SMP titanium CTP	1		0.0
SBE39 T	1		-0.2
SBE39 ext. T	1		-0.2
SBE39 ext. TP	1		-0.2
SBE39 plus TP	1		-0.2
SBE39 sync. T	1		-0.2
SBE56 T	18		-0.1
Sentinel	1		0.0
Sercel	1		0.0
Sercel+frame	1		-10.0
Signature 1000	1		0.0
Sonardyne ORT	2		0.0
Swivel	1		-4.0
Zn Anode	4		-0.1

Table 2: W310 ■: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
RBRquartz TP	213895	0.5	Anchor W310			0.5
Sonardyne ORT	262762-001 [65]	3.1	Ribuck Dual Kit for Sonardyne ORT			0.3
Sonardyne ORT	262762-002 [64]	3.1	Ribuck Dual Kit for Sonardyne ORT			0.3
FLNTUSB	2997	5.0	3/8 wire rope		A	0.6
SBE39 T	3975	5.1	3/8 wire rope		A	0.7
Zn Anode		7.5	3/8 wire rope		A	3.1
FLNTUSB	3194	9.4	3/8 wire rope		A	5.0
SBE56 T	7343	9.9	3/8 wire rope		A	5.5
SBE39 ext. T	3799	14.9	3/8 wire rope		A	10.5
FLNTUSB	1835	19.4	3/8 wire rope		A	15.0
SBE56 T	7344	19.9	3/8 wire rope		A	15.5
SBE39 sync. T	4456	24.9	3/8 wire rope		A	20.5
Sentinel	20089	31.0	75kHz+40in+Ti300kHz			0.4
Longranger	16870	32.5	75kHz+40in+Ti300kHz			1.9
SBE56 T	7345	33.6	3/8 wire rope		B	0.4
Zn Anode		37.7	3/8 wire rope		B	4.5
SBE56 T	7346	45.6	3/8 wire rope		B	12.4
SBE56 T	7347	58.1	3/8 wire rope		B	24.9
SBE56 T	7369	70.6	3/8 wire rope		B	37.4
SBE56 T	7370	83.1	3/8 wire rope		B	49.9
SBE37 SMP titanium CTP	11063	95.5	3/8 wire rope		B	62.3
SBE56 T	7371	108.1	3/8 wire rope		B	74.9
SBE56 T	12319	120.6	3/8 wire rope		B	87.4
SBE56 T	7374	133.1	3/8 wire rope		B	99.9
SBE56 T	7375	145.6	3/8 wire rope		B	112.4
SBE56 T	7376	158.1	3/8 wire rope		B	124.9
SBE37 SMP plastic CTP	12738	170.5	3/8 wire rope		B	137.3
SBE56 T	7377	183.1	3/8 wire rope		B	149.9
SBE39 plus TP	8222	195.6	3/8 wire rope		B	162.4
Zn Anode		203.7	3/8 wire rope		C	2.3
SBE56 T	7378	208.2	3/8 wire rope		C	6.8
SBE56 T	7399	220.7	3/8 wire rope		C	19.3
SBE37 SMP plastic CTP	12739	233.0	3/8 wire rope		C	31.6
SBE56 T	7400	245.7	3/8 wire rope		C	44.3
SBE56 T	7401	258.2	3/8 wire rope		C	56.8
SBE56 T	7402	270.7	3/8 wire rope		C	69.3
SBE37 SMP plastic CTP	9276	283.0	3/8 wire rope		C	81.6
Signature 1000	100244	290.6	100 cm Signature Frame			0.9
Zn Anode		293.1	3/8 wire rope		D	1.9
SBE39 ext. TP	6523	295.0	3/8 wire rope		D	3.8
Sercel	126989	297.3	Sercel+frame			0.4

Table 3: W310 ■: Clamped with summary

Clamp-on	Clamped with	Qty
----------	--------------	-----

Table 4: W310 ■: Assembly summary

Element	Serial	Length [m]	Section	Clamped with	Height [in ASB]
Anchor W310	side-by-side				0.0
RBRquartz TP	213895				0.5 [0.5 m AE]
16mmBS					0.5
3/8 chain SL		2.0			0.5
16mmBS					2.5
10mm Load Ring					2.6
Ribuck Dual Kit for Sonardyne ORT					2.8
Sonardyne ORT	262762-001 [65]				3.1 [0.3 m AE]
Sonardyne ORT	262762-002 [64]				3.1 [0.3 m AE]
16mmBS					3.7
8mm Load Ring					3.8
16mmBS					3.9
Swivel					3.9
16mmBS					4.1
8mm Load Ring					4.2
13mmBS					4.3
3/8 wire rope		26.0	A		4.4
FLNTUSB	2997		A		5.0 [0.6 m AE]
SBE39 T	3975		A		5.1 [0.7 m AE]
Zn Anode			A		7.5 [3.1 m AE]
FLNTUSB	3194		A		9.4 [5.0 m AE]
SBE56 T	7343		A		9.9 [5.5 m AE]
SBE39 ext. T	3799		A		14.9 [10.5 m AE]
FLNTUSB	1835		A		19.4 [15.0 m AE]
SBE56 T	7344		A		19.9 [15.5 m AE]
SBE39 sync. T	4456		A		24.9 [20.5 m AE]
13mmBS					30.4
8mm Load Ring					30.4
16mmBS					30.6
75kHz+40in+Ti300kHz					30.6
Sentinel	20089				31.0 [0.4 m AE]
Longranger	16870				32.5 [1.9 m AE]
16mmBS					32.9
8mm Load Ring					33.0
13mmBS					33.1
3/8 wire rope		167.0	B		33.2
SBE56 T	7345		B		33.6 [0.4 m AE]
Zn Anode			B		37.7 [4.5 m AE]
SBE56 T	7346		B		45.6 [12.4 m AE]
SBE56 T	7347		B		58.1 [24.9 m AE]
SBE56 T	7369		B		70.6 [37.4 m AE]
SBE56 T	7370		B		83.1 [49.9 m AE]
SBE37 SMP titanium CTP	11063		B		95.5 [62.3 m AE]
SBE56 T	7371		B		108.1 [74.9 m AE]
SBE56 T	12319		B		120.6 [87.4 m AE]
SBE56 T	7374		B		133.1 [99.9 m AE]
SBE56 T	7375		B		145.6 [112.4 m AE]
SBE56 T	7376		B		158.1 [124.9 m AE]
SBE37 SMP plastic CTP	12738		B		170.5 [137.3 m AE]
SBE56 T	7377		B		183.1 [149.9 m AE]
SBE39 plus TP	8222		B		195.6 [162.4 m AE]
13mmBS					200.2

10mm Load Ring					200.2
16mmBS					200.4
30in	7-13_Buoy59_300m				200.4
13mmBS					201.4
3/8 wire rope		88.0	C		201.4
Zn Anode			C		203.7 [2.3 m AE]
SBE56 T	7378		C		208.2 [6.8 m AE]
SBE56 T	7399		C		220.7 [19.3 m AE]
SBE37 SMP plastic CTP	12739		C		233.0 [31.6 m AE]
SBE56 T	7400		C		245.7 [44.3 m AE]
SBE56 T	7401		C		258.2 [56.8 m AE]
SBE56 T	7402		C		270.7 [69.3 m AE]
SBE37 SMP plastic CTP	9276		C		283.0 [81.6 m AE]
13mmBS					289.4
8mm Load Ring					289.5
16mmBS					289.6
100 cm Signature Frame					289.7
Signature 1000	100244				290.6 [0.9 m AE]
16mmBS					291.0
8mm Load Ring					291.0
13mmBS					291.1
3/8 wire rope		4.5	D		291.2
Zn Anode			D		293.1 [1.9 m AE]
SBE39 ext. TP	6523		D		295.0 [3.8 m AE]
13mmBS					295.7
10mm Load Ring					295.7
13mmBS					295.9
30in	7-13_Buoy62_300m				295.9
Sercel+frame					296.9
Sercel	126989				297.3 [0.4 m AE]
6mm AmSteel		1.0	E		297.4
16mmDS					298.4
14in Panther Plast					298.5

Table 5: N280 ■: Element summary

Element	Qty	Length [m]	Buoyancy [kg]
10mm Load Ring	3		0.5
13mmBS	5		-0.7
14in Panther Plast	1		17.6
16mmBS	9		-0.7
3/8 chain SL	1	1.8	-4.2
3/8 wire rope	2	257.5	-85.0
30in	2		149.0
6mm AmSteel	1	1.0	0.0
75kHz+30in_sph	1		20.0
8mm Load Ring	3		0.5
Anchor N280	1		-900.0
Longranger	1		0.0
RBR duet	1		-0.2
RBRquartz TP	1		-0.2
Ribuck Dual Kit for Sonardyne ORT	1		-35.0
SBE39 ext. T	19		-0.2
SBE39 ext. TP	2		-0.2
SBE39 int. TP	1		-0.2
SBE39 sync. T	4		-0.2
Sercel	1		0.0
Sercel+frame	1		-10.0
Sonardyne ORT	2		0.0
Swivel	1		-4.0
Zn Anode	2		-0.1

Table 6: N280 ■: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
RBRquartz TP	213896	0.6	Anchor N280			0.6
Sonardyne ORT	290238-004 [A4]	3.3	Ribuck Dual Kit for Sonardyne ORT			0.3
Sonardyne ORT	284837-003 [95]	3.3	Ribuck Dual Kit for Sonardyne ORT			0.3
Longranger	24613	6.0	75kHz+30in.sph			1.4
Zn Anode		9.2	3/8 wire rope		A	2.7
SBE39 ext. T	3719	11.2	3/8 wire rope		A	4.7
SBE39 ext. T	3753	16.2	3/8 wire rope		A	9.7
SBE39 ext. T	3721	21.2	3/8 wire rope		A	14.7
SBE39 ext. T	3722	31.2	3/8 wire rope		A	24.7
SBE39 ext. T	3723	41.2	3/8 wire rope		A	34.7
SBE39 sync. T	4452	51.2	3/8 wire rope		A	44.7
SBE39 ext. T	3724	61.2	3/8 wire rope		A	54.7
SBE39 ext. T	3725	71.2	3/8 wire rope		A	64.7
RBR duet	82536	81.2	3/8 wire rope		A	74.7
SBE39 sync. T	4453	91.2	3/8 wire rope		A	84.7
SBE39 ext. T	3726	101.2	3/8 wire rope		A	94.7
SBE39 ext. T	3727	111.2	3/8 wire rope		A	104.7
SBE39 ext. T	3728	121.2	3/8 wire rope		A	114.7
SBE39 ext. T	3729	131.2	3/8 wire rope		A	124.7
SBE39 ext. T	3730	141.2	3/8 wire rope		A	134.7
SBE39 ext. T	3731	151.2	3/8 wire rope		A	144.7
SBE39 ext. T	3747	161.2	3/8 wire rope		A	154.7
SBE39 sync. T	4454	171.2	3/8 wire rope		A	164.7
SBE39 ext. T	3749	181.2	3/8 wire rope		A	174.7
SBE39 ext. TP	6527	191.2	3/8 wire rope		A	184.7
SBE39 ext. T	3750	200.7	3/8 wire rope		A	194.2
Zn Anode		206.3	3/8 wire rope		B	3.5
SBE39 ext. T	3752	211.3	3/8 wire rope		B	8.5
SBE39 ext. TP	6528	221.3	3/8 wire rope		B	18.5
SBE39 ext. T	3754	231.3	3/8 wire rope		B	28.5
SBE39 sync. T	4455	241.3	3/8 wire rope		B	38.5
SBE39 ext. T	3798	251.3	3/8 wire rope		B	48.5
SBE39 int. TP	5082	264.7	3/8 wire rope		B	61.9
Sercel	126991	266.9	Sercel+frame			0.4

Table 7: N280 ■: Clamped with summary

Clamp-on	Clamped with	Qty
----------	--------------	-----

Table 8: N280 ■: Assembly summary

Element	Serial	Length [m]	Section	Clamped with	Height [in ASB]
Anchor N280	stack release				0.0
RBRquartz TP	213896				0.6 [0.6 m AE]
16mmBS					0.8
3/8 chain SL		1.8			0.9
16mmBS					2.7
10mm Load Ring					2.8
Ribuck Dual Kit for Sonardyne ORT					2.9
Sonardyne ORT	290238-004 [A4]				3.3 [0.3 m AE]
Sonardyne ORT	284837-003 [95]				3.3 [0.3 m AE]
16mmBS					3.8
8mm Load Ring					3.9
16mmBS					4.0
Swivel					4.1
16mmBS					4.3
8mm Load Ring					4.4
16mmBS					4.5
75kHz+30in_sph					4.5
Longranger	24613				6.0 [1.4 m AE]
16mmBS					6.3
8mm Load Ring					6.3
13mmBS					6.5
3/8 wire rope		195.0	A		6.5
Zn Anode			A		9.2 [2.7 m AE]
SBE39 ext. T	3719		A		11.2 [4.7 m AE]
SBE39 ext. T	3753		A		16.2 [9.7 m AE]
SBE39 ext. T	3721		A		21.2 [14.7 m AE]
SBE39 ext. T	3722		A		31.2 [24.7 m AE]
SBE39 ext. T	3723		A		41.2 [34.7 m AE]
SBE39 sync. T	4452		A		51.2 [44.7 m AE]
SBE39 ext. T	3724		A		61.2 [54.7 m AE]
SBE39 ext. T	3725		A		71.2 [64.7 m AE]
RBR duet	82536		A		81.2 [74.7 m AE]
SBE39 sync. T	4453		A		91.2 [84.7 m AE]
SBE39 ext. T	3726		A		101.2 [94.7 m AE]
SBE39 ext. T	3727		A		111.2 [104.7 m AE]
SBE39 ext. T	3728		A		121.2 [114.7 m AE]
SBE39 ext. T	3729		A		131.2 [124.7 m AE]
SBE39 ext. T	3730		A		141.2 [134.7 m AE]
SBE39 ext. T	3731		A		151.2 [144.7 m AE]
SBE39 ext. T	3747		A		161.2 [154.7 m AE]
SBE39 sync. T	4454		A		171.2 [164.7 m AE]
SBE39 ext. T	3749		A		181.2 [174.7 m AE]
SBE39 ext. TP	6527		A		191.2 [184.7 m AE]
SBE39 ext. T	3750		A		200.7 [194.2 m AE]
13mmBS					201.5
10mm Load Ring					201.5
16mmBS					201.7
30in	7-13_Buoy61_300m				201.8
13mmBS					202.7
3/8 wire rope		62.5	B		202.8
Zn Anode			B		206.3 [3.5 m AE]
SBE39 ext. T	3752		B		211.3 [8.5 m AE]
SBE39 ext. TP	6528		B		221.3 [18.5 m AE]
SBE39 ext. T	3754		B		231.3 [28.5 m AE]

SBE39 sync. T	4455		B		241.3 [38.5 m AE]
SBE39 ext. T	3798		B		251.3 [48.5 m AE]
SBE39 int. TP	5082		B		264.7 [61.9 m AE]
13mmBS					265.3
10mm Load Ring					265.3
16mmBS					265.5
30in	7-13_Buoy60_300m				265.5
Sercel+frame					266.5
Sercel	126991				266.9 [0.4 m AE]
6mm AmSteel		1.0	C		267.0
13mmBS					268.0
14in Panther Plast					268.1

Table 9: S245 ■: Element summary

Element	Qty	Length [m]	Buoyancy [kg]
100 cm Signature Frame	1		-7.5
10mm Load Ring	4		0.5
13mmBS	10		-0.7
14in Panther Plast	2		17.6
150kHz+30in_sph	1		57.0
16mmBS	13		-0.7
3/8 chain SL	1	1.8	-4.2
3/8 wire rope	4	214.5	-70.8
30in	1		149.0
35in	1		238.0
6mm AmSteel	1	4.5	0.0
8mm Load Ring	6		0.5
ADV+MP+uSquid+2B	1		-43.0
Anchor S245	1		-900.0
FP07	1		0.0
Quartermaster	1		0.0
RBR duet	1		-0.2
Ribuck Dual Kit for Sonardyne ORT	1		-35.0
SBE39 ext. TP	4		-0.2
SBE39 plus TP	1		-0.2
SBE56 T	32		-0.1
Sercel	1		0.0
Sercel+frame	1		-10.0
Signature 1000	1		0.0
Sonardyne ORT	2		0.0
Swivel	1		-4.0
Vector	1		0.0
Zn Anode	4		-0.1
uSquid	1		0.0

Table 10: S245 ■: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
SBE56 T	7372	0.6	Anchor S245			0.6
Sonardyne ORT	284837-002 [93]	3.2	Ribuck Dual Kit for Sonardyne ORT			0.3
Sonardyne ORT	284837-004 [99]	3.2	Ribuck Dual Kit for Sonardyne ORT			0.3
SBE56 T	00674	5.6	150kHz+30in_sph			1.1
Quartermaster	11795	5.9	150kHz+30in_sph			1.4
Zn Anode		8.7	3/8 wire rope		A	2.2
SBE39 plus TP	8223	10.2	3/8 wire rope		A	3.7
SBE56 T	00711	13.2	3/8 wire rope		A	6.7
RBR duet	82538	16.2	3/8 wire rope		A	9.7
SBE56 T	00725	19.2	3/8 wire rope		A	12.7
SBE56 T	00781	22.2	3/8 wire rope		A	15.7
SBE56 T	00877	25.2	3/8 wire rope		A	18.7
SBE56 T	00878	28.2	3/8 wire rope		A	21.7
SBE56 T	00879	31.2	3/8 wire rope		A	24.7
SBE56 T	00881	41.2	3/8 wire rope		A	34.7
SBE56 T	00907	51.2	3/8 wire rope		A	44.7
SBE39 ext. TP	6530	56.2	3/8 wire rope		A	49.7
SBE56 T	00908	61.2	3/8 wire rope		A	54.7
SBE56 T	00909	71.2	3/8 wire rope		A	64.7
SBE56 T	00910	81.2	3/8 wire rope		A	74.7
SBE56 T	00912	91.2	3/8 wire rope		A	84.7
SBE56 T	02975	101.2	3/8 wire rope		A	94.7
SBE56 T	02976	111.2	3/8 wire rope		A	104.7
SBE56 T	02977	121.2	3/8 wire rope		A	114.7
SBE56 T	02978	131.2	3/8 wire rope		A	124.7
SBE56 T	02981	141.2	3/8 wire rope		A	134.7
SBE39 ext. TP	6529	146.2	3/8 wire rope		A	139.7
SBE56 T	02983	151.0	3/8 wire rope		A	144.6
Zn Anode		156.2	3/8 wire rope		B	3.5
SBE56 T	6964	161.2	3/8 wire rope		B	8.5
SBE56 T	6965	171.2	3/8 wire rope		B	18.5
SBE56 T	7403	176.2	3/8 wire rope		B	23.5
SBE56 T	7274	181.2	3/8 wire rope		B	28.5
SBE39 ext. TP	6526	182.2	3/8 wire rope		B	29.5
SBE56 T	7308	183.8	3/8 wire rope		B	31.0
Vector	6015	186.0	ADV+MP+uSquid+2B			0.6
uSquid	002	186.0	ADV+MP+uSquid+2B			0.6
FP07	T937	186.0	ADV+MP+uSquid+2B			0.6
SBE56 T	7319	188.8	3/8 wire rope		C	1.2
Zn Anode		190.4	3/8 wire rope		C	2.8
SBE56 T	7338	191.3	3/8 wire rope		C	3.7
SBE56 T	7426	196.3	3/8 wire rope		C	8.7
SBE56 T	7339	201.3	3/8 wire rope		C	13.7
SBE56 T	7340	211.3	3/8 wire rope		C	23.7
Signature 1000	100608	221.2	100 cm Signature Frame			0.9
SBE56 T	7341	222.1	3/8 wire rope		D	0.3
Zn Anode		223.6	3/8 wire rope		D	1.8
SBE39 ext. TP	6617	225.9	3/8 wire rope		D	4.0
Sercel	126990	228.1	Sercel+frame			0.4
SBE56 T	7342	228.7	6mm AmSteel		E	0.4

Table 11: S245 ■: Clamped with summary

Clamp-on	Clamped with	Qty
----------	--------------	-----

Table 12: S245 ■: Assembly summary

Element	Serial	Length [m]	Section	Clamped with	Height [in ASB]
Anchor S245	stack non-release				0.0
SBE56 T	7372				0.6 [0.6 m AE]
16mmBS					0.8
3/8 chain SL		1.8			0.9
16mmBS					2.7
10mm Load Ring					2.7
Ribuck Dual Kit for Sonardyne ORT					2.9
Sonardyne ORT	284837-002 [93]				3.2 [0.3 m AE]
Sonardyne ORT	284837-004 [99]				3.2 [0.3 m AE]
16mmBS					3.8
8mm Load Ring					3.9
16mmBS					4.0
Swivel					4.1
16mmBS					4.3
8mm Load Ring					4.3
16mmBS					4.5
150kHz+30in.sph					4.5
SBE56 T	00674				5.6 [1.1 m AE]
Quartermaster	11795				5.9 [1.4 m AE]
16mmBS					6.2
10mm Load Ring					6.3
13mmBS					6.4
3/8 wire rope		145.0	A		6.5
Zn Anode			A		8.7 [2.2 m AE]
SBE39 plus TP	8223		A		10.2 [3.7 m AE]
SBE56 T	00711		A		13.2 [6.7 m AE]
RBR duet	82538		A		16.2 [9.7 m AE]
SBE56 T	00725		A		19.2 [12.7 m AE]
SBE56 T	00781		A		22.2 [15.7 m AE]
SBE56 T	00877		A		25.2 [18.7 m AE]
SBE56 T	00878		A		28.2 [21.7 m AE]
SBE56 T	00879		A		31.2 [24.7 m AE]
SBE56 T	00881		A		41.2 [34.7 m AE]
SBE56 T	00907		A		51.2 [44.7 m AE]
SBE39 ext. TP	6530		A		56.2 [49.7 m AE]
SBE56 T	00908		A		61.2 [54.7 m AE]
SBE56 T	00909		A		71.2 [64.7 m AE]
SBE56 T	00910		A		81.2 [74.7 m AE]
SBE56 T	00912		A		91.2 [84.7 m AE]
SBE56 T	02975		A		101.2 [94.7 m AE]
SBE56 T	02976		A		111.2 [104.7 m AE]
SBE56 T	02977		A		121.2 [114.7 m AE]
SBE56 T	02978		A		131.2 [124.7 m AE]
SBE56 T	02981		A		141.2 [134.7 m AE]
SBE39 ext. TP	6529		A		146.2 [139.7 m AE]
SBE56 T	02983		A		151.0 [144.6 m AE]
13mmBS					151.5
10mm Load Ring					151.5
16mmBS					151.7
30in	7-13_Buoy63_300m				151.7
13mmBS					152.7
3/8 wire rope		32.5	B		152.7
Zn Anode			B		156.2 [3.5 m AE]
SBE56 T	6964		B		161.2 [8.5 m AE]

SBE56 T	6965		B	171.2 [18.5 m AE]
SBE56 T	7403		B	176.2 [23.5 m AE]
SBE56 T	7274		B	181.2 [28.5 m AE]
SBE39 ext. TP	6526		B	182.2 [29.5 m AE]
SBE56 T	7308		B	183.8 [31.0 m AE]
13mmBS				185.2
8mm Load Ring				185.3
16mmBS				185.4
ADV+MP+uSquid+2B				185.5
Vector	6015			186.0 [0.6 m AE]
uSquid	002			186.0 [0.6 m AE]
FP07	T937			186.0 [0.6 m AE]
16mmBS				187.3
8mm Load Ring				187.4
13mmBS				187.5
3/8 wire rope		32.5	C	187.6
SBE56 T	7319		C	188.8 [1.2 m AE]
Zn Anode			C	190.4 [2.8 m AE]
SBE56 T	7338		C	191.3 [3.7 m AE]
SBE56 T	7426		C	196.3 [8.7 m AE]
SBE56 T	7339		C	201.3 [13.7 m AE]
SBE56 T	7340		C	211.3 [23.7 m AE]
13mmBS				220.1
8mm Load Ring				220.1
16mmBS				220.2
100 cm Signature Frame				220.3
Signature 1000	100608			221.2 [0.9 m AE]
16mmBS				221.6
8mm Load Ring				221.7
13mmBS				221.8
3/8 wire rope		4.5	D	221.8
SBE56 T	7341		D	222.1 [0.3 m AE]
Zn Anode			D	223.6 [1.8 m AE]
SBE39 ext. TP	6617		D	225.9 [4.0 m AE]
13mmBS				226.3
10mm Load Ring				226.4
16mmBS				226.5
35in	1-17_Buoy01_300m			226.6
Sercel+frame				227.7
Sercel	126990			228.1 [0.4 m AE]
13mmBS				228.2
6mm AmSteel		4.5	E	228.3
SBE56 T	7342		E	228.7 [0.4 m AE]
13mmBS				232.8
14in Panther Plast				232.8
14in Panther Plast				233.2

Table 13: L245 ■: Element summary

Element	Qty	Length [m]	Buoyancy [kg]
14in Panther Plast	2		17.6
16mmDS-L-16mmDS	1		-0.8
3/8 wire rope	1	70.6	-23.3
Edgetech MF SD	2		0.0
LISST_200X	1		-4.0
Lander frame	1		0.0
NTUS	3		-0.2
RBRquartz TP	1		-0.2
SBE 19+ cage	1		-20.0
Signature 1000	1		0.0
Sonardyne ORT	1		0.0
Vector	3		0.0
Zn Anode	1		-0.1
popup buoy	2		20.0

Table 14: L245 ■: Clamp-on summary

Name	Serial	H[m]	Clamped to	Clamped with	Section	Inline H[m]
NTUS	360	0.2	Lander frame			0.2
RBRquartz TP	213897	0.3	Lander frame			0.3
Signature 1000	100460	0.3	Lander frame			0.3
Vector	6329	0.5	Lander frame			0.5
NTUS	1521	0.5	Lander frame			0.5
Vector	6019	0.9	Lander frame			0.9
SBE 19+ cage	6530	1.1	Lander frame			1.1
NTUS	359	1.2	Lander frame			1.2
LISST_200X	2031	1.2	Lander frame			1.2
Vector	6017	1.5	Lander frame			1.5
Zn Anode		4.0	3/8 wire rope		A	1.2
Edgetech MF SD	54435	74.7	popup buoy			1.3
Edgetech MF SD	53086 (upper)	74.7	popup buoy			0.2
Sonardyne ORT	290238-004 [A4]	75.2	14in Panther Plast			0.0

Table 15: L245 ■: Clamped with summary

Clamp-on	Clamped with	Qty
----------	--------------	-----

Table 16: L245 ■: Assembly summary

Element	Serial	Length [m]	Section	Clamped with	Height [in ASB]
Lander frame					0.0
NTUS	360				0.2 [0.2 m AE]
RBRquartz TP	213897				0.3 [0.3 m AE]
Signature 1000	100460				0.3 [0.3 m AE]
Vector	6329				0.5 [0.5 m AE]
NTUS	1521				0.5 [0.5 m AE]
Vector	6019				0.9 [0.9 m AE]
SBE 19+ cage	6530				1.1 [1.1 m AE]
NTUS	359				1.2 [1.2 m AE]
LISST_200X	2031				1.2 [1.2 m AE]
Vector	6017				1.5 [1.5 m AE]
16mmDS-L-16mmDS					2.6
3/8 wire rope		70.6	A		2.8
Zn Anode			A		4.0 [1.2 m AE]
popup buoy					73.4
Edgetech MF SD	54435				74.7 [1.3 m AE]
14in Panther Plast					74.1
popup buoy					74.5
Edgetech MF SD	53086 (upper)				74.7 [0.2 m AE]
14in Panther Plast					75.2
Sonardyne ORT	290238-004 [A4]				75.2 [0.0 m AE]

Table 17: All: summary of instruments

Element	Serial number	Clamped with	Mooring
100 cm Signature Frame [n=2]			W310 
			S245 
150kHz+30in_sph [n=1]			S245 
75kHz+30in_sph [n=1]			N280 
75kHz+40in+Ti300kHz [n=1]			W310 
ADV+MP+uSquid+2B [n=1]			S245 
Edgetech MF SD [n=2]	53086 (upper)		L245 
	54435		L245 
FLNTUSB [n=3]	1835		W310 
	2997		W310 
	3194		W310 
FP07 [n=1]	T937		S245 
LISST_200X [n=1]	2031		L245 
Lander frame [n=1]			L245 
Longranger [n=2]	16870		W310 
	24613		N280 
NTUS [n=3]	1521		L245 
	359		L245 
	360		L245 
Quartermaster [n=1]	11795		S245 
RBR duet [n=2]	82536		N280 
	82538		S245 
RBRquartz TP [n=3]	213895		W310 
	213896		N280 
	213897		L245 
Ribuck Dual Kit for Sonardyne ORT [n=3]			W310 
			N280 
			S245 
SBE 19+ cage [n=1]	6530		L245 
SBE37 SMP plastic CTP [n=3]	12738		W310 
	12739		W310 
	9276		W310 
SBE37 SMP titanium CTP [n=1]	11063		W310 
SBE39 T [n=1]	3975		W310 
SBE39 ext. T [n=20]	3799		W310 
	3719		N280 
	3721		N280 
	3722		N280 
	3723		N280 
	3724		N280 
	3725		N280 
	3726		N280 
	3727		N280 
	3728		N280 
	3729		N280 
	3730		N280 
	3731		N280 
	3747		N280 
	3749		N280 
	3750		N280 
	3752		N280 
	3753		N280 
	3754		N280 
	3798		N280 

SBE39 ext. TP [n=7]	6523	W310 
	6527	N280 
	6528	N280 
	6526	S245 
	6529	S245 
	6530	S245 
	6617	S245 
SBE39 int. TP [n=1]	5082	N280 
SBE39 plus TP [n=2]	8222	W310 
	8223	S245 
SBE39 sync. T [n=5]	4456	W310 
	4452	N280 
	4453	N280 
	4454	N280 
	4455	N280 
SBE56 T [n=50]	12319	W310 
	7343	W310 
	7344	W310 
	7345	W310 
	7346	W310 
	7347	W310 
	7369	W310 
	7370	W310 
	7371	W310 
	7374	W310 
	7375	W310 
	7376	W310 
	7377	W310 
	7378	W310 
	7399	W310 
	7400	W310 
	7401	W310 
	7402	W310 
	00674	S245 
	00711	S245 
	00725	S245 
	00781	S245 
	00877	S245 
	00878	S245 
	00879	S245 
	00881	S245 
	00907	S245 
	00908	S245 
	00909	S245 
	00910	S245 
	00912	S245 
	02975	S245 
	02976	S245 
	02977	S245 
	02978	S245 
	02981	S245 
	02983	S245 
	6964	S245 
	6965	S245 
	7274	S245 
	7308	S245 
	7319	S245 

	7338		S245 
	7339		S245 
	7340		S245 
	7341		S245 
	7342		S245 
	7372		S245 
	7403		S245 
	7426		S245 
Sentinel [n=1]	20089		W310 
Sercel [n=3]	126989		W310 
	126991		N280 
	126990		S245 
Sercel+frame [n=3]			W310 
			N280 
			S245 
Signature 1000 [n=3]	100244		W310 
	100608		S245 
	100460		L245 
Sonardyne ORT [n=7]	262762-001 [65]		W310 
	262762-002 [64]		W310 
	284837-003 [95]		N280 
	290238-004 [A4]		N280 
	284837-002 [93]		S245 
	284837-004 [99]		S245 
	290238-004 [A4]		L245 
Swivel [n=3]			W310 
			N280 
			S245 
Vector [n=4]	6015		S245 
	6017		L245 
	6019		L245 
	6329		L245 
Zn Anode [n=11]			W310 
			W310 
			W310 
			W310 
			N280 
			N280 
			S245 
			S245 
			S245 
			S245 
			L245 
uSquid [n=1]	002		S245 

Table 18: All : Total count of each element

Name	L245 	N280 	S245 	W310 	Total
100 cm Signature Frame	0	0	1	1	2
10mm Load Ring	0	3	4	3	10
13mmBS	0	5	10	9	24
14in Panther Plast	2	1	2	1	6
150kHz+30in_sph	0	0	1	0	1
16mmBS	0	9	13	10	32
16mmDS	0	0	0	1	1
16mmDS-L-16mmDS	1	0	0	0	1
3/8 chain SL	0	1	1	1	3
3/8 wire rope	1	2	4	4	11
30in	0	2	1	2	5
35in	0	0	1	0	1
6mm AmSteel	0	1	1	1	3
75kHz+30in_sph	0	1	0	0	1
75kHz+40in+Ti300kHz	0	0	0	1	1
8mm Load Ring	0	3	6	6	15
ADV+MP+uSquid+2B	0	0	1	0	1
Anchor N280	0	1	0	0	1
Anchor S245	0	0	1	0	1
Anchor W310	0	0	0	1	1
Edgetech MF SD	2	0	0	0	2
FLNTUSB	0	0	0	3	3
FP07	0	0	1	0	1
LISST_200X	1	0	0	0	1
Lander frame	1	0	0	0	1
Longranger	0	1	0	1	2
NTUS	3	0	0	0	3
Quartermaster	0	0	1	0	1
RBR duet	0	1	1	0	2
RBRquartz TP	1	1	0	1	3
Ribuck Dual Kit for Sonardyne ORT	0	1	1	1	3
SBE 19+ cage	1	0	0	0	1
SBE37 SMP plastic CTP	0	0	0	3	3
SBE37 SMP titanium CTP	0	0	0	1	1
SBE39 T	0	0	0	1	1
SBE39 ext. T	0	19	0	1	20
SBE39 ext. TP	0	2	4	1	7
SBE39 int. TP	0	1	0	0	1
SBE39 plus TP	0	0	1	1	2
SBE39 sync. T	0	4	0	1	5
SBE56 T	0	0	32	18	50
Sentinel	0	0	0	1	1
Sercel	0	1	1	1	3
Sercel+frame	0	1	1	1	3
Signature 1000	1	0	1	1	3
Sonardyne ORT	1	2	2	2	7
Swivel	0	1	1	1	3
Vector	3	0	1	0	4
Zn Anode	1	2	4	4	11
popup buoy	2	0	0	0	2
uSquid	0	0	1	0	1

Table 19: All : Total count clamp types

Clamp-on	Clamped with	W310 ■	N280 ■	S245 ■	L245 ■	Total
----------	--------------	--	---	---	--	-------

Table 20: All: simple section summary

Mooring	Section	Material	Length
W310 ■		3/8 chain SL	2.0
W310 ■	A	3/8 wire rope	26.0
W310 ■	B	3/8 wire rope	167.0
W310 ■	C	3/8 wire rope	88.0
W310 ■	D	3/8 wire rope	4.5
W310 ■	E	6mm AmSteel	1.0
N280 ■		3/8 chain SL	1.8
N280 ■	A	3/8 wire rope	195.0
N280 ■	B	3/8 wire rope	62.5
N280 ■	C	6mm AmSteel	1.0
S245 ■		3/8 chain SL	1.8
S245 ■	A	3/8 wire rope	145.0
S245 ■	B	3/8 wire rope	32.5
S245 ■	C	3/8 wire rope	32.5
S245 ■	D	3/8 wire rope	4.5
S245 ■	E	6mm AmSteel	4.5
L245 ■	A	3/8 wire rope	70.6

Table 21: Summary of W310 ■, A, length: 26.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
FLNTUSB	2997	5.0	0.6
SBE39 T	3975	5.1	0.7
Zn Anode		7.5	3.1
FLNTUSB	3194	9.4	5.0
SBE56 T	7343	9.9	5.5
SBE39 ext. T	3799	14.9	10.5
FLNTUSB	1835	19.4	15.0
SBE56 T	7344	19.9	15.5
SBE39 sync. T	4456	24.9	20.5

Table 22: Summary of W310 ■, B, length: 167.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
SBE56 T	7345	33.6	0.4
Zn Anode		37.7	4.5
SBE56 T	7346	45.6	12.4
SBE56 T	7347	58.1	24.9
SBE56 T	7369	70.6	37.4
SBE56 T	7370	83.1	49.9
SBE37 SMP titanium CTP	11063	95.5	62.3
SBE56 T	7371	108.1	74.9
SBE56 T	12319	120.6	87.4
SBE56 T	7374	133.1	99.9
SBE56 T	7375	145.6	112.4
SBE56 T	7376	158.1	124.9
SBE37 SMP plastic CTP	12738	170.5	137.3
SBE56 T	7377	183.1	149.9
SBE39 plus TP	8222	195.6	162.4

Table 23: Summary of W310 ■, C, length: 88.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		203.7	2.3
SBE56 T	7378	208.2	6.8
SBE56 T	7399	220.7	19.3
SBE37 SMP plastic CTP	12739	233.0	31.6
SBE56 T	7400	245.7	44.3
SBE56 T	7401	258.2	56.8
SBE56 T	7402	270.7	69.3
SBE37 SMP plastic CTP	9276	283.0	81.6

Table 24: Summary of W310 ■, D, length: 4.5 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		293.1	1.9
SBE39 ext. TP	6523	295.0	3.8

Table 25: Summary of W310 ■, E, length: 1.0 m, material: 6mm AmSteel

Name	Serial number	Height [m]	Along element
------	---------------	------------	---------------

Table 26: Summary of N280 ■, A, length: 195.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		9.2	2.7
SBE39 ext. T	3719	11.2	4.7
SBE39 ext. T	3753	16.2	9.7
SBE39 ext. T	3721	21.2	14.7
SBE39 ext. T	3722	31.2	24.7
SBE39 ext. T	3723	41.2	34.7
SBE39 sync. T	4452	51.2	44.7
SBE39 ext. T	3724	61.2	54.7
SBE39 ext. T	3725	71.2	64.7
RBR duet	82536	81.2	74.7
SBE39 sync. T	4453	91.2	84.7
SBE39 ext. T	3726	101.2	94.7
SBE39 ext. T	3727	111.2	104.7
SBE39 ext. T	3728	121.2	114.7
SBE39 ext. T	3729	131.2	124.7
SBE39 ext. T	3730	141.2	134.7
SBE39 ext. T	3731	151.2	144.7
SBE39 ext. T	3747	161.2	154.7
SBE39 sync. T	4454	171.2	164.7
SBE39 ext. T	3749	181.2	174.7
SBE39 ext. TP	6527	191.2	184.7
SBE39 ext. T	3750	200.7	194.2

Table 27: Summary of N280 ■, B, length: 62.5 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		206.3	3.5
SBE39 ext. T	3752	211.3	8.5
SBE39 ext. TP	6528	221.3	18.5
SBE39 ext. T	3754	231.3	28.5
SBE39 sync. T	4455	241.3	38.5
SBE39 ext. T	3798	251.3	48.5
SBE39 int. TP	5082	264.7	61.9

Table 28: Summary of N280 ■, C, length: 1.0 m, material: 6mm AmSteel

Name	Serial number	Height [m]	Along element
------	---------------	------------	---------------

Table 29: Summary of S245 ■, A, length: 145.0 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		8.7	2.2
SBE39 plus TP	8223	10.2	3.7
SBE56 T	00711	13.2	6.7
RBR duet	82538	16.2	9.7
SBE56 T	00725	19.2	12.7
SBE56 T	00781	22.2	15.7
SBE56 T	00877	25.2	18.7
SBE56 T	00878	28.2	21.7
SBE56 T	00879	31.2	24.7
SBE56 T	00881	41.2	34.7
SBE56 T	00907	51.2	44.7
SBE39 ext. TP	6530	56.2	49.7
SBE56 T	00908	61.2	54.7
SBE56 T	00909	71.2	64.7
SBE56 T	00910	81.2	74.7
SBE56 T	00912	91.2	84.7
SBE56 T	02975	101.2	94.7
SBE56 T	02976	111.2	104.7
SBE56 T	02977	121.2	114.7
SBE56 T	02978	131.2	124.7
SBE56 T	02981	141.2	134.7
SBE39 ext. TP	6529	146.2	139.7
SBE56 T	02983	151.0	144.6

Table 30: Summary of S245 ■, B, length: 32.5 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		156.2	3.5
SBE56 T	6964	161.2	8.5
SBE56 T	6965	171.2	18.5
SBE56 T	7403	176.2	23.5
SBE56 T	7274	181.2	28.5
SBE39 ext. TP	6526	182.2	29.5
SBE56 T	7308	183.8	31.0

Table 31: Summary of S245 ■, C, length: 32.5 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
SBE56 T	7319	188.8	1.2
Zn Anode		190.4	2.8
SBE56 T	7338	191.3	3.7
SBE56 T	7426	196.3	8.7
SBE56 T	7339	201.3	13.7
SBE56 T	7340	211.3	23.7

Table 32: Summary of S245 ■, D, length: 4.5 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
SBE56 T	7341	222.1	0.3
Zn Anode		223.6	1.8
SBE39 ext. TP	6617	225.9	4.0

Table 33: Summary of S245 ■, E, length: 4.5 m, material: 6mm AmSteel

Name	Serial number	Height [m]	Along element
SBE56 T	7342	228.7	0.4

Table 34: Summary of L245 ■, A, length: 70.6 m, material: 3/8 wire rope

Name	Serial number	Height [m]	Along element
Zn Anode		4.0	1.2