THE CONSIGNMENT


BUYER	Demo EAF Steel Mill
DISPATCHED	5 Oct 2026
CONSIGNMENT	DS-2610-145
PRODUCT	Sorted metals by type, Processed spring steel, Processed ferrous scrap
WEIGHED OUT	26.79 t
BALES	42 (nominal)
CONTAINER	n/a
VEHICLE	B-double
PROCESSED	22 Sept 2026 – 1 Oct 2026
ORIGIN	The Metal Recycling Company, Victoria

WHAT WAS IN IT

one line per source load

PROCESSED	SOURCE STREAM → PRODUCT	ORIGIN CLASS	OUT (T)	DOCKET
22 Sept 2026	Mixed metals → Sorted metals by type	post-consumer · VIC	3.06	WB-2609-2317
24 Sept 2026	Mattress spring steel → Processed spring steel	post-consumer · VIC	6.00	WB-2609-2108
29 Sept 2026	Mattress spring steel → Processed spring steel	post-consumer · VIC	7.72	WB-2609-2109
29 Sept 2026	Ferrous scrap → Processed ferrous scrap	post-consumer (demolition) · QLD	3.49	WB-2609-2190
1 Oct 2026	Ferrous scrap → Processed ferrous scrap	pre-consumer (manufacturing offcuts) · VIC	6.52	WB-2610-2436
Total			**26.79**	

ORIGIN



- Post-consumer 17 t — 63%
- Pre-consumer (manufacturing offcuts) 6.5 t — 24%
- Post-consumer (demolition) 3.5 t — 13%

RECYCLED-CONTENT BASIS

- **Recycled content: 100%.** Everything dispatched is recovered scrap. No virgin metal is added at any stage.
- **Origin:** recovered and processed by The Metal Recycling Company in Victoria. Australian material, Australian processing.
- **Class:** post-consumer (mattresses, demolition, council and fit-out material) or pre-consumer (manufacturing offcuts), shown per dispatch and per line.
- **Weights:** every figure is the weighed output of the processing line. Lines marked * use the usual recovery rate for that metal because the output was not separately weighed.
- **Carbon:** scrap-based EAF steel averages 0.70 t CO_2 per tonne of crude steel against 2.32 t for blast-furnace steel (World Steel Association, 2023 data). The mill's own EPD governs its product; The Metal Recycling Company documents the scrap side.
- **What is not claimed:** the CO_2-e avoided by recycling this metal is reported to the partner who supplied it. Buyers see it for information, not as a credit.

HOW IT WAS PROCESSED

Mixed metals: Hand and magnet sorted into steel, copper and aluminium streams. **Mattress spring steel:** Shredded; steel pulled by magnets, cleaned by vibration, suction and electrostatic separation, then baled or loaded loose. **Ferrous scrap:** Sorted, cut to size where needed, non-ferrous and contamination removed, baled.

HOW THESE FIGURES ARE WORKED OUT

1. **Weighed in.** Every load crosses our weighbridge; the docket weight is the figure used.
2. **Turned into.** The load is processed on the line for its metal. The product it becomes is recorded against the load.
3. **Recovered.** The saleable metal weighed out. Where an output weight was not recorded, The Metal Recycling Company's usual recovery rate for that metal is used and the load is marked as an estimate.
4. **Saving.** Tonnes recovered × the published recycling credit for that metal: the carbon avoided by not making the same metal new from ore, net of collection and reprocessing (steel 1.5 t CO_2/t, worldsteel; copper 5.2, aluminium 7.9 and mixed metals 4.8 t CO_2-e/t, US EPA WARM). Metal in landfill does not break down, so no landfill methane is claimed.
5. **Trees.** CO_2-e avoided ÷ 0.060 t, what one tree seedling absorbs over ten years (US EPA).
6. Factors marked as stand-ins (brass, stainless) and usual recovery rates should be read as estimates.