



Title

rdhte_plot — Plot RD heterogeneous treatment effects across groups.

Syntax

```
rdhte_plot [, sort nozero title(string) xtitle(string) ytitle(string)
graph_options(string) ]
```

Description

rdhte_plot is a post-estimation command for **rdhte**. It reads the **e()** results left by the most recent **rdhte** run and draws one point per heterogeneity group at the conventional point estimate (**e(tau_hat)**) with the robust bias-corrected confidence interval (**e(tau_ci_lb)**, **e(tau_ci_ub)**). A dashed horizontal line at $y = 0$ provides a visual reference for the null effect.

The command requires that the preceding **rdhte** call used a categorical **covs_hte()** (i.e. a factor variable). Continuous **covs_hte()** or no **covs_hte()** are refused with an explanatory error.

The intervals shown are the same robust bias-corrected CIs reported in the **rdhte** table: they are centered on **e(tau_bc)** (not **e(tau_hat)**) and use the robust standard error. Because the point and the CI center can differ slightly, the point may sit just inside or just outside the bar; this is the **rdrobust** convention and is not a plotting bug.

Options

sort reorders groups along the x-axis by point estimate (ascending). Default keeps the original group order.

nozero suppresses the dashed reference line at $y = 0$.

title(string) overrides the plot title. Default is derived from the **rdhte** model and a "(Cluster-Robust)" suffix when **e(clustvar)** is set.

xtitle(string) overrides the x-axis title. Default is the name of the heterogeneity variable (**e(covs_hte)**).

ytitle(string) overrides the y-axis title. Default is "Treatment effect".

graph_options(string) is a free-form string passed verbatim to **twoway** after the built-in options. Use to set scheme, axis ranges, custom legends, etc.

Examples

Categorical heterogeneity with cluster-robust inference

```
. rdhte y x, covs_hte(i.region) vce(cluster id)
. rdhte_plot
```

Sort groups by effect size and rename the y-axis

```
. rdhte_plot, sort ytitle("ATE on outcome")
```

Pass extra **twoway** options

```
. rdhte_plot, graph_options(scheme(s2color) ylabel(0(0.5)2.5))
```

Author

Sebastian Calonico, UC Davis. scalonico@ucdavis.edu.

See also

[rdhte](#), [rdbwhite](#), [rdhte_lincom](#)