



Title

rdrobustplot — Diagnostic plot for a previous **rdrobust** result.

Syntax

```
rdrobustplot [, nbins(# #) binselect(binmethod) noci shade scale(# #)
  title(string) xtitle(string) ytitle(string) xlabel(rule) ylabel(rule)
  rdplot_options ]
```

Description

rdrobustplot produces a diagnostic RD plot for the results of the most recent **rdrobust** call. It wraps **rdplot** with the main bandwidth and polynomial order that **rdrobust** used, and decorates the subtitle with the estimated RD coefficient and its robust bias-corrected confidence interval.

This mirrors the **plot.rdrobust()** S3 method in the R package and the **plot_rdrobust()** function in the Python package.

Requires Stata 16 or later.

Options

nbins(# #) number of bins per side; default is 20 20.

binselect(*binmethod*) bin selection rule; default is **esmv** (mimicking-variance evenly-spaced bins). See **rdplot**.

noci suppresses the per-bin confidence intervals.

shade draws the pointwise confidence bands as a shaded ribbon instead of error bars.

title(), **xtitle()**, **ytitle()**, **xlabel()**, **ylabel()**, **scale()** are forwarded to the underlying graph. The default title follows **rdrobust**'s outcome and running variable.

masspoints(), **covs_drop()**, **covs_eval()**, **support()**, **genvars**, **nochecks** and **precision()** are forwarded to **rdplot** as analysis options.

graph_options(*twoway options*), and any option not listed above, are appended to the underlying **twoway** call after the defaults, so e.g. **legend(off)** or **xline(0.5)** take effect (later-wins). A misspelled option therefore errors from the graph command ("option ... not allowed") rather than silently disappearing.

Note: **col_dots()** and **col_lines()** were accepted by earlier versions but never had any effect -- the binned means and the fit line are drawn inside **rdplot**, which exposes no hook for per-plot colours. They are no longer accepted, so the mistake is reported instead of being silently ignored.

Stored results

rdrobustplot is **r**-class and stores the annotation shown in the subtitle, so a script can reuse the same numbers:

Scalars

r(tau)	RD point estimate, e(tau_cl) of the preceding rdrobust
r(se_rb)	robust bias-corrected standard error
r(ci_l)	lower robust bias-corrected confidence limit
r(ci_r)	upper robust bias-corrected confidence limit
r(pvalue)	two-sided p-value implied by r(tau) and r(se_rb)

Macros

r(subtitle)	the annotation string drawn above the plot
--------------------	--

The `e()` results of the preceding `rdrobust` call are left intact, so `rdrobustplot` may be called repeatedly (and followed by other post-estimation commands). Earlier versions delegated to the `e`-class `rdplot`, which cleared `e()` and made a second `rdrobustplot` call fail with `r(301)`.

Examples

```
sysuse rdrobust_senate, clear  
rdrobust vote margin  
rdrobustplot
```

With cluster-robust variance and fuzzy RD:
rdrobust vote margin, vce(cr3 state)
rdrobustplot, shade

Authors

Sebastian Calonico, University of California, Davis. scalonico@ucdavis.edu.
Matias D. Cattaneo, Princeton University. matias.d.cattaneo@gmail.com.
Max H. Farrell, University of California, Santa Barbara. mhfarrell@gmail.com.
Rocio Titiunik, Princeton University. rocio.titiunik@gmail.com.