

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

0 Nahuelbuta weather station

The data file contains data from a weather station in Nahuelbuta.

- Read in the CSV file "data0_no_time.csv". (use `np.loadtxt()` and `delimiter=","`)
- Write a function that filters out the invalid values (-9999.0) from the data.
- Plot the first (air temperature in deg C) and second column (solar radiation $\frac{W_{att}}{m^2}$) in two separate plots.
- The time information is missing, try to figure out from what time period the data is.

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

1 A GPS Station in Antarctica

Load data *XYShirase_GPS_Small.txt*. This datafile was recorded by a GPS station on an Antarctica Ice shelf. The data structure is as follows:

col1: coordinate polar stereographic East (m)
col2: coordinate polar stereographic South (m)
col3: coordinate longitude (decimal degrees)
col4: coordinate latitude (decimal degrees)
col5: elevation (m, relative to WGS84)
col6: days (relative to an arbitrary date in the past)

Visual the vertical coordinate as a function of time. Visualize the horizontal trajectory of the station. Fit a linear regression line to the horizontal trajectory. What is the approximate speed in meters per year?

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

2 Min, Max, Mean

- Read in data from the user as input from the command line. If the user types "x" stop reading.
- Write a function that calculates the min, max and mean values from that input. The function should return a tuple (a, b, c) containing the three values
- Print the values at the end

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

3 Daily average

The data given is from one year (2017) of the weather station in Santa Gracia. There are 24 values per day (1 hour average).

- Read in the CSV file "data3.csv". (use `np.loadtxt()`, `delimiter=","` and `usecols=(1,2)`)
- Write a function that filters out the invalid values (-9999.0) from the data.
- Write a function that calculates the average for each day (average over 24 values).
- Plot the data: first column contains air temperature, second column contains air relative humidity.

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

4 Derivative

The data given is from one year (2018) of the weather station in Santa Gracia. There are 24 values per day (1 hour average).

- Read in the CSV file "data4.csv". (use `np.loadtxt()`, `delimiter=","` and `usecols=(1,2)`)
- Write a function that filters out the invalid values (-9999.0) from the data.
- Write a function that calculates the first and second derivative.
- Plot the data: first column contains the average wind speed, second column contains the maximum wind speed.

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

5 Smoothing Data

Load data *XYShirase_GPS_Small.txt*. This datafile was recorded by a GPS station on an Antarctica Ice shelf. The data structure is as follows:

col1: coordinate polar stereographic East (m)
col2: coordinate polar stereographic South (m)
col3: coordinate longitude (decimal degrees)
col4: coordinate latitude (decimal degrees)
col5: elevation (m, relative to WGS84)
col6: days (relative to an arbitrary date in the past)

Visualize the vertical displacement as a function of time. The data are a bit noisy for your liking. Smooth the data with a running mean. This means, write a for loop that goes through the data and for each point in time you average values in its surrounding. This is called a running mean. It is not the best way to smooth data, but a good exercises. Write your own loop, don't use external functions.

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

6 A bit of geophysics, but not too much.

The data file is a derived product from a radar survey in Antarctica. The radar was towed behind a skidoo with lots of driving around. The data format is as follows:

col1: coordinate polar-stereographic East (m)
col2: coordinate polar-stereographic South (m)
col3: two-way traveltime to a sub-surface reflector (seconds)

Filter out all the NaN values. Visualize the skidoo-tracks in an x-y plot. Write a function that converts the two-way traveltime of the sub-surface reflector to a depth below the surface. Assume a radio-wave velocity of $1.72 \cdot 10^8 \text{ m s}^{-1}$. What is the average depth of the sub-surface reflector in meters? Can you visualize this using the scatter function in matplotlib?

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

7 Polynomial

The data given is from one month (2022.04) of the weather station in Nahuelbuta. There are 24 values per day (1 hour average).

- Read in the CSV file "data5.csv". (use `np.loadtxt()`, `delimiter=","` and `usecols=(1,2)`)
- Write a function that filters out the invalid values (-9999.0) from the data.
- Take one of the precipitation peaks (for example on 2022-04-24) and try to fit a second order polynomial using the function `polyfit`.
- Plot the data: first column contains the solar radiation, second column contains the precipitation.

Exercises

Get together in groups of three (max four) and prepare this small project as a conversation starter for the oral exam on Wednesday 16th in the time frame from 16:00 - 20:00. Note, this will only be a conversation starter and does not exhaustively cover all possible questions during the exam. You may also solve this problem individually.

8 A bit of geophysics, but not too much.

The data file is a derived product from a radar survey in Antarctica. The radar was towed behind a skidoo with lots of driving around. The data format is as follows:

col1: coordinate polar-stereographic East (m)
col2: coordinate polar-stereographic South (m)
col3: two-way travelttime to a sub-surface reflector (seconds)

Filter out all the NaN values. Visualize the skidoo-tracks in an x-y plot. Write a function (containing a for loop) that calculates the total distance travelled. The function should stop the calculation if the distance between two datapoints is larger than 500 m.