

The background of the slide is a dark, artistic photograph of a microscope. The central part of the image shows the eyepiece and the objective lenses, which are slightly out of focus, creating a sense of depth. The lighting is dramatic, with some parts of the microscope appearing brighter than others.

Multi And Threshold Signatures for Starknet

(Warming up for Lisbon Hackaton)

Renaud Dubois

Ledger
Innovation Team

October 13, 2022

Summary



(Classical) Signatures



Multi-Signatures



Threshold Signatures

Summary

1 Signatures, MultiSigs and ThresholdSigs

- Basic Concepts
- Under the hood

2 Use cases

- Multi factor authentication
- Voting system

3 Ledger/Starknet Musig2, call for Lisbon

Signatures

A digital signature is a mathematical scheme for verifying the authenticity of digital messages or documents.

Definition ((Classical) Digital Signature)

A signature scheme is a tuple of function:


- *Setup*: returns $E(F_p), G, H$
- *KeyGen*($E(F_p), G, H, seed$): returns $(pvk, pubk) = (x, Q)$
- *Sign*($x, message$): returns *Sig*
- *Verify*(*Sig*, *Q*): returns true/false

Most commonly used signature scheme is ECDSA (Bitcoin, Ethereum)

- implemented in Starknet/[Cairo](#) (P256, NTT/Stark friendly Starknet Curve)
- available in your favorite sdk [Ledger](#)

Multi-signatures

A multi-signature is a digital signature allowing users to *aggregate* their keys in an aggregated public key. The signatures are also aggregated. Verifier API is unchanged.



Multi-signatures

A multi-signature is a digital signature allowing users to *aggregate* their keys in an aggregated public key. The signatures are also aggregated. Verifier API is unchanged.

Definition ((Classical) Digital Signature)

A multisig scheme is a tuple of function:

- $(Setup, Keygen, Verify, Sign)$
- $KeyAgg(Q_1, \dots, Q_n)$ returns X
- $SignAgg(Sig_1, \dots, Sig_n)$ returns Sig

Multi-signatures

A multi-signature is a digital signature allowing users to *aggregate* their keys in an aggregated public key. The signatures are also aggregated. Verifier API is unchanged.

Advantages (over naive concatenation/trusted aggregator)

- only one signature over channel (bandwidth consumption)
- no need for a trusted aggregator (no remote private key, own your crypto !)
- no risk of contract failure (don't trust, no don't)
- verifier doesn't need to know the underlying group of users


Example: Bitcoin Taproot, [BIP340](#)

Multi-signatures

A multi-signature is a digital signature allowing users to *aggregate* their keys in an aggregated public key. The signatures are also aggregated. Verifier API is unchanged.


drawback

- increased computational complexities for signers
- requires (off chain) communications between signers
- computation in 2 rounds (Sig1, Sig2)



Threshold-signatures

A (k, n) threshold signature (TS-Sig) is a digital signature allowing a subset (threshold) of k users from n to *aggregate* a signature .



Threshold-signatures

A (k, n) threshold signature (TS-Sig) is a digital signature allowing a subset (threshold) of k users from n to *aggregate* a signature .

Definition ((Classical) Digital Signature)


A multisig scheme is a tuple of function:

- $(Setup, Verify, Sign)$
- $DistributedKeygen,$
- $KeyAgg(Q_1, \dots Q_n)$ returns X
- $SignAgg(Sig_1, \dots, Sig_n)$ returns Sig

Advantages (over naive concatenation/trusted aggregator)

- All of multisig ($k = n$ is equivalent)
- More flexibility in access policy

Disclaimer



EC-Schnorr and ECDSA

SetUP() : Pick a **curve** with parameters (p, a, b, Gx, Gy, q) (**weierstrass equations and formulaes**).

Operation	Schnorr	ECDSA
KeyGen	$Q = xG$	$Q = xG$
Nonce*	k	k
Ephemeral	$R = kG$	$R = kG$
Hash	$e = H(m R)$	$e = H(m)$
Sign	$s = k - xe$ $Sig = (R, s)$	$s = k^{-1}(e + xr)$ $Sig = (r, s)$
Verif	$R' = sG + eQ$ Accept if $R'=R$	$r' = (es^{-1}G + rs^{-1}Q)_x$ Accept if $r'=r$

(* nonce generation may use [RFC6979](#) for misuse resistance)


Musig2: using Schnorr additive properties

Schnorr's part is linear in (k, x) and **linearity** is cool:

$$s(k, x_1) + \text{Sig}(k, x_2) = s(k, x_1 + x_2), \quad \forall x = x_1 + x_2$$

$$s(k_1, x) + \text{Sig}(k_2, x) = s(k, x), \quad \forall k = k_1 + k_2$$

(while ECDSA has degree two monomial in (k, x))



Linearity allow homomorphic additions. Idea: split X into $X = \sum a_i X_i$, k into $k = \sum k_i$.

Musig2: using Schnorr additive properties

Operation	Schnorr	Insec_Musig
KeyGen	$X = xG$	$X_i = x_i G$
KeyAgg	-	$X = \sum_{i=0}^{n-1} a_i X_i$
Nonce*	k	k_i
Ephemeral	$R = kG$	$R_i = k_i G$
Aggregate R	-	$R = (\sum_{i=0}^{n-1} a_i \cdot k_i) \cdot G = k \cdot G$
Hash	$e = H(m R)$	$e = H(m R)$
Sign	$s = k - xe$	$s_i = k_i - a_i x_i e$
Aggregate s	-	$s = \sum s_i = k - xe$


Musig2: using Schnorr additive properties

Musig2 uses a vectorial nonce of length μ , injected in previous Insec_Musig scheme.

Operation	Schnorr	Musig2
KeyGen	$X = xG$	$X_i = x_i G$
KeyAgg	-	$X = \sum_{i=0}^{n-1} a_i X_i$
Nonce*	k	$\vec{k}_i = (k_{i1}, \dots, k_{i\mu})$
Ephemeral	$R = kG$	$\vec{R}_i = \vec{k}_i G$
Hash Nonce	-	$b = H(X R_0 \dots R_\mu m)$
Aggregate R	-	$R = \sum_{j=1}^{\mu} b^{j-1} (\sum_{i=0}^{n-1} a_i \cdot k_i) \cdot G = k \cdot G$
Hash	$e = H(m R)$	$e = H(m R)$
Sign	$s = k - xe$	$s_i = (\sum_{j=1}^{\mu} k_{ij} b^{j-1}) - a_i x_i e$
Aggregate s	-	$s = \sum s_i = k - xe$


Musig2: Thresholdisation Principle

Thresholdisation use the principle of [Shamir's secret sharing scheme](#) , which is in fact a reed solomon erasure code.
Goal: Given enough shares, it is possible to reconstruct the initial value.



Musig2: Thresholdisation Principle

Lagrange interpolation enables to switch from points to polynomial coefficients using the following formulae:



$$l_j(x) = \prod_{m \neq j} \frac{x - x_m}{x_j - x_m}.$$

$$L(x) = \sum_{j=0}^k P(x_j) l_j(x).$$

The transformation L from $(P_0 \dots P_k)$ to $(a_0 \dots a_k)$ is a **linear** transformation in x .

Sidenote: This is closely related to the principle of FRI used in starks.

Musig2: Thresholdisation Principle

Key ideas:

- interpret aggregated secret key as a polynomial P of degree k ,
- each share (user secret key) is a point of the polynomial,
- blind the computation in the curve domain to perform the aggregation only handling public elements,
- replace ' $\sum_{i=0}^n$ ' in previous scheme by Lagrange polynomials,
- some more steps are necessary (commitments) to avoid cheating.

Read [FROST](#) for full description.

Use cases



Multi factor authentication to Starknet Contract

Implement enhanced policy access to assets.

Access Policy

- Low amount: Host (hot wallet) only
- High amount: Host (smartphone) + HW wallet (Nano)

Voting system

Reduce risk and complexity of a contract implementing a voting system. A vote is adopted only though a valid TS-Sig.

Gnosis advanced

- implement a threshold voting system, with $k = \frac{n}{2}$

Ledger/Starknet Musig2

Specificities of Musig2 Starknet (ease Prover/Verifier computations)

- Uses Pedersen Hash as core hash function
- Uses Starknet curve as elliptic domain
- Implement x-only verification

The implementation is a generic one (takes hash and elliptic domain as SetUp parameter). The aim is to overlap with B340 if selecting P256k1 and SHA256 instead (TBD).

Ledger/Starknet Musig2

Current state:

- Schnorr verification available in Cairo,
- High-level simulation in Sagemath of full protocol (Sign/Verify for a pool of users)
- Musig2 implementation on top of a virtualization layer (only integrating bolos for now)
- currently working on thresholdization

C Library (Nano Signer)



SCAN ME

Cairo Code (Contract Verifier)



SCAN ME

Starknet Hackaton



Join the team for:

- Front end integration (wallet, current development over Argent) over verifier (Cairo) or signer (C)
- Integration of a different accelerator/library in the virtualization layer (C)
- Contribute to the threshold version (Sagemath/C)



Questions ?



C Library



SCAN ME

R. Dubois (LIT)

Slides



SCAN ME

Multi And Threshold Signatures for Starknet

Cairo&Sage



SCAN ME

October 13, 2022