

E06 Queries on KB

19214808 Yikun Liang

October 12, 2019

Contents

1	Problem Description	2
2	Relation Definition	2
3	Quests and Result	2

1 Problem Description

Given a KB `Restaurants.pl`, which describes the distribution of branches of 10 well-known restaurants in Guangzhou.

For example, `restaurant(ajukejiacai,2007,yuecai)` means that `ajukejiacai` was founded in 2007 and is a restaurant of `yuecai`. `branch(ajukejiacai,xintiandi)` means that `ajukejiacai` has a branch in `xintiandi`. `district(xintiandi,panyu)` means that `xintiandi` is an area of `panyu` district.

Please formulate each of the following questions as a query using Prolog's notation, pose it to Prolog, and obtain Prolog's answer:

1. What restaurants have branches in beigang?
2. What districts have restaurants of yuecai and xiangcai?
3. What restaurants have the least number of branches?
4. What areas have two or more restaurants?
5. Which restaurant has the longest history?
6. What restaurants have at least 10 branches?

Please define the new relation below using Prolog and test it.

- `sameDistrict(Restaurant1, Restaurant2)`: Restaurant1 and Restaurant2 have one or more branches in the same district.

You should write down a listing that shows the queries you submitted to Prolog, and the answer returned. Hand in a file named `E06_YourNumber.pdf`, and send it to `ai_201901@foxmail.com`

2 Relation Definition

`districtHaveCai(X,Y):- district(Z,X), branch(R,Z),restaurant(R,D,Y).` (Used for Q2)

`districtRest(D,R):- district(Area,D),branch(R,Area).`

`sameDistrict(Restaurant1,Restaurant2):-districtRest(D1,Restaurant1),districtRest(D2,Restaurant2),D1=D2, Restaurant1 \ = Restaurant2.`

3 Quests and Result

```
?- branch(X,beigang).
X = mixuebingcheng ;
X = huangmenjimifan ;
X = shaxianxiaochi.
```

Figure 1: quest 1

```
?- setof(X,(districtHaveCai(X,yuecai),districtHaveCai(X,xiangcai)),Res).
Res = [haizhu, liwan, panyu, tianhe, yuexiu].
```

Figure 2: quest 2

```
?- findall(R1,(setof(Area,branch(R1,Area),Results1),length(Results1,N1), \+ ( setof(A,branch(R2,A),Results2),length(Results2,N2),N2<N1 ) ),Res).
Res = [hongmenyan].
```

Figure 3: quest 3

```
?- setof(A,(setof(R,branch(R,A),Results),length(Results,N),N>=2),Res).
Results = [ajukejiacai, hongmenyan, mixuebingcheng, yangguofu],
N = 4,
Res = [xintiandi] ;
Results = [ajukejiacai, tongxianghui],
N = 2,
Res = [yongfu] ;
Results = [dagangxianmiaoshaoji, huangmenjimifan],
N = 2,
Res = [yuancun] ;
Results = [dagangxianmiaoshaoji, muwushaokao],
N = 2,
Res = [dongpu] ;
Results = [diandude, mixuebingcheng],
N = 2,
Res = [shiqiao] ;
Results = [diandude, tongxianghui],
N = 2,
Res = [bainachui, tianhebei] ;
Results = [huangmenjimifan, mixuebingcheng, shaxianxiaochi],
N = 3,
Res = [beigang].
```

Figure 4: quest 4

```
?- findall(R1,(restaurant(R1,Y1,_),\+ (restaurant(_,Y2,_),Y1>Y2) ),Res).
Res = [huangmenjimifan].

?- ■
```

Figure 5: quest 5

```

?- setof(A,(setof(Branches,branch(A,Branches),Results),length(Results,N),N>=10),Res).
Results = [bainahui, hanting, huizhoudasha, kaifadadao, maoshengdasha, shimaocheng, tianhebei, yongfu, yuanyangmingyuan|...].
N = 10,
Res = [tongxianghui]
Unknown action: ; (h for help)
Action? ;
Results = [bainahui, huachengdadao, huifudong, linhe, panfu, shiqiao, tianhebei, yangji, youtucbangshiguang|...].
N = 10,
Res = [diandude] ;
Results = [beigang, beiting, chentian, chisha, longdong, lujiang, shipaixi, shiqiao, wushan|...].
N = 12,
Res = [mixuebingcheng] ;
Results = [beishan, cencun, changxing, dongpu, fangcun, gaosheng, huadong, kecun, nanopudadao|...].
N = 11,
Res = [dagangxianmiaoshaoji] ;
Results = [diwangguangchang, dongpu, gangding, heguang, runzhengguangchang, shayuan, shengdi, tangxia, tonghe|...].
N = 10,
Res = [muvushaokao].

```

Figure 6: quest 6

```

?- setof(A,sameDistrict(diandude,A),Res).
Res = [ajukejiacai, dagangxianmiaoshaoji, hongmenyan, huangmenjimifan, mixuebingcheng, muvushaokao, shaxianxiaochi, tongxianghui, yangguofu].

```

Figure 7: Quest for sameDistrict