[VULTR AGENT RUSH · CHALLENGE 01: BLAST RADIUS ZERO]

HONEYPOT HUNTER

Autonomous Stunt-Double Browser & Canary Wiretrap

Pre-flight browser containment rig for AI Agents running on Vultr Cloud Compute with Vultr Serverless Inference (llama-3.3-70b-instruct) and Ed25519 cryptographic receipts.

0 SECRETS
Exposed to Untrusted Pages (Blast Radius Zero)

100%
Ephemeral Sandbox Auto-Teardown on Exit

ED25519
RFC 8032 Asymmetric + SHA-256 Receipts

[THE ACUTE PROBLEM]

AI Agents Cannot Tell a Login from a Phishing Trap

In 2026, enterprises deploy autonomous AI agents (OpenAI Operator, Claude Computer Use, CrewAI) to browse supplier sites and fill forms without human supervision.

VECTOR 01 · CREDENTIAL BLEED

Phishing & SSO Harvesters

Spoofed Okta and corporate login portals trick autonomous agents into submitting real API keys and passwords directly to attacker drop servers.

VECTOR 02 · PROMPT HIJACKING

Hidden DOM Prompt Injections

Hostile instructions hidden via zero-opacity CSS (opacity:0, aria-hidden) hijack naive DOM-scraping agents into exfiltrating private workspace tokens.

VECTOR 03 · INFRASTRUCTURE ABUSE

SSRF & Runaway Memory Bombs

Malicious scripts probe cloud metadata (169.254.169.254) or trigger unbounded heap allocation loops to crash the agent host machine.

[REAL-WORLD OPERATIONAL MODEL]

Three-Tier Enterprise Deployment Architecture

Built as an API-first pre-flight security rig for autonomous agents, paired with a real-time SOC analyst command studio.

TIER 01 · AGENT-TO-AGENT API

Pre-Flight MCP / REST Tool

Autonomous agents call POST /api/investigate before visiting unknown URLs. Honeypot Hunter sends the sacrificial stunt-double in first and returns a signed verdict.

TIER 02 · SOC COMMAND STUDIO

100vh Obsidian Telemetry HUD

Security analysts & judges inspect live browser optics locks, intercepted wire payloads, and verify cryptographic receipts with a 1-click Tamper Test.

TIER 03 · ENTERPRISE ROADMAP

Corporate Browser Extension

Lightweight Chrome/Brave extension automatically routing suspicious Slack and email links clicked by employees through the Vultr stunt-double sandbox.

[ACTIVE DECEPTION ENGINE]

Synthetic Canary Wiretrap & Socket Abortion

Unlike passive URL scanners that merely read HTML text, Honeypot Hunter actively baits suspect forms to catch credential theft red-handed on the wire.

STEP 01 · PERCEIVE

Optics Lock & Form Extraction

Detects deceptive login inputs and extracts cross-origin form submission targets with real-time DOM bounding-box coordinates.

STEP 02 · BAIT

Canary Secret Injection

Types tracked decoy credentials (canary.xxx@vault-honeypot.internal) into target fields while keeping 0 real secrets inside the sandbox.

STEP 03 · ABORT

In-Flight Egress Interception

Intercepts the outbound POST payload containing the canary token, records forensic wire evidence, and aborts the browser request before data escapes.

[VULTR PROTAGONIST ARCHITECTURE]

Powered by Vultr Compute & Serverless Inference

Engineered natively around Vultr cloud infrastructure with live telemetry provenance verified on every run.

COGNITIVE SYNTHESIS · LLAMA-3.3-70B-INSTRUCT

Vultr Serverless Inference

Queries api.vultrinference.com/v1/chat/completions in real time (~2.1s latency) to formulate autonomous investigation plans and synthesize structured incident dossiers.

CONTAINMENT HOST · UBUNTU 24.04 LTS

Vultr Cloud Compute VM

Runs Caddy TLS proxy, FastAPI control plane, Docker init reaper (tini), 256MB V8 heap cap, SSRF/DNS rebinding guard, and supervisor SIGKILL teardown.

[MATHEMATICAL CONTAINMENT PROOF]

Ed25519 Signatures & 1-Click Tamper Challenge

Every investigation is sealed with an asymmetric RFC 8032 Ed25519 signature and canonical SHA-256 digest verifiable offline or directly in the browser.

SUB-HASH BINDING

Frame + Payload + Timeline

Binds visual viewport JPEG hashes, intercepted wire payloads, and lifecycle telemetry into a deterministic canonical JSON structure.

ASYMMETRIC PROOF

RFC 8032 Ed25519 Signing

Signed by the host control-plane private key outside the browser sandbox. Anyone can verify authenticity via GET /api/public-key.

INTERACTIVE VERIFICATION

1-Click Tamper Test

Judges can click "Tamper Test" in the UI to corrupt 1 byte of the receipt and watch POST /api/verify-receipt immediately reject the forgery.

[ZERO FALSE POSITIVES]

Deterministic Guardrails & Verifiable Abstention

A security sandbox is useless if it cries wolf on benign websites. Honeypot Hunter proves restraint on clean arbitrary URLs.

LIVE CUSTOM URL EVALUATION

Unscripted Public Websites (e.g. example.com)

Judges can paste any public URL into the live command bar. Clean domains complete in ~7.5 seconds with 0 false-positive blocks and risk score 0/100.

TWO-LAYER BOUNDED GATE

SAFE_VERIFIED_ABSTENTION Verdict

Hard mathematical constraint gate prevents the LLM from hallucinating threats when wire telemetry records zero unauthorized egress or hidden DOM injections.

[READY FOR LIVE EVALUATION]

Don't Click Suspicious Links.
Send Our Agent In First.

Test the live autonomous stunt-double right now at https://139.84.149.182.nip.io

LIVE PRODUCTION URL

139.84.149.182.nip.io

Active HTTPS deployment on Vultr Cloud Compute with 1-click scenarios and custom URL input.

AUTOMATED TEST SUITE

8 / 8 Pytest Passed

100% pass rate across SSRF poison inputs, sandbox containment, concurrency, and Ed25519 tamper rejection.

OPEN SOURCE

MIT License

30-second clean-clone quickstart and reproducible Docker + Caddy deployment on Vultr.