- Change Documentation — aaziko-driver-mobile
  - 2026-10-19 16:13 — branch `main`
  - 2026-09-26 — branch `main` (history)
  - 2026-08-29 — branch `main` (history)
  - 2026-08-25 — branch `main` (history)

Change Documentation — aaziko-driver-mobile

> Auto-generated on every push, to any branch. Newest entry first. Old entries are never removed.

2026-10-19 16:13 — branch `main`

Overview

This push to branch `main` changed **2 file(s)**: 2 new, 0 modified, 0 removed (+457 / −0 lines).

Main areas touched: `.aaziko-flow` (1), `.github/workflows` (1).

New files

`.aaziko-flow/changelog.mjs`

New file — 347 lines

- Defines: `sh`, `shSafe`, `git`, `esc`, `code`, `list`, `repo`, `declName`, `collect`, `minusSet` and 9 more.
- Uses: `node:child_process`, `node:fs`, `node:path`.
- Reads environment variables: `BEFORE_SHA`, `AFTER_SHA`, `BASE_BRANCH`, `BRANCH`.

Other new files

- `.github/workflows/aaziko-changelog.yml` — 110 lines

Impact

- Code now reads `BEFORE_SHA` — make sure it is set in the `.env` / deployment.
- Code now reads `AFTER_SHA` — make sure it is set in the `.env` / deployment.
- Code now reads `BASE_BRANCH` — make sure it is set in the `.env` / deployment.
- Code now reads `BRANCH` — make sure it is set in the `.env` / deployment.
- Build/deploy configuration changed: `.github/workflows/aaziko-changelog.yml` — re-check the build and deployment.

> **History before automatic documentation was switched on** — one entry per day of the `main` branch, newest first.

2026-09-26 — branch `main` (history)

Overview

On this day, branch `main` received changes to **1 file(s)**: 1 new, 0 modified, 0 removed (+94 / −0 lines).

Main areas touched: `.github/workflows` (1).

New files

Other new files

- `.github/workflows/backup-to-gitlab.yml` — 94 lines

Impact

- Build/deploy configuration changed: `.github/workflows/backup-to-gitlab.yml` — re-check the build and deployment.

2026-08-29 — branch `main` (history)

Overview

On this day, branch `main` received changes to **42 file(s)**: 29 new, 12 modified, 1 removed (+4195 / −110 lines).

Main areas touched: `app` (8), `assets/images` (8), `components` (8), `(project root)` (6), `assets/images/_default_expo_backup` (5), `app/(tabs)` (3).

New files

`app/order-detail.tsx`

New file — 910 lines

- Defines: `OrderDetailScreen`, `qtyOf`, `isBoxComplete`, `firstIncompleteVerified`, `setQtyFor`, `captureFor`, `openScanner`, `onSubmit`, `captureTruckPhoto`, `onAllOk`, `handleScanned`, `boxKey`, `BoxRow`, `PillBtn`, `QuantitySlider`, `respond`.
- Uses: `@expo/vector-icons`, `expo-image`, `expo-image-picker`, `expo-router`, `expo-status-bar`, `react`, `react-native-safe-area-context`, `@/components/QrScanner`.

`app/orders.tsx`

New file — 829 lines

- Defines: `OrdersScreen`, `LoadSummaryCard`, `Container3DModal`, `BreakdownCard`, `RightSemi`, `Donut`, `OrderCard`, `openDirections`, `openDetail`, `onVerify`.
- Uses: `@expo/vector-icons`, `expo-image`, `expo-router`, `expo-status-bar`, `react`, `react-native-safe-area-context`, `@/components/LoadCalc3D`, `@/services/auth`.

services/orders.ts

New file — 356 lines

- Defines: `Assignment`, `ParsedOrder`, `InspectionBox`, `OrderInspection`, `normalizeMediaUrl`, `spId`, `authHeaders`, `Result`, `getMyAssignments`, `fromDescription`, `parseAssignment`, `isInspectionDone`, `fetchInspectionBoxes`, `BoxStatus`, `boxStatusKey`, `loadBoxStatus`, `saveBoxStatus`, `getBoxByQr`, `getOrderInspection`, `isOrderDone`, `Factory`, `getAssignmentDetails`, `getAssignmentImages`, `verifyOtp`.
- Uses: `@react-native-async-storage/async-storage`, `@/constants/api`, `@/services/auth`.

components/loadCalc3dHtml.ts

New file — 302 lines

- Defines: `Cargo3DItem`, `LoadCalc3DData`, `buildLoadCalc3dHtml`, `getShapeType`, `buildCargoBoxes`, `findOptimalLayout`, `capacityAtScale`, `findScale`, `fitCamera`, `makeGeo`, `resize`, `animate`.
- Uses: `three`, `three/addons/controls/OrbitControls.js`, `three/addons/environments/RoomEnvironment.js`.

app/order-map.tsx

New file — 245 lines

- Defines: `OrderMapScreen`.
- Uses: `@expo/vector-icons`, `expo-image`, `expo-router`, `expo-status-bar`, `react`, `react-native-safe-area-context`, `@/components/OrderMap`, `@/components/orderMapHtml`, `@/services/orders`.

app/login.tsx

New file — 239 lines

- Defines: `LoginScreen`, `onLogin`.
- Uses: `@expo/vector-icons`, `expo-image`, `expo-router`, `expo-status-bar`, `react`, `react-native-safe-area-context`, `@/services/auth`, `@/assets/images/delivery.png`.

app/order-completed.tsx

New file — 235 lines

- Defines: `banner`, `OrderCompletedScreen`, `ReadOnlyBox`.
- Uses: `@expo/vector-icons`, `expo-image`, `expo-router`, `expo-status-bar`, `react`, `react-native`, `react-native-safe-area-context`, `@/services/orders`.

services/loadCalc.ts

New file — 162 lines

- Defines: `ProductInput`, `LoadResult`, `loadCargoTypeDefaults`, `defaultDimsFor`, `productFromOrder`, `LoadResponse`, `calculateLoad`.
- Uses: `@/constants/api`, `@/components/loadCalc3dHtml`.

services/auth.ts

New file — 157 lines

- Defines: `DriverUser`, `LoginData`, `persistSession`, `loadSession`, `isSignedIn`, `clearSession`, `apiHost`, `LoginResult`, `loginServiceProvider`.
- Uses: `@react-native-async-storage/async-storage`, `@/constants/api`.

components/QrScanner.tsx

New file — 129 lines

- Defines: `QrScannerProps`, `QrScanner`, `handleBarcode`.
- Uses: `@expo/vector-icons`, `expo-camera`, `react`, `react-native`, `react-native-safe-area-context`.

components/orderMapHtml.ts

New file — 105 lines

- Defines: `OrderMapData`, `buildOrderMapHtml`, `placeAt`, `geocode`, `boot`.

components/QrScanner.web.tsx

New file — 99 lines

- Defines: `QrScannerProps`, `QrScanner`, `submit`.
- Uses: `@expo/vector-icons`, `react`, `react-native`.

app/(tabs)/home.tsx

New file — 98 lines

- Code moved here from other files: `HomeScreen`.
- Uses: `expo-image`, `react-native`, `@/components/hello-wave`, `@/components/parallax-scroll-view`, `@/components/themed-text`, `@/components/themed-view`, `expo-router`, `@/assets/images/partial-react-logo.png`.

components/LoadCalc3D.tsx

New file — 40 lines

- Defines: `LoadCalc3DProps`, `LoadCalc3D`.
- Uses: `react`, `react-native`, `react-native-webview`, `@/components/loadCalc3dHtml`.

components/LoadCalc3D.web.tsx

New file — 33 lines

- Defines: `LoadCalc3DProps`, `LoadCalc3D`.
- Uses: `react`, `@/components/loadCalc3dHtml`.

components/OrderMap.tsx

New file — 33 lines

- Defines: `OrderMapProps`, `OrderMap`.
- Uses: `react`, `react-native`, `react-native-webview`, `@/components/orderMapHtml`.

components/OrderMap.web.tsx

New file — 28 lines

- Defines: `OrderMapProps`, `OrderMap`.
- Uses: `react`, `@/components/orderMapHtml`.

`constants/api.ts`

New file — 12 lines

- Data / content file (no functions or components).
- Reads environment variables: `EXPO_PUBLIC_API_URL`.

`app/index.tsx`

New file — 9 lines

- Defines: `Index`.
- Uses: `expo-router`, `@/services/auth`.

Other new files

- `eas.json` — 21 lines
- `.env` — 4 lines
- `assets/images/_default_expo_backup/android-icon-background.png` — binary file
- `assets/images/_default_expo_backup/android-icon-foreground.png` — binary file
- `assets/images/_default_expo_backup/android-icon-monochrome.png` — binary file
- `assets/images/_default_expo_backup/favicon.png` — binary file
- `assets/images/_default_expo_backup/icon.png` — binary file
- `assets/images/aaziko-logo.png` — binary file
- `assets/images/delivery.png` — binary file
- `assets/images/splash-logo.png` — binary file

Changes to existing files

`app/_layout.tsx`

Existing file, modified — +18 / −1 lines

- Changed the code inside: `RootLayout`.
- Now also uses: `react`, `@/services/auth`.

`package.json`

Existing file, modified — +8 / −4 lines

- Added package `@react-native-async-storage/async-storage` 2.2.0
- Added package `expo-camera` ~17.0.10
- Added package `expo-image-picker` ~17.0.11
- Added package `react-native-webview` 13.15.0

`app/(tabs)/_layout.tsx`

Existing file, modified — +1 / −1 lines

- Changed the code inside: `TabLayout`.

`app/modal.tsx`

Existing file, modified — +1 / −1 lines

- Changed the code inside: `ModalScreen`.

Other modified files

- `package-lock.json` — +92 / −0 lines
- `app.json` — +28 / −5 lines
- `README.md` — +1 / −0 lines
- `assets/images/android-icon-background.png` — binary file
- `assets/images/android-icon-foreground.png` — binary file
- `assets/images/android-icon-monochrome.png` — binary file
- `assets/images/favicon.png` — binary file
- `assets/images/icon.png` — binary file

Removed files

`app/(tabs)/index.tsx`

Removed file — 98 lines removed

Impact

- Code now reads `EXPO_PUBLIC_API_URL` — make sure it is set in the `.env` / deployment.
- Dependencies changed in `package.json` — run `npm install` and rebuild the Docker image before deploying.
- Build/deploy configuration changed: `.env` — re-check the build and deployment.

2026-08-25 — branch `main` (history)

Overview

On this day, branch `main` received changes to **41 file(s)**: 41 new, 0 modified, 0 removed (+14162 / −0 lines).

Main areas touched: `assets/images` (10), `(project root)` (9), `components` (6), `app/(tabs)` (3), `components/ui` (3), `hooks` (3).

New files

`app/(tabs)/explore.tsx`

New file — 112 lines

- Defines: `TabTwoScreen`.
- Uses: `expo-image`, `react-native`, `@/components/ui/collapsible`, `@/components/external-link`, `@/components/parallax-scroll-view`, `@/components/themed-text`, `@/components/themed-view`, `@/components/ui/icon-symbol`, `@/constants/theme`, `@/assets/images/react-logo.png`.

scripts/reset-project.js

New file — 112 lines

- Defines: `Index`, `RootLayout`, `moveDirectories`.
- Uses: `fs`, `path`, `readline`.

app/(tabs)/index.tsx

New file — 98 lines

- Defines: `HomeScreen`.
- Uses: `expo-image`, `react-native`, `@/components/hello-wave`, `@/components/parallax-scroll-view`, `@/components/themed-text`, `@/components/themed-view`, `expo-router`, `@/assets/images/partial-react-logo.png`.

components/parallax-scroll-view.tsx

New file — 79 lines

- Defines: `Props`, `ParallaxScrollView`.
- Uses: `react`, `react-native`, `@/components/themed-view`, `@/hooks/use-color-scheme`, `@/hooks/use-theme-color`.

components/themed-text.tsx

New file — 60 lines

- Defines: `ThemedTextProps`, `ThemedText`.
- Uses: `react-native`, `@/hooks/use-theme-color`.

constants/theme.ts

New file — 53 lines

- Uses: `react-native`.

package.json

New file — 47 lines

- Added package `@expo/vector-icons` ^15.0.3
- Added package `@react-navigation/bottom-tabs` ^7.4.0
- Added package `@react-navigation/elements` ^2.6.3
- Added package `@react-navigation/native` ^7.1.8
- Added package `expo` ~54.0.36
- Added package `expo-constants` ~18.0.13
- Added package `expo-font` ~14.0.12
- Added package `expo-haptics` ~15.0.8
- Added package `expo-image` ~3.0.11
- Added package `expo-linking` ~8.0.12
- Added package `expo-router` ~6.0.24
- Added package `expo-splash-screen` ~31.0.13
- Added package `expo-status-bar` ~3.0.9

- Added package `expo-symbols` ~1.0.8
- Added package `expo-system-ui` ~6.0.9
- Added package `expo-web-browser` ~15.0.11
- Added package `react` 19.1.0
- Added package `react-dom` 19.1.0
- Added package `react-native` 0.81.5
- Added package `react-native-gesture-handler` ~2.28.0
- Added package `react-native-worklets` 0.5.1
- Added package `react-native-reanimated` ~4.1.1
- Added package `react-native-safe-area-context` ~5.6.0
- Added package `react-native-screens` ~4.16.0
- Added package `react-native-web` ~0.21.0
- Added package `@types/react` ~19.1.0
- Added package `typescript` ~5.9.2
- Added package `eslint` ^9.25.0
- Added package `eslint-config-expo` ~10.0.0
- Added npm script `start`
- Added npm script `reset-project`
- Added npm script `android`
- Added npm script `ios`
- Added npm script `web`
- Added npm script `lint`

`components/ui/collapsible.tsx`

New file — 45 lines

- Defines: `Collapsible`.
- Uses: `react`, `react-native`, `@/components/themed-text`, `@/components/themed-view`, `@/components/ui/icon-symbol`, `@/constants/theme`, `@/hooks/use-color-scheme`.

`components/ui/icon-symbol.tsx`

New file — 41 lines

- Defines: `IconMapping`, `IconSymbolName`, `IconSymbol`.
- Uses: `@expo/vector-icons/MaterialIcons`, `expo-symbols`, `react`, `react-native`.

`app/(tabs)/_layout.tsx`

New file — 35 lines

- Defines: `TabLayout`.
- Uses: `expo-router`, `react`, `@/components/haptic-tab`, `@/components/ui/icon-symbol`, `@/constants/theme`, `@/hooks/use-color-scheme`.

`components/ui/icon-symbol.ios.tsx`

New file — 32 lines

- Defines: `IconSymbol`.
- Uses: `expo-symbols`, `react-native`.

app/modal.tsx

New file — 29 lines

- Defines: `ModalScreen`.
- Uses: `expo-router`, `react-native`, `@/components/themed-text`, `@/components/themed-view`.

components/external-link.tsx

New file — 25 lines

- Defines: `Props`, `ExternalLink`.
- Uses: `expo-router`, `expo-web-browser`, `react`.
- Reads environment variables: `EXPO_OS`.

app/_layout.tsx

New file — 24 lines

- Defines: `RootLayout`.
- Uses: `@react-navigation/native`, `expo-router`, `expo-status-bar`, `react-native-reanimated`, `@/hooks/use-color-scheme`.

hooks/use-color-scheme.web.ts

New file — 21 lines

- Defines: `useColorScheme`.
- Uses: `react`, `react-native`.

hooks/use-theme-color.ts

New file — 21 lines

- Defines: `useThemeColor`.
- Uses: `@/constants/theme`, `@/hooks/use-color-scheme`.

components/hello-wave.tsx

New file — 19 lines

- Defines: `HelloWave`.
- Uses: `react-native-reanimated`.

components/haptic-tab.tsx

New file — 18 lines

- Defines: `HapticTab`.
- Uses: `@react-navigation/bottom-tabs`, `@react-navigation/elements`, `expo-haptics`.
- Reads environment variables: `EXPO_OS`.

components/themed-view.tsx

New file — 14 lines

- Defines: `ThemedViewProps`, `ThemedView`.
- Uses: `react-native`, `@/hooks/use-theme-color`.

`eslint.config.js`

New file — 10 lines

- Uses: `eslint/config`, `eslint-config-expo/flat`.

`hooks/use-color-scheme.ts`

New file — 1 lines

- Data / content file (no functions or components).

Other new files

- `package-lock.json` — 13091 lines
- `README.md` — 50 lines
- `app.json` — 48 lines
- `.gitignore` — 43 lines
- `tsconfig.json` — 17 lines
- `.vscode/settings.json` — 7 lines
- `.claude/settings.json` — 5 lines
- `AGENTS.md` — 3 lines
- `.vscode/extensions.json` — 1 lines
- `CLAUDE.md` — 1 lines
- `assets/images/android-icon-background.png` — binary file
- `assets/images/android-icon-foreground.png` — binary file
- `assets/images/android-icon-monochrome.png` — binary file
- `assets/images/favicon.png` — binary file
- `assets/images/icon.png` — binary file
- `assets/images/partial-react-logo.png` — binary file
- `assets/images/react-logo.png` — binary file
- `assets/images/react-logo@2x.png` — binary file
- `assets/images/react-logo@3x.png` — binary file
- `assets/images/splash-icon.png` — binary file

Impact

- Dependencies changed in `package.json` — run `npm install` and rebuild the Docker image before deploying.
- Code now reads `EXPO_OS` — make sure it is set in the `.env` / deployment.
- Build/deploy configuration changed: `tsconfig.json` — re-check the build and deployment.
