

OS 2/20

Reagan Shirk

February 20, 2020

C/GCP Stuff

- You can type the command `cd /proc` which is a folder that should automatically be created
 - If you type the command `ls | head`, you'll see a bunch of PIDs (process IDs)
- `sudo -i` will make you the root user, and keep in mind that with great power comes great responsibility so don't fuck up
- You can `cd` into a PID

File Descriptors

Standard File Descriptors

- Standard input (0), standard output (1), standard error (2)
- We can take advantage of these standard file descriptors in our code
- He has slides on the website, the second slide has instructions to download some files that we've spent most of the class looking at
- The file we've been going over is in `/fileio` and is called `copy.c`

Permissions

- When you type `ls -l` in a directory, you get something that looks like `-rwxrwxr-x` in front of every file/directory
 - This stands for read, write, execute and the groups of `rw` states the permissions for different users
 - * `[rwx(user) rwx(group) rwx(other)]`
 - * Setting each variable to a 1 means they have that permission, a 0 means they do not
 - * `rwxr-xrw- = 111101110`
 - * You can break the binary number into sets of 3 and convert to decimal, the decimal number is your permission string
 - `chown <decimal number>` will change the file permissions
 - * You can change the group, owner, etc by doing `chgrp` or `chown`