HBase 實做

Hbase Shell

檢查狀態

hbase> status

檢查版本

hbase> version

檢查跟表格相關說 明

hbase> table_help

使用者資訊

hbase> whoami

- ■啟用表格
 - □Syntax:
 - □enable 'table-name'
 - □Example:
 - enable 'easylearning'
- ■確認表格啟用
 - □Syntax:
 - □is_enabled 'table-name'
 - □Example:
 - □is_enabled 'easylearning'

- ■停止使用表格
 - ☐Syntax:
 - □disable 'table-name'
 - **□**Example:
 - disable 'easylearning'
- ■確認表格停止
 - □Syntax:
 - □is_disabled 'table-name'
 - **□**Example:
 - ■is_disabled 'easylearning'

```
建立表格
   ■ Syntax :
   □ create 'table-name', { NAME=>'column-family-name' }, {
      NAME=>'column-family-name' }
   ■ Example :
   □ create 'easylearning', {NAME=> 'Student'}, {NAME => 'Teacher'}
■ 檢視表格
   ■ Syntax :
   □ describe 'table-name'
   ■ Example :
   describe 'easylearning'
■ 表列所有表格
   ■ Syntax :
   □ list
```

- 確認表格是否存在
 - ☐ Syntax:
 - exists 'table_name'
 - Example:
 - exists 'easylearning'
- ■刪除表格
 - ☐ Syntax:
 - □ drop 'table_name'
 - Example :
 - □ disable 'easylearning'
 - □ drop 'easylearning'

- 刪除Column Family
 - ■Syntax:
 - □alter 'table name', 'delete' ⇒ 'column family'
 - ■Example:
 - □alter 'easylearning', 'delete' ⇒ 'student'

- ■新增資料
 - Syntax :
 - □ put 'table-name', 'Row-Key', 'Colum-family-name: column-name', 'value to be inserted'
 - Example :
 - put 'easylearning', 'stud-101', 'Student: stud_name', 'Alice'
- ■取得資料內容
 - ☐ Syntax:
 - ☐ get '','row1'
 - Example :
 - □ get 'easylearning', 'stud-101'

- 刪除Cell 資料
 - Syntax :
 - delete '', '<row>', '< Colum-family-name : column name >', '<timestamp>'
 - Example :
 - delete 'easylearning', 'stud-101', 'Student : stud_name', 1417521848375
- ■刪除全部資料
 - ☐ Syntax:
 - □ deleteall '', '<row>'
 - **□** Example :
 - □ deleteall 'easylearning', 'stud-101'

- ■取得特定表格資料
 - ☐ Syntax:
 - □ scan 'table-name'
 - Example :
 - □ scan 'easylearning'
- ■計算列數
 - ☐ Syntax:
 - □ count 'table-name'
 - Example :
 - □ count 'easylearning'

- ■重建表格
 - □Syntax:
 - □truncate 'table-name'
 - **□**Example:
 - ■truncate 'easylearning'

THANK YOU