

## ElasticSearch 5.x的创建的方法

```
1 @Configuration
2 public class EsConfig {
3
4     @Bean
5     public TransportClient client() throws UnknownHostException {
6
7         InetSocketAddress inetSocketAddress = new
InetSocketAddress(
8             InetAddress.getByName("localhost"), 9300
9         );
10
11         Settings settings = Settings.builder()
12             .put("cluster.name", "test_cluster")
13             .build();
14
15         TransportClient client = new PreBuiltTransportClient(settings);
16         client.addTransportAddress(inetSocketAddress);
17         return client;
18     }
19 }
```

但是到了 6.x 当中 `InetSocketAddress` 这个类没有了，可能被官方删除了。。。。

使用 `TransportAddress` 替代创建。

```
1 @Configuration
2 public class EsConfig {
3
4     @Bean
5     public TransportClient client() throws UnknownHostException {
6
7         TransportAddress transportAddress = new TransportAddress(
8             InetAddress.getByName("localhost"), 9300
9         );
10
11         Settings settings = Settings.builder()
12             .put("cluster.name", "test_cluster")
13             .build();
```

```
14
15     TransportClient client = new PreBuiltTransportClient(settings);
16     client.addTransportAddress(transportAddress);
17     return client;
18 }
19 }
```