

# Numpy Notes

by *Karthik Nair*

**Notes compiled from multiple sources including the Official Numpy Documentation**

## Numpy - introduction

NumPy is the fundamental package for scientific computing in Python. It is a Python library that provides a multi-dimensional array object, various derived objects (such as masked [arrays](#) and [matrices](#)), and an assortment of routines for fast operations on arrays, including mathematical, logical, shape manipulation, sorting, selecting, I/O, discrete Fourier transforms, basic linear algebra, basic statistical operations, random simulation and much more

## Why is numpy faster than lists?

NumPy uses ndarray. An ndarray is a collection of homogeneous data-types that are stored in contiguous memory locations. On the other hand, a list in Python is a collection of heterogeneous data types stored in non-contiguous memory locations. The NumPy package breaks down a task into multiple fragments and then processes all the fragments parallelly.

Ndarray classes are used to represent both Matrices and Vectors

## How are NumPy Arrays different from Python lists?

NumPy arrays have a fixed size at creation, unlike Python lists (which can grow dynamically). Changing the size of an ndarray will create a new array and delete the original

The elements in a NumPy array are all required to be of the same data type, and thus will be the same size in memory. The exception: one can have arrays of (Python, including NumPy) objects, thereby allowing for array of different sized elements

The NumPy package integrates C, C++, and Fortran codes in Python.

These programming languages have very little execution time compared to Python

```
import numpy as np # it has become a convention to use np as the alias for numpy
```

```
array0=np.array([1,2,3,4])  
  
print(type(array0)) # returns <class 'numpy.ndarray'>
```

```
<class 'numpy.ndarray'>
```

## Dimensions of an array

Ndarrays can be of different dimensions or **Axes** e.g. 0D , 1D (known as Vector), 2D (known as Matrix), 3D, etc  
Arrays of dimensions 3 or higher are commonly known as **Tensors**

**Rank** of an Array is the number of dimensions in an array

### Some important attributes of an Narray

`ndarray.ndim` Lets you see the number of axes(dimensions) of a numpy array

`ndarray.shape` Returns a tuple of integers indicating the size of the array in each dimension  
e.g. for a matrix with n rows and m columns, shape will be (n,m). (`len(ndarray.shape)==ndarray.ndim`)

`ndarray.size` Displays the total number of elements in an array. (This is equal to the product of elements of shape)

`ndarray.dtype` returns an object describing the type of elements in the array

`ndarray.itemsize` returns size (in bytes) of each element of the array (Equivalent to `ndarray.dtype.itemsize`)

`ndarray.data` returns the buffer containing the actual elements of the array

### Creating NumPy Arrays

#### Using array function

You can create an array from a regular Python list or tuple using the array function

```
np.array([1,2,3,4]) #from list
np.array((1,2,3,4)) #from tuple
```

```
array([1, 2, 3, 4])
```

#### Using placeholder functions

Placeholder functions are used when we need to create an array with its size known, but elements unknown (initially) For example, we might need to create an array to store data of 10 students where the elements would be filled later

`np.zeros` : creates an array full of zeros

```
np.zeros((2,4))
```

```
array([[0., 0., 0., 0.],  
       [0., 0., 0., 0.]])
```

**np.ones** : creates an array full of ones

```
np.ones((2,4))
```

```
array([[1., 1., 1., 1.],  
       [1., 1., 1., 1.]])
```

**np.empty** : creates an array whose initial content is random

```
np.empty((2,2)) #values could be anything
```

```
array([[4.67592012e-310, 0.00000000e+000],  
       [4.67647668e-310, 4.67647667e-310]])
```

### Functions to create sequence of numbers

**np.arange** : create sequences of numbers in a format analogous to Python's built-in **range**

```
np.arange( 10, 30, 5 )
```

```
array([10, 15, 20, 25])
```

```
np.arange( 0, 2, 0.3 ) # it also accepts float arguments
```

```
array([0. , 0.3, 0.6, 0.9, 1.2, 1.5, 1.8])
```

**np.linspace** : receives as an argument the number of elements that we want, instead of the step values

```
np.linspace( 0, 2, 9 )
```

```
array([0. , 0.25, 0.5 , 0.75, 1. , 1.25, 1.5 , 1.75, 2. ])
```

## Arrays of different dimensions

### 0D Arrays

Zero dimensional arrays are **scalars**. They can't be accessed using indices but can be converted into scalars  
Zero dimensional arrays are NOT equivalent to length-1 1D arrays

```
# Creating a zero dimensional array
```

```
array1=np.array(27)
```

```
array1
```

```
array(27)
```

```
array1.shape # returns () , which indicates zero dimension
```

```
()
```

```
array1.ndim # returns 0, which indicates 0 dimension
```

```
0
```

```
# converting zero-dimensional arrays to scalars  
scalar_array=array1.item()  
scalar_array
```

```
27
```

## Note

For a zero dimensional array:

- `print(array1[0])` #results in an error
- Trying to access the value in a 0D array using index results in an error

reason : 0D ndarrays are considered scalars

## 1D Arrays

In a 1D array, a single argument is passed to access a specific value e.g in array [1,2,3,4], element '3' can be accessed with its index 2

```
# Creating a length-1 one dimensional array

array2=np.array([27]) #unlike zero-dimensional arrays, in len1 1D arrays, we pass
the array element in sq brackets

array2
```

```
array([27])
```

```
# with length more than 1

array3=np.array([1,2,3,4])

array3
```

```
array([1, 2, 3, 4])
```

```
array2[0] # element can be accessed using index
```

```
27
```

```
array3[2] # accessing the third element in array
```

```
3
```

```
array3.shape # returns (4,) which indicates an array with 1 dimension and 4 elements
```

```
(4,)
```

```
array3.ndim # returns 1, indicating 1 dimension
```

```
1
```

## 2D Arrays

In 2D array, 2 arguments needs to be passed to access a single element

```
array4=np.array([[1,2,3],[43,22,11]]) # Creating a 2D numpy array
```

```
array4
```

```
# for instance, np.array([[1,2,3],[3,4,22],[43,22,11]]) indicates a 2D array with 3 layers and 3 elements in each layer
```

```
array([[ 1,  2,  3],  
       [43, 22, 11]])
```

```
array4[1][1]
```

```
# Accessing the second element from the 2nd layer of the 2nd dimension
```

```
22
```

```
array4.shape # returns (2,3)
```

```
(2, 3)
```

```
array4.ndim
```

```
2
```

### 3D Arrays

In 3D array, 3 argument needs to be passed to access a single element

```
array5=np.array([[[22,3,32],[33,1,32]],[[44,34,21],[3,29,32]]])  
# creating a 3D array with 2 layers and 2 sub-layers within each layer and 3  
elements in each sub-layer
```

```
array5
```

```
array([[[22,  3, 32],  
        [33,  1, 32]],  
       [[44, 34, 21],  
        [ 3, 29, 32]]])
```

```
array5[1][1][1]  
# accessing the 2nd element of the 2nd sub-layer of the second layer, ie 29
```

```
29
```

```
array5.ndim
```

```
3
```

```
array5.shape
```

```
(2, 2, 3)
```

```
array6=np.array([[[22,3,32],[33,1,32],[33,42,38]],[[44,34,21],[3,22,32],  
[99,43,88]]])  
# creating a 3D array with 2 layers and 3 sub-layers within each layer and 3  
elements in each layer  
  
array6
```

```
array([[[22,  3, 32],  
        [33,  1, 32],  
        [33, 42, 38]],  
  
       [[44, 34, 21],  
        [ 3, 22, 32],  
        [99, 43, 88]]])
```

```
array6.ndim
```

```
3
```

```
array6.shape
```

```
(2, 3, 3)
```

## Printing Arrays

When you print an array, NumPy displays it in a similar way to nested lists, but with the following layout:

- the last axis is printed from left to right,
- the second-to-last is printed from top to bottom,
- the rest are also printed from top to bottom, with each slice separated from the next by an empty line.





One-dimensional arrays are then printed as rows, bidimensionals as matrices and tridimensionals as lists of matrices

If an array is too large to be printed, NumPy automatically skips the central part of the array and only prints the corners:

To disable this behaviour and force numpy to print the whole array, we can change the printing options by using the `np.set_printoptions` method and passing either of the two arguments :

- `np.set_printoptions(threshold=np.inf)`
- `np.set_printoptions(threshold=sys.maxsize)` *after importing sys*

```
a=np.arange(10000)
a
```

```
array([  0,   1,   2, ..., 9997, 9998, 9999])
```

```
import sys
np.set_printoptions(threshold=sys.maxsize)
# now printing array a would print all the numbers
```

## Basic Array Operations

Arithmetic operators on arrays apply elementwise

```
a = np.array( [20,30,40,50] )
b = np.arange( 4 )
b
```

```
array([0, 1, 2, 3])
```

```
c=a-b
c
```

```
array([20, 29, 38, 47])
```

```
b**2
```

```
array([0, 1, 4, 9])
```

```
10*np.sin(a)
```

```
array([ 9.12945251, -9.88031624,  7.4511316 , -2.62374854])
```

```
a<30
```

```
array([ True, False, False, False])
```

The product operator `*` operates elementwise in NumPy arrays

```
a2=np.array([[1,2,3],[4,5,6]])
```

```
a3=np.array([[7,8,9],[10,11,12]])
```

```
a2*a3
```

```
array([[ 7, 16, 27],  
       [40, 55, 72]])
```

The matrix product can be performed using the `@` operator (in python  $\geq 3.5$ ) or the dot function or method:

```
a4=np.array([[3,4],[2,2]])
```

```
a5=np.array([[4,2],[9,4]])
```

```
a4@a5 #using @ operator
```

```
array([[48, 22],  
       [26, 12]])
```

```
a4.dot(a5) #using dot function
```

```
array([[48, 22],  
       [26, 12]])
```

```
a6=np.array([[1,2,3],[4,5,6]])
```

```
a7=np.array([[7,8],[9,10],[11,12]])
```

```
a6@a7 # matrix product of a 2*3 and 3*2 matrix
```

```
array([[ 58,  64],  
       [139, 154]])
```

```
a6.dot(a7) # also does matrix product
```

```
array([[ 58,  64],  
       [139, 154]])
```

