

# Module 02:

# Variables and Conditional Statements

Topics:

- More on Variables
- Conditional Statements
- Recursion in Python

Readings: ThinkP 5,6

# Python allows us to change the values of variables

The following Python assignments are valid:

```
x = "a"
```

```
x = 100
```

```
x = 2*x - 1
```

# Can changing one variable affect another variable?

Consider running this program:

```
x = 1000
```

```
y = x
```

```
x = "a"
```

What are the values of **x** and **y** now?

# What does this mean for our programs?

- Values of variables may change throughout a program
- Order of execution is very important
- We can write programs that keep track of changing information, for example:
  - current location in a gps program
  - player information in games
- We may not need a new variable for each intermediate calculation in a function

# Local vs Global variables

- Variables defined inside a function are called ***local*** variables
  - Local variables only can be updated inside the function they are defined in
- Variables defined outside a function are called ***global*** variables
  - Global variables cannot be updated inside any functions in CS116.

# Global constants

- We'll use the term *global constant* when a global variable's value is not changed after the initial assignment.
- You may use the value of any global constant inside any function you write, as you did in your Racket programs.

```
tax_rate = 0.13  
def total_owed(amount):  
    return amount * (1+tax_rate)
```

# Errors with global variables

- Consider the following program:

```
grade = 87
```

```
def increase_grade(inc):
```

```
    grade = grade + inc
```

```
>>> increase_grade(5)
```

- This causes an error. Why?
- Do not use *global variables* in CS116.

# Changing values of parameters?

Consider the program:

```
def add1(n):
```

```
    n = n + 1
```

```
    return n
```

```
starter = 0
```

```
>>> y = add1(starter)
```

- The value of **n** is changed locally, but the value of **starter** is not changed. The change to **n** is a *local* change only.
- Even if **starter** was called **n**, the same behaviour would be observed.
- Note: Things are more complicated with lists. (*Later...*)



# Making decisions in Python

As in Racket, in Python we

- Have a Boolean type (Bool)
- Can compare two values
- Can combine comparisons using **and**, **or**, **not**
- Have a conditional statement for choosing different actions depending on values of data

# Comparisons in Python

- Built-in type **Bool**:
  - **True, False**
- Equality testing: **==**
  - Use for all atomic values (except for floats)
- Inequality testing: **<, <=, >, >=**
- **!=** is shorthand for not equal

# Combining Boolean expressions

- Very similar to Scheme
  - **v1 and v2**  
**True** only if both **v1, v2** are **True**
  - **v1 or v2**  
**False** only if both **v1, v2** are **False**
  - **not v**  
**True** if **v** is **False**, otherwise **False**
- What's the value of  
**(2<=4) and ((4>5) or (5<4) or not(3==2))**

# Evaluating Boolean expressions

- Like Scheme, Python uses Short-Circuit evaluation
  - Evaluate from left to right, using precedence  
**not**, **and**, **or**
  - Stop evaluating as soon as answer is known
    - **or**: stop when one argument evaluates to **True**
    - **and**: stop when one argument evaluates to **False**
- **1 < 0 and (1/0) > 1**
- **1 > 0 or kjlkjjaq**
- **True or &32-\_-!**

# Basic Conditional Statement

```
if test:
    true_action_1
    ...
    true_action_K
```

```
def double_positive(x):
    result = x
    if x > 0:
        result = 2*x
    return result
```

# Another Conditional Statement

```
if test:
    true_action_1
    ...
    true_action_Kt
else:
    false_action_1
    ...
    false_action_Kf
```

```
def ticket_cost(age):
    if age < 18:
        cost = 5.50
    else:
        cost = 9.25
    return cost
```

# “Chained” Conditional Statement

```
if test1:
    action1_block
elif test2:
    action2_block
elif test3:
    action3_block
...
else:
    else_action_block
```

```
def ticket_cost(age):
    if age < 3:
        cost = 0.0
    elif age < 18:
        cost = 5.50
    elif age < 65:
        cost = 9.25
    else:
        cost = 8.00
    return cost
```

# Conditional statements can be nested

```
def categorize_x(x):  
    if x < 10:  
        if x > 5:  
            return "small"  
        else:  
            return "very small"  
    else:  
        return "big"
```



# Python so far


- Our Python coverage is now comparable to the material from the first half of CS115 (without structures and lists)
- Much more to come, but we can now write recursive functions on numbers

# “Countdown” Template in Python

```
def countdown_fn(n):  
    if n==0:  
        return base_answer  
    else:  
        answer = ... n ... countdown_fn(n-1)  
        return answer
```

# Revisiting `factorial`

```
## factorial(n) returns the product
##   of all the integers from 1 to n
## factorial: Nat -> Nat
## example:
## factorial(5) => 120
## factorial(0) => 1
def factorial (n):
    if n == 0:
        return 1
    else:
        return n * factorial(n - 1)
```



Important to include **return** statement in both base and recursive cases!

# Some limitations to recursion

`factorial(1500) →`

`RuntimeError: maximum recursion  
depth exceeded`

- There is a limit to how much recursion Python “can remember”
- Recursion isn’t as common in Python as in Scheme
- Still fine for small problem sizes
- We’ll see a new approach for bigger problems.

# Examples

Use recursion to write Python functions:

- **sum\_powers** that consumes a positive Natural number (b) and a Natural number (n) and returns the sum

$$1 + b + b^2 + b^3 + \dots + b^{n-1} + b^n.$$

- **is\_prime** that consumes a Natural number (n) and returns True if n is prime (its only positive divisors are 1 and n), and False otherwise.

# Background: Alternate representations of boolean values

- In Python,
  - **False** and 0 are equal
  - **True** and 1 are equal
  - Any nonzero number is treated as a **True** expression in an **if** statement
- For clarity, we will continue to use **True** and **False** exclusively for our Bool values (you should follow this practice on assignments)

# We are now Python programmers

- Our functions can do more ...
  - May include
    - assignment statements
    - conditional statements
    - function calls (including recursive calls)
    - **return** statements
  - Changing variables is common
  - Order of statements critical

# Goals of Module 2

- Become comfortable in Python
  - Changing values of variables
  - Local vs global variables/constants
  - Different formats of conditional statements
  - Recursive functions



# Extra Clicker questions

CQ7: What is the value of  $0.1 + 0.2 == 0.3$ ?

- A) True
- B) False
- C) Machine dependent
- D) Error

# CQ8: what is the final value of Y?

```
def f(X,Y):
```

```
    t = X
```

```
    X = Y
```

```
    Y = t
```

A. 9

B. None

C. 1

D. ERROR

```
X = 1
```

```
Y = 9
```

```
Y = f(X,Y)
```

# CQ9: what is the final value of X?

$X = 5$

if  $X > 0$ :

$X = -X$

$Y = -1$

if  $X > 2$ :

$X = X + 1$

$Y = 5$

A. 6

B. -4

C. -5

D. None

# CQ10: what is the final value of Y?

$X = 5$

if  $X > 0$ :

$X = -X$

$Y = -1$

if  $X > 2$ :

$X = -X$

$Y = 5$

A. None

B. 5

C. -1

D. 4

Which function returns  $1*2*.....*n$   
Assuming  $n \geq 1$

```
def f1(n):
```

```
    if n==1: 1
```

```
    else: n*f1(n-1)
```

```
def f2(n):
```

```
    if n==1: return 1
```

```
    else: return n*f2(n-1)
```

```
def f3(n):
```

```
    if n>1: return n*f3(n-1)
```

```
    return 1
```

```
def f4(n):
```

```
    if n==1: return 1
```

```
    return n*f4(n-1)
```