

Catchment Survey — Annual Report

1.1 Section heading 1

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

1.2 Section heading 2

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

1.3 Section heading 3

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

1.4 Section heading 4

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

Methodology and Instrumentation

2.1 Section heading 1

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

2.2 Section heading 2

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

2.3 Section heading 3

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

2.4 Section heading 4

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

Results by Sub-Basin

3.1 Section heading 1

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

3.2 Section heading 2

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

3.3 Section heading 3

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

3.4 Section heading 4

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

Discussion of Anomalies

4.1 Section heading 1

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

4.2 Section heading 2

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

4.3 Section heading 3

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

4.4 Section heading 4

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

Appendix A — Station Log

5.1 Section heading 1

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

5.2 Section heading 2

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.

5.3 Section heading 3

Annual precipitation across the surveyed basins varied by less than four percent year on year, which is consistent with the long-term record. The three monitoring stations installed in the upper catchment reported no instrument faults during the period, and the resulting dataset is complete apart from a two-day gap in March.

5.4 Section heading 4

Sediment yield was measured at each gauging point using the standard depth-integrated sampler. Values are reported in tonnes per square kilometre per year. Where a reading fell outside two standard deviations of the station mean it was flagged for review rather than discarded, and the review outcome is recorded in the appendix.