

DIMY COVID Contact Tracing System Report

Group number: 03

Member name & Zid: Jiawei Gao (z5242283), Siying Chen(z5277235), Yuntao Zhou(z5223985)

Overview

This is the front-end implementation of the DIMY COVID contact tracing system. The back-end is provided and hosted on AWS, and the URL is included in the `default_conf.json` after running the program. The implementation is purely written in Python 3 and has been tested in both Linux, macOS, and Windows environments with the python version ≥ 3.7 . To start the program with default parameters and configuration, please go into the root source tree directory which contains `Dimy.py` and run `[python|python3] ./Dimy.py`. To make modifications to the configurations please refer to `README.md`.

Implementation Features

Task Managers

- According to the protocol, we have several tasks that need to be scheduled periodically, such as the EphID generating and secret sharing task, DBF management, etc. Those tasks are implemented as background threads which will be triggered when the timer fires. In general, for each task we have a specific manager to manage it.
 - ID manager is responsible for generating the EphID using ECC every one minute and then uses the Shamir algorithm to generate 6 parts for the secret and broadcast them every 10 seconds.
 - Bloom Filter Manager is responsible for managing the DBF pool which has one DBF initially and continuously add a new DBF into the pool until the pool contains 6 DBFs. Besides, it will also update the DBFs pool by deleting or adding DBF and combine the pool into a QBF or CBF.
 - Background Task Manager is responsible for scheduling the background tasks that we listed above. Basically, it manages all the daemon threads and register a specific timer for each of them and then launch each thread.

Communication methods: Broadcasting and Receiving

- The implementation of broadcasting and receiving uses POSIX sockets. For each client application, one socket is used for broadcasting and the other one is used for receiving the broadcasting messages from other clients.
- The receiving method is implemented as a blocking daemon thread which checks the receiving buffer periodically. And the broadcasting method runs on another daemon thread, which broadcasts secret shares every 10 seconds.

Message Format

- The broadcasting message has its specific format as follow:

Length	3 Bytes	1 Byte	16 Bytes	4 Bytes
Field	Hash Tag	Section ID	Secret Part Payload	Sequence Number

- The Hash Tag is the first 3 bytes of the hash of the EphID calculated via sha256.
- Section ID indicates the order of the receiving parts, but the Shamir Algorithm doesn't require the ordering of the secret parts, so this field is just for counting purposes.
- Secret Part Payload is the secret part of the EphID generated using Shamir Algorithm.
- The Sequence Number field is our solution to the issue of the overlapping timing window. For example, let's define the initial time point as `t0`, client 1 sends the message at `t0 + 30` seconds, and then client 2 starts to send its shared secret at `t0 + 30` seconds as well. Then at time point `t0 + 60` seconds, Ideally, two clients should generate Encounter ID, but since the privacy which used to generate the EphID of the client1 has already been changed, we can't reconstruct the same Encounter ID. To fix this problem, we save the previous privacy as well as the current privacy, and use the sequence number to determine which privacy should use, the old one or the new one. To make it simple, we set the length of this field as 4 bytes, which is 32 bits long, which should be sufficient to run the program for a year.

Logging

The logging subsystem has two output streams. One is the `stdout` and the other one is the `log.txt` configured by the `ALL_LOG_FILE` entry. The `stdout` is used for demonstration and the log file is used for diagnosing or inspecting the procedure.

Configuration

The default configuration file is auto-generated into the location where the `Dimy.py` is at, also this must be the root source file tree. The user of this program can modify the default configuration file and feed it to the program to meet their requirements. For example, the testing can be time consuming as the timing parameters are relatively large. To achieve easy debugging purpose, we can manually configure the program's parameter's to simulate the behaviour but with a much shorter time interval.

Modules

The entire front-end system contains:

- `bfmng`: A storage component
 - `bfmgr.py` implements the management methods of the DBF pool. Includes updating the DBF pool and combining 6 DBFs into a QBF/CBF by using the union method provided by the BloomFilter class.
 - `bloomfilter.py` implements the basic data structure of the BloomFilter class. The underlying implementation is using an array of unsigned char types and some basic algorithms for manipulating the data structure such as union or insert. By default, it uses `murmurhash3` as the hash function.
- `bgwork`: A background task scheduler
 - `bgmgr.py` implements the background task scheduling method by maintaining a job queue, each of its entries contains a daemon thread.

- `exception.py` implements the custom run-time error.
- `job.py` implements the generic background task class.
- `common`: A communication module
 - `udpmgr.py` implements the client-to-client EphID broadcasting and receiving methods using two dedicated sockets for multiplexing the message. This is just a wrapper of the python socket module.
 - `tcpmgr.py` implements the helper function for uploading the CBF to the server and querying the server with QBF.
 - `msg.py` implements the broadcasting message format class.
- `config`: A configuration helper module
 - `configure.py` implements the default configuration and configuration parser.
- `idmng`: A client `EphID`, `EncntID` management component
 - `idmgr.py` implements the EphID generating methods, Encounter ID generation methods and secret sharing methods, etc. This module is implemented on top of the `sslcrypto` module. The EphID is generated using ECDH algorithm.
 - `shamir.py` is the implementation borrowed from [Shamir Secret Sharing](#) with some small modifications.
- `sslcrypto_client`: A module ported from `sslcrypto` which implements the `ECDH` algorithm
 - A module borrowed from online implements the `ECDH` algorithm.
- `test`: A module contains several unit tests for the various modules
 - Several unit tests against those custom implementations introduced above.
- `utils`: A module contains several helper functions
 - `helper.py` implements some helper functions for handling and converting data type.
- `tasks.py`: A file contains all the background tasks wrappers
 - All the background/non-background task wrapper functions go here.
- `Dimy.py`: The entrance of the whole front-end system
 - The main entry of the program implements several bootstrap functions and the user command parser.

Trade-offs

- Since we have several threads running in the background, preventing them from facing raise conditions is not quite easy. Also to achieve the synchronization, we used the `lock` and `conditional variable` which can potentially introduce performance overhead.
- Since client applications are broadcasting messages, which means they will receive the message that is sent from themselves as well. To avoid reconstructing their own EphID, we store the hash tag that clients have sent as a hash table. So the EphID will only be reconstructed if they are not in that local cache. However, this requires extra memory usage.

Diary

Contribution

Individual Part

- Jiawei is in charge of the following things **(1/3)**:
 - Implementing the communication library between clients and servers using TCP protocol and Implementing the message protocol.
 - Implement a BF management library that can be used for managing DBF, CBF, and QBF.
 - implement the background timer module for firing the alarm periodically.
- Siying is in charge of the following things **(1/3)**:
 - implement the privacy generating library which handles the ephemeral ID generation.
 - Implement the Diffie-Hellman library.
 - implement the argument parser.
- Yuntao is in charge of the following things **(1/3)**:
 - Implement the "k out of n" sharing protocol.
 - Implement the message passing library based on UDP protocol.
 - implement the configuration parser module of this project.

Common Part

- Diary, Report, Video and code testing

Progress

Week	Completion	Issue
5	Create Github repository, decide the main developing language and assign the presentation workload.	Questions about the DIMY protocol details, the format of diary and presentation and the wheels we can use.
6	Prepare presentation slides, record the video clips and assign tasks of implementation.	Questions about Video editing tool and Buckets to store videos.
7	Implement Background Timer Module and rapid prototype the framework.	Null.
8	Implement the helper modules and refine the framework.	Search for the appropriate libraries.
9	Implement ID management + BloomFilter management module	Multi-threading programming designs.
10	Merge and refine the code + report	Null.

