

Help keep this project alive

- [\\$5](#)
- [\\$10](#)
- [\\$20](#)
- [\\$50](#)
- [Donate](#)

Close

[Home](#) [Docs](#) [On Github](#)



Documentation

Learn to use the plugin

[Download Now](#)

1. Documentation
2. [Basic usage](#)
3. [Callback examples](#)
4. [On-the-fly_mask change](#)
5. [Mask as a function](#)
6. [Using HTML notation examples](#)
7. [Translation](#)
8. [Removing the mask](#)
9. [Getting the unmasked typed value](#)
10. [Getting a masked value programmatically](#)
11. Customization
12. [Field options](#)
13. [Public methods](#)
14. [Global options](#)

Documentation

Basic Usage

```
$(document).ready(function(){
  $('date').mask('00/00/0000');
  $('time').mask('00:00:00');
  $('date_time').mask('00/00/0000 00:00:00');
  $('cep').mask('00000-000');
  $('phone').mask('0000-0000');
  $('phone_with_ddd').mask('(00) 0000-0000');
  $('phone_us').mask('(000) 000-0000');
  $('mixed').mask('AAA 000-S0S');
  $('cpf').mask('000.000.000-00', {reverse: true});
  $('cnpj').mask('00.000.000/0000-00', {reverse: true});
  $('money').mask('000.000.000.000.000,00', {reverse: true});
  $('money2').mask("#.##0,00", {reverse: true});
  $('ip_address').mask('0ZZ.0ZZ.0ZZ.0ZZ', {
    translation: {
      'Z': {
        pattern: /[0-9]/, optional: true
      }
    }
  })
})
```

```

    }
  });
  $('ip_address').mask('099.099.099.099');
  $('percent').mask('##0,00%', {reverse: true});
  $('clear-if-not-match').mask("00/00/0000", {clearIfNotMatch: true});
  $('placeholder').mask("00/00/0000", {placeholder: "__/__/____"});
  $('fallback').mask("00r00r0000", {
    translation: {
      'r': {
        pattern: /[\\/] /,
        fallback: '/'
      },
      placeholder: "__/__/____"
    }
  });
  $('selectonfocus').mask("00/00/0000", {selectOnFocus: true});
});

```

Callback examples

```

var options = {
  onComplete: function(cep) {
    alert('CEP Completed!' + cep);
  },
  onKeyPress: function(cep, event, currentField, options){
    console.log('A key was pressed!:', cep, ' event: ', event,
      'currentField: ', currentField, ' options: ', options);
  },
  onChange: function(cep){
    console.log('cep changed! ', cep);
  },
  onInvalid: function(val, e, f, invalid, options){
    var error = invalid[0];
    console.log ("Digit: ", error.v, " is invalid for the position: ", error.p, ". We expect: ", error.e);
  }
};

$('cep_with_callback').mask('00000-000', options);

```

On-the-fly mask change

```

var options = {
  onKeyPress: function(cep, e, field, options) {
    var masks = ['00000-000', '0-00-00-00'];
    var mask = (cep.length>7) ? masks[1] : masks[0];
    $('crazy_cep').mask(mask, options);
  }
};

$('crazy_cep').mask('00000-000', options);

```

Mask as a function

```

var SPMaskBehavior = function (val) {
  return val.replace(/\D/g, '').length === 11 ? '(00) 00000-0000' : '(00) 0000-00009';
},
spOptions = {
  onKeyPress: function(val, e, field, options) {
    field.mask(SPMaskBehavior.apply({}, arguments), options);
  }
};

$('sp_celphones').mask(SPMaskBehavior, spOptions);

```

Using HTML notation examples

To get your mask applied with the data-mask attribute just use it as the same way you use with the \$.mask function.

```
<input type="text" name="field-name" data-mask="00/00/0000" />
```

Activating a reversible mask

```
<input type="text" name="field-name" data-mask="00/00/0000" data-mask-reverse="true" />
```

Using clearIfNotMatch option

```
<input type="text" name="field-name" data-mask="00/00/0000" data-mask-clearifnotmatch="true" />
```

Using selectOnFocus option

```
<input type="text" name="field-name" data-mask="00/00/0000" data-mask-selectonfocus="true" />
```

Translation

Teach to jQuery Mask Plugin how to apply your mask:

```
// now the digit 0 on your mask pattern will be interpreted
// as valid characters like 0,1,2,3,4,5,6,7,8,9 and *
$('.your-field').mask('00/00/0000', {'translation': {0: {pattern: /[0-9*]/}}});
```

By default, jQuery Mask Plugin only recognizes the logical digit A (Numbers and Letters) and S (A-Za-z) but you can extend or modify this behaviour by telling to jQuery Mask Plugin how to interpret those logical digits.

```
$('.your-field').mask('AA/SS/YYYY', {'translation': {
  A: {pattern: /[A-Za-z0-9]/},
  S: {pattern: /[A-Za-z]/},
  Y: {pattern: /[0-9]/}
}});
```

Now jQuery Mask Plugin knows the logic digit Y and you can create your own pattern.

Optional digits

You can also tell to jQuery Mask which digit is optional, to create a IP mask for example:

```
// way 1
$('.ip_address').mask('099.099.099.099');
// way 2
$('.ip_address').mask('0ZZ.0ZZ.0ZZ.0ZZ', {translation: {'Z': {pattern: /[0-9]/, optional: true}}});
```

Now, all Z digits in your masks is optional.

Recursive digits

With jQuery Mask Plugin you can also define recursive patterns inside your mask:

```
$('.money_example').mask('#.##0,00', {reverse: true});
```

With example above the mask will be placed from the right to the left (that's why `reverse:true` is defined). As soon as you start typing, a "0,00" will be applied followed by repeating recursively the following pattern "#.##". The result could be something like: 1.234.567,890.

You can also use that kind of feature to define what kind of data could be typed inside of a field:

```
$( '.example' ).mask( '0#' );
```

Now only numbers will be allowed inside your form field.

Fallback digits

When a user types a invalid char for the current position the plugin will replace it by its fallback instead of erasing them.

```
$( '.money_example' ).mask( '#.##0,00', { reverse: true } );
```

Removing the mask

```
$( '.date' ).unmask();
```

Getting the unmasked typed value

```
$( '.date' ).cleanVal();
```

Getting a masked value programmatically

```
$( '.date' ).masked( '19840807' );
```

Customization

Field options

```
var custom_options = {
  byPassKeys: [8, 9, 37, 38, 39, 40],
  translation: {
    '0': {pattern: /\d/},
    '9': {pattern: /\d/, optional: true},
    '#': {pattern: /\d/, recursive: true},
    'A': {pattern: /[a-zA-Z0-9]/},
    'S': {pattern: /[a-zA-Z]/}
  }
};
```

byPassKeys list of keyboard's keyCode that you want to be ignored when it was pressed.

translation object with all digits that should be interpreted as a special chars and its regex representation.

Public methods

```
/**
Applies the mask to the matching selector elements.

@selector elements to be masked.
```

```

@mask should be a string or a function.
@options should be an object.
**/
$(selector).mask(mask [, options]);

/**
Seek and destroy.

@selector elements to be masked.
**/
$(selector).unmask();

/**
Gets the value of the field without the mask.

@selector elements to be masked.
**/
$(selector).cleanVal();

/**
Applies the mask to the matching selector elements.

@selector optional: elements to be masked. The default behaviour it's to lookup for all el
**/
$.applyDataMask([selector]);

```

Global options

```

/**
nonInput: elements we consider nonInput
dataMask: we mask data-mask elements by default
watchInputs: watch for dynamically added inputs by default
watchDataMask: by default we disabled the watcher for dynamically
added data-mask elements by default (performance reasons)
**/

$.jMaskGlobals = {
  maskElements: 'input,td,span,div',
  dataMaskAttr: '*[data-mask]',
  dataMask: true,
  watchInterval: 300,
  watchInputs: true,
  watchDataMask: false,
  byPassKeys: [9, 16, 17, 18, 36, 37, 38, 39, 40, 91],
  translation: {
    '0': {pattern: /\d/},
    '9': {pattern: /\d/, optional: true},
    '#': {pattern: /\d/, recursive: true},
    'A': {pattern: /[a-zA-Z0-9]/},
    'S': {pattern: /[a-zA-Z]/}
  }
};

```



Created by Igor Escobar

1. [Twitter](#)
2. [Github](#)
3. [igorescobar.com](#)