Matched WEIRD and Serbian Debates Show No Detectable WEIRD Advantage in LLM Perspective Coverage

Anonymous TACL submission

Abstract

Large language models can describe political controversies accurately while omitting relevant perspectives. We test whether they recover fewer documented perspectives on Serbian controversies than on structurally matched topics from Western, Educated, Industrialised, Rich, and Democratic (WEIRD) settings. The benchmark pairs eight Serbian controversies with WEIRD counterparts; each of the 16 topics has five reference perspectives documented in surveys, polling, referendum results, research, or public debate. Thirteen LLMs each generated five perspectives per topic in English, and five LLM judges from other developers matched each output to a reference or returned no match. Mean recall was 0.581 on WEIRD topics and 0.594 on Serbian topics. The mean WEIRD-minus-Serbian difference across the eight pairs was -1.3 percentage points (95% t-based CI: -10.3 to 7.7), and an exact one-sided Wilcoxon signed-rank test found no evidence for the hypothesised WEIRD advantage ($p = 0.680$). Differences between individual pairs (-16.9 to $+19.1$ points) were much larger than the pooled difference. Inter-judge agreement was similar across the two settings (pooled Fleiss' $\kappa = 0.77$), but agreement does not establish accuracy. Coverage was incomplete in both settings, and the result does not establish equivalent coverage.

1 Introduction

An LLM answering a controversial political question selects both facts and perspectives. An answer about Kosovo's independence, immigration, or historical responsibility may be factually accurate yet omit positions held by people involved in the debate. As language models mediate access to political information, we therefore need to evaluate which perspectives their answers recover.

Coverage may depend on how frequently positions appear in training data, how readily models retrieve them, and whether post-training or safety procedures discourage their expression. These pressures may affect populations unevenly. The concentration of language-model development in Western, Educated, Industrialised, Rich, and Democratic (WEIRD) (Henrich et al., 2010) and English-language settings motivates concern about cultural representation (Sorensen et al., 2024; Feng et al., 2024; Wang et al., 2025; Zewail et al., 2026). We therefore hypothesise that models recover perspectives more completely on WEIRD controversies than on Serbian controversies.

Testing this expectation requires attention to topic selection. Political controversies differ in documentation, history, sensitivity, and structure. A comparison of unrelated WEIRD and Serbian topics could attribute differences in topic difficulty to cultural setting. We reduce this ambiguity by comparing structurally analogous controversies.

The benchmark contains 16 topics arranged into eight WEIRD-Serbian pairs. Each topic has five reference perspectives documented in surveys, polling, referendum results, peer-reviewed research, or clearly attested public debate. These references provide a fixed evaluation target; they do not exhaust the legitimate positions on an issue. Thirteen LLMs each generate five perspectives per topic in English. Five LLM judges independently match each generated perspective to one of the references or return no match. No judge evaluates a generator from its own model family. Recall then measures how much of the reference set the outputs recover.

We address three research questions:

RQ1 (primary). *Do LLMs recover fewer documented perspectives on Serbian sociopolitical topics than on structurally matched WEIRD topics?* We hypothesise higher recall on WEIRD topics.

RQ2 (secondary). *How does recall vary across individual models and across Frontier, larger open-weight, and smaller open-weight systems?*

RQ3 (exploratory). *How do the selected models from US and Chinese developers differ in overall recall and in their WEIRD-Serbian recall gaps?*

Recall is the principal outcome because all three questions concern recovery of documented perspectives. Precision and F1 provide supplementary descriptions of matching behaviour. The category and developer-country comparisons are exploratory; the model categories describe access and relative size, not a capability ranking.

We do not detect the predicted WEIRD advantage. Mean recall is 0.581 for WEIRD topics and 0.594 for Serbian topics, with four matched pairs favouring each side. Five of the 13 models had higher mean recall on WEIRD topics, but no model-level difference reached $p < 0.05$ even before Benjamini–Hochberg adjustment. Coverage nevertheless remains incomplete: even the highest-recall model misses roughly three of every ten reference perspectives on average.

The paper makes two contributions:

- **A matched evaluation set:** eight structurally analogous WEIRD–Serbian topic pairs, each topic with five reference perspectives documented in evidence about the relevant population, scored by LLM judges from other developers.
- **A matched comparison of perspective coverage:** we find no detectable WEIRD advantage; differences between individual topic pairs are much larger than the pooled difference, and models miss reference perspectives in both settings.

These findings motivate a more specific question for subsequent evaluation: which perspectives do models omit on which controversies?

2 Related work

Our study connects research on cultural representation, perspective coverage, and LLM-based evaluation.

2.1 Pluralistic alignment and cultural representation

Pluralistic alignment treats differences in human values and viewpoints as something to preserve, rather than collapse into a single preference target (Sorensen et al., 2024; Feng et al., 2024; Ali et al., 2025). This matters for political questions, where a useful answer may need to represent conflicting positions.

Sorensen et al. (2024) distinguish three forms of pluralism. Overton pluralism concerns the range of positions a model represents. Steerable pluralism concerns its ability to adopt a requested position. Distributional pluralism concerns whether output frequencies reflect a target population. Our benchmark measures Overton-style coverage: whether documented perspectives are recovered at all.

The concentration of training, preference, and evaluation data in WEIRD and English-language settings raises concerns about uneven cultural representation (Sorensen et al., 2024; Wang et al., 2025; Zewail et al., 2026). Multilingual and culturally adaptive prompting can improve diversity in some settings (Wang et al., 2025). Language-specific evaluation resources also remain unevenly developed. Serbian SuperGLUE addresses gaps in complex language-understanding evaluation for Serbian and motivates broader coverage of South Slavic languages (Perovic and Mihajlov, 2026). This work motivates our directional hypothesis, but does not determine whether a particular coverage difference reflects cultural setting or the topics chosen for comparison.

2.2 Measuring perspective coverage

Political controversies rarely have a complete, uncontested set of correct labels. Perspectivist NLP therefore treats disagreement as part of the phenomenon being studied (Basile et al., 2021; Plank, 2022; Frenda et al., 2025). Related approaches retain annotator-specific rationales or label distributions rather than combining all judgments into one target (Sarumi et al., 2026; Shetty et al., 2026). A fixed reference set can document positions known to exist, but cannot guarantee an exhaustive account of a debate.

Other work uses LLMs as proxies for human opinion. Under some prompting strategies, models can reproduce population-level polling patterns (Sun et al., 2024; Gong et al., 2026). Their ap-

parent political or cultural preferences can also change with prompt design and methodology (Khan et al., 2025). Hybrid approaches combine model-generated annotations with human attention to uncertain cases (Mehrotra et al., 2026). Our evaluation instead uses externally documented reference perspectives, keeping the scoring target separate from the models being evaluated.

The closest benchmark is OvertonBench, which evaluates perspective coverage using viewpoint groups derived from human responses and ratings of how well model outputs represent participants' views (Poole-Dayan et al., 2025). Our study instead measures recovery of fixed, externally documented reference perspectives in structurally matched WEIRD and Serbian controversies. The contribution is this matched comparison across settings; differences in reference construction and scoring preclude direct comparison of absolute scores between the two benchmarks.

2.3 Evaluating generated perspectives

Evaluating coverage requires deciding whether differently worded statements express the same stance. LLM judges can assess this relationship, but their agreement with human assessments can vary across the models being evaluated (Poole-Dayan et al., 2025).

We use five judges, present each generated perspective separately, randomise reference order, and exclude judges from the generator's model family. We also report inter-judge agreement and compare it across WEIRD and Serbian topics. These checks assess consistency of the matching procedure. They cannot establish correctness, because several judges may share an error, and they do not replace human validation.

3 Methodology

The benchmark fixes the topics and reference perspectives before model outputs are evaluated. It contains eight matched WEIRD-Serbian topic pairs, with five reference perspectives for each of the 16 topics. The evaluation then asks how much of each reference set a model recovers when prompted for five perspectives.

3.1 Selecting and matching topics

We began with Serbian sociopolitical controversies. Selection was informed by the first author's domain knowledge of Serbian history and politics. We sought notable controversies with multiple substantively distinct positions that could be documented using external sources.

For each Serbian topic, we identified a WEIRD counterpart with a comparable political structure. For example, the Kosovo and Catalan independence debates concern secession, territorial sovereignty, and self-determination. The Vučić and Orbán debates concern political leadership and authoritarian or illiberal governance. Matching concerned the structure of the controversy, rather than historical equivalence or similarity between the societies themselves.

The procedure was investigator-guided rather than algorithmic. A counterpart also needed enough external material to document distinct perspectives using the same construction procedure. Table 1 lists the resulting pairs and their matching rationales. Comparator selection was guided by broad Western, educational, industrial and economic characteristics, rather than a quantified country-classification rule. WEIRD therefore labels the selected comparator populations in Table 1; it is not a validated binary country classification or representative sampling of a cultural category. Poland was included as a borderline case under this investigator judgment. Matching reduces ambiguity due to topic selection without experimentally isolating cultural setting.

3.2 Constructing the reference sets

A reference perspective is a substantively distinct stance documented as being held within the target population. The first author constructed all 80 reference perspectives manually from research literature and news reporting, drawing on surveys, polling, referendum results, peer-reviewed research, and clearly attested public debate. The reference statements summarise positions supported by these sources, rather than positions generated by the models evaluated here. The first author selected five distinct stances per topic from the linked research and reporting. The source workbook records a source entry for each of the 80 reference perspectives. The accompanying source ledger links the evaluated reference identifiers to their workbook cells and preserves both the source text and any embedded hyperlink. All reference summaries and explanations in the workbook match the evaluated reference set exactly. Source entries identify the evidence used in con-

Table 1: The eight matched topic pairs. Parentheses in the WEIRD column identify the country used in the reference-population prompt. All Serbian topics use the population "people in Serbia"; WEIRD topics use "people in" the indicated country. Pairing concerns the political dispute, not historical equivalence.

Pair	WEIRD topic	Serbian topic	Matching rationale
1	Confederate monuments (United States)	Partisans and Chetniks	Public memory of opposing sides in a civil war
2	Catalan independence (Spain)	Kosovo independence	Secession and territorial sovereignty
3	Fracking / shale gas (United Kingdom)	Jadar lithium mine / Rio Tinto	Economic benefits and environmental risks
4	Catholic Church (Poland)	Serbian Orthodox Church	Secularisation and the role of the church
5	Residential schools (Canada)	Srebrenica	Public debate concerning genocide
6	Immigration after 2015 (Germany)	Migrants and the Balkan route	Migration policy
7	Viktor Orbán (Hungary)	Aleksandar Vučić	Democratic leadership and authoritarian governance
8	Brexit / EU membership (United Kingdom)	Serbia's West-Russia alignment	Foreign-policy alignment

struction; they do not imply that every clause of an advocate-style explanation is a quotation or a measured population belief.

Reference summaries and explanations were written in English. Sources cited for Serbian topics include English-language research, reporting, and survey materials; the language of the cited material was therefore not uniformly Serbian.

Each topic has five references so that all topics share the same evaluation budget. This is a design choice, not a claim that a controversy has exactly five legitimate positions. The score measures recovery of these references; it does not measure every position that might exist outside them. Each stored perspective consists of a short summary and a longer explanation. Judges receive both.

Table 2 shows an actual reference set. It illustrates why identifying a broad side of a controversy is insufficient: support for fracking may be unconditional, conditional, or opposed to local development; opposition may emphasise different grounds.

Table 2: Reference summaries for UK fracking, reproduced from the benchmark. The target population is "people in the United Kingdom". Each record also contains an explanation.

ID	Reference summary
1	Restart UK fracking for energy security and jobs.
2	Ban fracking permanently on environmental and seismic grounds.
3	Support fracking in principle but oppose it locally.
4	Reject fracking categorically on climate-emergency grounds.
5	Conditional pragmatist, support shale gas only with strict guarantees and a transition plan.

3.3 Evaluation procedure

The procedure separates generation, judging, and scoring. Generators receive a topic and its target population, but not the reference perspectives. Judges then compare each generated perspective with the references. We calculate recall from their assignments and use the resulting model-topic scores for the model summaries and matched cultural comparison.

3.3.1 Models and perspective generation

We evaluate 13 models (Table 3) and retain one response for each model-topic combination. The prompt asks for five distinct perspectives spanning mainstream, minority, and controversial positions genuinely held within the specified population. Each perspective is written in an advocate's voice. The prompt allows fewer than five positions if appropriate; all 208 retained responses contain five, giving 1,040 generated perspectives, and no model declined the task. Appendix A reproduces the prompt.

All generator prompts, judge prompts, and reference statements are in English. This holds elicitation and judging language constant across the two settings, but it does not test Serbian-language prompting. Generators and judges were queried through the OpenRouter API with temperature zero, a fixed request seed, and a requested limit of 4,096 completion tokens. The seed takes effect only for providers that support seeded sampling. We set no reasoning parameters and did not pin providers, so each model used OpenRouter's default reasoning behaviour and provider routing; the serving provider was not recorded. A response that could not be parsed received one repair request, and calls that still failed were re-run later. Valid responses were saved immediately and never regenerated, so no valid response was discarded. Each model-topic cell therefore has a single sample, and the analysis does not capture variation across repeated generations. Generation records date from 9-10 July 2026; judging, including retries, spans 10-20 July 2026. Appendix H lists the configured model identifiers.

For the exploratory category comparison, we group the models into five Frontier/API systems, six larger open-weight systems, and two smaller open-weight systems. Frontier/API denotes systems without a verified public-weight release; Qwen 3.7 Max is included because Alibaba documents it as a commercial API model.[1] The smaller open-weight group consists of the two selected systems labelled 31B and 70B, Gemma 4 31B and Llama 3.3 70B; the other six open-weight systems form the larger group. These labels identify the groups used in this comparison rather than a general size taxonomy. The categories describe access and relative size, not capability. Weight availability describes the model release, not where a model was run: all 13 systems were queried through the same API workflow. Appendix H records category membership and release-source links.

Table 3: The 13 generators, grouped by the access and relative-size categories used throughout the analysis.

Model	Developer
Frontier/API (5)	
Claude Opus 4.8	Anthropic
GPT 5.5	OpenAI
Gemini 3.1 Pro	Google
Grok 4.3	xAI
Qwen 3.7 Max	Alibaba
Larger open-weight (6)	
DeepSeek V4 Pro	DeepSeek
Kimi K2.6	Moonshot
GLM 5.2	Z.AI
Llama 4 Maverick	Meta
Mistral Large 3	Mistral
GPT-OSS 120B	OpenAI
Smaller open-weight (2)	
Gemma 4 31B	Google
Llama 3.3 70B	Meta

3.3.2 Judge assignments

Each of five LLM judges receives one generated perspective at a time, together with the topic, target population, and five reference perspectives. The judge selects the reference expressing the same underlying side and stance, or returns no match. Thematic overlap alone is insufficient; an output voiced from outside the target population also receives no match. In practice, no judge flagged any output as voiced from outside the target population, so every no-match reflects a difference in stance. Judges do not see one another's decisions. Their assignments are collected before recall is calculated.

For example, all five judges matched a GPT 5.5 output supporting UK fracking for energy security, jobs, and reduced import dependence to reference 1 in Table 2. A different output opposed fracking because it distrusted companies and regulators. Claude Sonnet 5 matched it to reference 2, whereas the other four judges returned no match. This disagreement concerns correspondence to the reference set, not whether the output expresses a legitimate position. Appendix G shows the saved outputs and all assignments; judges evaluated both summaries and explanations.

We use *family-disjoint judging*: no judge shares the generator's configured developer family. Google includes Gemini and Gemma, OpenAI includes GPT and GPT-OSS, and Anthropic includes Claude Opus and Claude Sonnet. The five judges in each panel also come from different developer families.

The base panel contains Gemini 3.1 Pro, GPT 5.5, Claude Sonnet 5, DeepSeek V4 Pro, and Kimi K2.6. When a generator shares a family with one of these judges, we replace that judge with a designated substitute, keeping five seats. Grok 4.5 substitutes for Google, OpenAI, Anthropic, or Moon-

[1] See Alibaba Cloud's Qwen3.7-Max commercial-model announcement.

shot; Qwen 3.7 Max substitutes for DeepSeek. Appendix C.1 gives the mapping. This prevents direct same-family evaluation, but cannot exclude shared bias across families. Each generator is judged by the same panel on its WEIRD and Serbian topics, avoiding changes in panel membership between the two settings. This does not exclude topic-dependent or culturally differential judging errors. Differences between panels may also affect comparisons of overall recall between generators (Section 4.2).

Reference order is randomised independently for every judgment, and returned indices are mapped back to the original identifiers. The design requires 25 decisions per model-topic response, or 5,200 in total. After retries, 5,184 decisions are valid: 1,024 outputs have five judgments and 16 have four. Failed calls are missing data. A valid no-match decision remains in the calculation and earns zero credit (Appendix C.6).

3.3.3 From assignments to recall

Recall measures the proportion of the five reference perspectives recovered by a model's five outputs. It is the primary metric because the research questions concern omissions from a fixed reference set. A repeated match uses an output slot without recovering an additional reference.

Step 1: count distinct references for one judge. In the worked example (Tables 2 and 11), Claude Sonnet 5 assigns GPT 5.5's five outputs to references 2, 2, 1, 5, and 1. These assignments recover three distinct references, so this judge's recall is $R_j = 3/5 = 0.60$. All five outputs match a reference, but they cover only three: precision counts matching outputs, whereas recall counts distinct references recovered.

Step 2: combine the judges. Let m identify the model, t the topic, and j the judge. We write R_{mtj} for the recall calculated from judge j's assignments and R_{mt} for the recall after combining the judges. When all five judges provide valid decisions for all five outputs, we average their recall scores:

$$R_{mt} = \frac{1}{5}\sum_{j=1}^{5} R_{mtj}. \tag{1}$$

For this response, the five judges' recalls are 0.60, 0.60, 0.60, 0.60, and 0.40, giving $R_{mt} = 0.56$ (Appendix G). Judges need not agree on which references were recovered; there is no majority-vote threshold.

Missing judgments require an adjustment because the available panel can differ between outputs. The implementation splits duplicate matches within each judge, averages credits over valid judges for each output, and caps the total for each reference at one. The exact equations appear in Appendix C.3. They reduce to Eq. 1 for complete panels. Every output in this dataset has at least four valid judgments.

Step 3: summarise a model across topics. Each topic receives equal weight. Let $\overline{R}_m$ denote the model's overall recall, and let $\overline{R}^{\mathrm{W}}_m$ and $\overline{R}^{\mathrm{S}}_m$ denote its mean recall on WEIRD and Serbian topics, respectively. Overall model recall averages its 16 model-topic scores; WEIRD and Serbian recall each average eight:

$$\overline{R}_m = \frac{1}{16}\sum_{t=1}^{16} R_{mt} = \frac{\overline{R}^{\mathrm{W}}_m + \overline{R}^{\mathrm{S}}_m}{2}. \tag{2}$$

When describing a topic across models, we instead average its scores over the 13 generators. These topic means and model means answer different descriptive questions. Precision and F1 are supplementary metrics defined in Appendix C.4 and reported in Appendix E.2.

3.3.4 Comparisons and statistical analysis

RQ1: compare the eight matched pairs. For each generator $m \in \{1, \ldots, 13\}$ and pair $p \in \{1, \ldots, 8\}$, we subtract Serbian recall from WEIRD recall:

$$d_{mp} = R^{\mathrm{W}}_{mp} - R^{\mathrm{S}}_{mp}. \tag{3}$$

A positive value favours the WEIRD topic. We then average over generators within each pair,

$$\Delta_p = \frac{1}{13}\sum_{m=1}^{13} d_{mp}, \tag{4}$$

and apply an exact one-sided Wilcoxon signed-rank test to the eight Δ_p values. The alternative is a positive shift, corresponding to the hypothesised WEIRD advantage. We also report the two-sided test. The test assumes independent pair-level differences with a symmetric distribution under the null; it does not directly test the arithmetic mean.

The mean gap describes effect size. Its 95% percentile bootstrap interval uses 10,000 resamples of the eight pairs, keeping all 13 models together within each sampled pair. Because eight

resampling units can make percentile intervals too narrow, we also report a t-based interval with seven degrees of freedom and the corresponding one-sided upper bound. The 104 model-pair differences share generators and topic pairs and are not treated as independent observations. Appendix D gives the calculation details and supplementary analyses using model means, crossed resampling, and two explicitly distinguished mixed-effects specifications.

RQ2: describe models and compare categories. We report overall recall, a 95% interval based on 10,000 bootstrap resamples of the 16 topics, and separate WEIRD and Serbian means for each model. For exploratory category comparisons, models receive equal weight within each category and matched pairs are the comparison blocks. We test four contrasts: the three pairwise category comparisons and Frontier/API versus all eight open-weight models combined. Exact two-sided sign-flip tests enumerate all $2^8 = 256$ sign assignments; Holm correction accounts for the four contrasts. These tests hold the selected models fixed (Appendix D.4). Pairwise model tests and model-level intervals are also checked using matched-pair blocks, because the individual-topic procedures do not retain the pairing (Appendices D.6 and D.1).

RQ3: distinguish overall recall from the cultural gap. We compare eight models from US developers with four from Chinese developers. Mistral, from France, is excluded only from this contrast. We separately compare overall recall and the WEIRD-Serbian recall gap, using equal model weights within each group. Both outcomes use pair-bootstrap intervals and exact two-sided pair-blocked sign-flip tests, with Holm correction across the two tests (Appendix D.5). These exploratory comparisons describe the selected systems, not a causal effect of developer country.

Check the consistency of judging. We report Fleiss' κ, Gwet's AC1, Krippendorff's α, and judge-level no-match rates overall and by cultural group. Leave-one-judge-out analyses describe sensitivity to panel composition. These checks assess consistency and sensitivity, not correctness or freedom from shared bias.

4 Results

4.1 RQ1: Recall on matched WEIRD and Serbian topics

Mean recall is 0.581 for WEIRD topics and 0.594 for Serbian topics. Across the eight matched topic pairs, the mean WEIRD-minus-Serbian difference is -0.013, or -1.3 percentage points (95% t-interval: -10.3 to 7.7; pair bootstrap: -8.1 to 5.8). The one-sided 95% upper bound is 5.9 points. The median pair-level difference is -0.014.

The exact one-sided Wilcoxon signed-rank test provides no evidence for the hypothesised WEIRD advantage ($p = 0.680$). The two-sided test gives $p = 0.742$, with a matched-pairs rank-biserial correlation of -0.17. The point estimate favours Serbian topics slightly, but the interval includes differences in both directions. This result does not establish equivalent coverage across the two settings.

Four matched pairs favour WEIRD topics and four favour Serbian topics. The largest differences point in opposite directions: recall is 19.1 percentage points higher for German immigration than for its Serbian migration-route counterpart, but 16.9 points lower for Canadian residential schools than for Srebrenica. Mean topic recall ranges from 0.449 for the Serbian migration-route topic to 0.685 for Serbia's West-versus-Russia alignment. Both extremes occur among the Serbian topics, indicating that topic-level variation does not follow a uniform cultural direction.

Supplementary analyses using model means, crossed resampling, and crossed random effects lead to the same interpretation (Appendix D.3). The eight-pair comparison remains the primary analysis. Figure 1 shows the eight pair-level gaps. Appendix E.1 presents the model-level and individual model-pair views.

4.2 RQ2: Recall by model and access category

Table 4 reports perspective recall, with separate columns for WEIRD and Serbian topics. Overall recall ranges from 0.458 for Llama 3.3 70B to 0.698 for Gemini 3.1 Pro. Even the highest-recall model leaves approximately 30% of the reference coverage unrecovered on average. Of the 78 pairwise model comparisons, 15 remain significant after Benjamini–Hochberg adjustment when the 16 topics are treated as separate sign-flip units.




Figure 1: Primary cultural comparison. Each point is the WEIRD-minus-Serbian recall difference averaged over the 13 generators for one matched pair. Positive gaps favour WEIRD topics. The diamond is the mean across eight pairs, with the 95% pair-bootstrap interval. Pair-specific confidence intervals are not shown. The t-based interval for the mean is reported in Section 4.1.

None remains significant when the eight matched pairs are retained as blocks (minimum adjusted $p = 0.087$). The inferential result is therefore sensitive to the unit of analysis, although the mean differences are unchanged (Appendix E.3).

The mean recall of the selected models is 0.615 in the Frontier/API group, 0.578 in the larger open-weight group, and 0.548 in the smaller open-weight group. Combining the eight open-weight models gives mean recall 0.570, compared with 0.615 for the five API systems, an observed difference of 4.5 percentage points. The exact pair-blocked test gives $p = 0.086$ before correction and $p = 0.258$ after Holm correction across the four RQ2 contrasts. None of those four comparisons meets the 0.05 threshold after correction; the smallest adjusted value is $p = 0.063$ for the API versus smaller open-weight comparison. These exploratory results do not establish equivalence or isolate the effects of size, openness, or capability.

Individual models also vary substantially within categories. Gemma 4 31B has recall 0.638, close to the 0.645 reported for GPT 5.5 and DeepSeek V4 Pro, whereas Llama 3.3 70B has recall 0.458. A category mean therefore does not describe every model in that category. Overlapping individual confidence intervals should not be interpreted as evidence of equivalence. Judge panels also differ across developers (Section 3.3.2), and judges differ in strictness: Gemini 3.1 Pro matched 52.7% of the outputs it judged to a reference, compared with 65.0–76.6% for the other judges. Removing it raises individual model recall by up to 3.6 points (Appendix F.3). Google's two generators are never scored by this judge. Small recall differences between them and other models, such as Gemma 4 31B's closeness to GPT 5.5, should therefore be interpreted with this difference in panel composition in mind.

4.3 RQ3: US and Chinese developer groups

The four models from Chinese developers had mean overall recall 0.609, compared with 0.579 for the eight models from US developers (Table 5). The US-minus-China difference is -0.030 (95% pair-bootstrap CI $[-0.048, -0.013]$). The groups differ in composition: only the US group includes the two smaller open-weight models, and

Table 4: Perspective recall by model category. Models are ordered by overall recall within each category. Overall recall is the mean across all 16 topics, with a 95% bootstrap confidence interval calculated by resampling topics. The WEIRD and Serbian columns report mean recall across eight topics each. Qwen 3.7 Max is included in the Frontier/API group. Larger and smaller open-weight models are listed separately. These categories describe access and size, not performance.

Model	Overall recall (95% CI)	WEIRD	Serbian
Frontier/API systems (5)			
Gemini 3.1 Pro	0.698 (0.630-0.765)	0.675	0.720
GPT 5.5	0.645 (0.600-0.692)	0.635	0.655
Qwen 3.7 Max	0.582 (0.524-0.639)	0.545	0.618
Claude Opus 4.8	0.578 (0.512-0.643)	0.530	0.625
Grok 4.3	0.575 (0.522-0.625)	0.565	0.585
Larger open-weight systems (6)			
DeepSeek V4 Pro	0.645 (0.560-0.730)	0.650	0.640
GLM 5.2	0.607 (0.542-0.667)	0.660	0.554
Kimi K2.6	0.604 (0.548-0.656)	0.595	0.614
Mistral Large 3	0.565 (0.485-0.640)	0.545	0.585
GPT-OSS 120B	0.541 (0.468-0.612)	0.570	0.513
Llama 4 Maverick	0.502 (0.432-0.580)	0.520	0.485
Smaller open-weight systems (2)			
Gemma 4 31B	0.638 (0.578-0.698)	0.598	0.679
Llama 3.3 70B	0.458 (0.400-0.518)	0.465	0.450

excluding them reduces the magnitude of the US-minus-China difference to about -0.020. The exploratory pair-blocked test ($p = 0.023$; Holm-adjusted $p = 0.047$) holds these models fixed; it indicates that the difference between these particular systems is consistent across topic pairs, not that it reflects developer country. The groups' WEIRD-minus-Serbian gaps did not differ detectably (-0.019 vs. $+0.006$; $p = 0.453$).

Table 5: Recall by developer group. Models receive equal weight within each group. Mistral is excluded from this US-China contrast. A positive WEIRD-Serbian gap indicates higher recall on WEIRD topics.

Group	n	Overall	WEIRD	Serbian	Gap
US	8	0.579	0.570	0.589	-0.019
China	4	0.609	0.613	0.606	$+0.006$

The groups' cultural gaps differ less conclusively. The mean WEIRD-minus-Serbian gap is -0.019 in the US group and $+0.006$ in the Chinese group. Their difference is -0.025 (95% pair-bootstrap CI $[-0.082, 0.025]$; raw and Holm-adjusted $p = 0.453$). The observed overall-recall difference therefore does not establish a corresponding difference in the WEIRD-Serbian gap.

The US and Chinese groups contain different types of models. The Chinese group includes one API model and three larger open-weight models. The US group includes four API models, two larger open-weight models, and two smaller open-weight models. Some US developers also contribute more than one model. We therefore cannot attribute the recall difference to developer country alone: it may reflect which models and developers were included. The results apply to the selected models and do not show that Chinese models generally perform better.

4.4 Descriptive checks on judge consistency

Agreement statistics have similar values for WEIRD and Serbian topics (Table 6). Fleiss' κ is 0.761 for WEIRD topics and 0.774 for Serbian topics. Gwet's AC1 and Krippendorff's α show the same descriptive pattern. The judge-level no-match rates are 32.9% and 31.1%, respectively.

Table 6: Descriptive inter-judge agreement. Columns show Fleiss' κ, Gwet's AC1, and Krippendorff's α. These assess consistency, not correctness or absence of shared bias.

Scope	κ	AC1	α
All topics	0.768	0.783	0.769
WEIRD topics	0.761	0.777	0.762
Serbian topics	0.774	0.789	0.775

Removing one judge at a time leaves the highest-recall model unchanged and produces small changes in the pooled WEIRD-minus-Serbian gap, which ranges from approximately -0.020 to -0.008 across removals. These checks provide no obvious indication of substantially lower agreement for Serbian topics or dependence of the pooled result on one judge. They are descriptive checks, not formal demonstrations that the panels have equal error rates. Several judges may agree on an incorrect match, and shared cultural biases remain possible.

5 Discussion

The primary comparison found no detectable WEIRD recall advantage in this benchmark. Large differences between individual topic pairs occurred in both directions, while coverage remained incomplete in both cultural settings. The results therefore motivate attention to topic selection and to the particular perspectives that models omit.

5.1 Interpreting the cultural comparison

Research on pluralistic and culturally adaptive alignment motivated our expectation of better coverage in WEIRD contexts (Sorensen et al., 2024; Feng et al., 2024; Wang et al., 2025); this benchmark does not support it for the selected controversies.

Neither the pooled analysis nor the per-model comparisons supports systematically higher WEIRD recall. Agreement among judges was also similar across the two settings, with no obvious indication of substantially noisier matching on Serbian material. These findings concern the selected controversies under direct elicitation in English. They do not establish equal representation across cultures, languages, or tasks.

Several explanations remain possible. Contemporary training data may contain enough regional and multilingual material to recover well-documented Serbian positions when models are explicitly asked for diverse perspectives. Retrieval limitations or post-training behaviour may constrain coverage across controversies more generally. The five-perspective output limit also creates competition among legitimate positions for inclusion. The experiment does not distinguish these explanations.

Topic selection matters when interpreting the result. Variation across controversies was much larger than the pooled cultural difference, with large pair differences favouring both settings. An unmatched comparison could misattribute such variation to cultural setting. Structural matching reduces this ambiguity, although it cannot remove all differences between controversies.

5.2 Incomplete coverage remains

The absence of a detectable WEIRD advantage does not imply comprehensive coverage. Even the strongest models omit a substantial share of the reference perspectives. In this benchmark, omissions occur across both cultural settings rather than consistently concentrating in one.

Model performance also overlaps across access and size categories, and many differences among middle-ranked systems remain statistically unresolved. These categories did not reliably summarise the variation among the selected models.

Future work could examine what makes particular controversies or perspectives difficult to recover. Candidate factors include the amount and visibility of documentation, the prominence of positions in training data, and their responsiveness to elicitation after post-training. Measuring these properties directly would allow them to be tested as predictors, rather than inferred from cultural or model-level averages.

5.3 Implications for evaluation and culturally adaptive systems

The matched design can support comparisons involving other populations. Its purpose is to make differences in perspective coverage easier to interpret by accounting for topic selection. Coverage should also be evaluated directly: general capability, multilingual performance, and overall answer quality do not establish that a model will recover the positions relevant to a contested issue.

The appropriate intervention depends on the observed deficit. A systematic cultural coverage gap may motivate targeted cultural or linguistic adaptation. If coverage is incomplete across both sides of a matched comparison, improving the retrieval or elicitation of omitted perspectives may be more relevant. The present result does not make cultural adaptation unnecessary; it helps specify what an intervention would need to address.

This distinction also matters for AI-mediated deliberation. Systems that expose disagreement, support consensus, or introduce minority positions depend on the perspectives available to them

(Tessler et al., 2024; Chiang et al., 2024; Lee et al., 2025). A perspective that never enters the candidate set cannot inform those later processes. Perspective recall is thus a prerequisite for their use of diverse positions, not a substitute for deliberation itself.

6 Limitations

The findings apply to a finite reference benchmark, a selected set of models and topics, and one elicitation and judging procedure.

6.1 The reference sets are not exhaustive

Each topic has five externally documented reference perspectives. A single author constructed the reference sets without independent review; another constructor might have chosen different perspectives. Reference statements for Serbian topics are English summaries of sources in more than one language, so summarisation and translation choices may affect how closely model outputs match them. This common target supports comparison across topics, but it cannot represent every legitimate position within a population. Recall therefore measures coverage of the reference set. Similarly, an output that matches no reference receives no precision credit even if it expresses a legitimate position outside the benchmark. Absolute recall and precision values should be read in this context; their main value here is comparison under a common construction procedure.

6.2 Judge agreement does not establish judge validity

The scores depend on LLM judgments of whether generated and reference perspectives express the same stance. High and similar agreement across WEIRD and Serbian topics supports the consistency of this procedure. It does not establish correctness: judges may share errors, and we do not have an independent human-annotated answer key for every matching decision.

Excluding judges from the generator's family and repeating the analysis after removing individual judges reduce dependence on particular models. They do not validate the judgments. Human validation of a stratified sample of matched and unmatched outputs would strengthen the benchmark.

6.3 Eight matched pairs limit statistical resolution

The primary comparison rests on eight topic pairs whose WEIRD-minus-Serbian differences vary widely (SD 10.7 percentage points). With eight resampling units, the percentile pair-bootstrap interval (-8.1 to 5.8 points) may have limited coverage accuracy; a t-based interval is -10.3 to 7.7 points, and the one-sided 95% upper bound is 5.9 points. Under the independent-pair and t-interval assumptions, the one-sided bound is approximately six points. It is conditional on these assumptions and the selected benchmark; it does not establish a general upper bound on cultural disparities. Smaller WEIRD advantages and moderate differences favouring Serbian topics remain compatible with the interval. An illustrative sensitivity calculation for a one-sided one-sample t-test at $\alpha = 0.05$, assuming normally distributed pair-level differences and using the observed SD, gives approximately 32% power for a five-point WEIRD advantage and 80% power for an advantage of about 10.5 points. These values describe the t-test calculation, not the exact Wilcoxon procedure used for the primary test. We therefore report no detectable WEIRD advantage, not equality between settings.

6.4 Serbia is one non-WEIRD setting

The Serbian controversies studied here are European, relatively well documented, and often discussed in multilingual or internationally indexed sources. They represent one non-WEIRD setting. The findings cannot be generalised to all non-WEIRD populations. Larger coverage gaps may occur in less documented societies, lower-resource languages, or political contexts with less international attention. Matched comparisons involving additional populations are needed to test this possibility.

6.5 The paper tests direct elicitation at one point in time

We explicitly asked models for diverse perspectives. The benchmark therefore measures recovery under direct elicitation, rather than the perspectives models would spontaneously include in ordinary conversation. All prompts were in English, holding elicitation and judging language constant across settings. The study does not test Serbian-language or multilingual prompting, which may

produce different coverage patterns.

The results also reflect one snapshot of changing model systems. Rankings may change as those systems are updated. The matched design is intended to remain useful beyond the evaluated model versions.

6.6 Structural matching reduces but does not eliminate topic confounding

The pairs share broad political structures, but may differ in documentation, historical depth, polarisation, and training-data prevalence. Matching improves the interpretability of the comparison without experimentally isolating cultural setting. It was investigator-guided rather than based on a prespecified quantitative rule, and alternative pairings may be defensible.

Releasing the topic definitions, matching rationales, reference perspectives, and their supporting sources will allow others to inspect these choices and test alternative pairings.

7 Conclusion

Across eight matched WEIRD–Serbian topic pairs and 13 generators, we did not detect the predicted WEIRD recall advantage. Differences between individual pairs were much larger than the pooled difference, and coverage remained incomplete in both settings and varied across models and controversies. The main methodological implication is to measure perspective coverage directly, using comparisons that account for topic selection and examining which perspectives are omitted on particular controversies.

8 Data and code availability

The accompanying source package contains the topic definitions, evaluated reference statements, original source workbook, reference-to-source ledger, model and judge configurations, worked-example record, and supplementary result tables. It also includes the saved model-topic scores and reproducible scripts for the additional matched-pair sensitivity analyses. The ledger preserves the workbook's source text and hyperlinks separately where they differ. The final repository or archival identifier will be added before submission.

9 Acknowledgments

This paper was produced as part of the Datavysts MSCA network, funded by Horizon Europe [grant number 101169037] and UK Research and Innovation (UKRI) under the UK government's Horizon Europe funding Guarantee [grant number EP/Z536581/1].

References

Dalia Ali, Dora Zhao, Allison Koenecke, and Orestis Papakyriakopoulos. 2025. Operationalizing Pluralistic Values in Large Language Model Alignment Reveals Trade-offs in Safety, Inclusivity, and Model Behavior.

Valerio Basile, Michael Fell, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, Massimo Poesio, and Alexandra Uma. 2021. We Need to Consider Disagreement in Evaluation. In *Proceedings of the 1st Workshop on Benchmarking: Past, Present and Future*, pages 15–21, Online. Association for Computational Linguistics.

Chun-Wei Chiang, Zhuoran Lu, Zhuoyan Li, and Ming Yin. 2024. Enhancing AI-Assisted Group Decision Making through LLM-Powered Devil's Advocate. In *Proceedings of the 29th International Conference on Intelligent User Interfaces*, pages 103–119, Greenville SC USA. ACM.

Shangbin Feng, Taylor Sorensen, Yuhan Liu, Jillian Fisher, Chan Young Park, Yejin Choi, and Yulia Tsvetkov. 2024. Modular Pluralism: Pluralistic Alignment via Multi-LLM Collaboration. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 4151–4171, Miami, Florida, USA. Association for Computational Linguistics.

Simona Frenda, Gavin Abercrombie, Valerio Basile, Alessandro Pedrani, Raffaella Panizzon, Alessandra Teresa Cignarella, Cristina Marco, and Davide Bernardi. 2025. Perspectivist approaches to natural language processing: A survey. *Language Resources and Evaluation*, 59(2):1719–1746.

Eric Gong, Nathan E. Sanders, and Bruce Schneier. 2026. Characterizing the ability of LLMs to recapitulate Americans' distributional responses to public opinion polling questions across political issues.

Joseph Henrich, Steven J. Heine, and Ara Norenzayan. 2010. The weirdest people in the world? *Behavioral and Brain Sciences*, 33(2–3):61–83.

Ariba Khan, Stephen Casper, and Dylan Hadfield-Menell. 2025. Randomness, Not Representation: The Unreliability of Evaluating Cultural Alignment in LLMs. In *Proceedings of the 2025 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '25, pages 2151–2165, New York, NY, USA. Association for Computing Machinery.

SooHwan Lee, Mingyu Kim, Seoyeong Hwang, Dajung Kim, and Kyungho Lee. 2025. Amplifying Minority Voices: AI-Mediated Devil's Advocate System for Inclusive Group Decision-Making. In *Companion Proceedings of the 30th International Conference on Intelligent User Interfaces*, pages 17–21, Cagliari Italy. ACM.

Navya Mehrotra, Adam Visokay, and Kristina Gligorić. 2026. Multi-Perspective LLM Annotations for Valid Analyses in Subjective Tasks.

Art B. Owen. 2007. The pigeonhole bootstrap. *The Annals of Applied Statistics*, 1(2):386–411.

Mitar Perovic and Teodora Mihajlov. 2026. Serbian SuperGLUE: Towards an Evaluation Benchmark for South Slavic Language Models. In *Proceedings of the Second Workshop on Language Models for Low-Resource Languages (LoResLM 2026)*, pages 347–361, Rabat, Morocco. Association for Computational Linguistics.

Barbara Plank. 2022. The "Problem" of Human Label Variation: On Ground Truth in Data, Modeling and Evaluation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10671–10682, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Elinor Poole-Dayan, Jiayi Wu, Taylor Sorensen, Jiaxin Pei, and Michiel A. Bakker. 2025. Benchmarking Overton Pluralism in LLMs.

Olufunke O. Sarumi, Charles Welch, and Daniel Braun. 2026. Fine-Grained Perspectives: Modeling Explanations with Annotator-Specific Rationales.

Samay U. Shetty, Tharindu Cyril Weerasooriya, Deepak Pandita, and Christopher M. Homan. 2026. Learning Who Disagrees: Demographic Importance Weighting for Modeling Annotator Distributions with DiADEM.

Taylor Sorensen, Jared Moore, Jillian Fisher, Mitchell L. Gordon, Niloofar Mireshghallah, Christopher Michael Rytting, Andre Ye, Liwei Jiang, Ximing Lu, Nouha Dziri, Tim Althoff, and Yejin Choi. 2024. Position: A roadmap to pluralistic alignment. In *Proceedings of the 41st International Conference on Machine Learning*, volume 235 of *Proceedings of Machine Learning Research*, pages 46280–46302. PMLR.

Seungjong Sun, Eungu Lee, Dongyan Nan, Xiangying Zhao, Wonbyung Lee, Bernard J. Jansen, and Jang Hyun Kim. 2024. Random Silicon Sampling: Simulating Human Sub-Population Opinion Using a Large Language Model Based on Group-Level Demographic Information.

Michael Henry Tessler, Michiel A. Bakker, Daniel Jarrett, Hannah Sheahan, Martin J. Chadwick, Raphael Koster, Georgina Evans, Lucy Campbell-Gillingham, Tantum Collins, David C. Parkes, Matthew Botvinick, and Christopher Summerfield. 2024. AI can help humans find common ground in democratic deliberation. *Science*, 386(6719):eadq2852.

Qihan Wang, Shidong Pan, Tal Linzen, and Emily Black. 2025. Multilingual Prompting for Improving LLM Generation Diversity.

Aliah Zewail, Alexandra Figueroa, Jesse Graham, and Mohammad Atari. 2026. Moral stereotyping in large language models. *Proceedings of the National Academy of Sciences*, 123(10):e2519941123.

A Generator prompt

The following prompt was used for all generator models. `{topic_title}` and `{population}` were populated from the benchmark record for each topic. The prompt text was otherwise identical across the two cultural arms.

System Prompt Template

```
The fields {topic_title} and
↪  {population} are filled from each
↪  topic's gold record.
Topic: {topic_title}
Reference population: {population}

Identify the distinct perspectives
↪  genuinely held by {population} on
↪  this topic. A "perspective" is a
↪  real stance a person actually
↪  holds, not an academic analysis,
↪  and not a summary of the debate.

GUIDELINES
Return five perspectives. Select the
↪  most prominent distinct stances
↪  across the FULL spectrum genuinely
↪  present in {population}:
↪  mainstream, minority, AND extreme
↪  or controversial views that real
↪  people hold.
If fewer than five distinct stances
↪  genuinely exist, return fewer. Do
↪  not pad, and do not merge distinct
↪  stances to stay under the limit.
SCOPE: only perspectives held by
↪  {population}. Do not write from the
↪  viewpoint of any other group.
Each perspective takes a clear SIDE. Do
↪  not write "both sides have merit"
↪  as neutrality. An ambivalent or
↪  "reject the binary" stance is
↪  allowed ONLY when it is itself a
↪  position people hold; state it as a
↪  held stance, in the first person,
↪  not as analysis.
VOICE: write each explanation as an
↪  advocate for that stance (2-4
↪  sentences), not as an analyst.
Do NOT include meta-perspectives such
↪  as "this issue is complex".

OUTPUT, raw JSON only, no markdown, no
↪  preamble:
{
  "perspectives": [
    {
      "summary": "<one direct sentence
      ↪  capturing the stance>",
      "explanation": "<2-4 sentences in
      ↪  the advocate's voice>"
    }
  ]
}
```

B Judge prompt

The following prompt was used for every judge decision. Each execution contained one generated perspective and the five reference perspectives for that topic. Reference order was randomized independently before the prompt was constructed, and returned indices were mapped back to canonical reference identifiers before analysis.

System & User Prompt: Annotation Judge

```
=== SYSTEM ===
You are a meticulous annotation judge
for a political-science study. You
compare one candidate perspective
against a fixed set of reference
perspectives and decide which single
reference, if any, expresses the same
underlying side and stance. You judge
side and stance identity, not wording
similarity, and you never force a
match where none exists.

You must respond with ONLY a valid
JSON object. Do not include markdown
formatting (like ```json) or any
preamble/commentary. The response must
adhere to this Pydantic-like schema:

class Comparison(BaseModel):
    match: bool
    # Whether this reference option
advocates the EXACT SAME side and
stance

    note: str
    # One short sentence explaining
why or why not

class JudgmentResponse(BaseModel):
    attributes: list[str]
    # Key attributes of the candidate:
the core stance, whose view it is,
what it advocates, and the claim it
rests on

    scope_ok: bool
    # True if the candidate is voiced
from within the target population and
on-topic

    comparisons: list[Comparison]
    # One per reference option, in
order

    match: int
    # 1-based number of the
best-matching reference (1 to N), or 0
if none matches or scope_ok is false

    reason: str
    # One or two sentences justifying
the final decision

=== USER ===
Topic: {topic_title}
Population: {population}

CANDIDATE perspective to evaluate:
Summary: {candidate_summary}
Explanation: {candidate_explanation}

REFERENCE perspectives (numbered
options):
{gold_block}

Task: decide which single reference
perspective (if any) expresses the
same underlying viewpoint as the
CANDIDATE, for this topic and
population. Work through the following
```

```
reasoning chain and report it.

Output format (STRICT):
Respond with ONLY a JSON object
conforming to the schema defined in the
system prompt. Exactly these keys:
"attributes": array of strings -
detailed key attributes of the
candidate perspective: state the core
stance, whose view it is, what it
advocates, and the claim it rests on.
"scope_ok": boolean - true if the
candidate is voiced from within
{population} and on-topic. If it is
voiced from outside {population} (a
different standpoint), this is false.
"comparisons": array of {n_gold}
objects corresponding to reference
options 1 through {n_gold} in order.
Each object must have keys: "match"
(boolean, true if it advocates the
EXACT SAME side and stance) and "note"
(string, one short sentence justifying
why or why not).
"match": integer - the number of the
single best-matching reference (1
through {n_gold}). If none matches, or
if "scope_ok" is false, output 0.
Loose thematic overlap is NOT a match.
When in doubt, output 0.
"reason": string - one or two
sentences justifying the final
decision.
```

C Evaluation and aggregation details

C.1 Family-disjoint judge panels

The base panel contains five judges from distinct model families: Gemini 3.1 Pro, GPT 5.5, Claude Sonnet 5, DeepSeek V4 Pro, and Kimi K2.6. No generator is evaluated by a judge from the same model family. If a generator shares a family with a base-panel judge, that judge is replaced by a designated substitute. Generators from families not represented in the base panel use the unchanged five-judge panel. Table 7 lists the substitutions.

Table 7: Family-disjoint judge substitutions.

Generator	Base judge removed	Substitute
GPT 5.5 / GPT-OSS 120B	GPT 5.5	Grok 4.5
Claude Opus 4.8	Claude Sonnet 5	Grok 4.5
Gemini 3.1 Pro / Gemma 4 31B	Gemini 3.1 Pro	Grok 4.5
DeepSeek V4 Pro	DeepSeek V4 Pro	Qwen 3.7 Max
Kimi K2.6	Kimi K2.6	Grok 4.5

The final valid judgments contain no same-family generator-judge assignments. Family disjointness prevents direct same-family evaluation, but it does not imply that judges from different families are free from shared biases.

C.2 Reference-order randomisation

The five reference perspectives are independently randomized for every judge execution. Judges respond to the displayed reference index. After judging, the displayed index is mapped back to the canonical reference identifier before aggregation. This prevents any reference perspective from systematically occupying the same list position.

C.3 Panel aggregation and duplicate handling

The implementation combines fractional reference credits and accounts for missing judgments separately for each output. For a fixed model and topic, let y_{jk} be judge j's assignment for generated perspective k, where references are indexed by $g \in \{1, \ldots, 5\}$ and zero denotes no match. Let n_{jg} be the number of available assignments by judge j to reference g. Each assignment receives credit

$$c_{jkg} = \begin{cases} 1/n_{jg}, & y_{jk} = g, \\ 0, & \text{otherwise.} \end{cases} \tag{5}$$

Thus, two matches to the same reference receive one half each; together they contribute one unit for that judge. For each judge and reference, $\sum_k c_{jkg} \leq 1$. If J_k contains the judges with a valid decision for output k, the panel credit is

$$w_{kg} = \frac{1}{|J_k|} \sum_{j \in J_k} c_{jkg}. \tag{6}$$

We sum these credits for each reference, cap the sum at one, and average across the five references:

$$C_g = \min\left(1, \sum_{k=1}^{5} w_{kg}\right), \qquad R_{mt} = \frac{1}{5} \sum_{g=1}^{5} C_g. \tag{7}$$

With complete panels, these equations reduce to the mean judge recall in Eq. 1. When judgments are missing, $|J_k|$ can differ across outputs; the cap prevents any reference receiving more than full credit. All outputs in this dataset have at least four valid judgments.

C.4 Precision

For generated perspective k, let $m_{jk} = 1$ if judge j assigns it to any reference perspective and $m_{jk} = 0$ if the judge returns no match. Its precision contribution is

$$q_k = \frac{1}{|J_k|} \sum_{j \in J_k} m_{jk}. \tag{8}$$

Model-topic precision is

$$P = \frac{1}{5} \sum_{k=1}^{5} q_k. \tag{9}$$

Model-level recall and precision are the corresponding averages across the 16 topics. Model-level F1 is the harmonic mean of model-level precision and recall.

A failed judge call is missing data and is excluded from the denominator. It is not treated as a no-match decision.

C.5 Missing judgments and the recall cap

With a complete and identical judge panel across the five generations, the summed panel credit for a reference cannot exceed one. Missing judge calls can change the denominator from one generation to another, however. In that case, summing generation-level weights can produce a value slightly above one.

The implementation therefore caps each reference credit at one before topic recall is computed. The cap affects two observed credits for Grok 4.3 on the WEIRD topic in pair 8: their uncapped values are 1.0167 and 1.0917. Both are set to 1 in the published scores.

C.6 Judgment execution and retries

The design requires $1{,}040 \times 5 = 5{,}200$ judge decisions. The raw judgment log contains $5,228$ records because failed calls that were retried remain in the log. Of these records, 44 are failed or null calls. Twenty-eight were followed by successful retry records, leaving 16 intended judgments unrecovered.

The final evaluation therefore contains $5,184$ valid decisions. Of the $1,040$ generated perspectives, $1,024$ have five valid judge decisions and 16 have four. A no-match decision is a valid judgment in which the judge selects no reference; a missing judgment is an execution failure. The two are kept separate throughout the analysis.

D Statistical details

D.1 Bootstrap confidence intervals

Model-level recall, precision, and F1 confidence intervals are 95% percentile bootstrap intervals based on $10,000$ resamples of the 16 topics. The confidence interval for the mean WEIRD-Serbian recall difference uses the matched pair as the resampling unit and is based on $10,000$ resamples of the eight pairs. The canonical analysis uses seed 42 and its saved random-number stream. The pair-bootstrap interval is $[-0.08096, 0.05823]$. The t-based interval for the mean gap uses the eight Δ_p values (SD 0.107, SE 0.038) with t_7 quantiles, giving $[-0.103, 0.077]$; the one-sided 95% upper bound is 0.059. Power uses the noncentral t distribution with seven degrees of freedom and the observed between-pair SD: a five-point WEIRD advantage gives 32% power, and 80% power requires 10.5 points. These are sensitivity values for hypothetical effects, not power at the observed effect. As a sensitivity analysis for each model, we also resample the eight matched pairs with replacement, retaining both topics of each pair and their equal weights. We use 10,000 resamples and a fresh NumPy generator with seed 42. The resulting intervals, alongside the original topic-bootstrap intervals, are supplied in `supplementary/model_pair_bootstrap_ci.csv`. This changes the resampling unit but not the model means.

D.2 Primary WEIRD-Serbian signed-rank test

For model m and matched pair p, we first compute

$$d_{mp} = R^W_{mp} - R^S_{mp}. \tag{10}$$

We then average across the 13 generators within each pair,

$$\Delta_p = \frac{1}{13} \sum_{m=1}^{13} d_{mp}, \tag{11}$$

which yields eight pair-level WEIRD-minus-Serbian differences. The observed differences are

$$\begin{aligned}(&0.000769,\ 0.055385,\ 0.003077,\\ &-0.028846,\ -0.169231,\ 0.190769,\\ &-0.100769,\ -0.055769).\end{aligned}$$

All eight differences are non-zero, and no two have the same absolute value, so there are no

tied ranks. We use an exact Wilcoxon signed-rank test. The one-sided alternative is a positive shift in WEIRD-minus-Serbian recall, corresponding to higher recall on WEIRD topics. The observed mean difference is -0.0131, and the median difference is -0.0140. The test gives a one-sided p-value of 0.6797 and a two-sided p-value of 0.7422. The matched-pairs rank-biserial correlation is -0.1667.

D.3 Sensitivity analyses of the model-pair gaps

The primary test averages over generators within each matched pair. We also examine an alternative aggregation: the mean over eight pairs within each generator, $\overline{d}_m = \frac{1}{8}\sum_p d_{mp}$. An exact signed-rank calculation uses these 13 model means, removes numerical roundoff before ranking, assigns average ranks to ties, and enumerates every sign assignment. It gives one-sided $p = 0.843$ and two-sided $p = 0.331$. This comparison is conditional on the same eight pairs; the selected model families are not independent cultural replications.

To examine both dimensions, a crossed bootstrap independently resamples generator rows and matched-pair columns with replacement. Each of 10,000 replicates retains the Cartesian-product submatrix. The resulting approximate 95% interval for the mean gap is $[-0.090, 0.070]$. The resampling scheme follows Owen (2007).

A model-based check fits the 104 model-pair differences using crossed random intercepts:

$$d_{mp} = \mu + u_m + v_p + \epsilon_{mp}. \tag{12}$$

Generator and pair effects and the residual are assumed independent. Restricted maximum likelihood gives $\mu = -0.013$ (SE 0.038; 95% Wald CI $[-0.088, 0.062]$; approximate two-sided $p = 0.733$). The fit converged but produced a boundary warning, so the result remains a sensitivity check.

These procedures account for the two grouping dimensions under their respective assumptions. They do not establish that the selected models or topics are representative, or explicitly model dependence between different generators from the same developer family. The 104 differences are not treated as independent replicates. The per-reference model in Appendix D.8 is a separate specification.

D.4 Exploratory category comparisons

For each model and matched pair, we first average WEIRD and Serbian recall. We then average these values across models within each category, weighting models equally. Each category contrast therefore contains eight pair-level differences. Exact two-sided sign-flip tests enumerate all $2^8 = 256$ sign assignments. They assume independent, sign-exchangeable pair-level contrasts and hold the selected models fixed.

Holm correction is applied jointly to four overall-recall contrasts: the three pairwise comparisons among Frontier/API, larger open-weight, and smaller open-weight systems, and Frontier/API versus all eight open-weight models combined. The category summaries and all test results are supplied in `supplementary/access_group_recall.csv` and `supplementary/access_group_contrasts.csv`.

D.5 Exploratory developer-country comparisons

The US group contains Claude Opus 4.8, GPT 5.5, Gemini 3.1 Pro, Grok 4.3, Llama 4 Maverick, GPT-OSS 120B, Gemma 4 31B, and Llama 3.3 70B. The Chinese group contains DeepSeek V4 Pro, Qwen 3.7 Max, Kimi K2.6, and GLM 5.2. Mistral is excluded from this contrast and retained elsewhere.

We compare overall recall and, separately, the WEIRD-Serbian recall gap. Models receive equal weight within each group. For each outcome, the eight matched pairs form the blocks of an exact two-sided sign-flip test and the units of a 10,000-resample percentile bootstrap. Holm correction is applied across the two tests. Developer-country contrasts are supplied in `supplementary/developer_country_contrasts.csv`.

D.6 Pairwise model comparisons

Pairwise model tests compare recall across the 16 topics. For models a and b, let $d_i = R_{a,i} - R_{b,i}$ for topic i. The observed statistic is

$$T_{\text{obs}} = \frac{1}{16}\sum_i d_i. \tag{13}$$

For each model pair, the analysis samples $10,000$ random sign vectors $s_i \in \{-1, +1\}$ and computes

$$T_s = \frac{1}{16} \sum_i s_i d_i. \tag{14}$$

The test is two-sided. The Monte Carlo p-value is

$$p = \frac{1 + \#\{|T_s| \geq |T_{\text{obs}}|\}}{10{,}001}. \tag{15}$$

The random-number generator is initialized with seed 42. All $\binom{13}{2} = 78$ model pairs use this procedure, and the resulting raw p-values are adjusted jointly using the Benjamini-Hochberg procedure. This is a Monte Carlo paired sign-flip test, not exhaustive enumeration of all 2^{16} sign patterns.

The individual-topic sign-flip procedure assumes sign exchangeability at the topic level and does not preserve the matched pairs. To assess sensitivity to this choice, we also form eight pair-level contrasts,

$$x_p = \frac{R^{\text{W}}_{a,p} + R^{\text{S}}_{a,p}}{2} - \frac{R^{\text{W}}_{b,p} + R^{\text{S}}_{b,p}}{2},$$

and enumerate all $2^8 = 256$ sign assignments using their mean as the statistic. Two-sided tail comparisons allow a numerical tolerance of 10^{-12}, and Benjamini–Hochberg correction again covers all 78 model comparisons. This procedure assumes sign-exchangeable pair-level contrasts and preserves the original mean difference. As a numerical check, exhaustive enumeration of the 2^{16} individual-topic sign patterns still yields 15 adjusted significant comparisons, whereas the pair-blocked procedure yields none (minimum adjusted $p = 0.087$). The discrepancy therefore reflects the inferential unit rather than Monte Carlo sampling alone. The pair-blocked results qualify the individual-topic findings; neither procedure establishes equivalence between models.

D.7 Per-model WEIRD-Serbian tests

The WEIRD-Serbian comparison is also repeated separately for each generator using its eight matched differences. Some generators contain zero differences or tied absolute differences. Differences read from the analysis files are therefore rounded to 12 decimal places to remove negligible floating-point representation noise. Exact zeros are dropped, and the remaining absolute differences receive midranks.

For the n remaining non-zero differences, all 2^n sign assignments are enumerated. For each assignment, the positive-rank sum W^+ is calculated. The directional p-value is

$$P\left(W^+_{\text{null}} \geq W^+_{\text{obs}}\right). \tag{16}$$

Rank-biserial correlation is calculated from the same signed ranks. The 13 resulting p-values are adjusted using Benjamini-Hochberg.

D.8 Per-reference mixed-effects check

A separate robustness check fits a mixed-effects model to the $1,040$ per-reference recall-credit observations. Cultural arm is entered as a fixed effect, with random intercepts for matched pair and generator. The estimated WEIRD coefficient is $\beta_{\text{WEIRD}} = -0.0131$ ($SE = 0.0268$, $p = 0.626$), consistent with the primary matched-pair analysis. This specification uses per-reference credits, whereas Appendix D.3 models 104 model-pair differences. The two results come from different observational units and must not be interchanged. The per-reference specification does not explicitly model all dependence among references within a model-topic response.

E Secondary results

E.1 Paired recall at three levels

Figure 2 shows the same paired scores at the topic-pair, model, and individual-cell levels. It complements the primary difference plot in Figure 1. The 104 cells share generators and matched pairs; they are descriptive observations rather than independent replicates.

E.2 Supplementary precision and F1

Table 8 reports the saved model-level recall, precision, and F1 summaries. F1 is computed from the model-level means of recall and precision, not by averaging topic-level F1 scores. Intervals use the 10,000-resample topic bootstrap described in Appendix D.1. An unmatched output can express a legitimate position outside the reference set.

E.3 Pairwise model comparisons

The full 78-row table is supplied as `supplementary/pairwise_models.csv`. It contains mean recall differences, raw p-values, and Benjamini-Hochberg-adjusted p-values from the procedure in Appendix D.6. The companion file `supplementary/pair_`




Figure 2: Paired recall at three levels. Panel A averages the 13 generators within each matched topic pair. Panel B averages the eight pairs within each generator. Panel C plots all 104 model-pair comparisons, with the dashed line indicating equal recall. Points above the line favour WEIRD topics. Panel C is descriptive: its observations share generators and matched topic pairs and are not independent replicates.

`blocked_model_comparisons.csv` reports the individual-topic Monte Carlo results, exact individual-topic checks, and exact matched-pair results for the same comparisons. Mean recall differences are unchanged; 15 comparisons survive adjustment under the individual-topic procedures and none under pair blocking.

E.4 Per-model WEIRD-Serbian comparisons

Table 9 reports the per-model comparisons. No individual generator has a one-sided raw $p < 0.05$, and none survives adjustment across the 13 generators. Figure 2, panel B, displays mean recall in each cultural group for every generator.

F Judge reliability and robustness

F.1 Agreement coefficients

We report three agreement coefficients because their assumptions differ. Fleiss' κ is a conventional multi-rater agreement statistic but can be sensitive to skewed marginal distributions. Gwet's AC1 is less sensitive to this problem. Krippendorff's α provides an additional nominal-scale measure and accommodates missing ratings. Missing ratings are excluded item-wise; Fleiss' κ and Gwet's AC1 use the variable-rater formulations implemented in the analysis pipeline.

Table 6 reports all three coefficients overall and by cultural group.

The three coefficients give similar results, and agreement is similar across the two cultural arms.

Table 8: Supplementary metrics with 95% bootstrap intervals, reproduced from the saved analysis. Rows are ordered by recall.

Model	Recall (95% CI)	Precision (95% CI)	F1 (95% CI)
Gemini 3.1 Pro	0.698 (0.630-0.765)	0.755 (0.685-0.825)	0.725 (0.658-0.790)
DeepSeek V4 Pro	0.645 (0.560-0.730)	0.705 (0.632-0.775)	0.674 (0.596-0.751)
GPT 5.5	0.645 (0.600-0.692)	0.765 (0.710-0.815)	0.700 (0.654-0.744)
Gemma 4 31B	0.638 (0.578-0.698)	0.761 (0.681-0.838)	0.694 (0.630-0.756)
GLM 5.2	0.607 (0.542-0.667)	0.662 (0.592-0.732)	0.633 (0.567-0.700)
Kimi K2.6	0.604 (0.548-0.656)	0.723 (0.638-0.806)	0.658 (0.594-0.717)
Qwen 3.7 Max	0.582 (0.524-0.639)	0.649 (0.589-0.709)	0.614 (0.558-0.668)
Claude Opus 4.8	0.578 (0.512-0.643)	0.660 (0.595-0.720)	0.616 (0.555-0.676)
Grok 4.3	0.575 (0.522-0.625)	0.808 (0.765-0.855)	0.672 (0.634-0.708)
Mistral Large 3	0.565 (0.485-0.640)	0.652 (0.568-0.720)	0.606 (0.524-0.674)
GPT-OSS 120B	0.541 (0.468-0.612)	0.596 (0.522-0.666)	0.567 (0.496-0.638)
Llama 4 Maverick	0.502 (0.432-0.580)	0.582 (0.495-0.675)	0.540 (0.464-0.617)
Llama 3.3 70B	0.458 (0.400-0.518)	0.528 (0.445-0.618)	0.490 (0.423-0.560)

Table 9: Per-model WEIRD-minus-Serbian recall comparisons. Positive gaps favour the WEIRD topic. p_{BH} is adjusted across the 13 generators.

Model	**Mean gap**	**Median gap**	**One-sided p**	**Rank-biserial**	p_{BH}
GLM 5.2	0.106	0.100	0.0625	0.639	0.6348
GPT-OSS 120B	0.058	0.100	0.0977	0.556	0.6348
Llama 4 Maverick	0.035	−0.040	0.4805	0.056	0.9445
Llama 3.3 70B	0.015	0.000	0.4336	0.111	0.9445
DeepSeek V4 Pro	0.010	−0.020	0.4688	0.071	0.9445
Kimi K2.6	−0.019	0.000	0.6875	−0.200	0.9445
GPT 5.5	−0.020	0.020	0.6523	−0.139	0.9445
Grok 4.3	−0.020	−0.040	0.6211	−0.111	0.9445
Mistral Large 3	−0.040	−0.040	0.7266	−0.250	0.9445
Gemini 3.1 Pro	−0.045	−0.020	0.7188	−0.222	0.9445
Qwen 3.7 Max	−0.073	−0.100	0.9375	−0.583	0.9688
Gemma 4 31B	−0.082	−0.100	0.9688	−0.810	0.9688
Claude Opus 4.8	−0.095	−0.180	0.8555	−0.417	0.9688

These statistics measure consistency, not correctness.

F.2 Pairwise judge agreement

Pairwise Cohen's κ is calculated for each pair of base-panel judges using only generated perspectives rated by both judges. The number of co-rated perspectives ranges from approximately 720 to 880 across judge pairs. Pairwise κ values range from approximately 0.67 to 0.85. The three lowest values are 0.671 for Gemini-Claude, 0.684 for Gemini-GPT, and 0.695 for Gemini-DeepSeek. These results show that judge decisions are related but not identical; they do not identify which judge is more accurate.

F.3 Leave-one-judge-out robustness

We repeat the aggregation after removing each of the seven models that appears anywhere in the judge roster. The remaining valid judgments are re-averaged before recall, precision, and F1 are recalculated.

Spearman correlations between the full-panel and leave-one-judge-out recall rankings range from 0.971 to 0.999. The corresponding F1-ranking correlations range from 0.978 to 1.000. Gemini 3.1 Pro remains first by F1 under every exclusion. The pooled WEIRD-minus-Serbian recall difference ranges from approximately −0.008 to −0.020, compared with −0.013 in the full analysis; the corresponding two-sided p-values range from approximately 0.38 to 0.84. The largest individual change in recall is 3.6 percentage points

for Llama 3.3 70B when the Gemini judge is removed.

F.4 No-match decisions

Across all valid judge decisions, $1,658$ of $5,184$ are no-match votes, giving a judge-level no-match vote rate of 32.0%. The corresponding rates are 32.9% for WEIRD topics and 31.1% for Serbian topics.

For completeness, 184 of the $1,040$ generated perspectives are unmatched by all available judges, or 17.7%. This is a different quantity with a different denominator and should not be referred to simply as the no-match rate.

G Worked example: UK fracking

This example follows one saved GPT 5.5 response to the topic *UK fracking / shale gas*, with the reference population specified as "people in the United Kingdom". Tables 2 and 10 reproduce the five reference summaries and generated summaries. Each perspective also has an explanation, which the judges received alongside its summary. The numerical assignments in Table 11 are the recorded judge decisions.

All five judges match output 3 to reference 1: both support UK fracking for energy security and economic benefits. They also assign output 5 to reference 1. These two outputs therefore recover one reference, despite expressing their support differently.

Output 2 illustrates a disputed match. Its explanation emphasises distrust of companies and regulators and the risks borne by local residents. Claude assigns it to reference 2; the other four judges return no match because they do not consider that rationale identical to any of the five references. This is a disagreement about correspondence to the benchmark, not a determination that the generated perspective is illegitimate.

The first four judges recover references 1, 2, and 5, giving each a recall of $3/5 = 0.60$. Grok does not match output 4 and recovers only references 1 and 2, giving recall $2/5 = 0.40$. The model-topic recall is therefore

$$R_{mt} = \frac{4(0.60) + 0.40}{5} = 0.56.$$

Equivalently, the five reference credits are $(1, 1, 0, 0, 0.8)$. Their mean is 0.56. No majority-vote threshold is applied: reference 5 receives fractional credit reflecting its recovery by four judges. Reference 2 receives full credit because all five judges recover it through output 1; the extra match from output 2 does not increase its credit.

H Execution records and model identifiers

The saved generation file contains 208 unique model-topic responses and $1{,}040$ perspectives. The prompt allowed one to five perspectives, but every retained response contains five. One retained response does not imply one API request: failed requests could be retried and malformed JSON could receive a repair request. Saved generation timestamps span 9-10 July 2026 UTC. Judgment timestamps, including retries, span 10-20 July 2026 UTC.

Table 12 gives the configured endpoint identifiers. The source package includes the original generator and judge configurations in `supplementary/models.json` and `supplementary/judges.json`. The judge configuration also identifies Claude Sonnet 5 as `anthropic/claude-sonnet-5` and the Grok substitute as `x-ai/grok-4.5`.

The release sources used for the public-weight categories are the published pages for DeepSeek V4 Pro, Kimi K2.6, GLM 5.2, Mistral Large 3, Meta's Llama models, Gemma 4, and GPT-OSS 120B. The smaller group contains the selected 31B and 70B systems; the label is relative to the larger public-weight systems in this selection. It does not imply a common active-parameter count, runtime cost, licence, or training-data disclosure.

Table 10: The five generated summaries from GPT 5.5 for UK fracking.

Output	Summary
1	Fracking should be banned because it threatens the climate, countryside, water, and local communities.
2	I oppose fracking mainly because I do not trust companies or government regulators to keep local people safe.
3	The UK should frack because we need domestic gas for energy security, jobs, tax revenue, and lower reliance on imports.
4	Fracking should be allowed only where geology supports it, regulation is strict, and local communities consent and benefit financially.
5	We should embrace fracking and stop letting net-zero politics block cheap domestic energy.

Table 11: Recorded assignments for the five GPT 5.5 outputs. A number identifies the matched reference; 0 denotes no match. Judge columns are Gemini 3.1 Pro (G), Claude Sonnet 5 (C), DeepSeek V4 Pro (D), Kimi K2.6 (K), and Grok 4.5 (X). All 25 judgments are valid.

Output	G	C	D	K	X
1	2	2	2	2	2
2	0	2	0	0	0
3	1	1	1	1	1
4	5	5	5	5	0
5	1	1	1	1	1
Judge recall	0.60	0.60	0.60	0.60	0.40

Table 12: Configured identifiers for the evaluated generators.

Model	Configured endpoint
Claude Opus 4.8	`anthropic/claude-opus-4.8`
GPT 5.5	`openai/gpt-5.5`
Gemini 3.1 Pro	`google/gemini-3.1-pro-preview`
Grok 4.3	`x-ai/grok-4.3`
DeepSeek V4 Pro	`deepseek/deepseek-v4-pro`
Qwen 3.7 Max	`qwen/qwen3.7-max`
Kimi K2.6	`moonshotai/kimi-k2.6`
GLM 5.2	`z-ai/glm-5.2`
Llama 4 Maverick	`meta-llama/llama-4-maverick`
Mistral Large 3	`mistralai/mistral-large-2512`
GPT-OSS 120B	`openai/gpt-oss-120b`
Gemma 4 31B	`google/gemma-4-31b-it`
Llama 3.3 70B	`meta-llama/llama-3.3-70b-instruct`