

C++ Template Lisp Interpreter

Spencer Tipping

July 6, 2010

Contents

| | |
|--|----------|
| 1 Introduction to Template Patterns | 1 |
| 1.1 Encoding constants | 1 |
| 1.2 First-order function encoding | 2 |
| 1.3 Higher-order function encoding | 3 |
| 1.4 Makefile for examples | 4 |

1 Introduction to Template Patterns

Template expansion provides a pure untyped lambda calculus. All equality is extensional and the calculus supports higher-order functions (templates) with annotations at invocation, but not declaration, time.¹ This section goes over the encoding of lambda calculus in the template system.

1.1 Encoding constants

Constants are simply structs, classes, or other types that don't take template parameters. It isn't a problem if they do take template parameters, of course; those will simply be specified later once the constant has propagated through the lambda expansion.

Listing 1: examples/constants.h

```
1 // Defining a constant term
2 struct foo {
3     enum {value = 10};
4 };
5
6 // Defining a global constant also_foo = foo
7 typedef foo also_foo;
8
```

¹This makes it untyped. C++ templates also support function types using nested template syntax – see [section ??](#).

```

9 // Defining two templated terms that act as constants
10 template<class t> struct has_a_field {
11     t field;
12 };
13
14 template<int n> struct has_a_number {
15     enum {number = n};
16 };

```

1.2 First-order function encoding

The idea is to have structs that represent terms of the calculus. If they are templates, then they represent functions (which are also terms). For example:

Listing 2: examples/first-order-functions.cc

```

1 #include <iostream>
2 #include "constants.h"
3
4 // Defining the identity function, where the result
5 // can be retrieved by specifying bar<T>::type
6 template<class t> struct bar {
7     typedef t type;
8 };
9
10 // Defining a global constant identity_result = bar(also_foo)
11 // This is analogous to the code 'let identity_result = bar also_foo'
12 // in Haskell.
13 typedef bar<also_foo>::type identity_result;
14
15 int main () {
16     std::cout << "foo::value          = " <<
17                 foo::value          << std::endl <<
18                 "also_foo::value     = " <<
19                 also_foo::value     << std::endl <<
20                 "identity_result::value = " <<
21                 identity_result::value << std::endl;
22 }

```

In practice there is some difficulty already. Notice the use of `::type` to retrieve the value of a function application. This slot had to be assumed by the caller; it is analogous to JavaScript code like this:

Listing 3: examples/unfriendly-identity.js

```

1 // An unfriendly identity function.
2 var identity = function (x) {
3     return {type: x};

```

```

4 };
5
6 // Invocations must now look like this:
7 var y = identity(x).type;

```

Having issues like this percolating through the design can be a real problem. Unless the slot is passed to every invocation site,² invocations will be divergent and will create errors. This means that return values should be unified to a single slot, in this library (and the Boost MPL) called `::type`.³

So we establish some conventions up front. Whenever you define a constant, it is used as-is without a contained `typedef` that we have to know about. This is OK because we shouldn't ever make assumptions about the members of types that are used as template parameters.

1.3 Higher-order function encoding

Higher-order functions are possible by encoding slots for invocations.⁴ We do this by declaring another template inside the first:

Listing 4: `examples/higher-order-functions.cc`

```

1 #include <iostream>
2 #include "constants.h"
3
4 // Defining the K combinator
5 template<class t>
6 struct k {
7     template<class u>
8     struct apply {
9         typedef t type;
10    };
11 };
12
13 // Using that on two types
14 typedef has_a_number<5> t1;
15 typedef has_a_number<6> t2;
16 typedef k<t1>::apply<t2>::type should_be_t1;
17
18 int main () {

```

²It also must be forwarded, which isn't possible in C++ to the best of my knowledge

³This may seem counter-intuitive, since the types here encode values in lambda-calculus. However, it does serve a mnemonic purpose later when value types are used as template parameters, and dependent value-type relations are established. Once this happens it becomes useful to explicitly distinguish between type template parameters and value template parameters.

⁴This is equivalent to the distinction between pure, extensional object-oriented programming and pure, extensional functional programming. In the latter, term juxtaposition (e.g. `f x`) constitutes invocation of the default slot, generally referred to as *apply*. In the former, slots are explicitly named, as would be the case in a language such as Java – thus juxtaposition has no meaning on its own.

```

19     std::cout << "t1::number          = " << t1::number          << std::endl <<
20         "should_be_t1::number = " << should_be_t1::number << std::endl;
21 }

```

In this example, `foo2` has a call slot `apply` that ultimately provides the value. So, for example, `foo2<x>::apply<y>::type` is equivalent to the more concise `foo2 x y` in Haskell, or `((foo2 x) y)` in Scheme.

At this point it should be clear that nothing is standardized here. Top-level functions are invoked directly, whereas returned functions use `::apply<x>`. Type results from template invocations are accessed as `::type`. One way to go about fixing it is to make a rule that a function gets encoded a bit less directly:

Listing 5: `examples/indirect-functions-broken.cc`

```

1  #include <iostream>
2  #include "constants.h"
3  // Encoding the K combinator uniformly
4  struct k {
5      template<class t>
6      struct apply {
7          template<class u>
8          struct invoke_foobar {
9              typedef t type;
10         };
11
12         typedef invoke_foobar apply;
13     };
14 };

```

However, if you compile it you get an error stating that you can't define a nested struct with the same name as the outer one.

1.4 Makefile for examples

This makefile will build all of the examples listed in the introduction.

Listing 6: `examples/makefile`

```

1  all: first-order-functions higher-order-functions
2  run: all
3      ./first-order-functions
4      ./higher-order-functions
5      ./indirect-functions-broken
6
7  %: %.cc
8      g++ -g -Wall $< -o $@

```