

Reproducible, portable, and efficient ancient genome reconstruction with nf-core/eager

This manuscript ([permalink](#)) was automatically generated from [apeltzer/eager2-paper@d834342](#) on June 1, 2020.

Authors

- **James A. Fellows Yates**

 [0000-0001-5585-6277](#) ·  [jfy133](#) ·  [jfy133](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Thiseas C. Lamnidis**

 [0000-0003-4485-8570](#) ·  [TCLamnidis](#) ·  [TCLamnidis](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Maxime Borry**

 [0000-0001-9140-7559](#) ·  [maxibor](#) ·  [notmaxib](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Aida Andrades Valtueña**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [aidaanva](#) ·  [aidaanva](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Zandra Fagernäs**

 [0000-0003-2667-3556](#) ·  [ZandraFagernas](#) ·  [ZandraSelina](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Stephen Clayton**

 [XXXX-XXXX-XXXX-XXXX](#) ·  [sc13-bioinf](#)

Department of Archaeogenetics, Max-Planck-Institute for the Science of Human History · Funded by Max Planck Society

- **Maxime U. Garcia**

 [0000-0003-2827-9261](#) ·  [MaxUlysse](#) ·  [gau](#)

Department of Oncology-Pathology, Karolinska Institutet · Funded by Barncancerfonden

- **Judith Neukamm**

 [0000-0001-8141-566X](#) ·  [JudithNeukamm](#) ·  [JudithNeukamm](#)

Palaeogenetics Group, Institute of Evolutionary Medicine, University of Zurich

- **Alexander Peltzer**

 [0000-0002-6503-2180](#) ·  [apeltzer](#) ·  [alex_peltzer](#)

Translational Medicine & Clinical Pharmacology, Boehringer Ingelheim Pharma GmbH & CO KG, Biberach an der Riss

Abstract

The broadening utilization of ancient DNA (aDNA) to address anthropological, palaeontological and biological questions is resulting in a rising diversity in the size of laboratories and scale of analyses being performed. In the context of this heterogeneous landscape, we present [nf-core/eager](#), an advanced and entirely redesigned pipeline for the analysis of ancient DNA genomic data. [nf-core/eager](#) builds on existing ideas and concepts introduced in the original EAGER pipeline [1](#), and improves various aspects of the analysis procedure by building on computational frameworks such as Nextflow [2](#) and [nf-core](#) [3](#). The pipeline aims to address three main points: adaptability to different computing configurations, reproducibility to ensure robust analytical standards in the field, and updating the EAGER pipeline to the latest routine and ancient genomic practises. This new version of EAGER has been developed within the [nf-core](#) initiative, to ensure high quality software development and maintenance support; contributing to a long-term lifecycle for the pipeline. [nf-core/eager](#) will assist in ensuring that ancient DNA sequencing data can be utilised by a diverse range of research groups and fields.

Introduction

Ancient DNA has become a widely accepted source of biological data, helping to provide new perspective for a range of fields including archaeology, ecology, cultural heritage, and palaeontology. The utilisation of next-generation-sequencing has allowed the recovery of ancient DNA from a wide variety of sources, including but not limited to, the skeletal remains of animals ([4](#), [5](#), [6](#), [\[???\]](#)), modern and archaic humans ([7](#), [8](#), [\[???\]](#)), bacteria ([9](#), [10](#), [11](#)), viruses ([12](#), [13](#)), plants ([14](#), [15](#)), but also coprolites ([16](#), [17](#)), dental calculus ([18](#), [19](#)), sediments ([20](#), [21](#)), medical slides ([22](#)), parchment ([23](#)), and most recently ancient 'chewing gum' ([24](#), [25](#)). Improvement in laboratory protocols to increase yields of otherwise trace amount of DNA has at the same time led to studies that can range from one to hundreds of ancient individuals ([26](#), [\[???\]](#)), spanning single ([27](#)) to thousands of organisms ([18](#)). These differences of disciplines have led to a heterogeneous landscape in terms of types of analyses and subsequently thus various types of computing resources required by different labs. Particularly, this is true for regions of the world where ancient DNA as a field of research is still emerging.

Two previously published and commonly used pipelines in the field are PALEOMIX ([28](#)) and EAGER ([1](#)). These two pipelines take a similar approach to link together standard tools used for Illumina NGS data processing (quality control, adapter removal/and or merging, mapping, genotyping etc.), but with a specific focus on tools that are designed for or well-suited for ancient DNA (such as [bwa aln](#) ([29](#)) for ultra-short reads and [mapDamage](#) ([30](#)) for aDNA characteristic evaluation). Yet, neither of these pipelines have had major updates to bring in line with current routinely carried out aDNA analyses. In particular, metagenomic screening of off-target genomic reads for pathogens or microbiomes ([18](#), [19](#)) has become particularly common, given it's role in revealing widespread infectious disease and possible epidemics that had previously been undetected in the archaeological record ([31](#), [32](#), [12](#), [13](#)). Without easy access to the latest field-established analytical routines, aDNA studies from groups new to the field risk being published without the necessary quality control checks that ensure authenticity of their data and without yielding the full range of possibilities from the data.

To address these shortcomings, we have completely re-implemented the latest version of the EAGER pipeline in Nextflow, a domain-specific-language (DSL) designed for the construction of omics analysis pipelines ([2](#)), **introduced new features (Sex determination, XXX), and more flexible pipeline configuration (bam input, better skip logic than eager1)**. In addition, the newly named pipeline - [nf-core/eager](#) - has been developed in the context of the [nf-core](#) community framework ([3](#)). [nf-core](#) enforces strict guidelines for best-practises in software development to ensure robust, long-term maintenance and high quality pipelines.

Results and Discussion

Scalability, Portability, and Efficiency

The reimplementation of EAGER into Nextflow offers a range of benefits over the original custom pipeline framework.

Firstly, the new framework provides immediate integration of nf-core/eager into various schedulers in POSIX High-Performance-Cluster (HPC) environments, cloud computing resources and as well as local workstations. This portability allows both small and big labs to run nf-core/eager regardless of the type of computer or cluster cluster sizes with minimal effort or configuration, facilitating reproducibility and therefore maintenance of standards within the field. This is further assisted by the in-built compatibility with software environments and containers such as conda, docker and singularity. This ensures exact versions of software are used by a user, regardless of the setup of their respective cluster environment. Another major change with nf-core/eager is that the GUI input is now replaced with a command-line-interface as the primary user interaction mode. This is more compatible and portable with most HPCs (that may not offer X11 forwarding) and is in line with the vast majority of bioinformatic tools. We therefore believe this will not be a hindrance to new researchers from outside computational biology, however there are plans within the nf-core to provide multiple alternatives in the near future including a command-line wizard, and a web-based input GUI.

Secondly, reproducibility is made easier through the use of 'profiles' that can define configuration parameters. These profiles can be managed at different hierarchical levels. HPC-level profiles can specify parameters for the computing environment (schedulers, cache locations, maximum resource etc.), which can be centrally managed to ensure all users of a group use the same settings. Pipeline-level profiles, specifying default parameters for nf-core/eager itself, can be shared, thus making the pipeline portable between different groups through separation of the parameters from input data. Compared to the original EAGER that utilised per-FASTQ XML files with hardcoded filepaths, nf-core/eager allows researchers to publish the specific profile used in their runs alongside their publications, to ensure other groups can generate the same results. Usage of profiles also reduces mistakes caused by insufficient 'prose' based reporting of program settings, which may occur in papers written by researchers unfamiliar with informatics. The default nf-core/eager profile uses parameters evaluated in different aDNA specific contexts (e.g. [33](#)), and will be updated in each new release as new studies are published.

nf-core/eager provides improved efficiency over the original EAGER pipeline by replacing the sample-by-sample sequential processing with Nextflow's asynchronous parallelisation. This, combined with pre-defined per-process customisation of resource parameters, reduces unnecessary resource allocation that can occur with new users to each step of an NGS data processing pipeline. This is particularly pertinent given the increasing use of centralised HPCs or cloud computing, which often use per-hour cost calculations.

Latest aDNA practices

nf-core/eager follows a similar structural foundation with the original EAGER. Given Illumina short-read FASTQ and/or BAM files, and a reference FASTA file.

This can be split into four main stages:

ADD CITATIONS

1. Preprocessing
 1. Sequencing quality control (FastQC [???]/)
 2. Sequencing artefact clean-up (AdapterRemoval2 ([34](#)))
 3. Preprocessing statistics generation
2. Mapping and post- processing
 1. Alignment against reference genome (BWA ([29](#), [35](#), [???]), CircularMapper([1](#)))
 2. Mapping quality filtering (Samtools ([36](#)))
 3. PCR duplicate removal (DeDup([1](#)), Picard MarkDuplicates([37](#)))
 4. Mapping statistics generation (PreSeq([38](#)), Qualimap2([39](#)))
3. aDNA Evaluation and Modification
 1. Damage profiling (DamageProfiler([40](#)))
 2. aDNA reads selection (PMDTools([41](#)))
 3. Damage removal (Bamutils([42](#)))
 4. (Human) contamination estimation (ANGSD([43](#)))
4. Genotyping and Consensus Sequencing (GATK([37](#)), VCF2Genome([1](#)))

In nf-core/eager, all tools also originally used in EAGER have been updated to latest versions, as available on Bioconda([44](#)) and conda-forge([45](#)) to ensure widespread accessibility and stability of utilized tools. The MapDamage2([46](#)) and Schmutzi([47](#)) methods have not been carried over to nf-core/eager, the first because a more performant successor method (DamageProfiler) exists and the latter because a stable release of the method could not be migrated to Bioconda. We anticipate that there will be an updated version of Schmutzi in the near future, that will allow us to integrate the method again in nf-core/eager once a version is released on Bioconda. Support for Bowtie2([48](#)) will be added in the near future, after consultation with the nf-core user community. New tools to the basic workflow include fastp ([49](#)) for the removal of poly-G sequencing artefacts that are common in 2-colour Illumina sequencing machines (such as the increasingly popular NextSeq and NovaSeq platforms). We have also included the FreeBayes genotyper as an alternative to the human-focused GATK tools. We have also maintained the possibility of using the now unsupported GATK UnifiedGenotyper, as the GATK HaplotypeCaller performs *de novo* assembly around possible variants, which may not be suitable for low-coverage aDNA data.

We have further extended functionality of the pipeline, primarily focusing on allowing for ancient metagenomic analysis to be run alongside genomic of the reference genome. We have added the ability to screen all off-target reads from mapping to the supplied reference FASTA with two metagenomic profilers: MALT ([50](#), [51](#)) and Kraken2 ([52](#)). Characterisation of properties of authentic ancient DNA ([53](#)) from MALT alignments is carried out with the HOPS pipeline ([54](#)). The pipeline also integrates a SNP alignment generation tool, MultiVCFAnalyzer (doi:10.1038/nature13591), which allows assessment of level of cross-mapping to a reference genome from different related taxa - a common challenge in ancient bacteria genome reconstruction ([55](#)). Simple coverage statistics of particular annotations (e.g. genes) of an input reference is offered by bedtools ([56](#)).

New tools supplied with the pipeline include a dedicated 'endogenous DNA' calculator (endorS.py, by A.A.V), to provide an approximate level of on-target DNA yield within a sample. Secondly, ancient metagenomic studies may include comparative samples from living day individuals ([57](#)). To support open data, whilst respecting data privacy, nf-core/eager includes a 'strip_fastq' script (by M.B.) which creates raw FASTQ files but with reference-genome mapped reads removed. This then allows safe upload of sequencing data to public repositories with identifiable data removed. When using a human reference genome, nf-core/eager also can give estimates of the biological sex of a given individual with Sex.DetEERRmine ([58](#)).

A major upgrade in contrast to the previous EAGER version is that the new pipeline supports complex sequencing strategies for many samples. Given the large amount of sequencing often required to yield sufficient genome coverage from ancient DNA data, palaeogeneticists tend to use multiple

(differently treated) libraries or sequencing runs. As an alternative to direct paths to FASTQ or BAM files, the pipeline can also accept a TSV file which includes file paths and additional metadata such as sample name, library name, sequencing lane, colour chemistry and UDG treatment. This allows simultaneous processing and appropriate merging of heterogeneous data of multiple sequencing runs and/or libraries types.

Finally, the original EAGER tabular report format has been replaced with a much more extensive MultiQC ([59](#)) report. The original EAGER pipeline required users to look through many independent output directories and files to make full assessment of their sequencing data. Aggregation of all log files into a single interactive report will assist users in making fuller assessment of their sequencing and analysis runs. Most tools within nf-core/eager have a corresponding MultiQC module to ensure as complete evaluation as possible.

Accessibility

Alongside the portable new pipeline report, we have written extensive documentation on all parts of running and interpreting the output of the pipeline. Given that a large fraction of aDNA researchers come from fields such as social sciences that have limited computational training (such as J.A.F.Y), we have written documentation that also gives guidance on how to interpret each section of the report, specifically in the context of NGS and aDNA. This includes schematic images (by Z.F.) of best practices or expected output, published under CC-BY licenses to allow for use in other training material. This open-access resource will make the aDNA discipline more accessible to researchers new to the field, by providing practical and 'applied' knowledge to how aDNA characteristics translate to downstream analyses.

The development of nf-core/eager in nextflow and the nf-core initiative will also improve open-source community contributions to the pipeline. While Nextflow is written primarily in Groovy, the Nextflow DSL simplifies a number of concepts to an intermediate level that bioinformaticians without Java/Groovy experience can easily access (regardless of own programming language experience). Furthermore, Nextflow places ubiquitous and more widely known command-line interfaces, such as bash, in a prominent position within the code, rather than custom java code and classes. We hope this will motivate further bug fixes and feature contributions from the community to keep the pipeline updated with standard practises during a longer life-cycle. This will also be supported by the active and welcoming nf-core community who provide general guidance and advice on developing nextflow and nf-core pipelines.

Conclusion

nf-core/eager is an efficient, portable, and accessible pipeline for processing ancient DNA genomic data. The re-implementation with Nextflow and nf-core will improve reproducibility and inclusion of rapidly increasing ancient DNA datasets, for both large and small laboratories. Extensive documentation also enables newcomers to the field get a practical understanding on how to interpret ancient DNA in the context of NGS data processing. Ultimately, nf-core/eager provides easier access to the latest tools and routine screening analysis commonly used in the field, and sets up the pipeline for staying at the forefront of palaeogenetic analysis.

Methods

Installation

nf-core/eager requires Java, Nextflow and either a functional conda installation *or* Docker/Singularity container installation. A quick installation guide to follow to get started can be found in the *Quickstart* section in the nf-core/eager [documentation](#).

Running

After the installation, users can run the pipeline using standard test data by utilizing some of the `test` profiles we provide (e.g. using Docker):

```
nextflow run nf-core/eager -r 2.1.0 -profile test,docker
```

This will fetch testdata automatically, run the pipeline locally with all software tools containerized in a Docker container and store the output of that run in the `./results` folder of your current directory.

Profiles

We utilize a central configuration profile repository to enable users from various institutions to use pipelines on their particular infrastructure [more easily](#). For details on how to add your own profile to that repository, there are multiple resources listed in this repository to add your own configuration profile with help from the nf-core community.

Users can customize this infrastructure profile once by themselves, with the nf-core community, or with their local system administrator to make sure that the pipeline runs successfully and can then rely on the Nextflow and nf-core framework to ensure compatibility upon further infrastructure changes. For example, in order to run the nf-core/eager pipeline at the Max Planck Institute for the Science of Human History in Jena, users only have to run:

```
nextflow run nf-core/eager -r 2.1.0 -profile shh_cdag,test
```

This runs the testing profile of the nf-core/eager pipeline with parameters specifically adapted to the HPC system at the MPI-SHH. In some cases, similar institutional configs for other institutions may already exist (originally utilised for different nf-core pipelines), so users need not write their own.

Inputs

The pipeline can be started using (raw) FASTQ from sequencing or pre-mapped BAM files. Additionally, the pipeline requires a FASTA reference genome. If users have complex setups, e.g. multiple sequencing lanes that require merging of files for example, the pipeline can be supplied with a tabular separated value (TSV) file to enable such complex data handling.

Monitoring

Users can either monitor their pipeline execution on the using nextflow's console running messages or utilize projects such as [Nextflow Tower](#) to monitor their analysis pipeline during runtime.

Output

The pipeline produces several dozen output files in various file formats, with a more detailed listing available in the user documentation. This includes metrics, statistical analysis data and standardized output files (BAM, VCF) for close inspection and further downstream analysis, as well as a MultiQC

report. If a emailing daemon is setup on the server, the latter can even be emailed to users automatically, when starting the pipeline with a dedicated `--email you@yourdomain.org`.

Data and software availability

All code is available on github at <https://github.com/nf-core/eager> and archived with Zenodo under the DOI [10.5281/zenodo.1465061](https://doi.org/10.5281/zenodo.1465061). All test data is from the ENA public repository available under ENA IDs: **FIXME**

Competing Interests

No competing interests are declared.

Acknowledgements

We thank the nf-core community for general support and suggestions during the writing of the pipeline. We also thank Arielle Munters, Hester van Schalkwyk, Irina Velsko, Katerine Eaton, Luc Venturini, Marcel Keller, Pierre Lindenbaum, Pontus Skoglund, Raphael Eisenhofer, Torsten Günter, Kevin Lord for bug reports and feature suggestions. We are grateful to the members of the Department of Archaeogenetics at the Max Planck Institute for the Science of Human History who performed beta testing of the pipeline. We thank the aDNA twitter community for responding to polls regarding design decisions of the pipeline.

We also acknowledge Christina Warinner and the Max Planck Society who provided funds for travel to nf-core events.

References

1. **EAGER: efficient ancient genome reconstruction**

Alexander Peltzer, Günter Jäger, Alexander Herbig, Alexander Seitz, Christian Kniep, Johannes Krause, Kay Nieselt

Genome Biology (2016-03-31) <https://doi.org/gggzpk>

DOI: [10.1186/s13059-016-0918-z](https://doi.org/10.1186/s13059-016-0918-z) · PMID: [27036623](https://pubmed.ncbi.nlm.nih.gov/27036623/) · PMCID: [PMC4815194](https://pubmed.ncbi.nlm.nih.gov/PMC4815194/)

2. **Nextflow enables reproducible computational workflows**

Paolo Di Tommaso, Maria Chatzou, Evan W Floden, Pablo Prieto Barja, Emilio Palumbo, Cedric Notredame

Nature Biotechnology (2017-04-11) <https://doi.org/gfj52z>

DOI: [10.1038/nbt.3820](https://doi.org/10.1038/nbt.3820) · PMID: [28398311](https://pubmed.ncbi.nlm.nih.gov/28398311/)

3. **The nf-core framework for community-curated bioinformatics pipelines**

Philip A. Ewels, Alexander Peltzer, Sven Fillinger, Harshil Patel, Johannes Alneberg, Andreas Wilm, Maxime Ulysse Garcia, Paolo Di Tommaso, Sven Nahnsen

Nature Biotechnology (2020-02-13) <https://doi.org/ggk3qh>

DOI: [10.1038/s41587-020-0439-x](https://doi.org/10.1038/s41587-020-0439-x) · PMID: [32055031](https://pubmed.ncbi.nlm.nih.gov/32055031/)

4. **Complete Genomes Reveal Signatures of Demographic and Genetic Declines in the Woolly Mammoth**

Eleftheria Palkopoulou, Swapan Mallick, Pontus Skoglund, Jacob Enk, Nadin Rohland, Heng Li, Ayça Omrak, Sergey Vartanyan, Hendrik Poinar, Anders Götherström, ... Love Dalén

Current Biology (2015-05) <https://doi.org/34d>

DOI: [10.1016/j.cub.2015.04.007](https://doi.org/10.1016/j.cub.2015.04.007) · PMID: [25913407](https://pubmed.ncbi.nlm.nih.gov/25913407/) · PMCID: [PMC4439331](https://pubmed.ncbi.nlm.nih.gov/PMC4439331/)

5. **Recalibrating Equus evolution using the genome sequence of an early Middle Pleistocene horse**

Ludovic Orlando, Aurélien Ginolhac, Guojie Zhang, Duane Froese, Anders Albrechtsen, Mathias Stiller, Mikkel Schubert, Enrico Cappellini, Bent Petersen, Ida Moltke, ... Eske Willerslev

Nature (2013-06-26) <https://doi.org/q7n>

DOI: [10.1038/nature12323](https://doi.org/10.1038/nature12323) · PMID: [23803765](https://pubmed.ncbi.nlm.nih.gov/23803765/)

6. **Ancient pigs reveal a near-complete genomic turnover following their introduction to Europe**

Laurent A. F. Frantz, James Haile, Audrey T. Lin, Amelie Scheu, Christina Geörg, Norbert Benecke, Michelle Alexander, Anna Linderholm, Victoria E. Mullin, Kevin G. Daly, ... Greger Larson

Proceedings of the National Academy of Sciences (2019-08-27) <https://doi.org/gf9hnf>

DOI: [10.1073/pnas.1901169116](https://doi.org/10.1073/pnas.1901169116) · PMID: [31405970](https://pubmed.ncbi.nlm.nih.gov/31405970/) · PMCID: [PMC6717267](https://pubmed.ncbi.nlm.nih.gov/PMC6717267/)

7. **137 ancient human genomes from across the Eurasian steppes**

Peter de Barros Damgaard, Nina Marchi, Simon Rasmussen, Michaël Peyrot, Gabriel Renaud, Thorfinn Korneliussen, J. Víctor Moreno-Mayar, Mikkel Winther Pedersen, Amy Goldberg, Emma Usmanova, ... Eske Willerslev

Nature (2018-05-09) <https://doi.org/gd8hs5>

DOI: [10.1038/s41586-018-0094-2](https://doi.org/10.1038/s41586-018-0094-2) · PMID: [29743675](https://pubmed.ncbi.nlm.nih.gov/29743675/)

8. **A High-Coverage Genome Sequence from an Archaic Denisovan Individual**

M. Meyer, M. Kircher, M.-T. Gansauge, H. Li, F. Racimo, S. Mallick, J. G. Schraiber, F. Jay, K. Prufer, C. de Filippo, ... S. Paabo

Science (2012-08-30) <https://doi.org/q8p>

DOI: [10.1126/science.1224344](https://doi.org/10.1126/science.1224344) · PMID: [22936568](https://pubmed.ncbi.nlm.nih.gov/22936568/) · PMCID: [PMC3617501](https://pubmed.ncbi.nlm.nih.gov/PMC3617501/)

9. **Pre-Columbian mycobacterial genomes reveal seals as a source of New World human tuberculosis**
Kirsten I. Bos, Kelly M. Harkins, Alexander Herbig, Mireia Coscolla, Nico Weber, Iñaki Comas, Stephen A. Forrest, Josephine M. Bryant, Simon R. Harris, Verena J. Schuenemann, ... Johannes Krause
Nature (2014-08-20) <https://doi.org/f6nk4g>
DOI: [10.1038/nature13591](https://doi.org/10.1038/nature13591) · PMID: [25141181](https://pubmed.ncbi.nlm.nih.gov/25141181/) · PMCID: [PMC4550673](https://pubmed.ncbi.nlm.nih.gov/PMC4550673/)
10. **Integrative approach using *Yersinia pestis* genomes to revisit the historical landscape of plague during the Medieval Period**
Amine Namouchi, Meriam Guellil, Oliver Kersten, Stephanie Hänsch, Claudio Ottoni, Boris V. Schmid, Elsa Pacciani, Luisa Quaglia, Marco Vermunt, Egil L. Bauer, ... Barbara Bramanti
Proceedings of the National Academy of Sciences (2018-12-11) <https://doi.org/ggfn3h>
DOI: [10.1073/pnas.1812865115](https://doi.org/10.1073/pnas.1812865115) · PMID: [30478041](https://pubmed.ncbi.nlm.nih.gov/30478041/) · PMCID: [PMC6294933](https://pubmed.ncbi.nlm.nih.gov/PMC6294933/)
11. **Ancient genomes reveal a high diversity of *Mycobacterium leprae* in medieval Europe**
Verena J. Schuenemann, Charlotte Avanzi, Ben Krause-Kyora, Alexander Seitz, Alexander Herbig, Sarah Inskip, Marion Bonazzi, Ella Reiter, Christian Urban, Dorthe Dangvard Pedersen, ... Johannes Krause
PLOS Pathogens (2018-05-10) <https://doi.org/gdrj4v>
DOI: [10.1371/journal.ppat.1006997](https://doi.org/10.1371/journal.ppat.1006997) · PMID: [29746563](https://pubmed.ncbi.nlm.nih.gov/29746563/) · PMCID: [PMC5944922](https://pubmed.ncbi.nlm.nih.gov/PMC5944922/)
12. **Ancient hepatitis B viruses from the Bronze Age to the Medieval period**
Barbara Mühlemann, Terry C. Jones, Peter de Barros Damgaard, Morten E. Allentoft, Irina Shevnina, Andrey Logvin, Emma Usmanova, Irina P. Panyushkina, Bazartseren Boldgiv, Tsevel Bazartseren, ... Eske Willerslev
Nature (2018-05-09) <https://doi.org/gddxvj>
DOI: [10.1038/s41586-018-0097-z](https://doi.org/10.1038/s41586-018-0097-z) · PMID: [29743673](https://pubmed.ncbi.nlm.nih.gov/29743673/)
13. **Neolithic and medieval virus genomes reveal complex evolution of hepatitis B**
Ben Krause-Kyora, Julian Susat, Felix M Key, Denise Kühnert, Esther Bosse, Alexander Immel, Christoph Rinne, Sabin-Christin Kornell, Diego Yepes, Sören Franzenburg, ... Johannes Krause
eLife (2018-05-10) <https://doi.org/gdhck2>
DOI: [10.7554/elife.36666](https://doi.org/10.7554/elife.36666) · PMID: [29745896](https://pubmed.ncbi.nlm.nih.gov/29745896/) · PMCID: [PMC6008052](https://pubmed.ncbi.nlm.nih.gov/PMC6008052/)
14. **Ancient reveals the timing and persistence of organellar genetic bottlenecks over 3,000 years of sunflower domestication and improvement**
Nathan Wales, Melis Akman, Ray H. B. Watson, Fátima Sánchez Barreiro, Bruce D. Smith, Kristen J. Gremillion, M. Thomas P. Gilbert, Benjamin K. Blackman
Evolutionary Applications (2018-02-13) <https://doi.org/gf568v>
DOI: [10.1111/eva.12594](https://doi.org/10.1111/eva.12594) · PMID: [30622634](https://pubmed.ncbi.nlm.nih.gov/30622634/) · PMCID: [PMC6304678](https://pubmed.ncbi.nlm.nih.gov/PMC6304678/)
15. **The origins and adaptation of European potatoes reconstructed from historical genomes**
Rafal M. Gutaker, Clemens L. Weiß, David Ellis, Noelle L. Anglin, Sandra Knapp, José Luis Fernández-Alonso, Salomé Prat, Hernán A. Burbano
Nature Ecology & Evolution (2019-06-24) <https://doi.org/ggxkk8>
DOI: [10.1038/s41559-019-0921-3](https://doi.org/10.1038/s41559-019-0921-3) · PMID: [31235927](https://pubmed.ncbi.nlm.nih.gov/31235927/)
16. **The *Prevotella copri* Complex Comprises Four Distinct Clades Underrepresented in Westernized Populations**
Adrian Tett, Kun D. Huang, Francesco Asnicar, Hannah Fehlner-Peach, Edoardo Pasolli, Nicolai Karcher, Federica Armanini, Paolo Manghi, Kevin Bonham, Moreno Zolfo, ... Nicola Segata

Cell Host & Microbe (2019-11) <https://doi.org/ggc9dc>
DOI: [10.1016/j.chom.2019.08.018](https://doi.org/10.1016/j.chom.2019.08.018) · PMID: [31607556](https://pubmed.ncbi.nlm.nih.gov/31607556/) · PMCID: [PMC6854460](https://pubmed.ncbi.nlm.nih.gov/PMC6854460/)

17. CoproID predicts the source of coprolites and paleofeces using microbiome composition and host DNA content

Maxime Borry, Bryan Cordova, Angela Perri, Marsha Wibowo, Tanvi Prasad Honap, Jada Ko, Jie Yu, Kate Britton, Linus Girdland-Flink, Robert C. Power, ... Christina Warinner
PeerJ (2020-04-17) <https://doi.org/dr8x>
DOI: [10.7717/peerj.9001](https://doi.org/10.7717/peerj.9001) · PMID: [32337106](https://pubmed.ncbi.nlm.nih.gov/32337106/) · PMCID: [PMC7169968](https://pubmed.ncbi.nlm.nih.gov/PMC7169968/)

18. Pathogens and host immunity in the ancient human oral cavity

Christina Warinner, João F Matias Rodrigues, Rounak Vyas, Christian Trachsel, Natallia Shved, Jonas Grossmann, Anita Radini, Y Hancock, Raul Y Tito, Sarah Fiddyment, ... Enrico Cappellini
Nature Genetics (2014-02-23) <https://doi.org/r4n>
DOI: [10.1038/ng.2906](https://doi.org/10.1038/ng.2906) · PMID: [24562188](https://pubmed.ncbi.nlm.nih.gov/24562188/) · PMCID: [PMC3969750](https://pubmed.ncbi.nlm.nih.gov/PMC3969750/)

19. Neanderthal behaviour, diet, and disease inferred from ancient DNA in dental calculus

Laura S. Weyrich, Sebastian Duchene, Julien Soubrier, Luis Arriola, Bastien Llamas, James Breen, Alan G. Morris, Kurt W. Alt, David Caramelli, Veit Dresely, ... Alan Cooper
Nature (2017-03-08) <https://doi.org/f9szrm>
DOI: [10.1038/nature21674](https://doi.org/10.1038/nature21674) · PMID: [28273061](https://pubmed.ncbi.nlm.nih.gov/28273061/)

20. Fifty thousand years of Arctic vegetation and megafaunal diet

Eske Willerslev, John Davison, Mari Moora, Martin Zobel, Eric Coissac, Mary E. Edwards, Eline D. Lorenzen, Mette Vestergård, Galina Gussarova, James Haile, ... Pierre Taberlet
Nature (2014-02-05) <https://doi.org/f2zr4s>
DOI: [10.1038/nature12921](https://doi.org/10.1038/nature12921) · PMID: [24499916](https://pubmed.ncbi.nlm.nih.gov/24499916/)

21. Neandertal and Denisovan DNA from Pleistocene sediments

Viviane Slon, Charlotte Hopfe, Clemens L. Weiß, Fabrizio Mafessoni, Marco de la Rasilla, Carles Lalueza-Fox, Antonio Rosas, Marie Soressi, Monika V. Knul, Rebecca Miller, ... Matthias Meyer
Science (2017-05-12) <https://doi.org/b6jd>
DOI: [10.1126/science.aam9695](https://doi.org/10.1126/science.aam9695) · PMID: [28450384](https://pubmed.ncbi.nlm.nih.gov/28450384/)

22. Plasmodium vivax Malaria Viewed through the Lens of an Eradicated European Strain

Lucy van Dorp, Pere Gelabert, Adrien Rieux, Marc de Manuel, Toni de-Dios, Shyam Gopalakrishnan, Christian Carøe, Marcela Sandoval-Velasco, Rosa Fregel, Iñigo Olalde, ... Carles Lalueza-Fox
Molecular Biology and Evolution (2020-03) <https://doi.org/ggqzq2>
DOI: [10.1093/molbev/msz264](https://doi.org/10.1093/molbev/msz264) · PMID: [31697387](https://pubmed.ncbi.nlm.nih.gov/31697387/) · PMCID: [PMC7038659](https://pubmed.ncbi.nlm.nih.gov/PMC7038659/)

23. Paging through history: parchment as a reservoir of ancient DNA for next generation sequencing

M. D. Teasdale, N. L. van Doorn, S. Fiddyment, C. C. Webb, T. O'Connor, M. Hofreiter, M. J. Collins, D. G. Bradley
Philosophical Transactions of the Royal Society B: Biological Sciences (2015-01-19)
<https://doi.org/ggqzq3>
DOI: [10.1098/rstb.2013.0379](https://doi.org/10.1098/rstb.2013.0379) · PMID: [25487331](https://pubmed.ncbi.nlm.nih.gov/25487331/) · PMCID: [PMC4275887](https://pubmed.ncbi.nlm.nih.gov/PMC4275887/)

24. A 5700 year-old human genome and oral microbiome from chewed birch pitch

Theis Z. T. Jensen, Jonas Niemann, Katrine Højholt Iversen, Anna K. Fotakis, Shyam Gopalakrishnan, Åshild J. Vågene, Mikkel Winther Pedersen, Mikkel-Holger S. Sinding, Martin R. Ellegaard, Morten E. Allentoft, ... Hannes Schroeder

Nature Communications (2019-12-17) <https://doi.org/ggfm6x>
DOI: [10.1038/s41467-019-13549-9](https://doi.org/10.1038/s41467-019-13549-9) · PMID: [31848342](https://pubmed.ncbi.nlm.nih.gov/31848342/) · PMCID: [PMC6917805](https://pubmed.ncbi.nlm.nih.gov/PMC6917805/)

25. Ancient DNA from mastics solidifies connection between material culture and genetics of mesolithic hunter-gatherers in Scandinavia

Natalija Kashuba, Emrah Kirdök, Hege Damlien, Mikael A. Manninen, Bengt Nordqvist, Per Persson, Anders Götherström

Communications Biology (2019-05-15) <https://doi.org/gggzqz>
DOI: [10.1038/s42003-019-0399-1](https://doi.org/10.1038/s42003-019-0399-1) · PMID: [31123709](https://pubmed.ncbi.nlm.nih.gov/31123709/) · PMCID: [PMC6520363](https://pubmed.ncbi.nlm.nih.gov/PMC6520363/)

26. The Beaker phenomenon and the genomic transformation of northwest Europe

Iñigo Olalde, Selina Brace, Morten E. Allentoft, Ian Armit, Kristian Kristiansen, Thomas Booth, Nadin Rohland, Swapan Mallick, Anna Szécsényi-Nagy, Alissa Mittnik, ... David Reich

Nature (2018-02-21) <https://doi.org/gcx74m>
DOI: [10.1038/nature25738](https://doi.org/10.1038/nature25738) · PMID: [29466337](https://pubmed.ncbi.nlm.nih.gov/29466337/) · PMCID: [PMC5973796](https://pubmed.ncbi.nlm.nih.gov/PMC5973796/)

27. A draft genome of *Yersinia pestis* from victims of the Black Death

Kirsten I. Bos, Verena J. Schuenemann, G. Brian Golding, Hernán A. Burbano, Nicholas Waglechner, Brian K. Coombes, Joseph B. McPhee, Sharon N. DeWitte, Matthias Meyer, Sarah Schmedes, ... Johannes Krause

Nature (2011-10-12) <https://doi.org/fk87wk>
DOI: [10.1038/nature10549](https://doi.org/10.1038/nature10549) · PMID: [21993626](https://pubmed.ncbi.nlm.nih.gov/21993626/) · PMCID: [PMC3690193](https://pubmed.ncbi.nlm.nih.gov/PMC3690193/)

28. Characterization of ancient and modern genomes by SNP detection and phylogenomic and metagenomic analysis using PALEOMIX

Mikkel Schubert, Luca Ermini, Clio Der Sarkissian, Hákon Jónsson, Aurélien Ginolhac, Robert Schaefer, Michael D Martin, Ruth Fernández, Martin Kircher, Molly McCue, ... Ludovic Orlando

Nature Protocols (2014-04-10) <https://doi.org/f5x3qm>
DOI: [10.1038/nprot.2014.063](https://doi.org/10.1038/nprot.2014.063) · PMID: [24722405](https://pubmed.ncbi.nlm.nih.gov/24722405/)

29. Fast and accurate short read alignment with Burrows-Wheeler transform

H. Li, R. Durbin

Bioinformatics (2009-05-18) <https://doi.org/dqt59j>
DOI: [10.1093/bioinformatics/btp324](https://doi.org/10.1093/bioinformatics/btp324) · PMID: [19451168](https://pubmed.ncbi.nlm.nih.gov/19451168/) · PMCID: [PMC2705234](https://pubmed.ncbi.nlm.nih.gov/PMC2705234/)

30. mapDamage: testing for damage patterns in ancient DNA sequences

Aurélien Ginolhac, Morten Rasmussen, M. Thomas P. Gilbert, Eske Willerslev, Ludovic Orlando

Bioinformatics (2011-08-01) <https://doi.org/cn45v7>
DOI: [10.1093/bioinformatics/btr347](https://doi.org/10.1093/bioinformatics/btr347) · PMID: [21659319](https://pubmed.ncbi.nlm.nih.gov/21659319/)

31. Early Divergent Strains of *Yersinia pestis* in Eurasia 5,000 Years Ago

Simon Rasmussen, Morten Erik Allentoft, Kasper Nielsen, Ludovic Orlando, Martin Sikora, Karl-Göran Sjögren, Anders Gorm Pedersen, Mikkel Schubert, Alex Van Dam, Christian Mollin Outzen Kapel, ... Eske Willerslev

Cell (2015-10) <https://doi.org/f3mxqd>
DOI: [10.1016/j.cell.2015.10.009](https://doi.org/10.1016/j.cell.2015.10.009) · PMID: [26496604](https://pubmed.ncbi.nlm.nih.gov/26496604/) · PMCID: [PMC4644222](https://pubmed.ncbi.nlm.nih.gov/PMC4644222/)

32. The Stone Age Plague and Its Persistence in Eurasia

Aida Andrades Valtueña, Alissa Mittnik, Felix M. Key, Wolfgang Haak, Raili Allmäe, Andrej Belinskij, Mantas Daubaras, Michal Feldman, Rimantas Jankauskas, Ivor Janković, ... Johannes Krause

Current Biology (2017-12) <https://doi.org/cgmjv>
DOI: [10.1016/j.cub.2017.10.025](https://doi.org/10.1016/j.cub.2017.10.025) · PMID: [29174893](https://pubmed.ncbi.nlm.nih.gov/29174893/)

33. **Improving ancient DNA read mapping against modern reference genomes**
Mikkel Schubert, Aurelien Ginolhac, Stinus Lindgreen, John F Thompson, Khaled AS AL-Rasheid, Eske Willerslev, Anders Krogh, Ludovic Orlando
BMC Genomics (2012) <https://doi.org/gb3ff7>
DOI: [10.1186/1471-2164-13-178](https://doi.org/10.1186/1471-2164-13-178) · PMID: [22574660](https://pubmed.ncbi.nlm.nih.gov/22574660/) · PMCID: [PMC3468387](https://pubmed.ncbi.nlm.nih.gov/PMC3468387/)
34. **AdapterRemoval v2: rapid adapter trimming, identification, and read merging**
Mikkel Schubert, Stinus Lindgreen, Ludovic Orlando
BMC Research Notes (2016-02-12) <https://doi.org/gfzqhb>
DOI: [10.1186/s13104-016-1900-2](https://doi.org/10.1186/s13104-016-1900-2) · PMID: [26868221](https://pubmed.ncbi.nlm.nih.gov/26868221/) · PMCID: [PMC4751634](https://pubmed.ncbi.nlm.nih.gov/PMC4751634/)
35. **Fast and accurate long-read alignment with Burrows–Wheeler transform**
Heng Li, Richard Durbin
Bioinformatics (2010-03-01) <https://doi.org/cm27kg>
DOI: [10.1093/bioinformatics/btp698](https://doi.org/10.1093/bioinformatics/btp698) · PMID: [20080505](https://pubmed.ncbi.nlm.nih.gov/20080505/) · PMCID: [PMC2828108](https://pubmed.ncbi.nlm.nih.gov/PMC2828108/)
36. **The Sequence Alignment/Map format and SAMtools**
H. Li, B. Handsaker, A. Wysoker, T. Fennell, J. Ruan, N. Homer, G. Marth, G. Abecasis, R. Durbin, 1000 Genome Project Data Processing Subgroup
Bioinformatics (2009-06-08) <https://doi.org/ff6426>
DOI: [10.1093/bioinformatics/btp352](https://doi.org/10.1093/bioinformatics/btp352) · PMID: [19505943](https://pubmed.ncbi.nlm.nih.gov/19505943/) · PMCID: [PMC2723002](https://pubmed.ncbi.nlm.nih.gov/PMC2723002/)
37. **The Genome Analysis Toolkit: A MapReduce framework for analyzing next-generation DNA sequencing data**
A. McKenna, M. Hanna, E. Banks, A. Sivachenko, K. Cibulskis, A. Kernytsky, K. Garimella, D. Altshuler, S. Gabriel, M. Daly, M. A. DePristo
Genome Research (2010-07-19) <https://doi.org/bnzbn6>
DOI: [10.1101/gr.107524.110](https://doi.org/10.1101/gr.107524.110) · PMID: [20644199](https://pubmed.ncbi.nlm.nih.gov/20644199/) · PMCID: [PMC2928508](https://pubmed.ncbi.nlm.nih.gov/PMC2928508/)
38. **Predicting the molecular complexity of sequencing libraries**
Timothy Daley, Andrew D Smith
Nature Methods (2013-02-24) <https://doi.org/gfx6f5>
DOI: [10.1038/nmeth.2375](https://doi.org/10.1038/nmeth.2375) · PMID: [23435259](https://pubmed.ncbi.nlm.nih.gov/23435259/) · PMCID: [PMC3612374](https://pubmed.ncbi.nlm.nih.gov/PMC3612374/)
39. **Qualimap 2: advanced multi-sample quality control for high-throughput sequencing data**
Konstantin Okonechnikov, Ana Conesa, Fernando García-Alcalde
Bioinformatics (2015-10-01) <https://doi.org/ggxrmx>
DOI: [10.1093/bioinformatics/btv566](https://doi.org/10.1093/bioinformatics/btv566) · PMID: [26428292](https://pubmed.ncbi.nlm.nih.gov/26428292/) · PMCID: [PMC4708105](https://pubmed.ncbi.nlm.nih.gov/PMC4708105/)
40. **Integrative-Transcriptomics/DamageProfiler: DamageProfiler v0.4.9**
Judith Neukamm, Alexander Peltzer
Zenodo (2019-11-29) <https://doi.org/ggxrmz>
DOI: [10.5281/zenodo.3557708](https://doi.org/10.5281/zenodo.3557708)
41. **Separating endogenous ancient DNA from modern day contamination in a Siberian Neandertal**
Pontus Skoglund, Bernd H. Northoff, Michael V. Shunkov, Anatoli P. Derevianko, Svante Pääbo, Johannes Krause, Mattias Jakobsson
Proceedings of the National Academy of Sciences (2014-02-11) <https://doi.org/f2z5sw>
DOI: [10.1073/pnas.1318934111](https://doi.org/10.1073/pnas.1318934111) · PMID: [24469802](https://pubmed.ncbi.nlm.nih.gov/24469802/) · PMCID: [PMC3926038](https://pubmed.ncbi.nlm.nih.gov/PMC3926038/)
42. **An efficient and scalable analysis framework for variant extraction and refinement from population-scale DNA sequence data**

Goo Jun, Mary Kate Wing, Gonalo R. Abecasis, Hyun Min Kang
Genome Research (2015-06) <https://doi.org/f7dz2d>
DOI: [10.1101/gr.176552.114](https://doi.org/10.1101/gr.176552.114) · PMID: [25883319](https://pubmed.ncbi.nlm.nih.gov/25883319/) · PMCID: [PMC4448687](https://pubmed.ncbi.nlm.nih.gov/PMC4448687/)

43. ANGSD: Analysis of Next Generation Sequencing Data

Thorfinn Sand Korneliussen, Anders Albrechtsen, Rasmus Nielsen
BMC Bioinformatics (2014-11-25) <https://doi.org/gb8wpz>
DOI: [10.1186/s12859-014-0356-4](https://doi.org/10.1186/s12859-014-0356-4) · PMID: [25420514](https://pubmed.ncbi.nlm.nih.gov/25420514/) · PMCID: [PMC4248462](https://pubmed.ncbi.nlm.nih.gov/PMC4248462/)

44. Bioconda: sustainable and comprehensive software distribution for the life sciences

Björn Grüning, Ryan Dale, Andreas Sjödin, Brad A. Chapman, Jillian Rowe, Christopher H. Tomkins-Tinch, Renan Valieris, Johannes Köster, The Bioconda Team
Nature Methods (2018-07-02) <https://doi.org/gd2xzp>
DOI: [10.1038/s41592-018-0046-7](https://doi.org/10.1038/s41592-018-0046-7) · PMID: [29967506](https://pubmed.ncbi.nlm.nih.gov/29967506/)

45. conda-forge | community driven packaging for conda<https://conda-forge.org/>

46. mapDamage2.0: fast approximate Bayesian estimates of ancient DNA damage parameters

Hákon Jónsson, Aurélien Ginolhac, Mikkel Schubert, Philip L. F. Johnson, Ludovic Orlando
Bioinformatics (2013-07) <https://doi.org/gb5g2t>
DOI: [10.1093/bioinformatics/btt193](https://doi.org/10.1093/bioinformatics/btt193) · PMID: [23613487](https://pubmed.ncbi.nlm.nih.gov/23613487/) · PMCID: [PMC3694634](https://pubmed.ncbi.nlm.nih.gov/PMC3694634/)

47. Schmutzi: estimation of contamination and endogenous mitochondrial consensus calling for ancient DNA

Gabriel Renaud, Viviane Slon, Ana T. Duggan, Janet Kelso
Genome Biology (2015-10-12) <https://doi.org/f72mvg>
DOI: [10.1186/s13059-015-0776-0](https://doi.org/10.1186/s13059-015-0776-0) · PMID: [26458810](https://pubmed.ncbi.nlm.nih.gov/26458810/) · PMCID: [PMC4601135](https://pubmed.ncbi.nlm.nih.gov/PMC4601135/)

48. Fast gapped-read alignment with Bowtie 2

Ben Langmead, Steven L Salzberg
Nature Methods (2012-03-04) <https://doi.org/gd2xzn>
DOI: [10.1038/nmeth.1923](https://doi.org/10.1038/nmeth.1923) · PMID: [22388286](https://pubmed.ncbi.nlm.nih.gov/22388286/) · PMCID: [PMC3322381](https://pubmed.ncbi.nlm.nih.gov/PMC3322381/)

49. fastp: an ultra-fast all-in-one FASTQ preprocessor

Shifu Chen, Yanqing Zhou, Yaru Chen, Jia Gu
Bioinformatics (2018-09-01) <https://doi.org/gd9mrb>
DOI: [10.1093/bioinformatics/bty560](https://doi.org/10.1093/bioinformatics/bty560) · PMID: [30423086](https://pubmed.ncbi.nlm.nih.gov/30423086/) · PMCID: [PMC6129281](https://pubmed.ncbi.nlm.nih.gov/PMC6129281/)

50. MALT: Fast alignment and analysis of metagenomic DNA sequence data applied to the Tyrolean Iceman

Alexander Herbig, Frank Maixner, Kirsten I. Bos, Albert Zink, Johannes Krause, Daniel H. Huson
bioRxiv (2016-04-27) <https://doi.org/ggxkk9>
DOI: [10.1101/050559](https://doi.org/10.1101/050559)

51. Salmonella enterica genomes from victims of a major sixteenth-century epidemic in Mexico

Åshild J. Vågene, Alexander Herbig, Michael G. Campana, Nelly M. Robles García, Christina Warinner, Susanna Sabin, Maria A. Spyrou, Aida Andrades Valtueña, Daniel Huson, Noreen Tuross, ... Johannes Krause
Nature Ecology & Evolution (2018-01-15) <https://doi.org/ggxkk7>
DOI: [10.1038/s41559-017-0446-6](https://doi.org/10.1038/s41559-017-0446-6) · PMID: [29335577](https://pubmed.ncbi.nlm.nih.gov/29335577/)

52. Improved metagenomic analysis with Kraken 2

Derrick E. Wood, Jennifer Lu, Ben Langmead

Genome Biology (2019-11-28) <https://doi.org/ggfk55>
DOI: [10.1186/s13059-019-1891-0](https://doi.org/10.1186/s13059-019-1891-0) · PMID: [31779668](https://pubmed.ncbi.nlm.nih.gov/31779668/) · PMCID: [PMC6883579](https://pubmed.ncbi.nlm.nih.gov/PMC6883579/)

53. Patterns of damage in genomic DNA sequences from a Neandertal

A. W. Briggs, U. Stenzel, P. L. F. Johnson, R. E. Green, J. Kelso, K. Prufer, M. Meyer, J. Krause, M. T. Ronan, M. Lachmann, S. Paabo

Proceedings of the National Academy of Sciences (2007-08-21) <https://doi.org/bs4w7h>

DOI: [10.1073/pnas.0704665104](https://doi.org/10.1073/pnas.0704665104) · PMID: [17715061](https://pubmed.ncbi.nlm.nih.gov/17715061/) · PMCID: [PMC1976210](https://pubmed.ncbi.nlm.nih.gov/PMC1976210/)

54. HOPS: automated detection and authentication of pathogen DNA in archaeological remains

Ron Hübler, Felix M. Key, Christina Warinner, Kirsten I. Bos, Johannes Krause, Alexander Herbig

Genome Biology (2019-12-16) <https://doi.org/ggxkmb>

DOI: [10.1186/s13059-019-1903-0](https://doi.org/10.1186/s13059-019-1903-0) · PMID: [31842945](https://pubmed.ncbi.nlm.nih.gov/31842945/) · PMCID: [PMC6913047](https://pubmed.ncbi.nlm.nih.gov/PMC6913047/)

55. A Robust Framework for Microbial Archaeology

Christina Warinner, Alexander Herbig, Allison Mann, James A. Fellows Yates, Clemens L. Weiß, Hernán A. Burbano, Ludovic Orlando, Johannes Krause

Annual Review of Genomics and Human Genetics (2017-08-31) <https://doi.org/gf5wqv>

DOI: [10.1146/annurev-genom-091416-035526](https://doi.org/10.1146/annurev-genom-091416-035526) · PMID: [28460196](https://pubmed.ncbi.nlm.nih.gov/28460196/) · PMCID: [PMC5581243](https://pubmed.ncbi.nlm.nih.gov/PMC5581243/)

56. BEDTools: a flexible suite of utilities for comparing genomic features

Aaron R. Quinlan, Ira M. Hall

Bioinformatics (2010-03-15) <https://doi.org/cmrms3>

DOI: [10.1093/bioinformatics/btq033](https://doi.org/10.1093/bioinformatics/btq033) · PMID: [20110278](https://pubmed.ncbi.nlm.nih.gov/20110278/) · PMCID: [PMC2832824](https://pubmed.ncbi.nlm.nih.gov/PMC2832824/)

57. Microbial differences between dental plaque and historic dental calculus are related to oral biofilm maturation stage

Irina M. Velsko, James A. Fellows Yates, Franziska Aron, Richard W. Hagan, Laurent A. F. Frantz, Louise Loe, Juan Bautista Rodriguez Martinez, Eros Chaves, Chris Gosden, Greger Larson, Christina Warinner

Microbiome (2019-07-06) <https://doi.org/ggxkmc>

DOI: [10.1186/s40168-019-0717-3](https://doi.org/10.1186/s40168-019-0717-3) · PMID: [31279340](https://pubmed.ncbi.nlm.nih.gov/31279340/) · PMCID: [PMC6612086](https://pubmed.ncbi.nlm.nih.gov/PMC6612086/)

58. Ancient Fennoscandian genomes reveal origin and spread of Siberian ancestry in Europe

Thiseas C. Lamnidis, Kerttu Majander, Choongwon Jeong, Elina Salmela, Anna Wessman, Vyacheslav Moiseyev, Valery Khartanovich, Oleg Balanovsky, Matthias Ongyerth, Antje Weihmann, ... Stephan Schiffels

Nature Communications (2018-11-27) <https://doi.org/ggxkk6>

DOI: [10.1038/s41467-018-07483-5](https://doi.org/10.1038/s41467-018-07483-5)

59. MultiQC: summarize analysis results for multiple tools and samples in a single report

Philip Ewels, Måns Magnusson, Sverker Lundin, Max Käller

Bioinformatics (2016-10-01) <https://doi.org/f3s996>

DOI: [10.1093/bioinformatics/btw354](https://doi.org/10.1093/bioinformatics/btw354) · PMID: [27312411](https://pubmed.ncbi.nlm.nih.gov/27312411/) · PMCID: [PMC5039924](https://pubmed.ncbi.nlm.nih.gov/PMC5039924/)