

Mitigating Racial Bias in Clinical Prediction Models: A D3M-Inspired Data Selection Approach

DBDS Student Talks Presentation

Rebecca Hurwitz

May 5, 2025

Agenda

1. Research Question Formulation
2. Experimental Outline
3. Background
4. Results
5. Analysis
6. Future Directions
7. Acknowledgments

Research Question Formulation

What are computational strategies to mitigate race-based outputs in LLMs?

- Machine learning models often reflect biases present in training data.
- Models inadvertently learn and amplify these biases, leading to unfair or inaccurate predictions.
- The sheer size of datasets makes it impossible to manually check and correct every data point.
- This necessitates **automated methods for debiasing datasets.**

What are computational strategies to mitigate race-based outputs in LLMs?

What are computational strategies to mitigate race-based outputs in LLMs?

What is the application area in which I will ask and answer this question?

Experimental Outline

- **Objective:** Improve worst subgroup performance for racial, protected, and underresourced groups using debiased fine-tuning.

Experimental Outline

- **Objective:** Improve worst subgroup performance for racial, protected, and underresourced groups using debiased fine-tuning.
- **Method:** Apply data selection method (D3M-inspired) to balance training datasets.

Experimental Outline

- **Objective:** Improve worst subgroup performance for racial, protected, and underresourced groups using debiased fine-tuning.
- **Method:** Apply data selection method (D3M-inspired) to balance training datasets.
- **Expected Outcome:** Boost accuracy in underperforming subgroups and achieve fairer, more robust models.

Background

How do we quantify data's impact in training?

- **Data attribution:** the task of predicting model outputs/behavior at test-time as a function of the input training data.
- In other words: *What would happen if I trained the model on a given subset of my training set?*

Background

- **TRAK**: data attribution method giving us coefficients (scores) to help identify examples that exacerbate discrepancies in group performance
- **D3M**: allows us to actually remove the examples and retrain on a dataset without the harmful examples

The diagram illustrates the TRAK attribution formula, $A_i = \frac{\sum_{g \in \mathcal{G}} \exp(\beta \ell_g) \cdot \tau(g)_i}{\sum_{g' \in \mathcal{G}} \exp(\beta \ell_{g'})}$, with callouts explaining its components:

- Top-left callout:** we set $\beta = 1$ (hyperparameter controlling the smoothness of the maximum)
- Top-right callout:** loss of a base classifier $\theta(S)$ on group g (evaluated on the validation set)
- Bottom-left callout:** group alignment score: the impact of training sample i on the overall worst-group performance
- Bottom-right callout:** the i -th coefficient for group g

The formula itself is centered, with arrows pointing from the callouts to the corresponding parts of the equation: β in the exponent, ℓ_g in the exponent, $\tau(g)_i$ in the numerator, and $\ell_{g'}$ in the denominator.


TRAK: Tracing with the Randomly-projected After Kernel

Algorithm 1 TRAK for multi-class classifiers (as implemented)

```
1: Input: Learning algorithm  $\mathcal{A}$ , dataset  $S$  of size  $n$ , sampling fraction  $\alpha \in (0, 1]$ , correct-class  
   likelihood function  $p(z; \theta)$ , projection dimension  $k \in \mathbb{N}$   
2: Output: Matrix of attribution scores  $\mathbf{T} \in \mathbb{R}^{n \times n}$   
3:  $f(z; \theta) := \log(\frac{p(z; \theta)}{1 - p(z; \theta)})$  ▷ Margin function  $f_\theta$   
4: for  $m \in \{1, \dots, M\}$  do  
5:   Sample random  $S' \subset S$  of size  $\alpha \cdot n$   
6:    $\theta_m^* \leftarrow \mathcal{A}(S')$  ▷ Train a model on  $S'$   
7:    $\mathbf{P} \sim \mathcal{N}(0, 1)^{p \times k}$  ▷ Sample projection matrix  
8:    $\mathbf{Q}^{(m)} \leftarrow \mathbf{0}_{n \times n}$   
9:   for  $i \in \{1, \dots, n\}$  do  
10:     $\phi_i \leftarrow \mathbf{P}^\top \nabla_\theta f(z_i; \theta_m^*)$  ▷ Compute gradient at  $\theta_m^*$  and project to  $k$  dimensions  
11:     $\mathbf{Q}_{ii}^{(m)} \leftarrow 1 - p(z_i; \theta_m^*)$  ▷ Compute weighting term  
12:   end for  
13:    $\Phi_m \leftarrow [\phi_1; \dots; \phi_n]^\top$   
14: end for  
15:  $\mathbf{T} \leftarrow \left[ \frac{1}{m} \sum_{m=1}^M \Phi_m (\Phi_m^\top \Phi_m)^{-1} \Phi_m^\top \right] \left[ \frac{1}{m} \sum_{m=1}^M \mathbf{Q}^{(m)} \right]$   
16: return SOFT-THRESHOLD( $\mathbf{T}$ )
```

D3M: Data Debiasing via Datamodeling

Training data correlation between **class (species)** and **extra feature (color)** leads to disparate performance.



Goal: “debias” dataset to improve *worst-group accuracy* (WGA):

$$\text{WGA} = \min_{\text{group} \in \{\text{beige dog}, \text{black dog}, \text{beige cat}, \text{black cat}\}} \text{Acc}(\text{group})$$

D3M: Data Debiasing via Datamodeling

Our approach: Data Debiasing via Datamodeling (D3M)

Compute impact of each training sample on WGA by predicting WGA as a function of dataset selection.

Worst-group accuracy on a (small) validation set

“Group alignment score”
Learned coefficient; impact of point i on WGA

$$\text{WGA} \approx \sum D_i \cdot A_i$$

Binary; whether we select the i -th training sample


Find selection that maximizes worst-group accuracy by removing most harmful examples.




- + Only changes data
- + Competitive accuracy
- + Less accuracy gap
- + Only needs test set labels

D3M: Data Debiasing via Datamodeling

- Given a training dataset S_{train} and a validation dataset S_{val} , produce a classifier f to minimize **worst case loss** over predefined subpopulations



What are computational strategies to mitigate race-based outputs in LLMs?



What is the application area in which I will ask and answer this question?

What are computational strategies to mitigate race-based outputs in LLMs?

Which datasets/models/techniques can I use to accomplish this?

What is the application area in which I will ask and answer this question?

Experimental Plan

Experimental Plan

- **Datasets:** MIMIC-CXR (metadata) + MIMIC-CXR-JPG (images and CheXpert labels) + MIMIC-IV (demographic/racial data)
- **Models:** ResNet-9, ResNet-50
- **Procedure:** Break down 14 classes into binary datasets. Find the classes with the most discrepancies between groups. Train model - after 5 epochs training, apply 10 epochs of D3M + separately 10 epochs of normal training (15 each).


What are computational strategies to mitigate race-based outputs in LLMs?

Which datasets/models/techniques can I use to accomplish this?

What is the application area in which I will ask and answer this question?

What are computational strategies to mitigate race-based outputs in ML models?

Experimental Plan




Results

TRAK

Top scoring TRAK images from the train set

Target: No Finding




No Finding



No Finding




No Finding



No Finding




No Finding



Worst Group Accuracies

Method	Worst Group Accuracy (%)				
	Cardiomegaly	Atalectasis	Support Devices	Pleural Effusion	Lung Opacity
ResNet-50	86.5%	87.7%	88.5%	84.9%	63.6%
ResNet-50 + D3M	87.6%	87.0%	92.3%	88.4%	54.6%

Worst Group Accuracies



Cardiomegaly

Race	Accuracy (%)			Δ	Δ in n
	ResNet-50 (n)	ResNet-50 + D3M (n)			
Asian	100.0 (65)	100.0 (51)	0.0		-14
★ Black or African American	86.5 (336)	87.6 (291)	+1.1		-45
Hispanic/Latino	92.1 (148)	92.1 (132)	0.0		-16
Other	95.2 (60)	95.2 (52)	0.0		-8
Unknown	93.9 (425)	93.9 (393)	0.0		-32
White	89.4 (1072)	88.3 (976)	-1.1		-96
Overall	90.5 (2108)	90.1 (1897)	0.0		-211

Support Devices

Race	Accuracy (%)			Δ in n
	ResNet-50 (n)	ResNet-50 + D3M (n)	Δ	
Asian	100.0 (65)	100.0 (48)	0.0	-17
Black or African American	98.9 (336)	98.9 (293)	0.0	-43
★ Hispanic/Latino	88.5 (148)	92.3 (139)	+3.8	-9
Other	100.0 (60)	100.0 (64)	0.0	4
Unknown	97.2 (425)	97.4 (377)	+0.2	-48
White	88.9 (1072)	89.3 (976)	+0.4	-96
Overall	93.0 (2108)	93.4 (1897)	0.4	-211

Atalectasis

Race	Accuracy (%)			Δ in n
	ResNet-50 (n)	ResNet-50 + D3M (n)	Δ	
Asian	93.8 (65)	93.8 (52)	0.0	-13
Black or African American	92.8 (336)	92.8 (299)	0.0	-37
Hispanic/Latino	91.4 (148)	91.4 (128)	0.0	-20
Other	91.7 (60)	95.8 (50)	+4.1	-10
Unknown	90.8 (425)	89.1 (373)	-1.7	-52
White	87.7 (1072)	87.0 (971)	-0.7	-101
Overall	89.8 (2108)	89.2 (1897)	-0.6	-211


Pleural Effusion

Race	Accuracy (%)			Δ in n
	ResNet-50 (n)	ResNet-50 + D3M (n)	Δ	
Asian	100.0 (65)	100.0 (59)	0.0	-6
★ Black or African American	84.9 (336)	88.4 (303)	+3.5	-33
Hispanic/Latino	91.9 (148)	86.5 (133)	-5.4	-15
Other	100.0 (60)	100.0 (54)	0.0	-6
Unknown	95.9 (425)	94.9 (355)	-1.0	-70
White	88.4 (1072)	89.1 (971)	+0.7	-101
Overall	90.1 (2108)	90.5 (1897)	0.4	-211

Lung Opacity

Race	Accuracy (%)			Δ	Δ in n
	ResNet-50 (n)	ResNet-50 + D3M (n)			
★ Asian	63.6 (65)	54.6 (60)	-9.1		-5
Black or African American	87.3 (336)	82.3 (299)	-5.0		-37
Hispanic/Latino	87.6 (148)	87.5 (132)	-0.1		-16
Other	89.5 (60)	89.5 (52)	0.0		-8
Unknown	92.6 (425)	92.3 (379)	-0.3		-46
White	85.2 (1072)	85.2 (975)	0.0		-97
Overall	86.7 (2108)	85.8 (1897)	-0.9		-211

Worst Group Accuracies



Quick note on D3M examples removed

```
def get_debiased_train_indices(
    self, group_alignment_scores, use_heuristic=True, num_to_discard=None
):
    """
    If use_heuristic is True, training examples with negative score will be discarded,
    and the parameter num_to_discard will be ignored
    Otherwise, the num_to_discard training examples with lowest scores will be discarded.
    """
    if use_heuristic:
        return [i for i, score in enumerate(group_alignment_scores) if score >= 0]

    if num_to_discard is None:
        raise ValueError("num_to_discard must be specified if not using heuristic.")

    sorted_indices = sorted(
        range(len(group_alignment_scores)),
        key=lambda i: group_alignment_scores[i],
    )
    return sorted_indices[num_to_discard:]
```

Analysis

Analysis

- **Did it work?** D3M increased accuracy of some subgroups but decreased accuracy of others.
- **Considerations:** Dataset size, domain, type of classification.
- **Purpose:** The intended purpose of D3M in our context was specifically to improve accuracy of minority groups.

What are computational strategies to mitigate race-based outputs in LLMs?

Which datasets/models/techniques can I use to accomplish this?

What is the application area in which I will ask and answer this question?

What are computational strategies to mitigate race-based outputs in ML models?

What are computational strategies to mitigate race-based outputs in LLMs?

Which datasets/models/techniques can I use to accomplish this?

What is the application area in which I will ask and answer this question?

What are computational strategies to mitigate race-based outputs in ML models?

Future Directions

- More data!
- Error analysis - what examples contributed to misclassification, specifically for which race?
- Other tasks beyond chest x-rays

Thank You!

Huge thank you to Nigam!

Acknowledgements



Research funded by
T15LM007033



Dept of Biomedical Data Science:

Sylvia Plevritis
Dennis Wall
Karen Matthys
Iffat Ahmed
Asmaa Eljibahi
Erica Peterson



Shah Lab

Shah Lab:
Nigam Shah
Alyssa Unell

Citations

Park, S. M., Georgiev, K., Ilyas, A., Leclerc, G., & Madry, A. (2023). TRAK: Attributing Model Behavior at Scale. arXiv preprint arXiv:2303.14186.

Jain, S., Hamidieh, K., Georgiev, K., Ilyas, A., Ghassemi, M., & Madry, A. (2024). Data Debiasing with Datamodels (D3M): Improving Subgroup Robustness via Data Selection. arXiv preprint arXiv:2406.16846.

I learned SO MUCH this rotation!

- Cuda
- Semaphore
- Not to use the login node
- Research Park
- Srun
- Importance of word choice

Background

- **TRAK**: data attribution method giving us coefficients (scores) to help identify examples that exacerbate discrepancies in group performance
- **D3M**: allows us to actually remove the examples and retrain on a dataset without the harmful examples