



SRD
MACHINES
By Sharda Industries



Leading supplier of Versatile Special Purpose Machines
(SPMs) for bearing components in Gujarat.

Fully Automatic Online/Offline Measuring Machine



- In Process Measuring, Post Process Measuring, In-line Measuring Module.
- Automatic Measuring Machine with High-Accuracy Production.
- It can be of online Measuring or offline Measuring Machine.

Operation Type

1. Multi-dimensional Measuring Unit
2. Dimension Checking for.
 - A. OD
 - B. Lug Height Checking
 - C. Bore
 - D. Width / Height
3. Post-process Gauges
4. 100% Dimension checking module in line
5. Radial Clearance Checking Module (RC Checking)
6. Tilting Unit (One Side feeding machine)
7. Dynamic measuring

Specifications

Speed	: Depends on Size and Operation
Accuracy	: $\pm 0.5\mu$ as required
Machine Grade	: Automatic. Auto loading and unloading, In-between machines, and available with Auto feeder.
Control System	: PLC Control/CNC Control - as per requirements
Unique Features	: 1. Multi-Measuring 2. Parameter wise separate rejection bin
Dimension(L x W)	: Customize as per job.

Auto CNC/PLC-Controlled Grinding Machine



- Automatic Grinding Machine with Auto Loading/Unloading.

Types Of Models

1.Internal Grinding

- With Oscillation
- Plunge cut

2.External Grinding — Centerless

- With Regulating wheel — Plunge cut/ through feed
- With Magnetic clamping

Operation Type

- 1.Bore Grinding
- 2.OD Grinding
- 3.Shaft Grinding
- 4.Raceway,'Track Grinding
- 5.Lip Grinding
- 6.Tip Grinding – Textile Spindle Shaft
- 7.Conjugate Grinding

Suitable For

- 1.Deep Groove Ball bearing (DGBB)
- 2.Taper roller bearing (TRB)
 - Conjugate Grinding(Three operations at a time)
- 3.Cylindrical Roller bearing (CRB)
- 4.Textile Shaft OD Profile Grinding
- 5.Textile Shaft Tip Grinding

Specifications

Accuracy	: > Surface finish -0.2 μ Ra, ii) Roundness - less than 1 μ , iii) Suitable for P5-P6 Class bearing production.
Machine Grade	: Automatic, Semi-automatic, With/without IPG.
Slides controls	: Servo Controlled. - Glass Scale for High Accuracy
Control System	: PLC Control / CNC Control / Motion Control - as per requirements
Other	: Conjugate Grinding
Dimension(L x W)	: According to design - In general 8 ft. x 6 ft.
Weight	: Internal Grinding machine : Up to 2 - 4 tons External Grinding machine : Up to 3 - 7 tons
Auto Balancer	
Profile Diamond dresser	
NC Dressing	
Can be comply with CBN Wheel	

Parting Machine With Feeder Table



- Mass Production Machine for Parting Operation.
- All Types of Material Can be Cut with Auto Pipe Feeder Table.
- Widely used in Auto Component Manufacturing.

Operation Type

- 1.OD / ID Chamfer and parting
- 2.Facing and Parting
- 3.OD and Parting
- 4.Bore and parting

Types Of Models

Sr. No.	Particulars	Models			
		PT-40	PT-75	PT-105	Customised
1	Tube/Pipe Dia.	8 mm to 40 mm	30 mm to 74 mm	74 mm to 104 mm	Can be Customised as per Requirements
2	Max. Tube/Pipe Length	20 ft.	20 ft.	20 ft.	
3	Max. Tube/Pipe Length	10 ft.	-	-	
4	Parting Size	as per Requirements	as per Requirements	as per Requirements	

Specifications

Material : All types of material (parting possible of welded pipe also).

Capacity : Cycle time - 3.5 seconds, and more with loading and unloading.

Accuracy : 50μ in parting width.

Machine Grade : Automatic.

Control System : PLC control / CNC control (as per requirement).

Tube/Pipe Length : Upto 6 Meter

Weight : Up to 1 ton with feeder table.

Fully Automatic Turning Line-Inter Connected Machines



- Automatic Turning Machine Line for High-Volume Production.
- CNC/PLC
- Auto Feeder Table
- Hard Part Turning
- For High Accuracy, High Production, High Cmk, Cost saving with Low Cycle Time, Low Tooling Cost, Low Production Cost.

Operation Type

All types of turning operations for Mass Production with Auto Loading.

E.g. OD, IO, Chamfer-Radius, Knurling, Threading, Hard part turning, and any other turning operation.

Suitable For

1. Component Dia. 8mm-52mm, Width-10mm to 60mm
2. Fully customized as per customer requirements.

Specifications

Material : All types of Materials.

Speed Cycle time : > 2.5 seconds, including loading and unloading.

Clamping types : 20

Machine Grade : Collet/Chuck. Internal or External clamping as per requirement

Slides controls : Servo/Hydraulic Controlled.

Control System : PLC Control / CNC Control - as per requirements

Other

1. Auto Loading and Unloading, Interlinking between machines and Auto feeder.
2. Multi-operational in one tool post and multi-tool post
3. Dry (Without coolant) Cutting

Dimension(L x W) : 5 feet x 4 feet

Fully Automatic SPM Turning Machine



- Automatic Turning Machine fine for High-Volume Production.
- Automatic Turning Machine with Auto Feeder Table.
- For High Accuracy, High Production, High Cmk, High Finishing, High Cost Saving with Low Cycle Time, Low Tooling Cost, Low Production Cost, Low Production Loss, Low Raw Material Cost.

Operation Type

All types of turning operation for Mass Production.

E.g OD,ID,Chamfer Radius, Knurling, Threading

Suitable For

- 1.Component Dia. 8 mm - 130 mm, Width - 10 mm to 60mm
- 2.Soft and hard Part Turning
- 3.Fully customized as per customer requirements.

Specifications

Material	: All types of materials (turning possible of welded pipe also)..
Speed Cycle time	: > 2.5 seconds, including loading and unloading.
Accuracy	: 20μ
Clamping types	: Collet/chuck. internal or external clamping as per requirement
Automation Grade : Auto loading Unloading and auto feeder.	
Slides controls	: Servo/Hydraulic controlled.
Control System	: PLC Control / CNC Control - as per requirements
Processing Type	: Hard Part Turning & Soft Part Turning
Other	: Multi-operational in one tool post and multi-tool post
Dimension(L x W)	: 6 feet x 5 feet
Weight	: Up to 1.5 ton .



- Multi Parameter checking.
- Out-of-value components / Reject components will automatically be thrown out into the respective rejection box.
- Dynamic ECT is done on both sides for O.D, Bore.

We Can Offer Below Types Of Models

1.Only ECT checking with double Station cycle & O.D. and Bore Single Station
4 Seconds

2.ECT + Visual – Full:
ECT: O.D + Bore + Face (Both Sides)
Visual: O.D + Bore

3.ECT – Full (Both Sides): O.D + Bore + Face

4.ECT + Visual:
ECT: O.D + Bore (Both Sides)
Visual: O.D + Bore

5.ECT – Both Sides: O.D + Bore

6.ECT + Visual – Full + Track:
ECT: O.D + Bore + Face (Both Sides) +
Track Visual: O.D + Bore

Specifications

Compact Design

Speed Cycle time : Depends on component size and model (2 sec to 5 sec)

Calibration : Auto Calibration

Machine grade : Fully automatic. Auto feeder, auto transfer from one station to another, in-between machines

Control system : PLC control (as per requirements)

Other : Displays graphical representation and data storage can be offered

We can provide spares and services Also provide service for required modification in future (If possible)

Our Valued Customers

SCHAEFFLER



SKF

nbc

flexible solutions

CK BIRLA GROUP



NBI®



Ravi Technoforge Private

SAURER.



BOYD
CORPORATION



Columbia®
MACHINE ENGINEERING (I) PVT. LTD.



AGRASEN



Solar
DIAMOND



SRD
MACHINES
By Sharda Industries



www.srdmachines.com



sales@srdmachines.com



Survey No. 159, Block No. 190/P1,
Raman Gamdi, G.I.D.C. Por, Vadodara - 391243



+91-9427189659 / +91 94263 89395