

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)


Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:



Hardware

CPU Name: 06/8f
Max MHz:
Nominal:
Enabled: cores, 1 chip, threads/core
Orderable:
Cache L1:
L2:
L3:
Other:
Memory: 1.785 GB fixme: If using DDR4, the format is:
'N GB (N x N GB nRxn PC4-nnnnX-X)'
Storage: 51 GB add more disk info here
Other:

Software

OS: Ubuntu 24.04 LTS
6.8.0-35-generic
Compiler: C/C++/Fortran: Version 10.1.0 of GCC, the
GNU Compiler Collection
Parallel: No
Firmware:
File System: ext4
System State: Run level 5 (add definition here)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other:
Power Management:

Errors

'reportable' flag not set during run
531.deepsjeng_r (base) did not have enough runs!
520.omnetpp_r (base) did not have enough runs!
500.perlbench_r (base) did not have enough runs!
523.xalancbmk_r (base) did not have enough runs!
557.xz_r (base) did not have enough runs!
502.gcc_r (base) did not have enough runs!
541.leela_r (base) did not have enough runs!
548.exchange2_r (base) did not have enough runs!
505.mcf_r (base) did not have enough runs!
525.x264_r (base) did not have enough runs!

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Errors (Continued)

502.gcc_r (base) had invalid runs!

Run of 502.gcc_r (base) was not valid; status is RE

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r	1	201	7.91											
502.gcc_r	1	4025	0.00											
505.mcf_r	1	286	5.64											
520.omnetpp_r	1	277	4.74											
523.xalancbmk_r	1	196	5.39											
525.x264_r	1	146	12.0											
531.deepsjeng_r	1	259	4.43											
541.leela_r	1	359	4.61											
548.exchange2_r	1	133	19.7											
557.xz_r	1	320	3.38											

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Environment Variables Notes

Environment variables set by runcpu before the start of the run:

LD_LIBRARY_PATH = "/usr/lib64/:/usr/lib/:/lib64"

Platform Notes

Sysinfo program /home/tdx/speccpu2017/bin/sysinfo
Rev: r6732 of 2022-11-07 fe91c89b7ed5c36ae2c92cc097bec197
running on tdx-guest Sun Oct 27 06:55:57 2024

SUT (System Under Test) info as seen by some common utilities.

Table of contents

1. uname -a
2. w
3. Username
4. ulimit -a
5. sysinfo process ancestry
6. /proc/cpuinfo
7. lscpu
8. numactl --hardware
9. /proc/meminfo

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Platform Notes (Continued)

```
10. who -r
11. Systemd service manager version: systemd 255 (255.4-lubuntu8.1)
12. Failed units, from systemctl list-units --state=failed
13. Services, from systemctl list-unit-files
14. Linux kernel boot-time arguments, from /proc/cmdline
15. cpupower frequency-info
16. sysctl
17. /sys/kernel/mm/transparent_hugepage
18. /sys/kernel/mm/transparent_hugepage/khugepaged
19. OS release
20. Disk information
21. /sys/devices/virtual/dmi/id
22. dmidecode
23. BIOS
-----

1. uname -a
Linux tdx-guest 6.8.0-35-generic #35-Ubuntu SMP PREEMPT_DYNAMIC Mon May 20 15:51:52 UTC 2024 x86_64 x86_64
x86_64 GNU/Linux
-----

2. w
 06:55:57 up 2:18, 1 user, load average: 2.60, 3.98, 4.64
USER  TTY      FROM          LOGIN@   IDLE   JCPU   PCPU WHAT
root   hvc0      -             05:34   1:19m  2.44s  0.02s w
-----

3. Username
From environment variable $USER: root
-----

4. ulimit -a
time(seconds)      unlimited
file(blocks)       unlimited
data(kbytes)       unlimited
stack(kbytes)      8192
coredump(blocks)   0
memory(kbytes)     unlimited
locked memory(kbytes) 233908
process            7107
nofiles            1024
vmemory(kbytes)    unlimited
locks              unlimited
rtprio             0
-----

5. sysinfo process ancestry
/sbin/init
/bin/login -p --
-bash
runcpu --config=tdx2.cfg --tune=base --size=ref all
runcpu --configfile tdx2.cfg --tune base --size ref --noreportable --nopower --runmode rate --tune base
--size refrate intrate --nopreenv --note-preenv --logfile
$SPEC/tmp/CPU2017.016/temlogs/preenv.intrate.016.2.log --lognum 016.2 --from_runcpu 2
specperl $SPEC/bin/sysinfo
$SPEC = /home/tdx/speccpu2017
-----

6. /proc/cpuinfo
```

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Platform Notes (Continued)

```
model name      : 06/8f
vendor_id       : GenuineIntel
cpu family      : 6
model           : 143
stepping        : 8
microcode       : 0x2b0005d1
bugs            : spectre_v1 spectre_v2 spec_store_bypass swapgs eibrs_porsb bhi
cpu cores       : 16
siblings        : 16
1 physical ids (chips)
16 processors (hardware threads)
physical id 0: core ids 0-15
physical id 0: apicids 0-15
```

Caution: /proc/cpuinfo data regarding chips, cores, and threads is not necessarily reliable, especially for virtualized systems. Use the above data carefully.

7. lscpu

From lscpu from util-linux 2.39.3:

```
Architecture:          x86_64
CPU op-mode(s):        32-bit, 64-bit
Address sizes:          52 bits physical, 57 bits virtual
Byte Order:             Little Endian
CPU(s):                 16
On-line CPU(s) list:   0-15
Vendor ID:              GenuineIntel
BIOS Vendor ID:        QEMU
Model name:             06/8f
BIOS Model name:        pc-q35-8.2 CPU @ 2.0GHz
BIOS CPU family:        1
CPU family:             6
Model:                  143
Thread(s) per core:    1
Core(s) per socket:    16
Socket(s):              1
Stepping:               8
BogoMIPS:               4800.00
Flags:                  fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat
                        clflush dts mmx fxsr sse sse2 ss ht tm syscall nx pdpe1gb rdtscp lm
                        constant_tsc bts rep_good nopl tsc_reliable nonstop_tsc cpuid
                        tsc_known_freq pni pclmulqdq dtes64 ds_cpl sse3 fma cx16 pdcm pcid
                        sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx
                        f16c rdrand hypervisor lahf_lm abm 3dnowprefetch cpuid_fault ssbd
                        ibrs ibpb stibp ibrs_enhanced tdx_guest fgsgbase bmi1 avx2 smep bmi2
                        erms invpcid avx512f avx512dq rdseed adx smap avx512ifma clflushopt
                        clwb avx512cd sha_ni avx512bw avx512vl xsaveopt xsavec xgetbv1 xsaves
                        avx_vnni avx512_bf16 wbnoinvd avx512vbmi umip pku ospke avx512_vbmi2
                        gfni vaes vpclmulqdq avx512_vnni avx512_bitalg avx512_vpopcntdq la57
                        rdpid bus_lock_detect cldemote movdiri movdir64b fsrm md_clear
                        serialize tsxldtrk amx_bf16 avx512_fp16 amx_tile amx_int8 flush_l1d
                        arch_capabilities
Hypervisor vendor:     KVM
Virtualization type:   full
L1d cache:             512 KiB (16 instances)
L1i cache:             512 KiB (16 instances)
L2 cache:              64 MiB (16 instances)
L3 cache:              16 MiB (1 instance)
NUMA node(s):          1
NUMA node0 CPU(s):     0-15
```

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Platform Notes (Continued)

Vulnerability Gather data sampling: Not affected
Vulnerability Itlb multihit: Not affected
Vulnerability Lltf: Not affected
Vulnerability Mds: Not affected
Vulnerability Meltdown: Not affected
Vulnerability Mmio stale data: Not affected
Vulnerability Reg file data sampling: Not affected
Vulnerability Retbleed: Not affected
Vulnerability Spec rstack overflow: Not affected
Vulnerability Spec store bypass: Mitigation; Speculative Store Bypass disabled via prctl
Vulnerability Spectre v1: Mitigation; usercopy/swapgs barriers and __user pointer sanitization
Vulnerability Spectre v2: Mitigation; Enhanced / Automatic IBRS; IBPB conditional; RSB filling; PBRSE-eIBRS SW sequence; BHI BHI_DIS_S
Vulnerability Srbds: Not affected
Vulnerability Tsx async abort: Not affected

From lscpu --cache:

NAME	ONE-SIZE	ALL-SIZE	WAYS	TYPE	LEVEL	SETS	PHY-LINE	COHERENCY-SIZE
L1d	32K	512K	8	Data	1	64	1	64
L1i	32K	512K	8	Instruction	1	64	1	64
L2	4M	64M	16	Unified	2	4096	1	64
L3	16M	16M	16	Unified	3	16384	1	64

8. numactl --hardware

NOTE: a numactl 'node' might or might not correspond to a physical chip.

available: 1 nodes (0)
node 0 cpus: 0-15
node 0 size: 1827 MB
node 0 free: 1314 MB
node distances:
node 0
0: 10

9. /proc/meminfo

MemTotal: 1871280 kB

10. who -r

run-level 5 Oct 27 04:37

11. Systemd service manager version: systemd 255 (255.4-lubuntu8.1)

Default Target: Status
graphical degraded

12. Failed units, from systemctl list-units --state=failed

UNIT	LOAD	ACTIVE	SUB	DESCRIPTION
* fwupd-refresh.service	loaded	failed	failed	Refresh fwupd metadata and update motd
* user@0.service	loaded	failed	failed	User Manager for UID 0

Legend: LOAD -> Reflects whether the unit definition was properly loaded.
ACTIVE -> The high-level unit activation state, i.e. generalization of SUB.
SUB -> The low-level unit activation state, values depend on unit type.
2 loaded units listed.

13. Services, from systemctl list-unit-files

STATE	UNIT FILES
-------	------------

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Platform Notes (Continued)

enabled ModemManager apparmor appport blk-availability cloud-config cloud-final cloud-init cloud-init-local console-setup cron dmesg e2scrub_reap finalrd getty@ grub-common grub-initrd-fallback keyboard-setup lvm2-monitor multipathd networkd-dispatcher open-iscsi open-vm-tools rsyslog secureboot-db setvtrgb snapd ssh sysstat systemd-networkd systemd-networkd-wait-online systemd-pstore systemd-resolved systemd-timesyncd ua-reboot-cmds ubuntu-advantage udisks2 ufw unattended-upgrades vgauth

enabled-runtime netplan-ovs-cleanup systemd-fsck-root systemd-remount-fs

disabled console-getty debug-shell iscsid nftables rsync systemd-boot-check-no-failures systemd-confext systemd-network-generator systemd-networkd-wait-online@ systemd-pcrlock-file-system systemd-pcrlock-firmware-code systemd-pcrlock-firmware-config systemd-pcrlock-machine-id systemd-pcrlock-make-policy systemd-pcrlock-secureboot-authority systemd-pcrlock-secureboot-policy systemd-sysexit systemd-time-wait-sync

indirect serial-getty@ systemd-sysupdate systemd-sysupdate-reboot uidd

masked cryptdisks cryptdisks-early hwclock multipath-tools-boot pollinate screen-cleanup sudo x11-common

14. Linux kernel boot-time arguments, from /proc/cmdline
BOOT_IMAGE=/vmlinuz-6.8.0-35-generic
root=UUID=41106c9c-97fc-4396-8622-4f692c8c5ba1
ro
console=tty1
console=ttyS0

15. cpupower frequency-info
analyzing CPU 6:
Unable to determine current policy
boost state support:
Supported: no
Active: no

16. sysctl
kernel.numa_balancing 0
kernel.randomize_va_space 2
vm.compaction_proactiveness 20
vm.dirty_background_bytes 0
vm.dirty_background_ratio 10
vm.dirty_bytes 0
vm.dirty_expire_centisecs 3000
vm.dirty_ratio 20
vm.dirty_writeback_centisecs 500
vm.dirtytime_expire_seconds 43200
vm.extfrag_threshold 500
vm.min_unmapped_ratio 1
vm.nr_hugepages 0
vm.nr_hugepages_mempolicy 0
vm.nr_overcommit_hugepages 0
vm.swappiness 60
vm.watermark_boost_factor 15000
vm.watermark_scale_factor 10
vm.zone_reclaim_mode 0

17. /sys/kernel/mm/transparent_hugepage
defrag always defer defer+madvise [madvise] never
enabled always [madvise] never
hpage_pmd_size 2097152

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Platform Notes (Continued)

shmem_enabled always within_size advise [never] deny force

18. /sys/kernel/mm/transparent_hugepage/khugepaged

alloc_sleep_millisecs 60000

defrag 1

max_ptes_none 511

max_ptes_shared 256

max_ptes_swap 64

pages_to_scan 4096

scan_sleep_millisecs 10000

19. OS release

From /etc/*-release /etc/*-version

os-release Ubuntu 24.04 LTS

20. Disk information

SPEC is set to: /home/tdx/speccpu2017

Filesystem	Type	Size	Used	Avail	Use%	Mounted on
/dev/vda1	ext4	51G	19G	33G	37%	/

21. /sys/devices/virtual/dmi/id

Vendor: QEMU

Product: Standard PC (Q35 + ICH9, 2009)

22. dmidecode

Additional information from dmidecode 3.5 follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

Memory:

1x QEMU Not Specified 2 GB

23. BIOS

(This section combines info from /sys/devices and dmidecode.)

BIOS Vendor: Ubuntu distribution of EDK II

BIOS Version: 2024.02-3+tdx1.0

BIOS Date: 07/03/2024

BIOS Revision: 0.0

Compiler Version Notes

C | 500.perlbench_r(base) 502.gcc_r(base) 505.mcf_r(base) 525.x264_r(base) 557.xz_r(base)

gcc (Ubuntu 13.2.0-23ubuntu4) 13.2.0

Copyright (C) 2023 Free Software Foundation, Inc.

This is free software; see the source for copying conditions. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

C++ | 520.omnetpp_r(base) 523.xalancbmk_r(base) 531.deepsjeng_r(base) 541.leela_r(base)

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Compiler Version Notes (Continued)

g++ (Ubuntu 13.2.0-23ubuntu4) 13.2.0

Copyright (C) 2023 Free Software Foundation, Inc.

This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

Fortran | 548.exchange2_r(base)

GNU Fortran (Ubuntu 13.2.0-23ubuntu4) 13.2.0

Copyright (C) 2023 Free Software Foundation, Inc.

This is free software; see the source for copying conditions. There is NO
warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

Base Compiler Invocation

C benchmarks:

gcc

C++ benchmarks:

g++

Fortran benchmarks:

gfortran

Base Portability Flags

500.perlbench_r: -DSPEC_LINUX_X64 -DSPEC_LP64

502.gcc_r: -DSPEC_LP64

505.mcf_r: -DSPEC_LP64

520.omnetpp_r: -DSPEC_LP64

523.xalancbmk_r: -DSPEC_LINUX -DSPEC_LP64

525.x264_r: -DSPEC_LP64

531.deepsjeng_r: -DSPEC_LP64

541.leela_r: -DSPEC_LP64

548.exchange2_r: -DSPEC_LP64

557.xz_r: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

-m64 -std=c99 -g -O3 -march=native -fno-strict-aliasing

-fno-unsafe-math-optimizations -fno-finite-math-only -fgnu89-inline

(Continued on next page)

SPEC CPU®2017 Integer Rate Result

Copyright 2017-2024 Standard Performance Evaluation Corporation

My Corporation

SPECrate®2017_int_base = 6.42

SPECrate®2017_int_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation

Tested by: My Corporation

Test Date: Oct-2024

Hardware Availability:

Software Availability:

Base Optimization Flags (Continued)

C++ benchmarks:

-m64 -std=c++03 -g -O3 -march=native

Fortran benchmarks:

-m64 -g -O3 -march=native

Base Other Flags

C benchmarks:

-fcommon

SPEC CPU and SPECrate are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU®2017 v1.1.9 on 2024-10-27 06:55:56+0000.

Report generated on 2024-10-27 08:40:28 by CPU2017 PDF formatter v6716.