PageSpeed Insights

Copy Link | Docs

Report from Apr 30, 2025, 10:02:09 AM

https://redplug.com.mx/ | Analyze

Mobile | Desktop

Discover what your real users are experiencing

No Data

Diagnose performance issues

97	95	100	100
Performance	Accessibility	Best Practices	SEO

Performance

97

Values are estimated and may vary. The performance score is calculated directly from these metrics. See calculator.

▲ 0–49 ■ 50–89 ● 90–100

METRICS — Expand view

- First Contentful Paint: 1.7 s
- Largest Contentful Paint: 2.3 s
- Total Blocking Time: 90 ms
- Cumulative Layout Shift: 0.025
- Speed Index: 2.6 s

Captured at Apr 30, 2025, 10:02 AM CDT | Initial page load | Emulated Moto G Power with Lighthouse 12.4.0 | Slow 4G throttling | Single page session | Using HeadlessChromium 134.0.6998.165 with lr

View Treemap

Show audits relevant to: All | FCP | LCP | TBT | CLS

DIAGNOSTICS

Reduce unused JavaScript — Potential savings of 103 KiB

Reduce unused JavaScript and defer loading scripts until they are required to decrease bytes consumed by network activity. Learn how to reduce unused JavaScript. LCP FCP

URL	Transfer Size	Potential Savings
redplug.com.mx 1st Party	223.1 KiB	102.7 KiB
/_nuxt/DmFBuD2t.js (redplug.com.mx)	177.1 KiB	82.1 KiB
/_nuxt/BXmeWFfj.js (redplug.com.mx)	46.0 KiB	20.6 KiB

Avoid an excessive DOM size — 1,105 elements

A large DOM will increase memory usage, cause longer style calculations, and produce costly layout reflows. Learn how to avoid an excessive DOM size. TBT

Statistic	Element	Value
Total DOM Elements		1,105
Maximum DOM Depth	Red Plug Website website?1.webp">	13
Maximum Child Elements	main > section#welcome > div#slider > svg.absolute <svg width="1600" height="640" class="absolute inset-0 h-full border border-gray-400/30 [mask-image:radia...">	640

Reduce JavaScript execution time — 2.4 s

Consider reducing the time spent parsing, compiling, and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to reduce JavaScript execution time. TBT

URL	Total CPU Time	Script Evaluation	Script Parse
redplug.com.mx 1st Party	3,271 ms	2,260 ms	11 ms
/_nuxt/BXmeWFfj.js (redplug.com.mx)	2,278 ms	1,753 ms	0 ms
https://redplug.com.mx	649 ms	166 ms	9 ms
/_nuxt/DmFBuD2t.js (redplug.com.mx)	344 ms	342 ms	2 ms
Unattributable	239 ms	88 ms	0 ms
Unattributable	239 ms	88 ms	0 ms

Minimize main-thread work — 3.5 s

Consider reducing the time spent parsing, compiling and executing JS. You may find delivering smaller JS payloads helps with this. Learn how to minimize main-thread work. TBT

Category	Time Spent
Script Evaluation	2,358 ms
Other	408 ms
Style & Layout	400 ms
Rendering	171 ms
Garbage Collection	153 ms
Parse HTML & CSS	34 ms
Script Parsing & Compilation	12 ms

Image elements do not have explicit width and height

Set an explicit width and height on image elements to reduce layout shifts and improve CLS. Learn how to set image dimensions. CLS

Use the `nuxt/image` component and specify explicit `width` and `height`. Learn more.

URL	
redplug.com.mx 1st Party	
Red Plug Logo `<img onerror="this.setAttribute('data-error', 1)" height="300" alt="Red Plug Logo" data-nuxt-img="" srcset="/_ipx/h_300:logo/red-plug-responsive.svg 1x, /_ipx/h_600:logo/red-plug-res..." class="inline-block mr-2 h-16 md:h-20" src="https://redplug.com.mx/_ipx/h_600:logo/red-plug-responsive.svg">`	.logo/red-plug-responsive.svg (redplug.com.mx)
Red Plug Logo `<img onerror="this.setAttribute('data-error', 1)" height="300" alt="Red Plug Logo" data-nuxt-img="" srcset="/_ipx/h_300:logo/red-plug-responsive.svg 1x, /_ipx/h_600:logo/red-plug-res..." class="h-16 md:h-18 inline-block mr-2" src="https://redplug.com.mx/_ipx/h_600:logo/red-plug-responsive.svg">`	.logo/red-plug-responsive.svg (redplug.com.mx)

Serve static assets with an efficient cache policy — 32 resources found

A long cache lifetime can speed up repeat visits to your page. Learn more about efficient cache policies.

Show 3rd-party resources (1)

URL	Cache TTL	Transfer Size
redplug.com.mx 1st Party		839 KiB
/_nuxt/DmFBuD2t.js (redplug.com.mx)	10m	178 KiB
...carlos-alfonso-stylist-portfolio1.webp (redplug.com.mx)	10m	115 KiB
/fonts/YEFRbyxgb...woff (redplug.com.mx)	10m	69 KiB
/fonts/JasQUv7tY...woff (redplug.com.mx)	10m	67 KiB
/fonts/C6qVQ0ow...woff (redplug.com.mx)	10m	66 KiB
/_nuxt/BXmeWFfj.js (redplug.com.mx)	10m	47 KiB
/fonts/ocFSgIsel...woff2 (redplug.com.mx)	10m	43 KiB
...red-plug-website-2/1.webp (redplug.com.mx)	10m	41 KiB
...andres-lopez-portfolio1.webp (redplug.com.mx)	10m	41 KiB
...red-plug-website1.webp (redplug.com.mx)	10m	27 KiB
/fonts/KD1nbdFj...woff (redplug.com.mx)	10m	25 KiB
/fonts/Onoeqpb4...woff (redplug.com.mx)	10m	25 KiB
/fonts/laXuKgTTc...woff (redplug.com.mx)	10m	24 KiB
/_nuxt/D4FaqPUp.js (redplug.com.mx)	10m	11 KiB
/_nuxt/CN6eKhQ8.js (redplug.com.mx)	10m	8 KiB
/_nuxt/CGWGqfqr.js (redplug.com.mx)	10m	6 KiB
/_nuxt/RJYKDPw.js (redplug.com.mx)	10m	5 KiB
/_nuxt/9eLZgyYO.js (redplug.com.mx)	10m	4 KiB
/_nuxt/CasSCdwW.js (redplug.com.mx)	10m	4 KiB
/_nuxt/Ctc8y77M.js (redplug.com.mx)	10m	4 KiB
/_nuxt/DZuSDdHk.js (redplug.com.mx)	10m	4 KiB
/_nuxt/Bq9cUw-Aw.js (redplug.com.mx)	10m	3 KiB
/_nuxt/BUS1kFMA.js (redplug.com.mx)	10m	3 KiB
...logo/red-plug-responsive.svg (redplug.com.mx)	10m	2 KiB
/_nuxt/CMCTUS0y.js (redplug.com.mx)	10m	2 KiB
/_nuxt/DgcVSena.js (redplug.com.mx)	10m	1 KiB
/_nuxt/BILSuYSn.js (redplug.com.mx)	10m	1 KiB
/_nuxt/kmZqDEWt.js (redplug.com.mx)	10m	1 KiB
/_nuxt/DZ2uNbfX.js (redplug.com.mx)	10m	1 KiB
/_nuxt/BzY5rRfR.js (redplug.com.mx)	10m	1 KiB
/_nuxt/index-bQ0-tXYd.css (redplug.com.mx)	10m	1 KiB
ahrefs.com		2 KiB
/analytics.js (analytics.ahrefs.com)	None	2 KiB

Properly size images — Potential savings of 185 KiB

Serve images that are appropriately-sized to save cellular data and improve load time. Learn how to size images. LCP FCP

Use the `nuxt/image` component and set the appropriate `sizes`. Learn more.

URL	Resource Size	Potential Savings
redplug.com.mx 1st Party	321.2 KiB	184.8 KiB
Carlos Alfonso Stylist `<img width="900" height="500" alt="Carlos Alfonso Stylist" data-nuxt-img="" srcset="/_ipx/s_900x500/images/blog/carlos-alfonso-stylist-portfolio1.webp 1x, /_ipx/q_75/images/blog/carlos-alfonso-stylist-portfolio1.webp 2x" ...>` ...carlos-alfonso-stylist-portfolio1.webp (redplug.com.mx)	114.4 KiB	95.5 KiB
Red Plug redserfo `<img width="900" height="500" alt="Red Plug redserfo" data-nuxt-img="" srcset="/_ipx/s_900x500/images/blog/red-plug-website-2/1.webp 1x, /_ipx/s_1600x900/..." ...>` ...red-plug-website-2/1.webp (redplug.com.mx)	40.8 KiB	34.0 KiB
Andres Lopez `<img width="900" height="500" alt="Andres Lopez" data-nuxt-img="" srcset="/_ipx/s_900x500/images/blog/andres-lopez-portfolio1.webp 1x, /_ipx/s_1600x..." ...>` ...andres-lopez-portfolio1.webp (redplug.com.mx)	40.0 KiB	33.3 KiB
Red Plug Website `<img width="900" height="500" alt="Red Plug Website" data-nuxt-img="" srcset="/_ipx/s_900x500/images/blog/red-plug-website1.webp 1x, /_ipx/s_1600x900/..." ...>` ...red-plug-website1.webp (redplug.com.mx)	26.0 KiB	21.7 KiB

Avoid long main-thread tasks — 2 long tasks found

Lists the longest tasks on the main thread, useful for identifying worst contributors to input delay. Learn how to avoid long main-thread tasks. TBT

URL	Start Time	Duration
redplug.com.mx 1st Party		363 ms
/_nuxt/BXmeWFfj.js (redplug.com.mx)	4,803 ms	220 ms
https://redplug.com.mx	1,224 ms	143 ms

Avoid large layout shifts — 3 layout shifts found

These are the largest layout shifts observed on the page. Each table item represents a single layout shift, and shows the element that shifted the most. Below each item are possible root causes that led to the layout shift. Some of these layout shifts may not be included in the CLS metric value due to windowing. Learn how to improve CLS. CLS

Element	Layout shift score
Conexos experiencias digitales simples, efectivas y memorables que se adaptan a ... `<p class="z-10 text-center text-md md:text-xl lg:text-2xl text-black dark:text-white,">`	0.024
Conecta tu negocio al mundo digital `<h2 class="z-10 text-center whitespace-pre-wrap text-4xl md:text-5xl lg:text-6xl tracu...">`	0.001
Red Plug Logo `<div class="flex items-center">`	0.000

Avoid non-composited animations — 57 animated elements found

Animations which are not composited can be janky and increase CLS. Learn how to avoid non-composited animations. CLS

Element	Name
mundo digital `<span class="inline-block px-1 pb-1 animated-highlight bg-gradient-to-r from-cyan-400 t...' style="--1507e5f2: 200ms; --47b00c7e: 0ms; --0:110deb:0: undefined;" data-v-a1b3072c="">`	
Unsupported CSS Property: background-size	background-expand-a1b3072c
Unsupported CSS Property: color	text-color-change-a1b3072c

Elements

sitio

Filter-related property may move pixels

web

Filter-related property may move pixels

oficial,

Filter-related property may move pixels

donde

Filter-related property may move pixels

puedes

Filter-related property may move pixels

encontrar

Filter-related property may move pixels

información

Filter-related property may move pixels

sobre

Filter-related property may move pixels

nuestros

Filter-related property may move pixels

servicios,

Filter-related property may move pixels

proyectos

Filter-related property may move pixels

y

Filter-related property may move pixels

más.

Filter-related property may move pixels

Con

Filter-related property may move pixels

blog,

Filter-related property may move pixels

un

Filter-related property may move pixels

portafolio

Filter-related property may move pixels

de

Filter-related property may move pixels

trabajos

Filter-related property may move pixels

y

Filter-related property may move pixels

un

Filter-related property may move pixels

formulario

Filter-related property may move pixels

de

Filter-related property may move pixels

contacto.

Filter-related property may move pixels

Un

Filter-related property may move pixels

sitio

Filter-related property may move pixels

web

Filter-related property may move pixels

moderno

Filter-related property may move pixels

y

Filter-related property may move pixels

fiero

Filter-related property may move pixels

de

Filter-related property may move pixels

estilo

Filter-related property may move pixels

para

Filter-related property may move pixels

representar

Filter-related property may move pixels

el

Filter-related property may move pixels

trabajo

Filter-related property may move pixels

de

Filter-related property may move pixels

un

Filter-related property may move pixels

stylist

Filter-related property may move pixels

de

Filter-related property may move pixels

moda.

Filter-related property may move pixels

Con

Filter-related property may move pixels

una

Filter-related property may move pixels

galería

Filter-related property may move pixels

de

Filter-related property may move pixels

imágenes,

Filter-related property may move pixels

una

Filter-related property may move pixels

sección

Filter-related property may move pixels

de

Filter-related property may move pixels

biografía

Filter-related property may move pixels

y

Filter-related property may move pixels

un

Filter-related property may move pixels

formulario

Filter-related property may move pixels

de

Filter-related property may move pixels

contacto.

Filter-related property may move pixels

Avoid chaining critical requests — 8 chains found

The Critical Request Chains below show you what resources are loaded with a high priority. Consider reducing the length of chains, reducing the download size of resources, or deferring the download of unnecessary resources to improve page load. Learn how to avoid chaining critical requests.

Maximum critical path latency: **366.22 ms**

Initial Navigation
- https://redplug.com.mx
  - /_nuxt/index.9QC-5Y-0.css (redplug.com.mx) - **95.950 ms, 0.58 KiB**
  - /_fonts/Cdqy0Qbwx...woff (redplug.com.mx) - **93.638 ms, 68.96 KiB**
  - /_fonts/mF2fgkxl...woff2 (redplug.com.mx) - **77.42 ms, 42.83 KiB**
  - /_fonts/laaQ2e7hY...woff (redplug.com.mx) - **50.926 ms, 98.89 KiB**
  - /_fonts/YEI8bqgG...woff (redplug.com.mx) - **107.885 ms, 86.52 KiB**
  - /_fonts/IxKqKgT1c...woff (redplug.com.mx) - **76.424 ms, 26.33 KiB**
  - /_fonts/Ovoaq0dA...woff (redplug.com.mx) - **59.027 ms, 24.82 KiB**
  - /_fonts/K21mdPj...woff (redplug.com.mx) - **47.572 ms, 24.96 KiB**

Minimize third-party usage — Third-party code blocked the main thread for 0 ms

Third-party code can significantly impact load performance. Limit the number of redundant third-party providers and try to load third-party code after your page has primarily finished loading. Learn how to minimize third-party impact. TBT

Third-Party	Transfer Size	Main-Thread Blocking Time
ahrefs.com	2 KiB	0 ms
/analytics.js (analytics.ahrefs.com)	2 KiB	0 ms
/apievent (analytics.ahrefs.com)	0 KiB	0 ms

Largest Contentful Paint element — 2,280 ms

This is the largest contentful element painted within the viewport. Learn more about the Largest Contentful Paint element. LCP

Element

Conecta tu negocio al mundo digital
```
<h2 class="z-10 text-center whitespace-pre-wrap text-4xl sm:text-5xl lg:text-6xl tra…">
```

Phase	% of LCP	Timing
TTFB	26%	600 ms
Load Delay	0%	0 ms
Load Time	0%	0 ms
Render Delay	74%	1,670 ms

More information about the performance of your application. These numbers don't directly affect the Performance score.

PASSED AUDITS (23) Hide

Eliminate render-blocking resources

Resources are blocking the first paint of your page. Consider delivering critical JS/CSS inline and deferring all non-critical JS/styles. Learn how to eliminate render-blocking resources. LCP FCP

Defer offscreen images

Consider lazy-loading offscreen and hidden images after all critical resources have finished loading to lower time to interactive. Learn how to defer offscreen images. LCP FCP

Use the `nuxt/image` component and set `loading="lazy"` for offscreen images. Learn more.

Minify CSS

Minifying CSS files can reduce network payload sizes. Learn how to minify CSS. LCP FCP

Minify JavaScript

Minifying JavaScript files can reduce payload sizes and script parse time. Learn how to minify JavaScript. LCP FCP

Reduce unused CSS

Reduce unused rules from stylesheets and defer CSS not used for above-the-fold content to decrease bytes consumed by network activity. Learn how to reduce unused CSS. LCP FCP

Efficiently encode images

Optimized images load faster and consume less cellular data. Learn how to efficiently encode images. LCP FCP

Use the `nuxt/image` component and set the appropriate `quality`. Learn more.

Serve images in next-gen formats

Image formats like WebP and AVIF often provide better compression than PNG or JPEG, which means faster downloads and less data consumption. Learn more about modern image formats. LCP FCP

Use the `nuxt/image` component and set `format="webp"`. Learn more.

Enable text compression

Text-based resources should be served with compression (gzip, deflate or brotli) to minimize total network bytes. Learn more about text compression. LCP FCP

Preconnect to required origins

Consider adding `preconnect` or `dns-prefetch` resource hints to establish early connections to important third-party origins. Learn how to preconnect to required origins. LCP FCP

- Initial server response time was short — Root document took 10 ms

  Keep the server response time for the main document short because all other requests depend on it. Learn more about the Time to First Byte metric. LCP FCP

URL	Time Spent
redplug.com.mx 1st Party	10 ms
https://redplug.com.mx	10 ms

- Avoid multiple page redirects

  Redirects introduce additional delays before the page can be loaded. Learn how to avoid page redirects. LCP FCP

- Use video formats for animated content

  Large GIFs are inefficient for delivering animated content. Consider using MPEG4/WebM videos for animations and PNG/WebP for static images instead of GIF to save network bytes. Learn more about efficient video formats. LCP FCP

- Remove duplicate modules in JavaScript bundles

  Remove large, duplicate JavaScript modules from bundles to reduce unnecessary bytes consumed by network activity. LCP FCP

- Avoid serving legacy JavaScript to modern browsers

  Polyfills and transforms enable legacy browsers to use new JavaScript features. However, many aren't necessary for modern browsers. For your bundled JavaScript, adopt a modern script deployment strategy using module/nomodule feature detection to reduce the amount of code shipped to modern browsers, while retaining support for legacy browsers. Learn how to serve modern JavaScript. LCP FCP

- Preload Largest Contentful Paint image

  If the LCP element is dynamically added to the page, you should preload the image in order to improve LCP. Learn more about preloading LCP elements. LCP

  Use the `next/image` component and specify `preload` for LCP image. Learn more.

- Avoids enormous network payloads — Total size was 898 KiB

  Large network payloads cost users real money and are highly correlated with long load times. Learn how to reduce payload sizes.

URL	Transfer Size
redplug.com.mx 1st Party	712.0 KiB
/_next/static/chunks/pages/index-0d9f9d0b.js redplug.com.mx	177.4 KiB
/_next/static/media/cartesi-sans-regular.woff2 redplug.com.mx	115.1 KiB
/_next/static/media/1f0f8bcc9d9d0f0d-s.p.woff redplug.com.mx	68.5 KiB
/_next/static/media/2c7f7f7f7f7f7f7f-s.p.woff redplug.com.mx	66.3 KiB
/_next/static/media/2c7f7f7f7f7f7f7f-s.p.woff redplug.com.mx	66.3 KiB
/_next/static/media/2c7f7f7f7f7f7f7f-s.p.woff redplug.com.mx	66.3 KiB
/_next/static/media/1f0f8bcc9d9d0f0d-s.p.woff redplug.com.mx	46.8 KiB
https://redplug.com.mx	46.2 KiB
/_next/static/chunks/pages/_app-0d9f9d0b.js redplug.com.mx	42.8 KiB
/_next/static/chunks/pages/_app-0d9f9d0b.js redplug.com.mx	42.8 KiB
/_next/static/chunks/pages/_app-0d9f9d0b.js redplug.com.mx	42.8 KiB
/_next/static/chunks/pages/index-0d9f9d0b.js redplug.com.mx	41.4

on screen readers. Learn how to name `meter` elements.

- ARIA `progressbar` elements have accessible names

  When a `progressbar` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to label `progressbar` elements.

- `[role]`s have all required `[aria-*]` attributes

  Some ARIA roles have required attributes that describe the state of the element to screen readers. Learn more about roles and required attributes.

- Elements with an ARIA `[role]` that require children to contain a specific `[role]` have all required children.

  Some ARIA parent roles must contain specific child roles to perform their intended accessibility functions. Learn more about roles and required children elements.

- `[role]`s are contained by their required parent element

  Some ARIA child roles must be contained by specific parent roles to properly perform their intended accessibility functions. Learn more about ARIA roles and required parent element.

- `[role]` values are valid

  ARIA roles must have valid values in order to perform their intended accessibility functions. Learn more about valid ARIA roles.

- Elements with the `role="text"` attribute do not have focusable descendants.

  Adding `role="text"` around a text node split by markup enables VoiceOver to treat it as one phrase, but the element's focusable descendents will not be announced. Learn more about the `role="text"` attribute.

- ARIA toggle fields have accessible names

  When a toggle field doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about toggle fields.

- ARIA `tooltip` elements have accessible names

  When a tooltip element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn how to name `tooltip` elements.

- ARIA `treeitem` elements have accessible names

  When a `treeitem` element doesn't have an accessible name, screen readers announce it with a generic name, making it unusable for users who rely on screen readers. Learn more about labeling `treeitem` elements.

- The page contains a heading, skip link, or landmark region

  Adding ways to bypass repetitive content lets keyboard users navigate the page more efficiently. Learn more about bypass blocks.

- `<dl>`'s contain only properly-ordered `<dt>` and `<dd>` groups, `<script>`, `<template>` or `<div>` elements.

  When definition lists are not properly marked up, screen readers may produce confusing or inaccurate output. Learn how to structure definition lists correctly.

- Definition list items are wrapped in `<dl>` elements

  Definition list items (`<dt>` and `<dd>`) must be wrapped in a parent `<dl>` element to ensure that screen readers can properly announce them. Learn how to structure definition lists correctly.

- ARIA IDs are unique

  The value of an ARIA ID must be unique to prevent other instances from being overlooked by assistive technologies. Learn how to fix duplicate ARIA IDs.

- No form fields have multiple labels

  Form fields with multiple labels can be confusingly announced by assistive technologies like screen readers which use either the first, the last, or all of the labels. Learn how to use form labels.

- `<frame>` or `<iframe>` elements have a title

  Screen reader users rely on frame titles to describe the contents of frames. Learn more about frame titles.

- `<html>` element has an `[xml:lang]` attribute with the same base language as the `[lang]` attribute.

  If the webpage does not specify a consistent language, then the screen reader might not announce the page's text correctly. Learn more about the lang attribute.

- Input buttons have discernible text.

  Adding discernable and accessible text to input buttons may help screen reader users understand the purpose of the input button. Learn more about input buttons.

- `<input type="image">` elements have `[alt]` text

  When an image is being used as an `<input>` button, providing alternative text can help screen reader users understand the purpose of the button. Learn about input image alt text.

- Links are distinguishable without relying on color.

  Low-contrast text is difficult or impossible for many users to read. Link text that is discernible improves the experience for users with low vision. Learn how to make links distinguishable.

- Lists contain only `<li>` elements and script supporting elements (`<script>` and `<template>`).

  Screen readers have a specific way of announcing lists. Ensuring proper list structure aids screen reader output. Learn more about proper list structure.

- List items (`<li>`) are contained within `<ul>`, `<ol>` or `<menu>` parent elements

  Screen readers require list items (`<li>`) to be contained within a parent `<ul>`, `<ol>` or `<menu>` to be announced properly. Learn more about proper list structure.

- The document does not use `<meta http-equiv="refresh">`

  Users do not expect a page to refresh automatically, and doing so will move focus back to the top of the page. This may create a frustrating or confusing experience. Learn more about the refresh meta tag.

- `<object>` elements have alternate text

  Screen readers cannot translate non-text content. Adding alternate text to `<object>` elements helps screen readers convey meaning to users. Learn more about alt text for `object` elements.

- Select elements have associated label elements.

  Form elements without effective labels can create frustrating experiences for screen reader users. Learn more about the `select` element.

- Skip links are focusable.

  Including a skip link can help users skip to the main content to save time. Learn more about skip links.

- No element has a `[tabindex]` value greater than 0

  A value greater than 0 implies an explicit navigation ordering. Although technically valid, this often creates frustrating experiences for users who rely on assistive technologies. Learn more about the `tabindex` attribute.

- Tables have different content in the summary attribute and `<caption>`.

  The summary attribute should describe the table structure, while `<caption>` should have the onscreen title. Accurate table mark-up helps users of screen readers. Learn more about summary and caption.

- Cells in a `<table>` element that use the `[headers]` attribute refer to table cells within the same table.

  Screen readers have features to make navigating tables easier. Ensuring `<td>` cells using the `[headers]` attribute only refer to other cells in the same table may improve the experience for screen reader users. Learn more about the `headers` attribute.

- `<th>` elements and elements with `[role="columnheader"/"rowheader"]` have data cells they describe.

  Screen readers have features to make navigating tables easier. Ensuring table headers always refer to some set of cells may improve the experience for screen reader users. Learn more about table headers.

- `[lang]` attributes have a valid value

  Specifying a valid BCP 47 language on elements helps ensure that text is pronounced correctly by a screen reader. Learn how to use the lang attribute.

- `<video>` elements contain a `<track>` element with `[kind="captions"]`

  When a video provides a caption it is easier for deaf and hearing impaired users to access its information. Learn more about video captions.

100

Best Practices

TRUST AND SAFETY

- Ensure CSP is effective against XSS attacks

  A strong Content Security Policy (CSP) significantly reduces the risk of cross-site scripting (XSS) attacks. Learn how to use a CSP to prevent XSS

Description	Directive	Severity
No CSP found in enforcement mode		High

- Use a strong HSTS policy

  Deployment of the HSTS header significantly reduces the risk of downgrading HTTP connections and eavesdropping attacks. A rollout in stages, starting with a low max-age is recommended. Learn more about using a strong HSTS policy.

Description	Directive	Severity
No HSTS header found		High

- Ensure proper origin isolation with COOP

  The Cross-Origin-Opener-Policy (COOP) can be used to isolate the top-level window from other documents such as pop-ups. Learn more about deploying the COOP header.

Description	Directive	Severity
No COOP header found		High

- Mitigate clickjacking with XFO or CSP

  The `X-Frame-Options` (XFO) header or the `frame-ancestors` directive in the `Content-Security-Policy` (CSP) header control where a page can be embedded. These can mitigate clickjacking attacks by blocking some or all sites from embedding the page. Learn more about mitigating clickjacking.

Description	Severity
No frame control policy found	High

GENERAL

- Detected JavaScript libraries

  All front-end JavaScript libraries detected on the page. Learn more about this JavaScript library detection diagnostic audit.

Name	Version
Nuxt.js	

- Missing source maps for large first-party JavaScript

  Source maps translate minified code to the original source code. This helps developers debug in production. In addition, Lighthouse is able to provide further insights. Consider deploying source maps to take advantage of these benefits. Learn more about source maps.

URL	Map URL
nelplug.com.mx 1st Party	
/_nuxt/DHFfkDIZt.js nelplug.com.mx)	
Large JavaScript file is missing a source map	

PASSED AUDITS (14) Hide

- Uses HTTPS

  All sites should be protected with HTTPS, even ones that don't handle sensitive data. This includes avoiding mixed content, where some resources are loaded over HTTP despite the initial request being served over HTTPS. HTTPS prevents intruders from tampering with or passively listening in on the communications between your app and your users, and is a prerequisite for HTTP/2 and many new web platform APIs. Learn more about HTTPS.

- Avoids deprecated APIs

  Deprecated APIs will eventually be removed from the browser. Learn more about deprecated APIs.

- Avoids third-party cookies

  Chrome is moving towards a new experience that allows users to choose to browse without third-party cookies. Learn more about third-party cookies.

- Allows users to paste into input fields

  Preventing input pasting is a bad practice for the UX, and weakens security by blocking password managers.Learn more about user-friendly input fields.

- Avoids requesting the geolocation permission on page load

  Users are mistrustful of or confused by sites that request their location without context. Consider tying the request to a user action instead. Learn more about the geolocation permission.

- Avoids requesting the notification permission on page load

  Users are mistrustful of or confused by sites that request to send notifications without context. Consider tying the request to user gestures instead. Learn more about responsibly getting permission for notifications.

- Displays images with correct aspect ratio

  Image display dimensions should match natural aspect ratio. Learn more about image aspect ratio.

- Serves images with appropriate resolution

  Image natural dimensions should be proportional to the display size and the pixel ratio to maximize image clarity. Learn how to provide responsive images.

- Has a `<meta name="viewport">` tag with `width` or `initial-scale`

  A `<meta name="viewport">` not only optimizes your app for mobile screen sizes, but also prevents a 300 milliseconds delay to user input. Learn more about using the viewport meta tag.

- Document uses legible font sizes — 100% legible text

  Font sizes less than 12px are too small to be legible and require mobile visitors to "pinch to zoom" in order to read. Strive to have >60% of page text ≥12px. Learn more about legible font sizes.

Source	Selector	% of Page Text	Font Size
`Legible text`		100.00%	≥ 12px

- Page has the HTML doctype

  Specifying a doctype prevents the browser from switching to quirks-mode. Learn more about the doctype declaration.

- Properly defines charset

  A character encoding declaration is required. It can be done with a `<meta>` tag in the first 1024 bytes of the HTML or in the Content-Type HTTP response header. Learn more about declaring the character encoding.

- No browser errors logged to the console

  Errors logged to the console indicate unresolved problems. They can come from network request failures and other browser concerns. Learn more about this errors in console diagnostic audit

- No issues in the `Issues` panel in Chrome Devtools

  Issues logged to the `Issues` panel in Chrome Devtools indicate unresolved problems. They can come from network request failures, insufficient security controls, and other browser concerns. Open up the Issues panel in Chrome DevTools for more details on each issue.

NOT APPLICABLE (1) Hide

- Redirects HTTP traffic to HTTPS

  Make sure that you redirect all HTTP traffic to HTTPS in order to enable secure web features for all your users. Learn more.

100

SEO

These checks ensure that your page is following basic search engine optimization advice. There are many additional factors Lighthouse does not score here that may affect your search ranking, including performance on Core Web Vitals. Learn more about Google Search Essentials.

ADDITIONAL ITEMS TO MANUALLY CHECK (1) Hide

- Structured data is valid

  Run the Structured Data Testing Tool and the Structured Data Linter to validate structured data. Learn more about Structured Data.

Run these additional validators on your site to check additional SEO best practices.

PASSED AUDITS (9) Hide

- Page isn't blocked from indexing

  Search engines are unable to include your pages in search results if they don't have permission to crawl them. Learn more about crawler directives.

- Document has a `<title>` element

  The title gives screen reader users an overview of the page, and search engine users rely on it heavily to determine if a page is relevant to their search. Learn more about document titles.

- Document has a meta description

  Meta descriptions may be included in search results to concisely summarize page content. Learn more about the meta description.

- Page has successful HTTP status code

  Pages with unsuccessful HTTP status codes may not be indexed properly. Learn more about HTTP status codes.

- Links have descriptive text

  Descriptive link text helps search engines understand your content. Learn how to make links more accessible.

- Links are crawlable

  Search engines may use `href` attributes on links to crawl websites. Ensure that the `href` attribute of anchor elements links to an appropriate destination, so more pages of the site can be discovered. Learn how to make links crawlable

- robots.txt is valid

  If your robots.txt file is malformed, crawlers may not be able to understand how you want your website to be crawled or indexed. Learn more about robots.txt.

- Image elements have `[alt]` attributes

  Informative elements should aim for short, descriptive alternate text. Decorative elements can be ignored with an empty alt attribute. Learn more about the `alt` attribute.

- Document has a valid `hreflang`

  hreflang links tell search engines what version of a page they should list in search results for a given language or region. Learn more about `hreflang`.

NOT APPLICABLE (1) Hide

- Document has a valid `rel=canonical`

  Canonical links suggest which URL to show in search results. Learn more about canonical links.

More on PageSpeed Insights

What's new

Documentation

Learn about Web Performance

Ask questions on Stack Overflow

Mailing list

Related Content

Updates

Web Fundamentals

Case Studies

Podcasts

Connect

Twitter

Youtube

Google for Developers Chrome Firebase All products

Terms and Privacy Policy

For details, see the Google Developers Site Policies.