

Introduction to SQL

Lecture 4

Dr. Reda M. Hussien

Self Join Example

- Relation emp-super

person	supervisor
Bob	Alice
Mary	Susan
Alice	David
David	Mary

- Find the supervisor of “Bob”
- Find the supervisor of the supervisor of “Bob”
- Find ALL the supervisors (direct and indirect) of “Bob”

String Operations

- SQL includes a string-matching operator for comparisons on character strings. The operator like uses patterns that are described using two special characters:
 - percent (%). The % character matches any substring.
 - underscore (_). The _ character matches any character.
- Find the names of all instructors whose name includes the substring “dar”.

```
select name from instructor where name like '%dar%'
```

- Match the string “100%

```
like '100\%' escape '\'
```

- in that above we use backslash (\) as the escape character.

String Operations (Cont.)

- Patterns are case sensitive.
- Pattern matching examples:
 - 'Intro%' matches any string beginning with "Intro".
 - '%Comp%' matches any string containing "Comp" as a substring.
 - '___' matches any string of exactly three characters.
 - '___%' matches any string of at least three characters.
- SQL supports a variety of string operations such as
 - concatenation (using "||")
 - converting from upper to lower case (and vice versa)
 - finding string length, extracting substrings, etc.

Ordering the Display of Tuples

- List in alphabetic order the names of all instructors

```
select distinct name from instructor order by name
```

- We may specify desc for descending order or asc for ascending order, for each attribute; ascending order is the default.
 - Example: order by name desc
- Can sort on multiple attributes
 - Example: order by dept_name, name

Where Clause Predicates

- SQL includes a between comparison operator
- Example: Find the names of all instructors with salary between \$90,000 and \$100,000 (that is, \geq \$90,000 and \leq \$100,000)

```
select name from instructor where salary between 90000 and 100000
```

- Tuple comparison

```
select name, course_id from instructor, teaches  
where (instructor.ID, dept_name) = (teaches.ID, 'Biology');
```

Duplicates



- In relations with duplicates, SQL can define how many copies of tuples appear in the result.
- Multiset versions of some of the relational algebra operators – given multiset relations r_1 and r_2 :
 - 1. $\sigma_{\theta}(r_1)$: If there are c_1 copies of tuple t_1 in r_1 , and t_1 satisfies selection σ_{θ} , then there are c_1 copies of t_1 in $\sigma_{\theta}(r_1)$.
 - 2. $\Pi_A(r)$: For each copy of tuple t_1 in r_1 , there is a copy of tuple $\Pi_A(t_1)$ in $\Pi_A(r_1)$ where $\Pi_A(t_1)$ denotes the projection of the single tuple t_1 .
 - 3. $r_1 \times r_2$: If there are c_1 copies of tuple t_1 in r_1 and c_2 copies of tuple t_2 in r_2 , there are $c_1 \times c_2$ copies of the tuple $t_1 \cdot t_2$ in $r_1 \times r_2$.

Duplicates (Cont.)

- Example: Suppose multiset relations r_1 (A, B) and r_2 (C) are as follows:

$$r_1 = \{(1, a) (2, a)\} \quad r_2 = \{(2), (3), (3)\}$$

- Then $\Pi_B(r_1)$ would be $\{(a), (a)\}$, while $\Pi_B(r_1) \times r_2$ would be

$$\{(a, 2), (a, 2), (a, 3), (a, 3), (a, 3), (a, 3)\}$$

- SQL duplicate semantics:

select A1,, A2, ..., An

from r1, r2, ..., rm

where P

- is equivalent to the multiset version of the expression: $\Pi_{A_1, A_2, \dots, A_n} (\sigma_P(r_1 \times r_2 \times \dots \times r_m))$

Set Operations

- Find courses that ran in Fall 2009 or in Spring 2010

```
(select course_id from section where sem = 'Fall' and year = 2009)  
union  
(select course_id from section where sem = 'Spring' and year = 2010)
```
- Find courses that ran in Fall 2009 and in Spring 2010

```
(select course_id from section where sem = 'Fall' and year = 2009)  
intersect  
(select course_id from section where sem = 'Spring' and year = 2010)
```
- Find courses that ran in Fall 2009 but not in Spring 2010

```
(select course_id from section where sem = 'Fall' and year = 2009)  
except  
(select course_id from section where sem = 'Spring' and year = 2010)
```

Set Operations (Cont.)

- Find the salaries of all instructors that are less than the largest salary.

```
select distinct T.salary from instructor as T, instructor  
as S where T.salary < S.salary
```

- Find all the salaries of all instructors

```
select distinct salary from instructor
```

- Find the largest salary of all instructors.

- (select "second query") except (select "first query")

Set Operations (Cont.)

- Set operations union, intersect, and except
 - Each of the above operations automatically eliminates duplicates
- To retain all duplicates use the corresponding multiset versions union all, intersect all and except all.
- Suppose a tuple occurs m times in r and n times in s , then, it occurs:
 - $m + n$ times in r union all s
 - $\min(m, n)$ times in r intersect all s
 - $\max(0, m - n)$ times in r except all s

Null Values



- It is possible for tuples to have a null value, denoted by null, for some of their attributes
- null signifies an unknown value or that a value does not exist.
- The result of any arithmetic expression involving null is null
 - Example: $5 + \text{null}$ returns null
- The predicate `is null` can be used to check for null values.
 - Example: Find all instructors whose salary is null.
`select name from instructor where salary is null`

Null Values and Three Valued Logic

- Three values – true, false, unknown
- Any comparison with null returns unknown
 - Example: $5 < \text{null}$ or $\text{null} <> \text{null}$ or $\text{null} = \text{null}$
- Three-valued logic using the value unknown:
 - OR: $(\text{unknown or true}) = \text{true}$,
 $(\text{unknown or false}) = \text{unknown}$
 $(\text{unknown or unknown}) = \text{unknown}$
 - AND: $(\text{true and unknown}) = \text{unknown}$,
 $(\text{false and unknown}) = \text{false}$,
 $(\text{unknown and unknown}) = \text{unknown}$
 - NOT: $(\text{not unknown}) = \text{unknown}$
 - “P is unknown” evaluates to true if predicate P evaluates to unknown
- Result of where clause predicate is treated as false if it evaluates to unknown

End of Lecture 4