Product Approval
USER: Public User

OFFICE OF THE SECRETARY

FL #	FL6393-R19
Application Type	Affirmation
Code Version	2023
Application Status	Approved
Comments	
Archived	☐
Product Manufacturer	Velux America, LLC
Address/Phone/Email	P.O. Box 5001 Greenwood, SC 29648 (864) 377-0691 Mike.rhoden@velux.com
Authorized Signature	Mike Rhoden Mike.rhoden@velux.com
Technical Representative	Mike Rhoden
Address/Phone/Email	104 Ben Casey Dr Fort Mill, SC 29708 (864) 377-0691 mike.rhoden@velux.com
Quality Assurance Representative	Mike Rhoden
Address/Phone/Email	104 Ben Casey Drive Fort Mill, SC 29708 (803) 396-5736 mike.rhoden@velux.com
Category	Sky Lights
Subcategory	Skylight
Compliance Method	Certification Mark or Listing
Certification Agency	Window and Door Manufacturer Association
Validated By	Window and Door Manufacturers Association

Referenced Standard and Year (of Standard)

Standard	Year
AAMA/WDMA 101/I.S.2/A440	2011
AAMA/WDMA 101/I.S.2/A440	2017
ASTM E1886	2019
ASTM E1996	2020
TAS 201	1994
TAS 202	1994
TAS 203	1994

Equivalence of Product Standards Certified By: Florida Licensed Professional Engineer or Architect

FL6393_R19_Equiv_FL6393-R18 Sun Tunnel Equivalency.pdf

☑ I affirm that there are no changes in the new Florida Building Code which affect my product(s) and my product(s) are in compliance with the new Florida Building Code.

Documentation from approved Evaluation or Validation Entity ○ Yes ○ No ○ N/A

FL6393_R19_COC_FL 6393 COMP.pdf

Product Approval Method: Method 1 Option A

Date Submitted: 07/13/2023
Date Validated: 07/13/2023
Date Pending FBC Approval:
Date Approved: 07/16/2023

Summary of Products

FL #	Model, Number or Name	Description
6393.1	VELUX Flat Glass Sun Tunnel (HVHZ)	[TZR or TZRL or TZRQ] + [014] + [1A00] 3.9mm tempered clear outer pane with 7mm laminated inner pane.
Limits of Use **Approved for use in HVHZ:** Yes **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +120/-80 **Other:** Wind Zone 4, Missile D, Cycle Pressure +50/-50; Max tube dia. 356 mm (14 in). Tested for cycling per ASTM E1886/ASTM E1996. Glass meets ASTM E1300: 3.9mm tempered clear outer pane with 7mm laminate using 2.3mm panes and three 0.030" PVB interlayers. Anchorage fasteners provided to secure skylight to curb : #8 1 3/4" (4.2 x 45mm) pan head st. st. metal screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_FL6393 TZR_TZRL_TZRQ (impact) 014 1A00.pdf **Quality Assurance Contract Expiration Date** 02/23/2031 **Installation Instructions** FL6393_R19_II_TZR-TZRL-TZRQ Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.2	VELUX Flat Glass Sun Tunnel (Non-Impact)	[TZR or TZRL or TZRQ] + [014] + [2A00] 3mm tempered LowE366 outer pane with 7mm diamond wire inner pane.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +140/-140 **Other:** SKG-PG140; Max tube dia. 356 mm (14 in). PG140 means minimum capacity is 140 psf. Glazing assembly is 3mm tempered LowE366 outer pane with 7mm diamond wire inner pane. Anchorage fasteners provided to secure skylight to curb : #8 1 3/4" (4.2 x 45mm) pan head st. st. metal screws		**Certification Agency Certificate** FL6393_R19_C_CAC_FL6393 TZR_TZRL_TZRQ (non-impact) 014 2A00.pdf **Quality Assurance Contract Expiration Date** 03/05/2031 **Installation Instructions** FL6393_R19_II_TZR-TZRL-TZRQ Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.3	VELUX Sun Tunnel TSR 0000	TSR 010 size (426-H-626.07)
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +200/-180 **Other:** TDDCC-PG180; Size tested 254 mm dia (10 in). PG180 means minimum capacity is 180 psf. Dome glazing is minimum 3mm thick. Flashing nails directly to roof deck. Anchorage fasteners provided are 10 ga. galv. ring shank nails.		**Certification Agency Certificate** FL6393_R19_C_CAC_426-H-626.07.pdf **Quality Assurance Contract Expiration Date** 04/03/2027 **Installation Instructions** FL6393_R19_II_TSR_010_Installation.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.4	VELUX Sun Tunnel TLR (Tempered Glass)	TLR 014 + [2000A or 2000AE1] (426-H-693.02)

Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +150/-245 **Other:** TDDCC-PG150; Max. tube dia. 356 mm (14 in) - TDD. PG150 means minimum capacity is 150 psf. Exterior glazing is minimum 4mm thick clear tempered glass meeting ASTM E1300. Anchorage fasteners provided: 2.2 mm x 3/4" ring shank nails for alignment on top of roof deck, and #6 pan head sheet metal screws for clamping on underside of deck.		**Certification Agency Certificate** FL6393_R19_C_CAC_426-H-693.02.pdf **Quality Assurance Contract Expiration Date** 10/03/2025 **Installation Instructions** FL6393_R19_II_TLR_014_Installation.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.5	VELUX TCC 022 (Curb Mount) Commercial Sun Tunnel - Impact Resistant	TCC 022 + 5000 (426-H-708.04) Polycarb Dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-160 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDOC/TDDCC-PG160; Max. tube dia. 559 mm (22 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to curb. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TCC 022 5000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 10/22/2031 **Installation Instructions** FL6393_R19_II_TCC Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TOC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TTC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.6	VELUX TCC 022 (Curb Mount) Commercial Sun Tunnel - Non-Impact	TCC 022 + 3000 (426-H-708.10/.11) Acrylic Dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-160 **Other:** TDDOC/TDDCC-PG160; Max. tube dia. 559 mm (22 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to curb. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TCC 022 3000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/04/2032 **Installation Instructions** FL6393_R19_II_TCC Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TOC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TTC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.7	VELUX TCR/TCC 014 (Curb Mount) Sun Tunnel - Impact Resistant	TCR/TCC 014 + 1000 (426-H-706.08) Polycarb Dome
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-165 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDCC-PG165; Max. tube dia. 356 mm (14 in) - TDD. PG165 means minimum capacity is 165 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to curb. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TCR-TCC 014 1000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/24/2031 **Installation Instructions** FL6393_R19_II_TCC Installation Instructions.pdf FL6393_R19_II_TCR Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TOC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.8	VELUX TCR/TCC 014 (Curb Mount) Sun Tunnel - Non-Impact	TCR/TCC 014 + 0000 (426-H-706.04/.05) Acrylic Dome
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-165 **Other:** TDDCC-PG165; Max. tube dia. 356 mm (14 in) - TDD. PG165 means minimum capacity is 165 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to curb. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TCR-TCC 014 0000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/24/2031 **Installation Instructions** FL6393_R19_II_TCC Installation Instructions.pdf FL6393_R19_II_TCR Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:

6393.9	VELUX TGC 022 (Deck Mount) Commercial Sun Tunnel - Impact Resistant	TGC 022 + 5000 (426-H-708.05) Polycarb Dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-160 **Other:** Wind Zone 3, Missile C, Cycle Pressure +70/-70; Tested for cycling per ASTM E1886/ASTM E1996. TDDOC/TDDCC-PG160; Max. tube dia. 559 mm (22 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGC 022 5000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/18/2032 **Installation Instructions** FL6393_R19_II_TGC Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TOC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TTC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.10	VELUX TGC 022 (Deck Mount) Commercial Sun Tunnel - Non-Impact	TGC 022 + 3000 (426-H-708.06/.07) Acrylic Dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-160 **Other:** TDDOC/TDDCC-PG160; Max. tube dia. 559 mm (22 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGC 022 3000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/18/2032 **Installation Instructions** FL6393_R19_II_TGC Installation Instructions.pdf FL6393_R19_II_THC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TOC_Diffuser_Installation Instructions.pdf FL6393_R19_II_TTC_Diffuser_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.11	VELUX TGF 014 (Deck Mount) Sun Tunnel - Impact Resistant	TGF 014 + 1000 (426-H-705.05) Polycarb dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-160 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDCC-PG160; Max. tube dia. 356 mm (14 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGF 014 1000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/28/2031 **Installation Instructions** FL6393_R19_II_TGF-TMF 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.12	VELUX TGF 014 (Deck Mount) Sun Tunnel - Non-Impact	TGF 014 + 0000 (426-H-705.11/.12) Acrylic dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-160 **Other:** TDDCC-PG160; Max. tube dia. 356 mm (14 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGF 014 0000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/12/2032 **Installation Instructions** FL6393_R19_II_TGF-TMF 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.13	VELUX TGF 022 (Deck Mount) Sun Tunnel - Impact Resistant	TGF 022 + 1000 (426-H-705.05) Polycarb dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-130 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDCC-PG130; Max. tube dia. 559 mm (22 in) - TDD. PG130 means minimum capacity is 130 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGF 022 1000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/28/2031 **Installation Instructions** FL6393_R19_II_TGF-TMF Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.14	VELUX TGF 022 (Deck Mount) Sun Tunnel - Non-Impact	TGF 022 + 0000 (426-H-705.07/.08) Acrylic dome.

Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-130 **Other:** TDDCC-PG130; Max. tube dia. 559 mm (22 in) - TDD. PG130 means minimum capacity is 130 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGF 022 0000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/10/2032 **Installation Instructions** FL6393_R19_II_TGF-TMF Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.15	VELUX TGR/TGC 010 & 014 (Deck Mount) Sun Tunnel - Impact Resistant	TGR/TGC 010 or 014 + 1000 (426-H-705.06) Polycarb dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-160 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDCC/TDDOC-PG160; Max. tube dia. 356 mm (14 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGR-TGC 010 or 014 1000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/28/2031 **Installation Instructions** FL6393_R19_II_TGC Installation Instructions.pdf FL6393_R19_II_TGR-TMR-THR 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.16	VELUX TGR/TGC 010 & 014 (Deck Mount) Sun Tunnel - Non-Impact	TGR/TGC 010 or 014 + 0000 (426-H-705.15/.16) Acrylic dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-160 **Other:** TDDCC/TDDOC-PG160; Max. tube dia. 356 mm (14 in) - TDD. PG160 means minimum capacity is 160 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TGR-TGC 010 or 014 0000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/10/2032 **Installation Instructions** FL6393_R19_II_TGC Installation Instructions.pdf FL6393_R19_II_TGR-TMR-THR 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.17	VELUX TMF/TMR/THR 010 & 014 (Deck Mount) Sun Tunnel - Impact Resistant	TMF/TMR/THR 010 or 014 + 1000 (426-H-705.04) Polycarb dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** Yes **Design Pressure:** +300/-165 **Other:** Wind Zone 3, Missile C, Cycle Pressure +50/-50; Tested for cycling per ASTM E1886/ASTM E1996. TDDCC-PG165; Max. tube dia. 356 mm (14 in) - TDD. PG165 means minimum capacity is 165 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TMF-TMR-THR 010 or 014 1000 (Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 09/30/2031 **Installation Instructions** FL6393_R19_II_TGF-TMF Installation Instructions.pdf FL6393_R19_II_TGR-TMR-THR 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:
6393.18	VELUX TMF/TMR/THR 010 & 014 (Deck Mount) Sun Tunnel - Non-Impact	TMF/TMR/THR 010 or 014 + 0000 (426-H-705.19/.20) Acrylic dome.
Limits of Use **Approved for use in HVHZ:** No **Approved for use outside HVHZ:** Yes **Impact Resistant:** No **Design Pressure:** +300/-165 **Other:** TDDCC-PG165; Max. tube dia. 356 mm (14 in) - TDD. PG165 means minimum capacity is 165 psf. Dome glazing is minimum 3 mm thick. Flashing attaches to roof deck. Anchorage fasteners provided are black #8 st. stl. pan head screws.		**Certification Agency Certificate** FL6393_R19_C_CAC_TMF-TMR-THR 010 or 014 0000 (Non-Impact) CCL.pdf **Quality Assurance Contract Expiration Date** 01/26/2032 **Installation Instructions** FL6393_R19_II_TGF-TMF Installation Instructions.pdf FL6393_R19_II_TGR-TMR-THR 014_Installation Instructions.pdf Verified By: Window and Door Manufacturer Association Created by Independent Third Party: **Evaluation Reports** Created by Independent Third Party:

Back Next

Contact Us :: 2601 Blair Stone Road, Tallahassee FL 32399 Phone: 850-487-1824

The State of Florida is an AA/EEO employer. Copyright 2007-2013 State of Florida. :: Privacy Statement :: Accessibility Statement :: Refund Statement

Under Florida law, email addresses are public records. If you do not want your e-mail address released in response to a public-records request, do not send electronic mail to this entity. Instead, contact the office by phone or by traditional mail. If you have any questions, please contact 850.487.1395. *Pursuant to Section 455.275(1), Florida Statutes, effective October 1, 2012, licensees licensed under Chapter 455, F.S. must provide the Department with an email address if they have one. The emails provided may be used for official communication with the licensee. However email addresses are public record. If you do not wish to supply a personal address, please provide the Department with an email address which can be made available to the public. To determine if you are a licensee under Chapter 455, F.S., please click here .

Product Approval Accepts:

Credit Card Safe securityMETRICS