
耐摩耗性きわめて優れ、空冷で硬化する冷間ダイス鋼





基本仕様14頁

〈前頁(A	B (幅)	/C/ T(厚さ)						
A (長さ)		28	30	35	40	50	60	70
60	60	<u> </u>	0	0	0	0	0	
80		0	0	0	0	0	0	
500		0	0	0	0	0	0	
600			0	0	0	0		
63	63	0	0	0	0	0	0	
80	03	0	0	0	0	0	0	
80	80	0	0	0	0	0	0	0
100		0	0	0	0	0	0	0
125		0	0	0	0	0	0	0
150		0	0	0	0	0	0	0
160		<u> </u>	0	0	0	0	0	0
180		<u> </u>	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		<u> </u>	0	0	0	0	0	0
250		<u> </u>	0	0	0	0	0	0
300		0	0	0	0	0	0	0
500			0	0	0	0	00	0
600			0	0	0	0		0
100	- 1	<u> </u>	0	0	0	0	0	0
125 150	100	0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		<u> </u>	0	0	0	0	0	0
200		0	0	0	0	Ö	0	0
210		<u> </u>	0	<u> </u>	0	<u> </u>	0	Ö
250		<u> </u>	0	Ö	Ö	Ö	Ö	Ö
300		<u> </u>	Ö	Ö	Ö	Ö	Ö	Ŏ
350		Ö	Ö	Ö	Ö	Ö	Ö	Ö
400		<u> </u>	Ö	Ö	0	Ö	Ö	Ö
500		0	0	Ö	Ö	Ö	0	0
600			Ö	0	Ö	0	0	0
125	125	0	0	0	0	0	0	0
150		0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		0	0	0	0	0	0	0
250		0	0	0	0	0	0	0
300		0	0	0	0	0	0	0
350		0	0	0	0	0	0	0
400		<u> </u>	0	0	0	0	0	0
450		0	0	0	0	0	0	0
500		0	0	0	0	0	0	0
600	1		0	0			0	0