


## 優れた靭性、強度をもつ汎用冷間ダイス鋼





## ●注文方法 材質·T(厚さ)×A(長さ)×B(幅)=枚数

## 〈前頁のつづき〉

(別具	<u> </u>	, c ,						
Α								
(長さ)	(幅)	28	30	35	40	50	60	70
60	60	0	0	0	0	0	0	
80		0	0	0	0	0	0	
500		0	0	0	0	0	0	
600			0	0	0	0		
63	63	0	0	0	0	0	0	
80		0	0	0	0	0	0	
80	80	0	0	0	0	0	0	
100		0	0	0	0	0	0	0
125		0	0	0	0	0	0	0
150		0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		$\circ$	0	0	0	0	0	0
210		0	0	0	0	0	0	0
250		0	0	0	0	0	0	0
300		0	0	0	0	0	0	0
500		0	0	0	0	0	0	0
600			0	0	0	0	0	0
100	100	0	0	0	0	0	0	0
125		0	0	0	0	0	Q	0
150		0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		0	0	0	0	0	0	0
250		0	0	0	0	0	0	0
300		0	0	0	0	0	0	0
350		0	0	0	0	0	0	0
400		0	0	0	0	0	0	0
500		0	0	0	0	0	0	0
600			0			0	0	0