
耐摩耗性きわめて優れ、空冷で硬化する冷間ダイス鋼





基本仕様14頁

Δ	B (幅)	T(厚さ)						
さ)		28	30	35	40	50	60	70
06	60	0	0	0	0	0	0	
80		0	0	0	0	0	0	
0		0	0	0	0	0	0	
0		_	0	0	0	0		
3	63	<u> </u>	0	0	0	0	0	
0		0	0	0	0	0	0	
0	-	0	0	0	0	0	00	0
0		0	0	0	0	0	0	
5	80	<u> </u>	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	-	0	0
0		0	0	0	0	0	0	$\frac{\circ}{\circ}$
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	
0		0	Ö	0	0	Ö	0	<u> </u>
0		Ö	0		0		0	$\frac{\circ}{\circ}$
0			Ö	Ö	0	Ö	Ö	Ö
0	100	0	Ö	Ö	Ö	Ö	Ö	Ŏ
5		Ö	Ö	Ö	Ö	Ŏ	Ö	Ō
0		0	O	Ö	0	Ö	Ö	Ŏ
0		Ö	Ö	Ö	Ö	Ŏ	Ö	Ō
0		Ö	Ö	0	Ö	0	Ō	0
0		0	0	0	Ö	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0			0	0	0	0	0	0
5		0	0	0	0	0	0	0
0		0	0	0	0	0	0	
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0		0
0	125	<u> </u>	0	0	0	0	0	0
_		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	_	- 0
0		0	0	0	0	0	0	0
0		0	0	0	0	0	0	0
0		0		0	0	0	0	0