■順送型用

特

- ■LF(炉外精錬)による清浄鋼を用いた信頼度の 高い金型材です。
- ■焼入れ性が良好。空冷、真空ガス冷に最適です。

焼入れ歪が非常に小さく精密金型に適します。

■耐摩耗性がきわめて優れております。 (ステンレスや高硬度材のプレス型に適します。)

注文方法 材質·T(厚さ)×A(長さ)×B(幅)=枚数

묾 成



SKD11



/26頁



順送型用ダイホルダ SKD11/106頁

Α	B (幅)	T(厚さ)						
(長さ)		10	13	15	16	20	22	25
60	60	0	0	0	0	0	Ö	0
80		Ö	0	0	0	0	0	0
500		0	0	0	0	0	0	0
600		0		0		0		0
63	63	Ō	0	0	0	0	0	0
80		0	0	0	0	0	0	0
80	80	0	0	0	0	0	0	0
100		0	0	0	0	0	0	0
125		0	0	0	0	0	0	0
150		0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		0	0	0	0	0	0	0
250		0	0	0	0	0	0	0
300		0	0	0	0	0	0	0
500		0	0	0	0	0	0	0
600	1	0		0		0		0
100		0	0	0	0	0	0	0
125	1	0	0	0	0	0	0	0
150	1	0	0	0	0	0	0	0
160	100	0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		0		0			0	0
250		0	0	0	0	0	0	0
300		0				0	0	0
350		0	0	0	0	0	0	0
400		0		0	0	0	0	0
500		0	0	0	0	0	0	0
600		0		0		0		0
125	125	0	0	0	0	0	0	0
150		0	0	0	0	0	0	0
160		0	0	0	0	0	0	0
180		0	0	0	0	0	0	0
200		0	0	0	0	0	0	0
210		0	0	0	0	0	0	0
250		0	0	0	0	0	0	0
300		0	0	0	0	0	0	0
350		0	0	0	0	0	0	0
400		0	0	0	0	0	0	0
450		0	0	0	0	0	0	0
500 600		0	0	0	0	0	0	0
600		0		0				0

26