

Title: Maximum inner-product search

URL: [https://en.wikipedia.org/wiki/Maximum\\_inner-product\\_search](https://en.wikipedia.org/wiki/Maximum_inner-product_search)

PageID: 71220531

Categories: Category:Computational problems, Category:Machine learning, Category:Search algorithms

Source: Wikipedia (CC BY-SA 4.0).

-----

Maximum inner-product search ( MIPS ) is a search problem , with a corresponding class of search algorithms which attempt to maximise the inner product between a query and the data items to be retrieved. MIPS algorithms are used in a wide variety of big data applications, including recommendation algorithms and machine learning . [ 1 ]

Formally, for a database of vectors  $x_i$  defined over a set of labels  $S$  in an inner product space with an inner product  $\langle \cdot, \cdot \rangle$ , MIPS search can be defined as the problem of determining for a given query  $q$  .

Although there is an obvious linear-time implementation, it is generally too slow to be used on practical problems. However, efficient algorithms exist to speed up MIPS search. [ 1 ] [ 2 ]

Under the assumption of all vectors in the set having constant norm, MIPS can be viewed as equivalent to a nearest neighbor search (NNS) problem in which maximizing the inner product is equivalent to minimizing the corresponding distance metric in the NNS problem. [ 3 ] Like other forms of NNS, MIPS algorithms may be approximate or exact. [ 4 ]

MIPS search is used as part of DeepMind 's RETRO algorithm. [ 5 ]

References

See also

Nearest neighbor search