

LLD Chapter 12: Scenario-Based LLD Interview Questions & Senior Staff Grills

Core Learning Objective: Master the tough architectural cross-examinations asked by LLD interviewers at Google, Uber, Amazon, and Meta. Learn how to justify pattern choices, resolve deadlocks, defend concurrency decisions, and demonstrate clean refactoring.

1. Architectural Defense Questions

Question 1: "Why did you use the Strategy Pattern instead of the State Pattern?"


The Strong Hire Answer:

- **Intent Difference:**
 - The **Strategy Pattern** is used when the **client wants to choose an interchangeable algorithm from the outside** (e.g., choosing Credit Card vs. UPI at checkout, or Lowest Floor First vs. Nearest to Entrance for parking). The object does not change its behavior automatically—the caller explicitly passes the strategy.
 - The **State Pattern** is used when the **object automatically changes its internal behavior as its internal state transitions** across its lifecycle (e.g., a Vending Machine transitioning from `Idle` to `HasMoney` to `Dispensing`, or a Movie Seat transitioning from `Available` to `Locked` to `Booked`). The client does not manually switch states; the context transitions itself.
-

Question 2: "In your Movie Booking system, two users attempt to book seats A1 and A2 in reverse order simultaneously. How do you prevent a distributed deadlock?"

The Scenario:

- Thread 1: User 1 locks Seat A1, then requests Seat A2.
- Thread 2: User 2 locks Seat A2, then requests Seat A1.
- Result: Classic circular wait deadlock! Both threads wait forever.



The Solution (Strict Global Lock Ordering):

*"To eliminate deadlocks, we must break Coffman's Circular Wait condition. Regardless of the order in which the user requested the seats [A2, A1], our service **sorts the seat IDs lexicographically** before acquiring locks. Both Thread 1 and Thread 2 will always attempt to acquire **Seat A1** first, and only then acquire **Seat A2**. One thread will acquire A1; the other will wait without holding A2, eliminating deadlock."*

Question 3: "How would you add Undo / Redo functionality to this system?"

The Interviewer Asks:

"We want users to be able to undo and redo their actions in the editor or reservation tool. Which pattern do you introduce and why?"

The Strong Hire Answer:

- Introduce the **Command Pattern** paired with the **Memento Pattern**:
 - Each user action is encapsulated into a **Command** object with both **execute()** and **undo()** methods.
 - An **Invoker** maintains two stacks: **undo_stack** and **redo_stack**.
 - If the action mutates internal object state that cannot easily be reversed algebraically, the **Memento** pattern captures a snapshot of the object's internal state before the command executes.

Question 4: "How do you test this system in isolation without spinning up real databases or payment gateways?"

The Strong Hire Answer:

- Emphasize **Dependency Inversion (DIP)**:
 - Classes must depend on abstract **Protocols** or interfaces (`PaymentGateway` , `SeatRepository`), not concrete classes (`StripeGateway` , `PostgresDB`).
 - In unit tests, inject an in-memory **Mock Repository** (`MockPaymentGateway` returning `True/False`) directly into the constructor.
 - This allows running 1,000 test cases in 50 milliseconds in CI/CD without external network dependencies.

2. Failure, Extension and Test Questions

Question 5: "Your payment call succeeds but the process crashes before the seat is marked booked. What now?"

This is the **dual write** problem: two systems change and no transaction spans both. State the options in order of preference:

1. **Idempotency key**: send the booking id with the charge; on restart, retry the whole confirm step and the gateway returns the first result instead of charging twice.
2. **Record intent first**: write `PAYMENT_PENDING` to durable storage before calling the gateway; a recovery job finds pending bookings and asks the gateway what happened.
3. **Outbox or saga**: write the booking change and an event to the same database transaction; a relay publishes the event, and a compensating action refunds when the booking cannot complete.

Say plainly that "make it atomic" is not available across a network, and name the compromise you chose.

Question 6: "A teammate adds a new vehicle type and has to edit six `if/elif` blocks. How do you fix the design?"

The design violates the Open/Closed Principle: adding a case should not edit existing code. Move the varying rule behind a lookup keyed by the type, so a new type is one new entry:

When the rule is behaviour rather than data, register a strategy object in the same kind of table. Mention the trade-off: a registry is easy to extend but spreads the rules across files, so keep one place that lists them.

Question 7: "How would you make your in-memory rate limiter work across ten servers?"

Local counters give each server its own limit, so the real limit is ten times higher. Options: a central store with an atomic script (Redis), sticky routing by client key so each client always hits the same server, or a hybrid where servers keep a local allowance and refill it from the central store in batches. State what you give up with each: the central store adds latency and a dependency, sticky routing breaks when a server dies, the hybrid allows a bounded overshoot.

Question 8: "What do you write first when asked to design a system in 45 minutes?"

A defensible order: requirements and non-goals (5 minutes), entities and relationships (5), the main interface and the one hard algorithm or concurrency point (15), code or pseudo-code for that part (15), then edge cases and extensions (5). Interviewers score clarifying questions, a design that survives the follow-up requirement, correct handling of the hard part, and visible testing thought, more than the number of patterns used.

3. What Interviewers Actually Score

Dimension	Strong signal	Weak signal
Requirements	Asks about scale, concurrency, failure before drawing	Starts coding at once
Modelling	Small classes with one reason to change	One class that does everything, or a class per noun with no behaviour
Patterns	Names the force, then the pattern, and says when not to use it	Pattern name-dropping
Concurrency	Finds the check-then-act and lock-ordering hazards unprompted	Adds locks everywhere or nowhere
Extensibility	Handles the curveball by adding code, not editing	Rewrites the design
Testing	Injects clocks, randomness and I/O so tests are deterministic	"I would test it manually"

Further Reading

- [Refactoring Guru: pattern catalog](#)

- [UML diagrams reference](#)
 - [Wikipedia: SOLID](#)
-

Check Yourself

Answer in your head or on paper first, then open each answer.

- ▶ 1. How do you handle 'design a parking lot' in the first 5 minutes?
- ▶ 2. What do interviewers want to see in the extensibility discussion?
- ▶ 3. How do you address concurrency in a booking system?
- ▶ 4. What is a strong closing statement?