


HLD Chapter 4: Caching, Load Balancing, CDNs & Edge Networks

Core Learning Objective: Master high-performance data delivery architectures. Understand the 4 write policies, how to defend against cache stampedes, L4 vs L7 load balancing, and global CDN edge caching.

1. Caching Strategies & Write Policies



Write Policies Comparison Matrix

Strategy	Read Latency	Write Latency	Data Consistency	Crash Risk
Cache-Aside	Fast on hit, slow on initial miss	Fast	Potential stale reads until TTL expires	Zero data loss (DB is source of truth)
Write-Through	Always fast (warm cache)	Higher (dual write: Cache + DB)	High consistency	Zero data loss
Write-Behind	Ultra fast	Minimal (RAM write speed)	Eventual consistency	High: Power loss before async flush loses data!

2. The 4 Fatal Cache Failure Modes & Defenses

1. Cache Stampede (Thundering Herd)

- **What happens:** A hot key (e.g. homepage top news viewed by 50,000 QPS) expires from cache. 50,000 concurrent threads simultaneously miss the cache and overwhelm the underlying SQL database with identical queries, causing a total database outage.
- **Defense: Distributed Mutex Lock / Probabilistic Early Expiration (XFetch):**


2. Cache Penetration

- **What happens:** An attacker queries non-existent keys (e.g., `user_id = -999999`). The cache misses, queries the DB, finds nothing, and does not cache the result. Every malicious request hits the database directly.
- **Defense: Bloom Filters** at the gateway (guarantees a key definitely does not exist in $O(1)$) OR cache `null` with a short 60-second TTL.

3. Cache Avalanche

- **What happens:** Hundreds of thousands of keys were populated at the same time with identical TTLs (e.g., exactly 24 hours). When the 24 hours expire, they all drop out simultaneously, crashing the DB.
- **Defense: Add Jitter to TTL:** `TTL = base_ttl + random.randint(0, 300)`.

3. Load Balancing: Layer 4 vs Layer 7



Dimension	Layer 4 (Transport)	Layer 7 (Application)
Data Inspected	IP addresses & TCP/UDP Ports	Full HTTP/HTTPS payload, URI path, headers, cookies
TLS / SSL Termination	Pass-through (Client negotiates directly)	Terminates SSL at the load balancer
Throughput & Latency	Millions of QPS; microsecond latency (zero packet inspection)	High latency overhead; smart routing decisions
Routing Capability	Round-robin across static IP pools	Path-based routing, A/B testing, auth inspection

4. Content Delivery Networks (CDNs) & Anycast Routing

A CDN is a geographically distributed network of **Edge Proxy Servers (Points of Presence - POPs)** that cache static and streaming content (images, videos, JS/CSS bundles) close to the user.

- **Anycast DNS Routing:** Multiple worldwide CDN POPs advertise the **exact same public IP address** via BGP (Border Gateway Protocol). The internet's routing fabric automatically directs user packets to the topologically closest datacenter.
- **Origin Shielding:** A secondary caching layer between CDN edge servers and your main datacenter to ensure origin servers are never flooded during cache misses.

Further Reading

- [Redis documentation](#)
 - [NGINX load balancing](#)
 - [Wikipedia: Consistent hashing](#)
-

Check Yourself

Answer in your head or on paper first, then open each answer.

- ▶ 1. Cache-aside versus write-through?
- ▶ 2. What is a cache stampede and a fix?
- ▶ 3. Layer 4 versus layer 7 load balancing?
- ▶ 4. What is consistent hashing for?