

Technical data sheet Starter battery

Battery type	12V 105Ah +D M11	Product code	CGAJ1050

Specification		
Nominal voltage	12 V	
Capacity (C20)	105 Ah at 25°C to 10,5V	
Reserve capacity	122 min	
(25A discharge)		
Cold cranking current (EN -18°C)	720 A	
Cold cranking current (DIN -18°C)	420 A	
Weight	20.6 kg ± 5%	
Technology	Flooded/SLI	


Overall dimensions	
Length	303 +0/-2 mm
Width	173 +0/-2 mm
Height	225 +0/-3 mm
Base hold-down	B03
Layout	0
Terminal type	1
Container material	PP
Box color	Black
Lid color	Black

Electrolyte		
Electrolyte type	H ₂ SO ₄	
Electrolyte spec density at 25°C	$1.28 \pm 0.01 \text{ g/cm}3$	

Cell properties		
Grid prod. technology	Punched	
+ grid alloy	PbCa	
+ strip / grid thickness	0.9 / 1.3 mm	
(-) grid	CE-	
Grid prod. technology	Expanded	
- grid alloy	PbCa	
- strip / grid thickness	0.75 / 1.25 mm	
Separator		
Туре	PE	
Thickness	1.0 - 1.2 mm	

Base hold-down	Layout
5 notches	
SIDE	

Terminal type	Key characteristics	
1	- Maintenance free	
e 19,5 e 17,9 ← pos. neg.	Wide range of applicationUniversal EN designLid type: K2 with push in plug	
pos. neg.	- Lid type: K2 with push in plug	







Fabricado en C.E. según las normas ISO 9001 – ISO 14001 e I.P.P.C.

Date: 01/01/2020