

Technical data sheet Starter battery

Battery type	70Ah +R L3 START&STOP	Product code	CGAAGM70

Specification		
Nominal voltage	12 V	
Capacity (C20)	70 Ah at 25°C to 10,5V	
Reserve capacity	179 min	
(25A discharge)		
Cold cranking current (EN -18°C)	760 A	
Cold cranking current (DIN -18°C)	450 A	
Weight	20.6 kg ± 5%	
Technology	AGM vrla, maintenance free	

Overall dimensions	
Length	276 +0/-2 mm
Width	175 +0/-2 mm
Height	190 ₊₀ /-з mm
Base hold-down	B13
Layout	0
Terminal type	1
Container material	PP
Box color	Black
Lid color	Black

Electrolyte		
Electrolyte type	H ₂ SO ₄	
Electrolyte spec density at 25°C	1.28 ± 0.01 g/cm3	

Cell properties		
Grid prod. technology	Expanded	
+ grid alloy	PbCa	
+ strip / grid thickness	0.9 / 1.3 mm	
(-) grid	CE-	
Grid prod. technology	Expanded	
- grid alloy	PbCa	
- strip / grid thickness	0.75 / 1.25 mm	
Separator		
Туре	fiberplass	
Thickness	1.0 - 1.2 mm	

ase hold-down	Layout
5 notches	
SIDE	L L

Terminal type	Key characteristics	
1	- Maintenance free	
	Wide range of applicationUniversal EN designLid type: K2 with push in plug	
100 av		





Date: 01/01/2020